

# Planning with Attitude

Brian Jackson<sup>1</sup> and Zachary Manchester<sup>1</sup>

## I. INTRODUCTION

Many useful robotic systems—including quadrotors, airplanes, satellites, autonomous underwater vehicles, and quadrupeds—can perform arbitrarily large three-dimensional translations and rotations as part of their normal operation. While simply representing the attitude of these systems is nontrivial, generating and tracking motion plans for floating-base systems is an even more challenging problem.

Many approaches have been taken to address the problem of motion planning and control on the space of rigid body motions [2, 4, 5]; most of these rely heavily on ideas and notation from differential geometry. Despite some impressive results, many of these ideas have not been widely adopted by the robotics community, and many practitioners continue to ignore the group structure of rotations. One issue preventing wider adoption is that accounting for this structure requires low-level changes to the underlying optimization algorithms, which is difficult or impossible when relying on existing off-the-shelf solvers.

To address this lack of solver support, we formulate a straightforward, generic method for adapting existing Newton and gradient-based algorithms to correctly account for the group structure of rotations. Based entirely on basic mathematical tools from linear algebra and calculus, our method is computationally efficient and should be both accessible and familiar to most roboticists. We apply this method to the ALTRO solver [1] and demonstrate its performance on several constrained trajectory optimization problems.

## II. NOTATION AND CONVENTIONS

We begin by defining some useful conventions and notation. Attitude is defined as the rotation from the robot’s body frame to a global inertial frame. We also define gradients to be row vectors, that is, for  $f(x) : \mathbb{R}^n \rightarrow \mathbb{R}$ ,  $\frac{\partial f}{\partial x} \in \mathbb{R}^{1 \times n}$ .

We represent—following the Hamilton convention—a quaternion  $\mathbf{q} \in \mathbb{H}$  as a standard vector  $q \in \mathbb{R}^4 := [q_s \ q_v^T]^T$  where  $q_s \in \mathbb{R}$  and  $q_v \in \mathbb{R}^3$  are the scalar and vector part of the quaternion, respectively. We denote the composition of two quaternions as  $q_3 = q_2 \otimes q_1$ .

## III. QUATERNION DIFFERENTIAL CALCULUS

Most modern methods for planning and control require derivatives with respect to the state vector. We present a simple but powerful method for taking derivatives of quaternion-valued state vectors. The extension of this method to more general state vectors that contain Cartesian products of  $SO(3)$ ,  $SE(3)$ , and  $\mathbb{R}^n$  is straightforward.

<sup>1</sup>Robotics Institute, Carnegie Mellon University, 5000 Forbes Ave, Pittsburgh, PA, USA



Fig. 1. Snapshots of quadrotor flip trajectory solved using a modified version of ALTRO that correctly accounts for the group structure of rotations. These modifications make it easier to find trajectories that undergo large changes in attitude, such as the loop-de-loop shown here.

The key idea of this section is that differential quaternions live in three-dimensional space instead of the four-dimensional space of quaternions; this idea should match our intuition given rotations are inherently three-dimensional and differential rotations should live in the same space as angular velocity, i.e.  $\mathbb{R}^3$ .

In practice, we have found Rodrigues Parameters to be a very effective representation for three-dimensional differential rotations since they are computationally efficient and do not inherit the sign ambiguity of quaternions.

The mapping between a vector of Rodrigues parameters  $\phi \in \mathbb{R}^3$  and a unit quaternion  $q$  is known as the Cayley map:

$$q = \varphi(\phi) = \frac{1}{\sqrt{1 + \|\phi\|^2}} \begin{bmatrix} 1 \\ \phi \end{bmatrix}. \quad (1)$$

We will also make use of the inverse Cayley map:

$$\phi = \varphi^{-1}(q) = \frac{q_v}{q_s}. \quad (2)$$

### A. Jacobian of Vector-Valued Functions

When taking derivatives with respect to quaternions, we must take into account both the composition rule and the nonlinear mapping between the space of unit quaternions and our chosen three-parameter error representation.

Let  $\phi \in \mathbb{R}^3$  be a differential rotation applied to a function with unit quaternion inputs  $y = h(q) : \mathbb{S}^3 \rightarrow \mathbb{R}^p$ , such that

$$y + \delta y = h(q \otimes \varphi(\phi)) \approx h(q) + \nabla h(q)\phi. \quad (3)$$

We can calculate the Jacobian  $\nabla h(q) \in \mathbb{R}^{p \times 3}$  by differentiating (3) with respect to  $\phi$ , evaluated at  $\phi = 0$ :

$$\nabla h(q) = \frac{\partial h}{\partial q} \begin{bmatrix} -q_v^T \\ sI_3 + [q_v]^\times \end{bmatrix} := \frac{\partial h}{\partial q} G(q) \quad (4)$$

where  $G(q) \in \mathbb{R}^{4 \times 3}$  is referred to as the *attitude Jacobian*, which essentially becomes a “conversion factor” allowing us to apply results from standard vector calculus to the space of unit quaternions. This form is particularly useful in practice since  $\partial h / \partial q \in \mathbb{R}^{p \times 4}$  can be obtained using finite difference or automatic differentiation. As an aside, although we have used Rodrigues parameters,  $G(q)$  is actually the same (up to a constant scaling factor) for any choice of three-parameter attitude representation.

### B. Other derivatives

Using similar techniques, we find useful expressions for the Hessian of a scalar-valued function (i.e.  $p = 1$ ):

$$\nabla^2 h(q) = G(q)^T \frac{\partial^2 h}{\partial q^2} G(q) + I_3 \frac{\partial h}{\partial q} q, \quad (5)$$

and the Jacobian of a quaternion-valued function  $q' = f(q) : \mathbb{S}^3 \rightarrow \mathbb{S}^3$ :

$$\nabla f(q) = G(q')^T \frac{\partial f}{\partial q} G(q). \quad (6)$$

## IV. FAST CONSTRAINED TRAJECTORY OPTIMIZATION WITH ATTITUDE STATES

### A. Algorithmic Modifications

Here we briefly outline the changes to the ALTRO solver [1] to efficiently solve trajectory optimization problems for systems with 3D rotations in the state vector.

The linearization of the nonlinear discrete dynamics function  $x_{k+1} = f(x_k, u_k)$  is “corrected” using 6:

$$A = E(f(x, u))^T \frac{\partial f}{\partial x} E(x); \quad B = E(f(x, u))^T \frac{\partial f}{\partial u}. \quad (7)$$

Here we define the *state attitude Jacobian*  $E(x)$  to be a block-diagonal matrix where the block is an identity matrix for any vector-valued state and  $G(q)$  for any quaternion in the state vector. Using (4), (5), (6) we can derive similar modifications to the expansions of the cost and constraint functions. We refer the reader to the original ALTRO paper [1] for further details on the algorithm.

These adjustments effectively modify the optimization so that it is performed on the quaternion error state (or Rodrigues Parameters) instead of the space of unit quaternions. In practice, this is analagous to the Multiplicative Extended Kalman Filter [3] in the state estimation community.

The algorithm only needs one small modification to the “forward pass,” where the trajectory is modified by simulating the system forward using the optimal feedback policy,  $\delta u = K\delta x + d$ , computed during the “backward” pass. Instead of computing  $\delta x$  using simple subtraction, we now compute the error state using the inverse Cayley map (2) for the quaternion states. The rest of the forward pass is unmodified.

### B. Examples

To demonstrate the effectiveness of the proposed approach, we tested the modified version of ALTRO by solving for a quadrotor flip trajectory (see Figure II). Four soft “waypoint” costs were placed along the trajectory, encouraging the quadrotor to follow a loop. The trajectory was initialized with hover controls and a state trajectory that smoothly rotated the quadrotor one full rotation about the x-axis while moving to the goal. The modified version of ALTRO solved the problem in 270 ms and 26 iterations, while the original version that naively treated the quaternion as a vector in  $\mathbb{R}^4$  solved in 870 ms and 91 iterations. The original version failed to provide a nice, smooth loop and instead reversed direction halfway through the loop.

It’s also worthwhile to note that this problem cannot be solved as-is with any three-parameter representation because of the singularities that occur at 90, 180, and 360 degrees for Euler angles, Rodrigues parameters, and MRP’s, respectively. A classic approach to overcome this issue is to do discrete switching of the reference orientation, which requires previous knowledge of the topology of the optimal solution.

## V. CONCLUSION

We have proposed a general, accessible, and computationally efficient approach to doing planning and control for systems with one or more unit quaternions in their state vectors. The approach allows for straightforward adaptation of many gradient-based methods for optimal control and motion planning, which we demonstrated on the ALTRO solver. Initial results suggest that our approach can significantly reduce solve times by improving convergence rates for problems that require large changes in attitude over the course of the trajectory. Future work will extend these ideas to Newton-based methods such as direct collocation and other domains outside of trajectory optimization.

## REFERENCES

- [1] Taylor A Howell, Brian E Jackson, and Zachary Manchester. “ALTRO: A fast solver for constrained trajectory optimization”. In: *2019 IEEE International Conference on Intelligent Robots and Systems, IEEE*. 2019.
- [2] Marin B. Kobilarov and Jerrold E. Marsden. “Discrete Geometric Optimal Control on Lie Groups”. In: *IEEE Transactions on Robotics* 27.4 (Aug. 2011), pp. 641–655. ISSN: 1941-0468. DOI: 10.1109/TRO.2011.2139130.
- [3] F Landis Markley and John L Crassidis. *Fundamentals of spacecraft attitude determination and control*. Vol. 33. Springer, 2014.
- [4] Alessandro Saccon, John Hauser, and A. Pedro Aguiar. “Optimal Control on Lie Groups: The Projection Operator Approach”. In: *IEEE Transactions on Automatic Control* 58.9 (Sept. 2013), pp. 2230–2245. ISSN: 2334-3303. DOI: 10.1109/TAC.2013.2258817.
- [5] Michael Watterson and Vijay Kumar. “Control of quadrotors using the HOPF fibration on  $SO(3)$ ”. In: *Robotics Research*. Springer, 2020, pp. 199–215.