

Table of Contents

MSpace SMS Api V2.....	4
How To Generate ApiKey.....	4
Send SMS	5
Option 1: Rest api	5
Option 2: Http api	5
Response for both POST and GET:.....	6
Delivery Reports	6
Option 1: Rest api	6
Option 2: Http api	7
Response for both POST and GET:.....	7
Sms Balance Query	7
Option 1: Rest api	7
Option 2: Http api	8
Response for both POST and GET:.....	8
Query Sub Users	8
Option 1: Rest api	8
Option 2: Http api	8
Response for both POST and GET:.....	8
Query Reseller Clients.....	9
Option 1: Rest api	9
Option 2: Http api	9
Response for both POST and GET:.....	9
Sub-Account Top Up.....	10
Option 1: Rest api	10
Option 2: Http api	10
Response for both POST and GET:.....	11
Reseller Client Top Up	11
Option 1: Rest api	11

Option 2: Http api	11
Response for both POST and GET:	11
XML Formats for POST request bodies	11
Send SMS	12
Delivery Reports	12
Sms Balance Query	12
Query Sub Users	13
Query Reseller Clients	13
Sub-Account Top Up	14
Reseller Client Top Up	14
Solutions to Errors encountered: eg status http 400, 404, etc	15
OTHER CODE Formats for POST request bodies	15
SEND SMS	15
PHP	16
C#	17
JAVA	17
GO	18
PYTHON	19
CURL	20
DELIVERY REPORTS	20
C#	21
JAVA	21
GO	22
PHP	23
PYTHON	24
CURL	25
SMS BALANCE QUERY	25
C#	25
JAVA	26
GO	26

PHP	28
PYTHON	29
CURL	29
QUERY SUB USERS	29
POST	29
C#.....	29
JAVA.....	30
GO.....	30
PHP	32
PYTHON	33
CURL	34
QUERY RESLLER CLIENTS.....	34
POST	34
C#.....	34
JAVA.....	34
GO.....	35
PHP	37
PYTHON	37
CURL	38
SUB ACCOUNT TOP UP	38
POST	38
C#.....	38
JAVA.....	39
GO.....	39
PHP	41
PYTHON	42
CURL	42
RESELLER CLIENT TOP UP.....	43
POST	43
C#.....	43

JAVA.....	43
GO.....	44
PHP.....	45
PYTHON.....	47
CURL.....	47

MSPACE SMS API V2

HOW TO GENERATE APIKEY



- 1.) Login to the system.
- 2.) Click on the API tab. Then click on SMS and finally Generate keys.
- 3.) Input the name and select the user, then click on generate key. Once the Key has been generated you can copy it.

Send bulk emails or newsletters at once with our bulk email software and start your marketing campaigns now! [Sign up for one month free trial](#)

Welcome Catherine Logout

[Switch to](#)

Hide

- SMS
 - Dashboard
 - New Sms
 - Excel to SMS
 - Sent Sms
 - Received SMS
 - Address Book
 - Birthday Schedule
 - Manage Templates
- Reports
- My Account
- MSpacePESA
- API
 - Mpesa
 - SMS
 - Generate Keys

1 Name: 2 User:

3 [Generate Key](#)

4 [Copy](#)

69b5fdf2116a720d685c05672ae0ba585749c7e3ab059e396b4be528a4c238166abb953c6f67770ac0ee9d1ebb86a0dd285c24535d35e951f10c63ce229bcc0d

User's Generated API Keys			
Name	User	Key	Update
No records found.			

SEND SMS

OPTION 1: REST API

POST Endpoint: <https://api.mspace.co.ke/smsapi/v2/sendtext>

JSON Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/json

Header 3: Content-Type: application/json

Request Body:

```
{
  "username": "MyUsername",
  "senderId": "MSpace",
  "recipient": "0722XXXXXX,254733YYYYYY",
  "message": "Awesome Lord Jesus Christ."
}
```

OPTION 2: HTTP API

GET Endpoint:

https://api.mspace.co.ke/smsapi/v2/sendtext/apikey=<The_generated_ApiKey>/username=MyUsername/senderId=MSpace/recipient=0722XXXXXX,254733YYYYYY/message=Awesome Lord Jesus Christ.

RESPONSE FOR BOTH POST AND GET:

```
{  
  "message": [  
    {  
      "messageId": "49032372",  
      "recipient": "0722XXXXXX",  
      "status": 111,  
      "statusDescription": "Message sent succesfully"  
    },  
    {  
      "messageId": "49032374",  
      "recipient": "254733YYYYYY",  
      "status": 111,  
      "statusDescription": "Message sent succesfully"  
    }  
  ]  
}
```

DELIVERY REPORTSOPTION 1: REST API**POST** Endpoint: <https://api.mspace.co.ke/smsapi/v2/deliveryreport>JSON Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/json

Header 3: Content-Type: application/json

Request Body:

```
{
```

```
"username": "MyUsername",  
"messageId": "49032372"  
}
```

OPTION 2: HTTP API**GET** Endpoint:

[https://api.mspace.co.ke/smsapi/v2/deliveryreport/apikey=<The_generated_ApiKey>/username=MyUsername/messageId= 49032372](https://api.mspace.co.ke/smsapi/v2/deliveryreport/apikey=<The_generated_ApiKey>/username=MyUsername/messageId=49032372)

RESPONSE FOR BOTH POST AND GET:

```
{  
  "message": [  
    {  
      "messageId": "49032372",  
      "recipient": "0722XXXXXX",  
      "status": 3,  
      "statusDescription": "Delivered"  
    }  
  ]  
}
```

SMS BALANCE QUERY**OPTION 1: REST API****POST** Endpoint: <https://api.mspace.co.ke/smsapi/v2/balance>**JSON Sample Request:**

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/json

Header 3: Content-Type: application/json

Request Body:

```
{
```

```
"username": "MyUsername"
}
```

OPTION 2: HTTP API**GET** Endpoint:

https://api.mspace.co.ke/smsapi/v2/balance/apikey=<The_generated_ApiKey>/username=MyUser
name

RESPONSE FOR BOTH POST AND GET:

7628

QUERY Sub UsersOPTION 1: REST API**POST** Endpoint: https://api.mspace.co.ke/smsapi/v2/subusersJSON Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/json

Header 3: Content-Type: application/json

Request Body:

```
{
  "username": "MyUsername"
}
```

OPTION 2: HTTP API**GET** Endpoint:

https://api.mspace.co.ke/smsapi/v2/subusers/apikey=<The_generated_ApiKey>/username=MyUse
rname

RESPONSE FOR BOTH POST AND GET:

```
[
{
  "smsBalance": "21345",
```



```
"subAccUser": "User1"
},
{
  "smsBalance": "6199",
  "subAccUser": "User2"
}
]
```

QUERY RESELLER CLIENTS

OPTION 1: REST API

POST Endpoint: <https://api.mspace.co.ke/smsapi/v2/resellerclients>

JSON Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/json

Header 3: Content-Type: application/json

Request Body:

```
{
  "username": "MyUsername"
}
```

OPTION 2: HTTP API

GET Endpoint:

https://api.mspace.co.ke/smsapi/v2/resellerclients/apikey=<The_generated_ApiKey>/username=MyUsername

RESPONSE FOR BOTH POST AND GET:

```
[
{
  "clientUserName": "User1",
```

```
"smsBalance": "6199"
},
{
  "clientUserName": "User2",
  "smsBalance": "99998"
}
]
```

SUB-ACCOUNT TOP UP

OPTION 1: REST API

POST Endpoint: <https://api.mspace.co.ke/smsapi/v2/subaccttopup>

JSON Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/json

Header 3: Content-Type: application/json

Request Body:

```
{
  "username": "MyUsername",
  "subaccname": "favoredbyGod",
  "noOfSms": 9000
}
```

OPTION 2: HTTP API

GET Endpoint:

https://api.mspace.co.ke/smsapi/v2/subaccttopup/apikey=<The_generated_ApiKey>/username=MyUsername/subaccname=favoredbyGod/noofsms=9000

RESPONSE FOR BOTH POST AND GET:

Successful Top up of 9000 SMS to favoredbyGod

RESELLER CLIENT TOP UPOPTION 1: REST API

POST Endpoint: <https://api.mspace.co.ke/smsapi/v2/resellerclienttopup>

JSON Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/json

Header 3: Content-Type: application/json

Request Body:

```
{  
  "username": "MyUsername",  
  "clientname": "user2",  
  "noOfSms": 1000  
}
```

OPTION 2: HTTP API

GET Endpoint:

https://api.mspace.co.ke/smsapi/v2/resellerclienttopup/apikey=<The_generated_ApiKey>/username=MyUsername/clientname=user2/noofsms=1000

RESPONSE FOR BOTH POST AND GET:

Successful Top up of 1000 SMS to user2

XML FORMATS FOR POST REQUEST BODIES

SEND SMS

POST Endpoint: <https://api.mspace.co.ke/smsapi/v2/sendtext>

XML Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/xml

Header 3: Content-Type: application/xml

Request Body:

```
<sms>
  <username>MyUsername</username>
  <senderId>MSpace</senderId>
  <recipient>0722XXXXXX,254733YYYYYY</recipient>
  <message>Awesome Lord Jesus Christ.</message>
</sms>
```

DELIVERY REPORTS

POST Endpoint: <https://api.mspace.co.ke/smsapi/v2/deliveryreport>

XML Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/xml

Header 3: Content-Type: application/xml

Request Body:

```
<dlr>
  <username>MyUsername</username>
  <messageId>49032372</messageId>
</dlr>
```

SMS BALANCE QUERY

POST Endpoint: <https://api.mspace.co.ke/smsapi/v2/balance>

XML Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/xml

Header 3: Content-Type: application/xml

Request Body:

<user>

<username>MyUsername</username>

</user>

QUERY Sub Users

POST Endpoint: <https://api.mspace.co.ke/smsapi/v2/subusers>

XML Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/xml

Header 3: Content-Type: application/xml

Request Body:

<user>

<username>MyUsername</username>

</user>

QUERY RESELLER CLIENTS

POST Endpoint: <https://api.mspace.co.ke/smsapi/v2/resellerclients>

XML Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/xml

Header 3: Content-Type: application/xml

Request Body:

<user>

<username>MyUsername</username>

</user>

SUB-ACCOUNT TOP UP

POST Endpoint: https://api.mspace.co.ke/smsapi/v2/subaccttopup

XML Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/xml

Header 3: Content-Type: application/xml

Request Body:

<subAccTopups>

<username>MyUsername</username>

<subaccname>favoredbyGod</subaccname>

<noOfSms>9000</noOfSms>

</subAccTopups>

RESELLER CLIENT TOP UP

POST Endpoint: https://api.mspace.co.ke/smsapi/v2/resellerclienttopup

XML Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/xml

Header 3: Content-Type: application/xml

Request Body:

<resellerClientTopups>

<username>MyUsername</username>

<clientname>user2</clientname>

<noOfSms>1000</noOfSms>

</resellerClientTopups>

SOLUTIONS TO ERRORS ENCOUNTERED: EG STATUS HTTP 400, 404, ETC

1. Ensure endpoint url is correct
2. Ensure the endpoint type is correct: ie Get or POST
3. Ensure apikey is spelled correctly not ApiKey. Same for all parameters if any.

OTHER CODE FORMATS FOR POST REQUEST BODIES

SEND SMS

Endpoint: <https://api.mspace.co.ke/smsapi/v2/sendtext>

JSON Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/json

Header 3: Content-Type: application/json

Request Body:

{

```
"username": "MyUsername",  
"senderId": "MSpace",  
"recipient": "0722XXXXXX,254733YYYYYY",  
"message": "Awesome Lord Jesus Christ."  
}
```

PHP

<?php

```
$curl = curl_init();  
  
curl_setopt_array($curl, array(  
    CURLOPT_URL => 'https://api.mspace.co.ke/smsapi/v2/sendtext',  
    CURLOPT_RETURNTRANSFER => true,  
    CURLOPT_ENCODING => '',  
    CURLOPT_MAXREDIRS => 10,  
    CURLOPT_TIMEOUT => 0,  
    CURLOPT_FOLLOWLOCATION => true,  
    CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,  
    CURLOPT_CUSTOMREQUEST => 'POST',  
    CURLOPT_POSTFIELDS => '{  
"username": "myusername",  
"senderId": "mysenderid",  
"recipient": "07xxxxxxxx,2547xxxxxxxx",  
"message": "mymessage."  
}',  
    CURLOPT_HTTPHEADER => array(  
        'apikey: myapikey',  
        'Accept: application/json',  
        'Content-Type: application/json'  
    ),  
);
```



```
));
```

```
$response = curl_exec($curl);
```

```
curl_close($curl);
```

```
echo $response;
```

C#

```
var client = new HttpClient();
```

```
var request = new HttpRequestMessage(HttpMethod.Post,  
"https://api.mspace.co.ke/smsapi/v2/sendtext");
```

```
request.Headers.Add("apikey", "myapikey");
```

```
request.Headers.Add("Accept", "application/json");
```

```
var content = new StringContent("{\n\"username\": \"myusername\", \n\"senderId\":  
\"mysenderid\", \n\"recipient\": \"07xxxxxxx,2547xxxxxxx\", \n\"message\": \"mymessage.\", \n}\",  
null, "application/json");
```

```
request.Content = content;
```

```
var response = await client.SendAsync(request);
```

```
response.EnsureSuccessStatusCode();
```

```
Console.WriteLine(await response.Content.ReadAsStringAsync());
```

JAVA

```
OkHttpClient client = new OkHttpClient().newBuilder()
```

```
.build();
```

```
MediaType mediaType = MediaType.parse("application/json");
```

```
RequestBody body = RequestBody.create(mediaType, "{\n\"username\":  
\"myusername\", \n\"senderId\": \"mysenderid\", \n\"recipient\":  
\"07xxxxxxx,2547xxxxxxx\", \n\"message\": \"Awesome Lord Jesus Christ.\", \n}");
```

```
Request request = new Request.Builder()
```

```
.url("https://api.mspace.co.ke/smsapi/v2/sendtext")
```

```
.method("POST", body)
```

```
.addHeader("apikey", "myapikey")
.addHeader("Accept", "application/json")
.addHeader("Content-Type", "application/json")
.build();
```

```
Response response = client.newCall(request).execute();
```

GO

```
package main
```

```
import (
    "fmt"
    "strings"
    "net/http"
    "io/ioutil"
)

func main() {

    url := "https://api.mspace.co.ke/smsapi/v2/sendtext"
    method := "POST"
    payload := strings.NewReader(`{
    "username": "myusername",
    "senderId": "mysenderid",
    "recipient": "07xxxxxxx,2547xxxxxxx",
    "message": "Awesome Lord Jesus Christ."
    }`)
    client := &http.Client {
    }
    req, err := http.NewRequest(method, url, payload)
    if err != nil {
```

```
fmt.Println(err)

return

}

req.Header.Add("apikey", "myapikey")
req.Header.Add("Accept", "application/json")
req.Header.Add("Content-Type", "application/json")
res, err := client.Do(req)
if err != nil {
    fmt.Println(err)
    return
}
defer res.Body.Close()
body, err := ioutil.ReadAll(res.Body)
if err != nil {
    fmt.Println(err)
    return
}
fmt.Println(string(body))
}
```

PYTHON

```
import http.client
import json

conn = http.client.HTTPSConnection("api.mspace.co.ke")
payload = json.dumps({
    "username": "myusername",
    "senderId": "mysenderid",
    "recipient": "07xxxxxxxx,2547xxxxxxxx",
    "message": "Awesome Lord Jesus Christ."
})
```

```
headers = {  
    'apikey': 'myapikey',  
    'Accept': 'application/json',  
    'Content-Type': 'application/json'  
}  
conn.request("POST", "/smsapi/v2/sendtext", payload, headers)  
res = conn.getresponse()  
data = res.read()  
print(data.decode("utf-8"))
```

CURL

```
curl --location 'https://api.mspace.co.ke/smsapi/v2/sendtext' \  
--header 'apikey: myapikey' \  
--header 'Accept: application/json' \  
--header 'Content-Type: application/json' \  
--data '{  
    "username": "myusername",  
    "senderId": "mysenderid",  
    "recipient": "07xxxxxxxx,254xxxxxxxx",  
    "message": "Awesome Lord Jesus Christ."  
}'
```

DELIVERY REPORTS

Endpoint: <https://api.mspace.co.ke/smsapi/v2/deliveryreport>

JSON Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/json

Header 3: Content-Type: application/json

Request Body:

```
{  
  "username": "MyUsername",  
  "messageId": "49032372"  
}
```

C#

```
var client = new HttpClient();  
  
var request = new HttpRequestMessage(HttpMethod.Post,  
  "https://api.mspace.co.ke/smsapi/v2/deliveryreport");  
  
request.Headers.Add("apikey", "myapikey");  
  
request.Headers.Add("Accept", "application/json");  
  
var content = new StringContent("{\n\"username\": \"myusername\", \n\"messageId\":  
  \"49152799\"\n}", null, "application/json");  
  
request.Content = content;  
  
var response = await client.SendAsync(request);  
  
response.EnsureSuccessStatusCode();  
  
Console.WriteLine(await response.Content.ReadAsStringAsync());
```

JAVA

```
OkHttpClient client = new OkHttpClient().newBuilder()  
  .build();  
  
MediaType mediaType = MediaType.parse("application/json");  
  
RequestBody body = RequestBody.create(mediaType, "{\n\"username\":  
  \"myusername\", \n\"messageId\": \"49152799\"\n}");  
  
Request request = new Request.Builder()  
  .url("https://api.mspace.co.ke/smsapi/v2/deliveryreport")  
  .method("POST", body)  
  .addHeader("apikey", "myapikey")  
  .addHeader("Accept", "application/json")  
  .addHeader("Content-Type", "application/json")  
  .build();  
  
Response response = client.newCall(request).execute();
```

GO

package main

```
import (  
    "fmt"  
    "strings"  
    "net/http"  
    "io/ioutil"  
)  
  
func main() {  
    url := "https://api.mspace.co.ke/smsapi/v2/deliveryreport"  
    method := "POST"  
    payload := strings.NewReader(`{  
"username": "myusername",  
"messageId": "49152799"  
}`)  
  
    client := &http.Client {  
    }  
    req, err := http.NewRequest(method, url, payload)  
  
    if err != nil {  
        fmt.Println(err)  
        return  
    }  
    req.Header.Add("apikey", "myapikey")  
    req.Header.Add("Accept", "application/json")  
    req.Header.Add("Content-Type", "application/json")  
    res, err := client.Do(req)
```

```
if err != nil {  
    fmt.Println(err)  
    return  
}  
defer res.Body.Close()  
  
body, err := ioutil.ReadAll(res.Body)  
if err != nil {  
    fmt.Println(err)  
    return  
}  
fmt.Println(string(body))  
}
```

PHP

```
<?php
```

```
$curl = curl_init();  
  
curl_setopt_array($curl, array(  
    CURLOPT_URL => 'https://api.mspace.co.ke/smsapi/v2/deliveryreport',  
    CURLOPT_RETURNTRANSFER => true,  
    CURLOPT_ENCODING => '',  
    CURLOPT_MAXREDIRS => 10,  
    CURLOPT_TIMEOUT => 0,  
    CURLOPT_FOLLOWLOCATION => true,  
    CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,  
    CURLOPT_CUSTOMREQUEST => 'POST',  
    CURLOPT_POSTFIELDS => '{  
"username": "myusername",
```

```
"messageId": "49152799"
}',
CURLOPT_HTTPHEADER => array(
    'apikey: myapikey',
    'Accept: application/json',
    'Content-Type: application/json'
),
));
```

```
$response = curl_exec($curl);
```

```
curl_close($curl);
```

```
echo $response;
```

PYTHON

```
import http.client
```

```
import json
```

```
conn = http.client.HTTPSConnection("api.mspace.co.ke")
```

```
payload = json.dumps({
```

```
    "username": "myusername",
```

```
    "messageId": "49152799"
```

```
})
```

```
headers = {
```

```
    'apikey': 'myapikey',
```

```
    'Accept': 'application/json',
```

```
    'Content-Type': 'application/json'
```

```
}
```

```
conn.request("POST", "/smsapi/v2/deliveryreport", payload, headers)
```



```
res = conn.getResponse()
data = res.read()
print(data.decode("utf-8"))
```

CURL

```
curl --location 'https://api.mspace.co.ke/smsapi/v2/deliveryreport' \
--header 'apikey: myapikey' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--data '{
"username": "myusername",
"messageId": "49152799"
}'
```

SMS BALANCE QUERY

Endpoint: <https://api.mspace.co.ke/smsapi/v2/balance>

JSON Sample Request:

Header 1:apikey: <The_generated_ApiKey>

Header 2:Accept: application/json

Header 3: Content-Type: application/json

Request Body:

```
{
  "username": "MyUsername"
}
```

C#

```
var client = new HttpClient();
```

```
var request = new HttpRequestMessage(HttpMethod.Post,
"https://api.mspace.co.ke/smsapi/v2/balance");

request.Headers.Add("apikey", "myapikey");

request.Headers.Add("Accept", "application/ecmascript");

var content = new StringContent("{\n\"username\": \"MyUsername\"\n}", null,
"application/ecmascript");

request.Content = content;

var response = await client.SendAsync(request);

response.EnsureSuccessStatusCode();

Console.WriteLine(await response.Content.ReadAsStringAsync());
```

JAVA

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();

MediaType mediaType = MediaType.parse("application/ecmascript");

RequestBody body = RequestBody.create(mediaType, "{\n\"username\": \"MyUsername\"\n}");

Request request = new Request.Builder()
    .url("https://api.mspace.co.ke/smsapi/v2/balance")
    .method("POST", body)
    .addHeader("apikey", "myapikey")
    .addHeader("Accept", "application/ecmascript")
    .addHeader("Content-Type", "application/json")
    .build();

Response response = client.newCall(request).execute();
```

GO

```
package main
```

```
import (
```

```
"fmt"
"strings"
"net/http"
"io/ioutil"
)

func main() {

    url := "https://api.mspace.co.ke/smsapi/v2/balance"
    method := "POST"

    payload := strings.NewReader(`{
"username": "MyUsername"
}`)

    client := &http.Client {
    }

    req, err := http.NewRequest(method, url, payload)

    if err != nil {
        fmt.Println(err)
        return
    }

    req.Header.Add("apikey", "myapikey")
    req.Header.Add("Accept", "application/ecmascript")
    req.Header.Add("Content-Type", "application/ecmascript")

    res, err := client.Do(req)
    if err != nil {
        fmt.Println(err)
```

```
        return
    }

    defer res.Body.Close()

    body, err := ioutil.ReadAll(res.Body)
    if err != nil {
        fmt.Println(err)
        return
    }
    fmt.Println(string(body))
}
```

PHP

```
<?php
$client = new Client();
$headers = [
    'apikey' => 'myapikey',
    'Accept' => 'application/ecmascript',
    'Content-Type' => 'application/ecmascript'
];
$body = '{
    "username": "MyUsername"
}';
$request = new Request('POST', 'https://api.mspace.co.ke/smsapi/v2/balance', $headers, $body);
$res = $client->sendAsync($request)->wait();
echo $res->getBody();
```

PYTHON

```
import http.client
```

```
conn = http.client.HTTPSConnection("api.mspace.co.ke")
payload = "{\n\"username\": \"MyUsername\"\n}"
headers = {
    'apikey': 'myapikey',
    'Accept': 'application/ecmascript',
    'Content-Type': 'application/ecmascript'
}
conn.request("POST", "/smsapi/v2/balance", payload, headers)
res = conn.getresponse()
data = res.read()
print(data.decode("utf-8"))
```

CURL

```
curl --location 'https://api.mspace.co.ke/smsapi/v2/balance' \
--header 'apikey: myapikey' \
--header 'Accept: application/ecmascript' \
--header 'Content-Type: application/ecmascript' \
--data '{
"username": "MyUsername"
}'
```

QUERY SUB USERS

POST

C#

```
var client = new HttpClient();
```

```
var request = new HttpRequestMessage(HttpMethod.Post,
"https://api.mspace.co.ke/smsapi/v2/subusers");

request.Headers.Add("apikey", "myapikey");

request.Headers.Add("Accept", "application/json");

var content = new StringContent("{\n\"username\": \"myusername\"\n}", null, "application/json");

request.Content = content;

var response = await client.SendAsync(request);

response.EnsureSuccessStatusCode();

Console.WriteLine(await response.Content.ReadAsStringAsync());
```

JAVA

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();

MediaType mediaType = MediaType.parse("application/json");

RequestBody body = RequestBody.create(mediaType, "{\n\"username\": \"myusername\"\n}");

Request request = new Request.Builder()
    .url("https://api.mspace.co.ke/smsapi/v2/subusers")
    .method("POST", body)
    .addHeader("apikey", "myapikey")
    .addHeader("Accept", "application/json")
    .addHeader("Content-Type", "application/json")
    .build();

Response response = client.newCall(request).execute();
```

GO

```
package main
```

```
import (
    "fmt"
```

```
"strings"  
"net/http"  
"io/ioutil"  
)  
  
func main() {  
  
    url := "https://api.mspace.co.ke/smsapi/v2/subusers"  
    method := "POST"  
  
    payload := strings.NewReader(`{  
"username": "myusername"  
}`)  
  
    client := &http.Client {  
    }  
    req, err := http.NewRequest(method, url, payload)  
  
    if err != nil {  
        fmt.Println(err)  
        return  
    }  
    req.Header.Add("apikey", "myapikey")  
    req.Header.Add("Accept", "application/json")  
    req.Header.Add("Content-Type", "application/json")  
  
    res, err := client.Do(req)  
    if err != nil {  
        fmt.Println(err)  
        return
```

```
}
```

```
defer res.Body.Close()
```

```
body, err := ioutil.ReadAll(res.Body)
```

```
if err != nil {
```

```
    fmt.Println(err)
```

```
    return
```

```
}
```

```
fmt.Println(string(body))
```

```
}
```

PHP

```
<?php
```

```
$curl = curl_init();
```

```
curl_setopt_array($curl, array(
```

```
    CURLOPT_URL => 'https://api.mspace.co.ke/smsapi/v2/subusers',
```

```
    CURLOPT_RETURNTRANSFER => true,
```

```
    CURLOPT_ENCODING => '',
```

```
    CURLOPT_MAXREDIRS => 10,
```

```
    CURLOPT_TIMEOUT => 0,
```

```
    CURLOPT_FOLLOWLOCATION => true,
```

```
    CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
```

```
    CURLOPT_CUSTOMREQUEST => 'POST',
```

```
    CURLOPT_POSTFIELDS => '{
```

```
    "username": "myusername"
```

```
}',
```

```
    CURLOPT_HTTPHEADER => array(
```



```
'apikey: myapikey',  
'Accept: application/json',  
'Content-Type: application/json'  
,  
));
```

```
$response = curl_exec($curl);
```

```
curl_close($curl);
```

```
echo $response;
```

PYTHON

```
import http.client
```

```
import json
```

```
conn = http.client.HTTPSConnection("api.mspace.co.ke")
```

```
payload = json.dumps({
```

```
    "username": "myusername"
```

```
})
```

```
headers = {
```

```
    'apikey': 'myapikey',
```

```
    'Accept': 'application/json',
```

```
    'Content-Type': 'application/json'
```

```
}
```

```
conn.request("POST", "/smsapi/v2/subusers", payload, headers)
```

```
res = conn.getresponse()
```

```
data = res.read()
```

```
print(data.decode("utf-8"))
```

CURL

```
curl --location 'https://api.mspace.co.ke/smsapi/v2/subusers' \  
--header 'apikey: myapikey' \  
--header 'Accept: application/json' \  
--header 'Content-Type: application/json' \  
--data '{  
"username": "myusername"  
}'
```

QUERY RESLLER CLIENTS

POST

C#

```
var client = new HttpClient();  
  
var request = new HttpRequestMessage(HttpMethod.Post,  
"https://api.mspace.co.ke/smsapi/v2/resellerclients");  
  
request.Headers.Add("apikey", "myapikey");  
request.Headers.Add("Accept", "application/json");  
  
var content = new StringContent("{\n\"username\": \"MyUsername\"\n}", null, "application/json");  
request.Content = content;  
  
var response = await client.SendAsync(request);  
response.EnsureSuccessStatusCode();  
Console.WriteLine(await response.Content.ReadAsStringAsync());
```

JAVA

```
OkHttpClient client = new OkHttpClient().newBuilder()  
    .build();  
MediaType mediaType = MediaType.parse("application/json");
```

```
RequestBody body = RequestBody.create(mediaType, "{\n\"username\": \"MyUsername\"\n}");
```

```
Request request = new Request.Builder()
```

```
.url("https://api.mspace.co.ke/smsapi/v2/resellerclients")
```

```
.method("POST", body)
```

```
.addHeader("apikey", "myapikey")
```

```
.addHeader("Accept", "application/json")
```

```
.addHeader("Content-Type", "application/json")
```

```
.build();
```

```
Response response = client.newCall(request).execute();
```

GO

```
package main
```

```
import (
```

```
    "fmt"
```

```
    "strings"
```

```
    "net/http"
```

```
    "io/ioutil"
```

```
)
```

```
func main() {
```

```
    url := "https://api.mspace.co.ke/smsapi/v2/resellerclients"
```

```
    method := "POST"
```

```
    payload := strings.NewReader(`{
```

```
    "username": "MyUsername"
```

```
}`)
```

```
client := &http.Client {  
}  
  
req, err := http.NewRequest(method, url, payload)  
  
  
if err != nil {  
    fmt.Println(err)  
    return  
}  
  
req.Header.Add("apikey", "myapikey")  
req.Header.Add("Accept", "application/json")  
req.Header.Add("Content-Type", "application/json")  
  
  
res, err := client.Do(req)  
if err != nil {  
    fmt.Println(err)  
    return  
}  
defer res.Body.Close()  
  
  
body, err := ioutil.ReadAll(res.Body)  
if err != nil {  
    fmt.Println(err)  
    return  
}  
fmt.Println(string(body))  
}
```

PHP

```
<?php
```

```
$client = new Client();

$headers = [

    'apikey' => 'myapikey',

    'Accept' => 'application/json',

    'Content-Type' => 'application/json'

];

$body = '{

    "username": "MyUsername"

}';

$request = new Request('POST', 'https://api.mspace.co.ke/smsapi/v2/resellerclients', $headers, $body);

$res = $client->sendAsync($request)->wait();

echo $res->getBody();
```

PYTHON

```
import http.client

import json

conn = http.client.HTTPSConnection("api.mspace.co.ke")

payload = json.dumps({

    "username": "MyUsername"

})

headers = {

    'apikey': 'myapikey',

    'Accept': 'application/json',

    'Content-Type': 'application/json'

}

conn.request("POST", "/smsapi/v2/resellerclients", payload, headers)
```

```
res = conn.getResponse()
data = res.read()
print(data.decode("utf-8"))
```

CURL

```
curl --location 'https://api.mspace.co.ke/smsapi/v2/resellerclients' \
--header 'apikey: myapikey' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--data '{
"username": "MyUsername"
}'
```

SUB ACCOUNT TOP UP POST C#

```
var client = new HttpClient();

var request = new HttpRequestMessage(HttpMethod.Post,
"https://api.mspace.co.ke/smsapi/v2/subacctopup");

request.Headers.Add("apikey", "myapikey");

request.Headers.Add("Accept", "application/json");

var content = new StringContent("{\n  \"username\": \"myusername\", \n  \"subaccname\": \"subaccname\", \n  \"noOfSms\": 10\n}", null, "application/json");

request.Content = content;

var response = await client.SendAsync(request);

response.EnsureSuccessStatusCode();

Console.WriteLine(await response.Content.ReadAsStringAsync());
```

JAVA

```
OkHttpClient client = new OkHttpClient().newBuilder()
    .build();

MediaType mediaType = MediaType.parse("application/json");

RequestBody body = RequestBody.create(mediaType, "{\n  \"username\":\n  \"myusername\",\n  \"subacname\": \"subacname\",\n  \"noOfSms\": 10\n}");

Request request = new Request.Builder()
    .url("https://api.mspace.co.ke/smsapi/v2/subacctpup")
    .method("POST", body)
    .addHeader("apikey", "myapikey")
    .addHeader("Accept", "application/json")
    .addHeader("Content-Type", "application/json")
    .build();

Response response = client.newCall(request).execute();
```

GO

```
package main
```

```
import (
    "fmt"
    "strings"
    "net/http"
    "io/ioutil"
)
```

```
func main() {
```

```
    url := "https://api.mspace.co.ke/smsapi/v2/subacctpup"
```

```
    method := "POST"
```

```
payload := strings.NewReader(`{
    "username": "myusername",
    "subaccname": "subaccname",
    "noOfSms": 10
}`)

client := &http.Client {
}

req, err := http.NewRequest(method, url, payload)

if err != nil {
    fmt.Println(err)
    return
}

req.Header.Add("apikey", "myapikey")
req.Header.Add("Accept", "application/json")
req.Header.Add("Content-Type", "application/json")

res, err := client.Do(req)
if err != nil {
    fmt.Println(err)
    return
}
defer res.Body.Close()

body, err := ioutil.ReadAll(res.Body)
if err != nil {
    fmt.Println(err)
    return
}
```



```
fmt.Println(string(body))
}
```

PHP

```
<?php
```

```
$curl = curl_init();

curl_setopt_array($curl, array(
    CURLOPT_URL => 'https://api.mspace.co.ke/smsapi/v2/subacctopup',
    CURLOPT_RETURNTRANSFER => true,
    CURLOPT_ENCODING => '',
    CURLOPT_MAXREDIRS => 10,
    CURLOPT_TIMEOUT => 0,
    CURLOPT_FOLLOWLOCATION => true,
    CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
    CURLOPT_CUSTOMREQUEST => 'POST',
    CURLOPT_POSTFIELDS => '{
        "username": "myusername",
        "subaccname": "subaccname",
        "noOfSms": 10
    }',
    CURLOPT_HTTPHEADER => array(
        'apikey: myapikey',
        'Accept: application/json',
        'Content-Type: application/json'
    ),
));
```

```
$response = curl_exec($curl);
```

```
curl_close($curl);
```

```
echo $response;
```

PYTHON

```
import http.client
```

```
import json
```

```
conn = http.client.HTTPSConnection("api.mspace.co.ke")
```

```
payload = json.dumps({
```

```
    "username": "myusername",
```

```
    "subaccname": "subaccname",
```

```
    "noOfSms": 10
```

```
})
```

```
headers = {
```

```
    'apikey': 'myapikey',
```

```
    'Accept': 'application/json',
```

```
    'Content-Type': 'application/json'
```

```
}
```

```
conn.request("POST", "/smsapi/v2/subacctopup", payload, headers)
```

```
res = conn.getresponse()
```

```
data = res.read()
```

```
print(data.decode("utf-8"))
```

CURL

```
curl --location 'https://api.mspace.co.ke/smsapi/v2/subacctopup' \
```

```
--header 'apikey: myapikey' \
```

```
--header 'Accept: application/json' \  
--header 'Content-Type: application/json' \  
--data '{  
    "username": "myusername",  
    "subaccname": "subaccname",  
    "noOfSms": 10  
}'
```

RESELLER CLIENT TOP UP POST C#

```
var client = new HttpClient();  
  
var request = new HttpRequestMessage(HttpMethod.Post, "Endpoint:  
https://api.mspace.co.ke/smsapi/v2/resellerclienttopup");  
  
request.Headers.Add("apikey", "myapikey");  
request.Headers.Add("Accept", "application/json");  
  
var content = new StringContent("{\n\"username\": \"MyUsername\", \n\"clientname\":  
\"user2\", \n\"noOfSms\": 1000\n}", null, "application/json");  
  
request.Content = content;  
  
var response = await client.SendAsync(request);  
response.EnsureSuccessStatusCode();  
  
Console.WriteLine(await response.Content.ReadAsStringAsync());
```

JAVA

```
OkHttpClient client = new OkHttpClient().newBuilder()  
    .build();  
  
MediaType mediaType = MediaType.parse("application/json");  
  
RequestBody body = RequestBody.create(mediaType, "{\n\"username\":  
\"MyUsername\", \n\"clientname\": \"user2\", \n\"noOfSms\": 1000\n}");  
  
Request request = new Request.Builder()
```

```
.url("Endpoint: https://api.mspace.co.ke/smsapi/v2/resellerclienttopup")
```

```
.method("POST", body)
```

```
.addHeader("apikey", "myapikey")
```

```
.addHeader("Accept", "application/json")
```

```
.addHeader("Content-Type", "application/json")
```

```
.build();
```

```
Response response = client.newCall(request).execute();
```

GO

```
package main
```

```
import (
```

```
    "fmt"
```

```
    "strings"
```

```
    "net/http"
```

```
    "io/ioutil"
```

```
)
```

```
func main() {
```

```
    url := "Endpoint: https://api.mspace.co.ke/smsapi/v2/resellerclienttopup"
```

```
    method := "POST"
```

```
    payload := strings.NewReader(`{
```

```
    "username": "MyUsername",
```

```
    "clientname": "user2",
```

```
    "noOfSms": 1000
```

```
}`)
```

```
    client := &http.Client {
```

```
    }
```

```
req, err := http.NewRequest(method, url, payload)
```

```
if err != nil {  
    fmt.Println(err)  
    return  
}  
req.Header.Add("apikey", "myapikey")  
req.Header.Add("Accept", "application/json")  
req.Header.Add("Content-Type", "application/json")
```

```
res, err := client.Do(req)
```

```
if err != nil {  
    fmt.Println(err)  
    return  
}
```

```
defer res.Body.Close()
```

```
body, err := ioutil.ReadAll(res.Body)
```

```
if err != nil {  
    fmt.Println(err)  
    return  
}
```

```
fmt.Println(string(body))
```

```
}
```

PHP

```
<?php
```

```
$curl = curl_init();
```

```
curl_setopt_array($curl, array(
    CURLOPT_URL => 'Endpoint: https://api.mspace.co.ke/smsapi/v2/resellerclienttopup',
    CURLOPT_RETURNTRANSFER => true,
    CURLOPT_ENCODING => '',
    CURLOPT_MAXREDIRS => 10,
    CURLOPT_TIMEOUT => 0,
    CURLOPT_FOLLOWLOCATION => true,
    CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
    CURLOPT_CUSTOMREQUEST => 'POST',
    CURLOPT_POSTFIELDS => '{
        "username": "MyUsername",
        "clientname": "user2",
        "noOfSms": 1000
    }',
    CURLOPT_HTTPHEADER => array(
        'apikey: myapikey',
        'Accept: application/json',
        'Content-Type: application/json'
    ),
));

$response = curl_exec($curl);

curl_close($curl);
echo $response;
```

PYTHON

```
import http.client
```

```
import json
```

```
conn = http.client.HTTPSConnection("api.mspace.co.ke")
payload = json.dumps({
    "username": "MyUsername",
    "clientname": "user2",
    "noOfSms": 1000
})
headers = {
    'apikey': 'myapikey',
    'Accept': 'application/json',
    'Content-Type': 'application/json'
}
conn.request("POST", "/smsapi/v2/resellerclienttopup", payload, headers)
res = conn.getresponse()
data = res.read()
print(data.decode("utf-8"))
```

CURL

```
curl --location 'Endpoint: https://api.mspace.co.ke/smsapi/v2/resellerclienttopup' \
--header 'apikey: myapikey' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--data '{
    "username": "MyUsername",
    "clientname": "user2",
    "noOfSms": 1000
}'
```