

LIGO GNSS Processing: Implementation Modifications

Engineering Change Summary

2 August 2026

1 Scope

This document summarizes the modifications made to the LIGO GNSS processing pipeline. The work had two objectives: improve the structure and maintainability of the original monolithic GNSS processing implementation, add a base-station/rover carrier-phase processing path that produces a floating-point RTK solution through double-difference factors, and resolve validated carrier ambiguities to integers for a fixed RTK solution.

2 GNSS processing redesign

The large processing flow in `src/GNSS_Processing_fg.cpp` was separated into focused operations with explicit responsibilities. The extracted logic includes:

- GNSS buffer clearing and initialization-window shifting;
- receiver clock prediction;
- insertion of frame state estimates into GTSAM;
- extraction of optimized states from the iSAM2 estimate;
- carrier-phase history pruning by frame number and observation time;
- LiDAR information-matrix normalization; and
- selection of the first valid constellation clock bias during GNSS initialization.

Repeated buffer-management and state-copying blocks were replaced by these helpers. Factor insertion order and factor identifiers were retained so that the existing fixed-lag graph-deletion behavior remains compatible. LiDAR information normalization now detects a non-positive diagonal before scaling, preventing division by zero and marking the LiDAR update invalid for that epoch.

3 Base-station observation input

The new `BaseStationData` component reads surveyed base-station coordinates and carrier observations from RINEX 3.x observation data, with RINEX 3.02 verified explicitly. Its input may be a plain observation file, a ZIP archive containing an observation member, or a directory of files and archives. ZIP members are read in place through `libzip`; no manual extraction or CSV conversion is required. The base antenna position is read in Earth-Centered, Earth-Fixed (ECEF) coordinates from:

APPROX POSITION XYZ

The reader assembles multiline `SYS / ## / OBS TYPES` header records, reads primary/secondary/L5 carrier phase and LLI fields, applies GLONASS frequency channels, deduplicates multiple tracking codes on one satellite/frequency, and handles special RINEX event records. GPS and Galileo bands 1 and 5, BeiDou B1I (RINEX 3.02 band 1, with band 2 also accepted) and B2a, and GLONASS L1 are mapped to their physical carrier frequencies. UTC and BDT observation times are converted to GPST before epochs are stored and matched to the rover time within a configurable tolerance.

RINEX LLI and SSI fields do not encode carrier standard deviation, so the reader assigns the configured `base_carrier_std_cycles` value. It rejects malformed headers, absent ECEF coordinates, inconsistent positions across files, and inputs with no supported carrier observations. The active configuration points to `Data/2026-Aug-02_001813`, which contains the 08:00 and 09:00 GPST zipped HKSC observation files for 21 March 2025. These epochs overlap the rover bag in `Dataset`; the enclosing directory date is only the local download name.

4 Double-difference carrier factors

For every synchronized rover/base epoch, the processing pipeline performs the following operations:

1. Match rover and base observations by satellite and carrier frequency.
2. Retain the primary band and, when enabled, GPS L5, Galileo E5a, and BeiDou B2a observations at 1176.45 MHz.
3. Group observations by GNSS constellation and signal band.
4. Select the lowest-noise carrier observation in each constellation/band group as its reference satellite.
5. Form the carrier measurement double difference

$$\Delta\nabla L = (L_r^s - L_b^s) - (L_r^q - L_b^q),$$

where r and b denote rover and base receivers, s is the subject satellite, and q is the same-constellation reference satellite.

6. Add a geometric range double-difference factor and a persistent, real-valued ambiguity state to the iSAM2 graph.

Two factor variants were implemented in `include/gnss_factor/gnss_double_diff_carrier_factor.hpp`. The first uses the local LiDAR/IMU position together with the estimated local-to-ECEF alignment. The second directly uses the ECEF navigation state when LiDAR is disabled. Both factors include analytical Jacobians for the connected pose, position, alignment, and ambiguity variables.

The ambiguity associated with a satellite/reference/band tuple is initialized from the difference between measured and predicted geometry. It remains a continuous GTSAM `Vector1` state across epochs. A new ambiguity is created after a receiver or base loss-of-lock indication, an observation gap, or a change of reference pair. L1 and L5 therefore have independent ambiguity arcs and wavelengths. Until integer validation succeeds, these states provide the floating-point RTK solution.

5 LAMBDA integer ambiguity resolution

The new `LambdaAmbiguityResolver` implements integer least-squares decorrelation and search. Ambiguities and their full joint marginal covariance are converted from metres to cycles before resolution. Only same-frequency double differences are eligible; this excludes combinations whose metre-valued ambiguity cannot be represented by one integer wavelength. All eligible primary-band and L5 ambiguities enter the same joint covariance and integer search; no ionosphere-free carrier combination is used because that would destroy the direct integer nature of the original ambiguities.

Integer fixing is guarded by a minimum number of ambiguities, a continuous lock-epoch requirement, a maximum float standard deviation, and the ratio of the second-best to best LAMBDA squared residual. Partial ambiguity resolution removes the highest-variance ambiguity and retries when the complete set is not sufficiently precise or does not pass validation. Failure at any gate leaves the float graph unchanged.

After a successful ratio test, each accepted integer is converted back to metres and inserted as a tight ambiguity prior. iSAM2 is updated a second time in the same epoch, so the constrained navigation state is returned immediately. The constraint is held for the continuous ambiguity arc; a receiver/base loss-of-lock flag or observation gap starts a new float ambiguity instead of reusing the old integer.

6 Configuration

The following parameters were added to the GNSS section of `config/avia.yaml`:

Parameter	Default	Purpose
<code>use_double_differences</code>	true	Enable base/rover carrier factors
<code>use_secondary</code>	true	Add GPS L2, Galileo E5b, and BeiDou B2
<code>use_l5</code>	true	Add supported 1176.45 MHz carrier factors
<code>base_station_file</code>	HKSC directory	RINEX file, ZIP, or directory under <code>Data</code>
<code>base_epoch_tolerance</code>	0.05 s	Maximum rover/base epoch offset
<code>rtk_ambiguity_gap_tolerance</code>	1.5 s	Continuous-arc gate for 1 Hz base data
<code>base_carrier_std_cycles</code>	0.01 cycles	Assumed RINEX phase uncertainty
<code>double_difference_sigma</code>	0.02 m	Carrier factor standard deviation
<code>ambiguity_prior_sigma</code>	100 m	Loose float-ambiguity prior
<code>enable_integer_fixing</code>	true	Enable validated LAMBDA fixing
<code>lambda_min_ambiguities</code>	3	Smallest partial-fix subset for this dataset
<code>lambda_min_lock_epochs</code>	10	Required continuous ambiguity arc
<code>lambda_ratio_threshold</code>	3.0	Integer candidate ratio gate
<code>lambda_max_std_cycles</code>	0.25 cycles	Float precision gate
<code>fixed_ambiguity_sigma_cycles</code>	0.001 cycles	Fix-and-hold prior sigma
<code>rtk_debug</code>	true	Emit structured RTK diagnostics
<code>rtk_debug_epoch_interval</code>	10 epochs	Period for repeated float/DD reports

Double differences are enabled for the synchronized rover bag and the 08:00–10:00 GPST HKSC base observations.

7 RTK runtime diagnostics (2 August 2026)

Structured log messages now make the RTK state explicit. [RTK-DD] reports synchronized epochs, reference satellites per constellation/band, matched candidates, factors added, L5 factors,

new ambiguity arcs, cycle-slip resets, missing base epochs, zero-factor epochs, and cumulative DD totals. A new arc also prints its measured DD, geometric DD, and initial float ambiguity in metres and cycles.

[RTK-FLOAT] prints active float/fixed counts, lock progress, each eligible ambiguity estimate in cycles, and its marginal standard deviation. [RTK-LAMBDA] prints the attempt number, precision rejections, solver rejections, the best and second-best squared norms, ratio-test decisions, and each accepted integer with its float-to-fixed correction. A successful fix is unambiguous: the log contains `FIX SUCCESS` and the public status is `FIXED`. Statuses such as `FLOAT_WAITING_FOR_LOCK`, `FLOAT_REJECTED_PRECISION`, and `FLOAT_REJECTED_RATIO` identify why the solution remains float. Public counters expose attempts, successful fixes, and current float/fixed ambiguity counts to debuggers.

8 RTK continuity repair and replay (2 August 2026)

The ambiguity continuity gate is now independent of the 10 Hz rover sampling period. A 1.5 s RTK gap tolerance preserves arcs across consecutive 1 Hz RINEX epochs. RINEX LLI is interpreted as a bit mask: bits 0 and 1 invalidate an integer arc, while Galileo bit 2 only marks BOC tracking and no longer causes a false cycle-slip reset. Reference satellites are held while still observed, and LAMBDA is invoked only after an epoch actually adds DD factors.

The reader and DD classifier now include the second frequencies present in the bag: GPS L2, Galileo E5b, and BeiDou B2. Real-data compatibility consequently increased from 2975 to 4449 matched carriers and from 2100 to 3011 potential DD factors; the bag contains 31825 secondary-frequency observations and no L5.

A real ROS replay confirmed that ambiguity keys are reused across consecutive base epochs (for example the second synchronized epoch reported zero new or reset arcs). At lock epoch 10, LAMBDA executed with three eligible float ambiguities. Their marginal standard deviations were approximately 0.85–1.41 cycles, above the configured 0.25-cycle gate, so the integer fix was correctly rejected as `FLOAT_REJECTED_PRECISION`. The processing defect is repaired, but this replay does not claim a validated fixed solution.

9 Build and verification

The GNSS processor header and implementation now contain structured source annotations for the class lifecycle, graph-key convention, initialization branches, fixed-lag update, state import/export, satellite preparation, six factor-assembly stages, multi-frequency ambiguity arcs, and LAMBDA validation. The comments describe ownership, frames, and failure behavior rather than merely restating individual C++ expressions. A separate pipeline reference is provided in `paper/GNSS_Processing_fg_pipeline.tex`. The LAMBDA resolver is likewise annotated with its matrix convention, unimodular transform, integer Gauss operations, conditional-variance permutations, depth-first zig-zag enumeration, pruning radius, candidate ordering, back-transformation, and float-fallback failure behavior.

The build definition now compiles `src/BaseStationData.cpp` and `src/LambdaAmbiguityResolver.cpp` into `ligo_mapping`. The base reader and its test executable link `libzip`. The package-level CMake configuration no longer overwrites a caller-supplied build type, which also resolves a mismatch between the package and catkin’s bundled GoogleTest library.

The complete ROS executable was built and linked successfully with a single-job Release build. Base-file parsing remains in `test/test_base_station_data.cpp`. A separate RTK core suite in `test/test_rtk_core.cpp` verifies both double-difference factor variants, including zero residuals and every analytical Jacobian against central finite differences. It also verifies a known correlated LAMBDA solution, candidate ordering, integer-translation invariance, invalid-input rejection, and 40 deterministic covariance cases against exhaustive integer search.

The RTK suite also verifies primary/secondary/L5 classification, LLI bit-mask handling, RTK gap continuity, frequency-specific base matching, disabling L5, and rejection of unsupported GLONASS L5. The base reader suite verifies a compact multiline RINEX 3.02 fixture and directly loads the two actual HKSC ZIP archives, including multi-frequency extraction, surveyed ECEF coordinates, aggregation across both hours, epoch matching, and a flag-4 receiver event. A separate diagnostic test prints per-constellation primary and L5/E5a satellite counts from the first epoch of the actual HKSC ZIP. A rosbag compatibility test scans all 3040 rover epochs and reports 304 synchronized epochs, 4449 matched carrier observations, and 3011 potential DD factors. The four LIGO test executables reported fifteen passing tests. The complete catkin result collector, including the workspace’s generated test records, reported:

30 tests, 0 errors, 0 failures, 0 skipped.

The bag contains no 1176.45 MHz rover observations, so the real-data path can exercise L1 but not L5. A headless replay loads and initializes the IMU, but does not reach GNSS graph processing because the bag publishes `livox_ros_driver2/CustomMsg` while this repository consumes `livox_ros_driver/CustomMsg`; the experimental no-LiDAR loop also does not dispatch the GNSS callback. A message adapter or driver-2 port is needed for a complete factor-graph replay and runtime accuracy evaluation.