

Transport:

TCP/IP

Routing and Configuration Information:

Save Bytes (Primary)

Mnemonic (Secondary)

- The site assigned ORI for a device (or for the site) should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.
- The assigned Mnemonic for a device should be placed in the **<Authentication>/<Mnemonic>** field in the ConnectCIC header.
- The assigned User ID should be placed in the **<Authentication>/<UserName>** field in the ConnectCIC header.
- The agency assigned Terminal Identifier should be placed in the **<Authentication>/<DeviceId>** field in the ConnectCIC header. This field is required only when CLETS mnemonic pooling is used. If this field is not provided, the IP Address of the ConnectCIC server on the state network is used.

Security Requirements:

Agency must adhere to all requirements set forth by San Luis Obispo for operation of a direct connection.

Logon Requirements:

None

Transaction Requirements:

Beginning July 21, 2021 CLETS requires a “Purpose Code” field to be supplied with every CLETS transaction. The information regarding this purpose code was published by CLETS in Information Bulletin 20-03-CJIS and covers the “Purpose Code” field added to satisfy Assembly Bill (AB) 1747.

Any transaction which does not supply a valid Purpose Code value will be rejected by CLETS. ConnectCIC does not default the value of field; it must be provided by the partner implementation as a user selectable field.

The CLETS “Purpose Code” value must be supplied to ConnectCIC via the **<CaRequestPurposeCode>** element as a sibling to the transaction-specific elements

covered in this document. The <CaRequestPurposeCode> element is mandatory for all transactions.

The element is a single character value which may be one of the following:

- C – Criminal Justice
- I – Immigration Enforcement
- U – Investigate Violations of Title 8, section 1325 of the United States Code

Certification Requirements:

None

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV(IDOT) (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleBrand	ArticleBrand	C	6	
ArticleCategory	ArticleCategory	O	1	
ArticleSerialNumber	ArticleSerialNumber	C	20	
ArticleTypeCode	ArticleTypeCode	C	6	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleBrand, [ArticleCategory]
2. (In/Out) ArticleSerialNumber, ArticleTypeCode, [ArticleCategory]

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	20	
RegistrationNumber	RegistrationNumber	C	8	
State	State	O	2	

Possible Combinations

1. (In/Out) BoatHullIdNumber, [State]
2. (In/Out) RegistrationNumber, [State]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	

PurposeCode	PurposeCode	O	1	
SexCode	SexCode	C	1	
State	State	C	2	

Possible Combinations

1. (In) Name, [BirthDate]
2. (In) OperatorLicenseNumber
3. (Out) BirthDate, Name, SexCode, State, [Attention, PurposeCode]
4. (Out) OperatorLicenseNumber, State, [Attention, PurposeCode]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	C	1	
State	State	O	2	

Possible Combinations

1. (In) Name, [BirthDate]
2. (In) OperatorLicenseNumber
3. (Out) Name, BirthDate, SexCode, [State]
4. (Out) OperatorLicenseNumber, [State]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	O	3	
GunSerialNumber	GunSerialNumber	C	20	
GunTypeCode	GunTypeCode	O	2	

Possible Combinations

1. (In/Out) GunSerialNumber, [GunCaliber, GunMake, GunTypeCode]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	AP, CO, TK, TR, MC, RE, PE, TL, PC, AQ, AT, DX, EX, DL, AR, IP, TM
LicensePlateYear	LicensePlateYear	C	4	
State	State	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	30	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In) LicensePlateNumber, LicensePlateTypeCode
2. (In) VehicleIdentificationNumber, [VehicleMakeCode]
3. (Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, State
4. (Out) VehicleIdentificationNumber, State [VehicleMakeCode, VehicleYear]

Transactions Supported:

None

Expanded Transactions Supported:

None

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- CLETS System TCP/IP Spec.
- CLETS CLEW Website Documentation
- Various supporting documents including NCIC 2000 message switch/implementation updates