

California (CA) ASAFE

[Disclaimer Statement](#)

This section only covers CLETS and ASAFE queries through the San Bernardino message switch. If you are looking for information on the direct CLETS interface please refer to the following section: [CA CLETS.htm](#).

To request metadata for this interface, enter 'CA_ASAFE' in the <State> field on all metadata requests.

Transport:

TCP/IP CLETS (San Bernardino Regional Interface)

Routing and Configuration Information:

Save Bytes (Primary)

Mnemonic (Secondary)

- The CLETS assigned ORI for a device (or for the site) should be placed in the <Authentication>/<ORI> field in the ConnectCIC header.
- The CLETS assigned Mnemonic for a device should be placed in the <Authentication>/<Mnemonic> field in the ConnectCIC header.
- The CLETS assigned User ID should be placed in the <Authentication>/<UserName> field in the ConnectCIC header.
- A valid CLETS Purpose Code value must be supplied in the <CaRequestPurposeCode> element of the ConnectCIC transaction body as a sibling to all other transaction-specific fields. For more information about the CaRequestPurposeCode element, see the Transaction Requirements section below.

Security Requirements:

None

Logon Requirements:

None

Transaction Requirements:

Beginning July 21, 2021 CLETS requires a "Purpose Code" field to be supplied with every CLETS transaction. The information regarding this purpose code was published by CLETS in Information Bulletin 20-03-CJIS and covers the "Purpose Code" field added to satisfy Assembly Bill (AB) 1747.

Any transaction which does not supply a valid Purpose Code value will be rejected by CLETS. ConnectCIC does not default the value of field; it must be provided by the partner implementation as a user selectable field.

The CLETS “Purpose Code” value must be supplied to ConnectCIC via the **<CaRequestPurposeCode>** element as a sibling to the transaction-specific elements covered in this document. The **<CaRequestPurposeCode>** element is mandatory for all transactions.

The element is a single character value which may be one of the following:

- **C** – Criminal Justice
- **I** – Immigration Enforcement
- **U** – Investigate Violations of Title 8, section 1325 of the United States Code

Certification Requirements:

None

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV(IDOT) (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleBrand	ArticleBrand	O	6	
ArticleCategory	ArticleCategory	O	1	
ArticleSerialNumber	ArticleSerialNumber	C	11	
ArticleTypeCode	ArticleTypeCode	O	6	
OwnerAppliedNumber	OwnerAppliedNumber	C	20	

Possible Combinations

1. (In/Out) ArticleSerialNumber, [ArticleBrand, ArticleCategory, ArticleTypeCode]
2. (In/Out) OwnerAppliedNumber, [ArticleBrand, ArticleCategory, ArticleTypeCode]

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
BoatHullIdNumber	BoatHullIdNumber	C	20	
Name	Name	C	30	
OwnerAppliedNumber	OwnerAppliedNumber	C	20	
RegistrationNumber	RegistrationNumber	C	8	
State	State	O	2	

Possible Combinations

1. (In/Out) BoatHullIdNumber
2. (In/Out) OwnerAppliedNumber
3. (In/Out) RegistrationNumber, [State]
4. (Out) BirthDate, Name, State
5. (Out) BoatHullIdNumber, State
6. (Out) RegistrationNumber, State

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
ORI	ORI	O	9	
PurposeCode	PurposeCode	O	1	
SexCode	SexCode	C	1	
State	State	O	2	

Possible Combinations *(fields within the square brackets are optional)*

1. Name, BirthDate, SexCode, [State, PurposeCode, Attention]
2. OperatorLicenseNumber [State, PurposeCode, Attention]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
CriminalIdNumber	CriminalIdNumber	C	11	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	C	11	
State	State	O	2	

Possible Combinations

1. (In) Name
2. (In) OperatorLicenseNumber
3. (In/Out) CriminalIdNumber, [OperatorLicenseNumber, SocialSecurityNumber]
4. (In/Out) Name, [SexCode]
5. (In/Out) OperatorLicenseNumber, [CriminalIdNumber, SocialSecurityNumber]
6. (In/Out) SocialSecurityNumber, [CriminalIdNumber, OperatorLicenseNumber]
7. (Out) Name, State, [SexCode]
8. (Out) OperatorLicenseNumber, State

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	O	2	
BirthDate	BirthDate	O	8	
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	O	3	
GunSerialNumber	GunSerialNumber	C	20	
GunTypeCode	GunTypeCode	O	2	

Name	Name	C	30	
------	------	---	----	--

Possible Combinations

1. (In/Out) GunSerialNumber, [GunCaliber, GunMake, GunTypeCode]
2. (In/Out) Name, [Age]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
State	State	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	30	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In) LicensePlateNumber
2. (In) VehicleIdentificationNumber
3. (In/Out) LicensePlateNumber, [State]
4. (In/Out) VehicleIdentificationNumber, [VehicleMakeCode]
5. (Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, State, [VehicleMakeCode, VehicleYear]
6. (Out) VehicleIdentificationNumber, State, [VehicleMakeCode, VehicleYear]

Transactions Supported:

None

Expanded Transactions Supported:

CaAsafePersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	13	
AddressCountyCode	AddressCountyCode	O	2	
AddressStreetNumber	AddressStreetNumber	O	3	
Age	Age	C	2	
BirthDate	BirthDate	C	6	
CriminalIdentificationNumber	CriminalIdentificationNumber	O	9	
ExpandedNameSearchIndicator	ExpandedNameSearchIndicator	O	1	
FBI Number	FBI Number	O	9	
FileControlNumber	FileControlNumber	O	13	
FromAge	FromAge	C	2	
Height	Height	O	3	
Name	Name	M	10	
NCICNumber	NCICNumber	O	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	8	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
RaceCode	RaceCode	O	1	
SexCode	SexCode	C	1	

SocialSecurityNumber	SocialSecurityNumber	O	9	
StateIdNumber	StateIdNumber	O	9	
ToAge	ToAge	C	2	
ZoneCode	ZoneCode	O	1	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, [CriminalIdentificationNumber, FBINumber, FileControlNumber, FromAge, NCICNumber, OperatorLicenseNumber, OperatorLicenseStateCode, RaceCode, SocialSecurityNumber, StateIdNumber, ToAge]
2. (In/Out) FromAge, Name, SexCode, ToAge, [BirthDate, CriminalIdentificationNumber, FBINumber, FileControlNumber, NCICNumber, OperatorLicenseNumber, OperatorLicenseStateCode, RaceCode, SocialSecurityNumber, StateIdNumber]
3. (In/Out) Name, [AddressCity, AddressCountyCode, AddressStreetNumber, Age, BirthDate, ZoneCode]
4. (In/Out) Name, SexCode, [AddressCountyCode, Age, BirthDate, ExpandedNameSearchIndicator, Height, OriginatingAgencyORI, RaceCode]

CAIMissingPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	C	2	
Area	Area	O	3	
BirthDate	BirthDate	C	8	
DentalCharacteristics	DentalCharacteristics	C	64	
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	
EyeColorCode	EyeColorCode	C	4	
FBINumber	FBINumber	C	9	
FileControlNumber	FileControlNumber	C	13	
HairColorCode	HairColorCode	C	4	
Height	Height	C	3	
LastContactDate	LastContactDate	O	8	
LicensePlateNumber	LicensePlateNumber	C	10	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NcicOnlyIndicator	NcicOnlyIndicator	C	1	Y – Yes N – No
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	C	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleColorPrimaryCode	VehicleColorPrimaryCode	C	7	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	24	
VehicleModelCode	VehicleModelCode	O	3	
VehicleStyleCode	VehicleStyleCode	O	2	
VehicleYear	VehicleYear	O	4	
Weight	Weight	C	3	

Possible Combinations

1. (In/Out) Age, EyeColorCode, HairColorCode, Height, Name, NcicOnlyIndicator, RaceCode, SexCode, Weight, [ExpandedNameSearchCode]
2. (In/Out) Age, Height, RaceCode, SexCode, [Area, EyeColorCode, HairColorCode, LastContactDate, ScarsMarksTattoosCode, Weight]
3. (In/Out) Age, Name, SexCode, [ExpandedNameSearchCode, EyeColorCode, HairColorCode, Height, LastContactDate, RaceCode, RelatedHitSearchIndicator, Weight]
4. (In/Out) BirthDate, Name, NcicOnlyIndicator, SexCode, [ExpandedNameSearchCode]
5. (In/Out) BirthDate, Name, SexCode, [ExpandedNameSearchCode, EyeColorCode, HairColorCode, Height, LastContactDate, RaceCode, RelatedHitSearchIndicator, Weight]
6. (In/Out) DentalCharacteristics
7. (In/Out) FBI Number, Name, NcicOnlyIndicator, SexCode, [ExpandedNameSearchCode]
8. (In/Out) FileControlNumber
9. (In/Out) LicensePlateNumber
10. (In/Out) LicensePlateNumber, NcicOnlyIndicator
11. (In/Out) MiscellaneousNumber, Name, NcicOnlyIndicator, SexCode, [ExpandedNameSearchCode]
12. (In/Out) Name, NcicOnlyIndicator, OperatorLicenseNumber, SexCode, [ExpandedNameSearchCode]
13. (In/Out) Name, NcicOnlyIndicator, OriginatingAgencyCaseNumber, SexCode, [ExpandedNameSearchCode]
14. (In/Out) Name, NcicOnlyIndicator, SexCode, SocialSecurityNumber, [ExpandedNameSearchCode]
15. (In/Out) Name, NcicOnlyIndicator, SexCode, VehicleIdentificationNumber, [ExpandedNameSearchCode]
16. (In/Out) Name, SexCode, [ExpandedNameSearchCode, EyeColorCode, HairColorCode, Height, LastContactDate, RaceCode, RelatedHitSearchIndicator, Weight]
17. (In/Out) NCICNumber, NcicOnlyIndicator
18. (In/Out) OperatorLicenseNumber
19. (In/Out) OriginatingAgencyCaseNumber
20. (In/Out) VehicleColorPrimaryCode, VehicleMakeCode, [VehicleModelCode, VehicleStyleCode, VehicleYear]

CAIUnidentifiedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCountyCode	AddressCountyCode	O	2	
Age	Age	C	3	
BodyPartStatusCode	BodyPartStatusCode	C	14	
DentalCharacteristics	DentalCharacteristics	C	7	
EstimatedDeathDate	EstimatedDeathDate	O	8	
EyeColorCode	EyeColorCode	C	3	
FileControlNumber	FileControlNumber	C	13	
HairColorCode	HairColorCode	C	3	
Height	Height	C	3	
NCICNumber	NCICNumber	C	10	
NcicOnlyIndicator	NcicOnlyIndicator	C	1	Y – Yes N - No
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	
RaceCode	RaceCode	C	1	
SexCode	SexCode	C	1	
Weight	Weight	C	3	

Possible Combinations

1. (In/Out) Age, EyeColorCode, HairColorCode, Height, NcicOnlyIndicator, RaceCode, SexCode, Weight
2. (In/Out) Age, Height, RaceCode, SexCode, [AddressCountyCode, EyeColorCode, HairColorCode, ScarsMarksTattoosCode, Weight]
3. (In/Out) BodyPartStatusCode, [AddressCountyCode, SexCode]
4. (In/Out) DentalCharacteristics
5. (In/Out) FileControlNumber
6. (In/Out) NCICNumber, NcicOnlyIndicator
7. (In/Out) NcicOnlyIndicator, OriginatingAgencyCaseNumber
8. (In/Out) OriginatingAgencyCaseNumber

HazardousMaterialQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
UnitedNationsNumber	UnitedNationsNumber	M	4	

Possible Combinations

1. (In/Out) UnitedNationsNumber

RegionalNameCheckQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
CriminalIdentificationNumber	CriminalIdentificationNumber	C	9	
FBINumber	FBINumber	C	9	
FileControlNumber	FileControlNumber	C	13	
FromAge	FromAge	C	2	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	C	8	
RaceCode	RaceCode	O	1	
SearchFieldCode	SearchFieldCode	C	1	This field is used to select a single system, otherwise if left empty all will be queried. S – SAW A – APROB J – JPROB
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateAbbreviation	StateAbbreviation	C	2	
StateIdNumber	StateIdNumber	C	9	
ToAge	ToAge	C	2	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode [RaceCode, SearchFieldCode]
2. (In/Out) FromAge, Name, SexCode, ToAge [RaceCode, SearchFieldCode]
3. (In/Out) OperatorLicenseNumber, StateAbbreviation, [SearchFieldCode]
4. (In/Out) FileControlNumber, [SearchFieldCode]
5. (In/Out) SocialSecurityNumber, [SearchFieldCode]
6. (In/Out) NCICNumber, [SearchFieldCode]
7. (In/Out) CriminalIdentificationNumber, [SearchFieldCode]
8. (In/Out) StateIdNumber, [SearchFieldCode]
9. (In/Out) FBINumber, [SearchFieldCode]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- CLETS System TCP/IP Spec.
- CLETS CLEW Website Documentation
- Various supporting documents including NCIC 2000 message switch/implementation updates
- ExternalMSSInterfaceRev1_ASFAE.doc