

California (CA) CLETS Humboldt County Switch

[Disclaimer Statement](#)

This section only covers CLETS queries through the Humboldt County message switch. If you are looking for information on the direct CLETS interface please refer to the following section: [CA_CLETS.htm](#).

To request metadata for this interface, enter 'CA_CLETS_DB' in the <State> field on all metadata requests.

Transport:

Database (ODBC)

Routing and Configuration Information:

Save Bytes (Primary)

DeviceId (Secondary)

- The CLETS assigned ORI for a device (or for the site) should be placed in the <Authentication>/<ORI> field in the ConnectCIC header.
- The Humboldt assigned Station ID should be placed in the <Authentication>/<DeviceId> field in the ConnectCIC header.

To receive responses, create an entry into the Alias Configuration Tool with a DeviceId set to the name of the device (Station ID).

Security Requirements:

None

Logon Requirements:

Use LogonRequest transaction with a valid UserName and Password to initiate a session with the Humboldt County switch. Use the corresponding LogoffTransaction with the same UserName to terminate the session.

Certification Requirements:

None

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV(IDOT) (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Query Transactions:

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCounty	AddressCounty	O	3	
Age	Age	C	2	
BirthDate	BirthDate	C	8	
CriminalIdNumber	CriminalIdNumber	C	11	
Height	Height	O	3	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
RaceCode	RaceCode	O	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	11	
State	State	O	2	

Possible Combinations

1. (In) Name
2. (In) OperatorLicenseNumber
3. (In/Out) Age, Name, SexCode, [AddressCounty, Height, RaceCode]
4. (In/Out) BirthDate, Name, SexCode, [AddressCounty, Age, Height, RaceCode]
5. (In/Out) CriminalIdNumber, [OperatorLicenseNumber, SocialSecurityNumber]
6. (In/Out) OperatorLicenseNumber, [CriminalIdNumber, SocialSecurityNumber]
7. (In/Out) SocialSecurityNumber, [CriminalIdNumber, OperatorLicenseNumber]
8. (Out) BirthDate, Name, SexCode, [State]
9. (Out) OperatorLicenseNumber, [State]

Transactions Supported:

None

Expanded Transactions Supported:

LogoffRequest

Field Name	XML Tag Name	M/C/O	Size	Possible Values
UserName	UserName	M	30	

Possible Combinations

1. (In/Out) UserName

LogonRequest

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Password	Password	M	10	
UserName	UserName	M	30	

Possible Combinations

1. (In/Out) Password, UserName

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

Receiving responses for a device is done by adding an entry into the Alias Configuration Tool with a DeviceId set to the name of the device (Station ID).

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- CLETS CLEW Website Documentation
- Various supporting documents including NCIC 2000 message switch/implementation updates
- Humboldt CLETS Inquiry Functionality document