

Canada (CN_CPIC_MQ)

[Disclaimer Statement](#)

This section only covers Canadian queries through the CPIC MQ message switch.

Transport:

Oracle MQ CLIENT

Routing and Configuration Information:

Save Bytes (Primary)

Mnemonic (Secondary)

- The assigned Mnemonic for a device should be placed in the **<Authentication>/<Mnemonic>** field in the ConnectCIC header.
- The assigned user name for a user should be placed in the **<Authentication>/<UserName>** field in the ConnectCIC header.

Security Requirements:

None

Logon Requirements:

None

Certification Requirements:

None

Data-Mined Transactions:

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalRecords	AdditionalRecords	O	2	
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	O	2	AA, BI, BU, CO, HH, JE, MI, MT, OM, OT, PA, PE, PH, RA, SC, SP
QueryReason	QueryReason	M	3	ADM, CP, INV
RecordStartNumber	RecordStartNumber	O	3	
Remarks	Remarks	M	30	

UserName	UserName	O	10	
----------	----------	---	----	--

Possible Combinations

1. (In/Out) ArticleSerialNumber, QueryReason, Remarks, [AdditionalRecords, ArticleTypeCode, RecordStartNumber, UserName]

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalRecords	AdditionalRecords	O	2	
BoatHullIdNumber	BoatHullIdNumber	C	20	
BROIndicator	BROIndicator	O	1	
QueryReason	QueryReason	M	3	ADM, CP, INV
RecordStartNumber	RecordStartNumber	O	3	
RegistrationNumber	RegistrationNumber	C	8	
Remarks	Remarks	M	30	
UserName	UserName	O	10	

Possible Combinations

1. (In/Out) BoatHullIdNumber, QueryReason, Remarks, [AdditionalRecords, BROIndicator, RecordStartNumber, UserName]
2. (In/Out) RegistrationNumber, QueryReason, Remarks, [AdditionalRecords, BROIndicator, RecordStartNumber, UserName]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalRecords	AdditionalRecords	O	2	
Age	Age	O	3	
BirthDate	BirthDate	O	8	
GivenName	GivenName	O	20	
GivenName2	GivenName2	O	20	
GivenName3	GivenName3	O	20	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
Province	Province	C	2	
QueryReason	QueryReason	C	3	ADM, CP, INV
RaceCode	RaceCode	O	1	
RecordStartNumber	RecordStartNumber	O	3	
Remarks	Remarks	C	30	
SexCode	SexCode	O	1	
Surname	Surname	C	40	
UserName	UserName	O	10	

Possible Combinations

1. (In/Out) OperatorLicenseNumber, Province
2. (In/Out) QueryReason, Remarks, Surname, [AdditionalRecords, Age, BirthDate, GivenName, GivenName2, GivenName3, Province, RaceCode, RecordStartNumber, SexCode, UserName]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalRecords	AdditionalRecords	O	2	

Age	Age	O	3	
BirthDate	BirthDate	O	10	
GivenName	GivenName	O	20	
GivenName2	GivenName2	O	20	
GivenName3	GivenName3	O	20	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
Province	Province	O	2	
QueryReason	QueryReason	C	3	ADM, CP, INV
RaceCode	RaceCode	O	1	
RecordStartNumber	RecordStartNumber	O	3	
Remarks	Remarks	C	30	
SexCode	SexCode	O	1	
Surname	Surname	C	40	
UserName	UserName	O	10	

Possible Combinations

1. (In/Out) OperatorLicenseNumber, [Province]
2. (In/Out) QueryReason, Remarks, Surname, [AdditionalRecords, Age, BirthDate, GivenName, GivenName2, GivenName3, OperatorLicenseNumber, Province, RaceCode, RecordStartNumber, SexCode, UserName]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalRecords	AdditionalRecords	O	2	
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	O	3	
GunSerialNumber	GunSerialNumber	M	23	
QueryReason	QueryReason	M	3	
RecordStartNumber	RecordStartNumber	O	3	
Remarks	Remarks	M	30	
UserName	UserName	O	10	

Possible Combinations

1. (In/Out) GunSerialNumber, QueryReason, Remarks, [AdditionalRecords, GunCaliber, GunMake, RecordStartNumber, UserName]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalRecords	AdditionalRecords	O	2	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateYear	LicensePlateYear	O	4	
Province	Province	O	2	
QueryReason	QueryReason	M	3	
RecordStartNumber	RecordStartNumber	O	3	
Remarks	Remarks	M	30	
UserName	UserName	O	10	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In/Out) QueryReason, Remarks, LicensePlateNumber, [AdditionalRecords, LicensePlateYear, Province, RecordStartNumber, UserName]

2. (In/Out) QueryReason, Remarks, VehicleIdentificationNumber, [AdditionalRecords, Province, RecordStartNumber, UserName]

Transactions Supported:

Wanted Missing Person Inquiries (WMP-I)

WMPIMissingPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalRecords	AdditionalRecords	O	2	
Age	Age	O	3	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	3	
GivenName	GivenName	O	20	
GivenName2	GivenName2	O	20	
GivenName3	GivenName3	O	20	
QueryReason	QueryReason	M	3	
RaceCode	RaceCode	O	1	
RecordStartNumber	RecordStartNumber	O	3	
Remarks	Remarks	M	30	
SexCode	SexCode	M	1	
Surname	Surname	M	40	
UserName	UserName	O	10	
UsState	UsState	O	2	

Possible Combinations

1. (In/Out) QueryReason, Remarks, SexCode, Surname, [AdditionalRecords, Age, BirthDate, BirthPlaceCode, GivenName, GivenName2, GivenName3, RaceCode, RecordStartNumber, UserName, UsState]

WMPIWantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalRecords	AdditionalRecords	O	2	
Age	Age	O	3	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	3	
CNIQueryLevel	CNIQueryLevel	O	1	3,4,5,6,7
EyeColorCode	EyeColorCode	O	6	
FBINumber	FBINumber	O	9	
GivenName	GivenName	O	20	
GivenName2	GivenName2	O	20	
GivenName3	GivenName3	O	20	
HeightMetric	HeightMetric	O	3	
Interpol	Interpol	O	4	Y, ONLY
PurposeCode	PurposeCode	O	1	C, J
QueryReason	QueryReason	O	3	ADM, CP, INV
RaceCode	RaceCode	O	1	W, N, U
Reason	Reason	O	2	A, B, C, D

RecordStartNumber	RecordStartNumber	O	3	
Remarks	Remarks	O	30	
RSVP	RSVP	O	12	
SexCode	SexCode	O	1	F, M, U, O
StateIdNumber	StateIdNumber	O	10	
Surname	Surname	M	40	
UserName	UserName	O	10	
UsState	UsState	O	2	
WeightMetric	WeightMetric	O	3	

Possible Combinations

1. (In/Out) Remarks, Surname, [AdditionalRecords, Age, BirthDate, BirthPlaceCode, CNIQueryLevel, EyeColorCode, FBINumber, GivenName, GivenName2, GivenName3, HeightMetric, Interpol, PurposeCode, QueryReason, RaceCode, Reason, RecordStartNumber, RSVP, SexCode, StateIdNumber, UserName, UsState, WeightMetric]

Expanded Transactions Supported:

CnBoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalRecords	AdditionalRecords	O	2	
BoatHullIdNumber	BoatHullIdNumber	C	20	
BROIndicator	BROIndicator	O	1	
MotorMake	MotorMake	O	20	
MotorSerialNumber	MotorSerialNumber	C	8	
MotorType	MotorType	O	20	
QueryReason	QueryReason	O	3	
RecordStartNumber	RecordStartNumber	O	3	
RegistrationNumber	RegistrationNumber	C	8	
Remarks	Remarks	O	30	
UserName	UserName	O	10	

Possible Combinations

1. (In/Out) QueryReason, Remarks, BoatHullIdNumber, [AdditionalRecords, BROIndicator, RecordStartNumber, UserName]
2. (In/Out) QueryReason, Remarks, MotorSerialNumber, [AdditionalRecords, BROIndicator, MotorMake, MotorType, RecordStartNumber, UserName]
3. (In/Out) QueryReason, Remarks, RegistrationNumber, [AdditionalRecords, BROIndicator, RecordStartNumber, UserName]

CnGunCFROQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCounty	AddressCounty	C	35	See Note*
AddressLocation	AddressLocation	C	14	See Note*
AddressMunicipality	AddressMunicipality	C	35	See Note*
AddressStreetDirection	AddressStreetDirection	O	2	
AddressStreetName	AddressStreetName	C	35	See Note*
AddressStreetNameSecond	AddressStreetNameSecond	O	6	
AddressStreetNumber	AddressStreetNumber	C	6	See Note*
AddressStreetType	AddressStreetType	O	10	
AddressTownship	AddressTownship	C	35	See Note*

AddressZipCode	AddressZipCode	O	6	
Age	Age	O	3	
BirthDate	BirthDate	O	8	
BusinessName	BusinessName	C	40	
GivenName	GivenName	O	20	
GivenName2	GivenName2	O	20	
GivenName3	GivenName3	O	20	
Province	Province	C	4	See Note*
RecordStartNumber	RecordStartNumber	O	3	
Remarks	Remarks	M	30	
SexCode	SexCode	O	1	
Surname	Surname	C	40	
TelephoneNumber	TelephoneNumber	C	10	
UserName	UserName	O	10	

***NOTE:** Address queries must include Province with AddressStreetNumber and AddressStreetName or AddressLocation. It must also include AddressMunicipality or AddressTownship or AddressCounty.

Possible Combinations

1. (In/Out) BusinessName, Remarks, [RecordStartNumber, UserName]
2. (In/Out) Province, Remarks, [AddressCounty, AddressLocation, AddressMunicipality, AddressStreetDirection, AddressStreetName, AddressStreetNameSecond, AddressStreetNumber, AddressStreetType, AddressTownship, AddressZipCode, RecordStartNumber, UserName]
3. (In/Out) Surname, Remarks, [Age, BirthDate, GivenName, GivenName2, GivenName3, RecordStartNumber, SexCode, UserName]
4. (In/Out) TelephoneNumber, Remarks, [RecordStartNumber, UserName]

DriverLicenseCFROQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalRecords	AdditionalRecords	O	2	
Age	Age	O	3	
BirthDate	BirthDate	O	10	
CFROIndicator	CFROIndicator	O	1	Y, N
GivenName	GivenName	O	20	
GivenName2	GivenName2	O	20	
GivenName3	GivenName3	O	20	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
Province	Province	O	2	
QueryReason	QueryReason	O	3	
RaceCode	RaceCode	O	1	
RecordStartNumber	RecordStartNumber	O	3	
Remarks	Remarks	O	30	
SexCode	SexCode	O	1	
Surname	Surname	C	40	
UserName	UserName	O	10	

Possible Combinations

1. (In/Out) OperatorLicenseNumber, [Province]

2. (In/Out) Remarks, QueryReason, Surname, SexCode, [AdditionalRecords, Age, BirthDate, CFROIndicator, GivenName, GivenName2, GivenName3, OperatorLicenseNumber, Province, RaceCode, RecordStartNumber, UserName]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- External CPIC MOM Interface Specification.pdf