

Colorado (CO) CBI

[Disclaimer Statement](#)

Transport:

TCPIP

Frame <STX> <ETX>

Routing and Configuration Information:

Mnemonic Routing.

ORI required.

- The CBI assigned ORI for a device (or for the site) should be placed in the <**Authentication**>/<**ORI**> field in the ConnectCIC header.
- The CBI assigned Mnemonic for a device should be placed in the <**Authentication**>/<**Mnemonic**> field in the ConnectCIC header.
- The CBI assigned Login ID should be placed in the <**Authentication**>/<**UserName**> field in the ConnectCIC header.

Security Requirements:

Vendor employees who could be exposed to CJIS data must be fingerprinted for background checks for sponsor site (i.e. first agency in state).

Logon Requirements:

Each user must have a login number supplied by CBI. The user must log into CBI before running any inquiries.

Logon: <UserName>, **Exp:** Logon Expiration is by Time (Military)

Logoff: User will be automatically logged off when time equals what was entered in Logon Expiration field.

Certification Requirements:

Agency sponsor is required.

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

Note: The ORI is a required field for each message transaction, please be sure to include the ORI in the header of each transaction to ConnectCIC.

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Article Brand	ArticleBrand	O	2-6	
Article Type Code	ArticleTypeCode	O	4-7	
FormORI	FormORI	O	9	
Serial Number	ArticleSerialNumber	C	1-20	
Unit Number	UnitId	O	1-5	

Possible Combinations (fields within the square brackets are optional)

1. ArticleSerialNumber [ArticleTypeCode, ArticleBrand, FormORI, UnitId]

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Boat Hull Identification Number	BoatHullIdNumber	C	1-20	
FormORI	FormORI	O	9	
Registration Expiration Year	RegistrationExpirationYear	O	2-4	
Registration Number	RegistrationNumber	C	1-8	
Registration State Code	State	O	2-2	
Unit Number	UnitId	O	1-5	

Possible Combinations (fields within the square brackets are optional)

1. BoatHullIdNumber [FormORI, UnitId]
2. RegistrationNumber [FormORI, State, RegistrationExpirationYear, UnitId]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Birth Date	BirthDate	C	8-8	
FormORI	FormORI	O	9	
Name	Name	C	3-30	
Operator License Number	OperatorLicenseNumber	C	1-20	
State	State	O	2-2	
Property Code	PropertyCode	O	1-1	
Reason Code	ReasonCode	O	1-1	
Sex Code	SexCode	C	1-1	
Unit Number	UnitId	O	1-5	

Possible Combinations (fields within the square brackets are optional)

1. Name, BirthDate, SexCode [FormORI, State, UnitId]
2. OperatorLicenseNumber [FormORI, State, PropertyCode, ReasonCode, UnitId]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FormORI	FormORI	O	9	
Gun Make	GunMake	O	2-23	
Gun Caliber	GunCaliber	O	1-4	
Serial Number	GunSerialNumber	C	1-20	
Unit Number	UnitId	O	1-5	

Possible Combinations (fields within the square brackets are optional)

1. GunSerialNumber [FormORI, GunMake, GunCaliber, UnitId]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FormORI	FormORI	O	9	
License Plate Number	LicensePlateNumber	C	1-10	
State	State	O	2-2	
License Plate Type Code	LicensePlateTypeCode	O	2-2	
License Plate Year	LicensePlateYear	O	2-4	
Property Code	PropertyCode	O	1-1	
Reason Code	ReasonCode	O	1-1	
Vehicle Identification Number	VehicleIdentificationNumber	C	1-20	
Vehicle Make Code	VehicleMakeCode	O	2-24	
Vehicle Year	VehicleYear	O	2-4	
Unit Number	UnitId	O	1-5	

Possible Combinations (fields within the square brackets are optional)

1. LicensePlateNumber [FormORI, State, LicensePlateTypeCode, LicensePlateYear, UnitId]
2. VehicleIdentificationNumber [FormORI, State, PropertyCode, ReasonCode, VehicleYear, VehicleMakeCode, UnitId]

Transactions Supported:

Computerized Criminal History (CCH)

CCHCriminalHistoryAQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
DestinationORI	DestinationORI	M	9	
FormORI	FormORI	O	9	
FreeText	FreeText	O	14400	
PurposeCode	PurposeCode	M	1	

Possible Combinations

1. (In/Out) Attention, DestinationORI, PurposeCode, [FormORI, FreeText]

CCHCriminalHistoryFQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address	Address	O	30	
Attention	Attention	M	30	
Building	Building	O	30	
CityAndState	CityAndState	O	30	
DepartmentName	DepartmentName	O	30	
FormORI	FormORI	O	9	
ImageIndicator	ImageIndicator	O	1	
PurposeCode	PurposeCode	M	1	
State	State	M	2	
StateIDNumber	StateIDNumber	M	10	
ZipCode	ZipCode	O	9	

Possible Combinations

1. (In/Out) Attention, PurposeCode, State, StateIDNumber, [Address, Building, CityAndState, DepartmentName, ImageIndicator, FormORI, ZipCode]

CCHCriminalHistoryIQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	8	
FormORI	FormORI	O	9	
ImageIndicator	ImageIndicator	O	1	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
PurposeCode	PurposeCode	M	1	
RaceCode	RaceCode	O	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	M	2	

Possible Combinations

1. (In/Out) Attention, BirthDate, Name, PurposeCode, SexCode, State, [FormORI, ImageIndicator, MiscellaneousNumber, RaceCode, SocialSecurityNumber]
2. (In/Out) Attention, MiscellaneousNumber, Name, PurposeCode, State, [FormORI, ImageIndicator]
3. (In/Out) Attention, Name, PurposeCode, SocialSecurityNumber, State, [FormORI, ImageIndicator]

CCHCriminalHistoryQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	
FormORI	FormORI	O	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
PurposeCode	PurposeCode	M	1	
RaceCode	RaceCode	C	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateIDNumber	StateIDNumber	C	10	
UnitId	UnitId	O	5	

Possible Combinations

1. (In/Out) Attention, BirthDate, MiscellaneousNumber, Name, PurposeCode, RaceCode, SexCode, [FormORI, UnitId]
2. (In/Out) Attention, BirthDate, Name, PurposeCode, RaceCode, SexCode, [FormORI, UnitId]
3. (In/Out) Attention, BirthDate, Name, PurposeCode, RaceCode, SexCode, SocialSecurityNumber, [FormORI, UnitId]
4. (In/Out) Attention, FBINumber, Name, PurposeCode, [FormORI, UnitId]
5. (In/Out) Attention, FBINumber, PurposeCode, [FormORI, UnitId]
6. (In/Out) Attention, MiscellaneousNumber, Name, PurposeCode, [FormORI, UnitId]
7. (In/Out) Attention, Name, PurposeCode, SocialSecurityNumber, [FormORI, UnitId]
8. (In/Out) Attention, Name, PurposeCode, StateIDNumber, [FormORI, UnitId]
9. (In/Out) Attention, PurposeCode, StateIDNumber, [FormORI, UnitId]

CCHCriminalHistoryQRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

Address	Address	O	30	
Attention	Attention	O	30	
Building	Building	O	30	
CityAndState	CityAndState	O	30	
DepartmentName	DepartmentName	O	30	
FBINumber	FBINumber	C	9	
FormORI	FormORI	O	9	
PurposeCode	PurposeCode	M	1	
StateIDNumber	StateIDNumber	C	10	
UnitId	UnitId	O	5	
ZipCode	ZipCode	O	9	

Possible Combinations

1. (In/Out) Attention, FBINumber, PurposeCode, [Address, Building, CityAndState, DepartmentName, FormORI, UnitId, ZipCode]
2. (In/Out) Address, PurposeCode, StateIDNumber, [Attention, Building, CityAndState, DepartmentName, FormORI, UnitId, ZipCode]

CCHCriminalHistoryZRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FBINumber	FBINumber	C	9	
FormORI	FormORI	O	9	
PurposeCode	PurposeCode	O	1	
StateIDNumber	StateIDNumber	C	10	

Possible Combinations

1. (In/Out) FBINumber, [FormORI, PurposeCode]
2. (In/Out) StateIDNumber, [FormORI, PurposeCode]

Expanded Transactions Supported:

LogonRequest

Field Name	XML Tag Name	M/C/O	Size	Possible Values
User Name	UserName	M	5-5	
Logon Expiration	LogonExpiration	M	4-4	Military Time

UserName (login ID) can be in the session block instead of normal transaction data if desired. User will be automatically logged off based upon entered Logon Expiration Time. For example, if it is 0900 and the user wants to remain in this session for 2 hours they would enter 1100 in the LogonExpiration field.

Possible Combinations

UserName, LogonExpiration

QueryPassThrough

Field Name	XML Tag Name	M/C/O	Size	Possible Values
MessageData	FreeText	M		

Possible Combinations

1. FreeText

*This is a message key pass through and does not require the header of the message, only the body.

Example: (Header)**QA.ORI/123456789.TYP/YTHING.SER/123456** or
RQ.CAR/CAR12.ORI/CO1234567.LIC/ABC123.LIS/OK.LIT/PC.LIY/2007
Bolded text would be sent to ConnectCIC server in the FreeText tag.

WantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Birth Date	BirthDate	C	8-8	
FormORI	FormORI	O	9	
Name	Name	C	3-30	
Operator License Number	OperatorLicenseNumber	C	1-20	
State	State	O	2-2	
Race Code	RaceCode	C	1-1	
Sex Code	SexCode	C	1-1	
Unit Number	UnitId	O	1-5	

Possible Combinations (*fields within the square brackets are optional*)

1. Name, BirthDate, RaceCode, SexCode [FormORI, State, UnitId]
2. OperatorLicenseNumber [FormORI, State, UnitId]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

The ORI is a required field on each message transaction and is contained in the ConnectCIC header. If you are not using our device alias table, you will need to ensure you include the ORI field on each message transaction submitted to ConnectCIC.

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- CBI Documentation