

## **Connecticut (CT) COLLECT XML V2**

[Disclaimer Statement](#)

### **Transport:**

WEB Services

### **Routing and Configuration Information:**

Save Byte Routing

- The COLLECT assigned ORI should be placed in the <**Authentication**>/<**ORI**> field in the ConnectCIC header.
- The COLLECT assigned UserName for a user should be placed in the <**Authentication**>/<**UserName**> field in the ConnectCIC header.
- The agency assigned Mnemonic for each device should be placed in the <**Authentication**><**Mnemonic**> field in the ConnectCIC header.

### **Security Requirements:**

Vendor site requirements

Need Site Sponsor

### **Logon Requirements:**

None

### **Certification Requirements:**

None

Need Site Sponsor

### **Data-Mined Transactions & Fields:**

NCIC (QA, QB, QG, QV, QWA) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

## Basic Queries Supported:

### ArticleSingleQuery

| Field Name                | XML Tag Name              | M/C/O | Size | Possible Values                    |
|---------------------------|---------------------------|-------|------|------------------------------------|
| ArticleSerialNumber       | ArticleSerialNumber       | C     | 20   |                                    |
| ArticleTypeCode           | ArticleTypeCode           | O     | 7    |                                    |
| RelatedHitSearchIndicator | RelatedHitSearchIndicator | O     | 5    | true, false" *default for IN & OUT |
| SearchNCICIndicator       | SearchNCICIndicator       | O     | 5    | true*, false *default for IN & OUT |
| MessageNumber             | MessageNumber             | C     | 10   |                                    |

#### Possible Combinations

1. (In/Out) ArticleSerialNumber [ArticleTypeCode, RelatedHitSearchIndicator, SearchNCICIndicator]
2. (In) MessageNumber

### BoatQuery

| Field Name                | XML Tag Name              | M/C/O | Size | Possible Values                    |
|---------------------------|---------------------------|-------|------|------------------------------------|
| BoatHullIdNumber          | BoatHullIdNumber          | C     | 20   |                                    |
| MessageNumber             | MessageNumber             | C     | 10   |                                    |
| RecordOffset              | RecordOffset              | O     | 5    |                                    |
| RegistrationNumber        | RegistrationNumber        | C     | 8    |                                    |
| RelatedHitSearchIndicator | RelatedHitSearchIndicator | O     | 5    | true, false* *default for IN & OUT |
| SearchDEPIndicator        | SearchDEPIndicator        | O     | 5    | true*, false *default for IN       |
| SearchDMVIndicator        | SearchDMVIndicator        | O     | 5    | true*, false *default for IN       |
| SearchNCICIndicator       | SearchNCICIndicator       | O     | 5    | true*, false *default for IN & OUT |
| SearchNLETSIndicator      | SearchNLETSIndicator      | O     | 5    | true*, false *default for OUT      |
| State                     | State                     | O     | 2    |                                    |
| UserName                  | UserName                  | O     | 10   |                                    |

#### Possible Combinations

1. (In) BoatHullIdNumber, [RecordOffset, RelatedHitSearchIndicator, SearchDEPIndicator, SearchDMVIndicator, SearchNCICIndicator, SearchNLETSIndicator, UserName]
2. (In) BoatHullIdNumber, RegistrationNumber, [RelatedHitSearchIndicator, SearchDEPIndicator, SearchDMVIndicator, SearchNCICIndicator, SearchNLETSIndicator, State, UserName]
3. (In) RegistrationNumber, [RecordOffset, RelatedHitSearchIndicator, SearchDEPIndicator, SearchDMVIndicator, SearchNCICIndicator, SearchNLETSIndicator, State, UserName]
4. (In/Out) MessageNumber, [UserName]
5. (Out) BoatHullIdNumber, [RelatedHitSearchIndicator, SearchDEPIndicator, SearchDMVIndicator, SearchNCICIndicator, SearchNLETSIndicator, UserName]
6. (Out) BoatHullIdNumber, RegistrationNumber, State, [RelatedHitSearchIndicator, SearchDEPIndicator, SearchDMVIndicator, SearchNCICIndicator, SearchNLETSIndicator, UserName]
7. (Out) RegistrationNumber, State, [RelatedHitSearchIndicator, SearchDEPIndicator, SearchDMVIndicator, SearchNCICIndicator, SearchNLETSIndicator, UserName]

### DriverHistoryQuery

| Field Name            | XML Tag Name          | M/C/O | Size | Possible Values               |
|-----------------------|-----------------------|-------|------|-------------------------------|
| Attention             | Attention             | C     | 30   |                               |
| BirthDate             | BirthDate             | C     | 10   |                               |
| ImageRequestIndicator | ImageRequestIndicator | O     | 5    | true, false* *default for OUT |

|                       |                       |   |    |  |
|-----------------------|-----------------------|---|----|--|
| Name                  | Name                  | C | 30 |  |
| Operator              | Operator              | C | 30 |  |
| OperatorLicenseNumber | OperatorLicenseNumber | C | 20 |  |
| PurposeCode           | PurposeCode           | C | 1  |  |
| Reason                | Reason                | O | 9  |  |
| SexCode               | SexCode               | C | 1  |  |
| State                 | State                 | O | 2  |  |
| State2                | State2                | O | 2  |  |
| State3                | State3                | O | 2  |  |
| State4                | State4                | O | 2  |  |
| State5                | State5                | O | 2  |  |
| UserName              | UserName              | O | 10 |  |

#### Possible Combinations

1. (Out) Attention, BirthDate, Name, Operator, PurposeCode, SexCode, State, [ImageRequestIndicator, Reason, State2, State3, State4, State5, UserName]
2. (Out) Attention, Operator, OperatorLicenseNumber, PurposeCode, State, [ImageRequestIndicator, Reason, State2, State3, State4, State5, UserName]

**\*\* Note: At the time of this writing, DriverHistoryQuery is currently not available for Connecticut drivers.**

### *DriverLicenseQuery*

| Field Name                | XML Tag Name              | M/C/O | Size | Possible Values                    |
|---------------------------|---------------------------|-------|------|------------------------------------|
| BirthDate                 | BirthDate                 | O     | 10   |                                    |
| MessageNumber             | MessageNumber             | C     | 10   |                                    |
| Name                      | Name                      | C     | 30   |                                    |
| OperatorLicenseNumber     | OperatorLicenseNumber     | C     | 20   |                                    |
| RaceCode                  | RaceCode                  | O     | 1    |                                    |
| RecordOffset              | RecordOffset              | O     | 5    |                                    |
| RelatedHitSearchIndicator | RelatedHitSearchIndicator | O     | 5    | true, false* *default for IN & OUT |
| SearchDEPIndicator        | SearchDEPIndicator        | O     | 5    | true, false* *default for IN & OUT |
| SearchDMVIndicator        | SearchDMVIndicator        | O     | 5    | true*, false *default for IN       |
| SearchInterpollIndicator  | SearchInterpollIndicator  | O     | 5    | true, false* *default for IN & OUT |
| SearchNCICIndicator       | SearchNCICIndicator       | O     | 5    | true*, false *default for IN & OUT |
| SearchNLETSIndicator      | SearchNLETSIndicator      | O     | 5    | true, false* *default for OUT      |
| SearchPRAWNIndicator      | SearchPRAWNIndicator      | O     | 5    | true*, false *default for IN       |
| SearchWEAPONSIndicator    | SearchWEAPONSIndicator    | O     | 5    | true, false* *default for IN & OUT |
| SexCode                   | SexCode                   | O     | 1    |                                    |
| State                     | State                     | O     | 2    |                                    |
| UserName                  | UserName                  | O     | 10   |                                    |

#### Possible Combinations

1. (In) Name, [RaceCode, RecordOffset, RelatedHitSearchIndicator, SearchDEPIndicator, SearchDMVIndicator, SearchInterpollIndicator, SearchNCICIndicator, SearchNLETSIndicator, SearchPRAWNIndicator, SearchWEAPONSIndicator, SexCode, State, UserName]
2. (In) OperatorLicenseNumber, [RecordOffset, RelatedHitSearchIndicator, SearchDEPIndicator, SearchDMVIndicator, SearchInterpollIndicator, SearchNCICIndicator, SearchNLETSIndicator, SearchPRAWNIndicator, SearchWEAPONSIndicator, State, UserName]
3. (In/Out) MessageNumber, [UserName]
4. (Out) Name, State, [RaceCode, RecordOffset, RelatedHitSearchIndicator, SearchDEPIndicator, SearchDMVIndicator, SearchInterpollIndicator, SearchNCICIndicator,

SearchNLETSIndicator, SearchPRAWNIndicator, SearchWEAPONSIndicator, SexCode, UserName]

5. (Out) OperatorLicenseNumber, State, [RecordOffset, RelatedHitSearchIndicator, SearchDEPIndicator, SearchDMVIndicator, SearchInterpollIndicator, SearchNCICIndicator, SearchNLETSIndicator, SearchPRAWNIndicator, SearchWEAPONSIndicator, UserName]

## GunQuery

| Field Name                | XML Tag Name              | M/C/O | Size | Possible Values                    |
|---------------------------|---------------------------|-------|------|------------------------------------|
| GunCaliber                | GunCaliber                | O     | 4    |                                    |
| GunMake                   | GunMake                   | O     | 23   |                                    |
| GunSerialNumber           | GunSerialNumber           | C     | 20   |                                    |
| RelatedHitSearchIndicator | RelatedHitSearchIndicator | O     | 5    | true, false* *default for IN & OUT |
| SearchNCICIndicator       | SearchNCICIndicator       | O     | 5    | true*, false *default for IN & OUT |
| SearchWEAPONSIndicator    | SearchWEAPONSIndicator    | O     | 5    | true*, false *default for IN       |
| MessageNumber             | MessageNumber             | C     | 10   |                                    |

### Possible Combinations

1. (In/Out) GunSerialNumber, [GunCaliber, GunMake, RelatedHitSearchIndicator, SearchNCICIndicator, SearchWEAPONSIndicator]
2. (In/Out) MessageNumber

## VehicleRegistrationQuery

| Field Name                  | XML Tag Name                | M/C/O | Size | Possible Values                    |
|-----------------------------|-----------------------------|-------|------|------------------------------------|
| Expired                     | Expired                     | O     | 5    | true, false* *default for IN       |
| LicensePlateNumber          | LicensePlateNumber          | C     | 10   |                                    |
| LicensePlateTypeCode        | LicensePlateTypeCode        | O     | 30   |                                    |
| RegistrationExpirationYear  | RegistrationExpirationYear  | O     | 4    |                                    |
| RelatedHitSearchIndicator   | RelatedHitSearchIndicator   | O     | 5    | true, false* *default for IN & OUT |
| SearchDEPIndicator          | SearchDEPIndicator          | O     | 5    | true, false* *default for IN & OUT |
| SearchDMVIndicator          | SearchDMVIndicator          | O     | 5    | true*, false *default for IN       |
| SearchInterpollIndicator    | SearchInterpollIndicator    | O     | 5    | true, false* *default for IN & OUT |
| SearchNCICIndicator         | SearchNCICIndicator         | O     | 5    | true*, false *default for IN & OUT |
| SearchNLETSIndicator        | SearchNLETSIndicator        | O     | 5    | true*, false *default for OUT      |
| SearchPRAWNIndicator        | SearchPRAWNIndicator        | O     | 5    | true*, false *default for IN       |
| SearchWEAPONSIndicator      | SearchWEAPONSIndicator      | O     | 6    | true, false* *default for IN & OUT |
| State                       | State                       | O     | 2    |                                    |
| MessageNumber               | MessageNumber               | O     | 10   |                                    |
| UserName                    | UserName                    | O     | 10   |                                    |
| VehicleIdentificationNumber | VehicleIdentificationNumber | C     | 20   |                                    |
| VehicleMakeCode             | VehicleMakeCode             | O     | 8    |                                    |
| VehicleYear                 | VehicleYear                 | O     | 4    |                                    |

### Possible Combinations

1. (In) LicensePlateNumber, [Expired, LicensePlateTypeCode, RegistrationExpirationYear, RelatedHitSearchIndicator, SearchDEPIndicator, SearchDMVIndicator, SearchInterpollIndicator, SearchNCICIndicator, SearchNLETSIndicator, SearchPRAWNIndicator, SearchWEAPONSIndicator, State, UserName]
2. (In) VehicleIdentificationNumber, [RelatedHitSearchIndicator, SearchDEPIndicator, SearchDMVIndicator, SearchInterpollIndicator, SearchNCICIndicator, SearchNLETSIndicator, SearchPRAWNIndicator, SearchWEAPONSIndicator, State, UserName, VehicleMakeCode, VehicleYear]
3. (In/Out) MessageNumber, [StateIdNumber, UserName]

4. (Out) LicensePlateNumber, State, [Expired, LicensePlateTypeCode, RegistrationExpirationYear, RelatedHitSearchIndicator, SearchDEPIndicator, SearchDMVIndicator, SearchInterpollIndicator, SearchNCICIndicator, SearchNLETSIndicator, SearchPRAWNIndicator, SearchWEAPONSIndicator, UserName]
5. (Out) VehicleIdentificationNumber, State, [RelatedHitSearchIndicator, SearchDEPIndicator, SearchDMVIndicator, SearchInterpollIndicator, SearchNCICIndicator, SearchNLETSIndicator, SearchPRAWNIndicator, SearchWEAPONSIndicator, UserName, VehicleMakeCode, VehicleYear]

### Transactions Supported:

None

### Expanded Transactions Supported:

#### *CorrelatedMessageRequest*

| Field Name  | XML Tag Name | M/C/O | Size | Possible Values             |
|-------------|--------------|-------|------|-----------------------------|
| CorrelID    | CorrelID     | O     | 20   |                             |
| ServiceName | ServiceName  | O     | 7    | NCIC, NLETS, PRAWN, WEAPONS |

#### Possible Combinations

1. (In/Out) [CorrelID, ServiceName]

### Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

### Notes:

This document is subject to change as this WEB service is still under development by the state.

### References:

- NCIC 2000 Operations Manual (12/99)
- NLETS User Guide (10/1/98)
- Connecticut COLLECT Software Interface Specifications (Unknown publish date)