

Iowa (IA) IOWA

[Disclaimer Statement](#)

Transport:

TCP/IP – DMPP-2020 using OFML, released May, 2005

Routing and Configuration Information:

Save Byte Routing (primary)

Mnemonic Routing (secondary)

- The IOWA assigned ORI for a device (or for the site) should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.
- The IOWA assigned Mnemonic for a device should be placed in the **<Authentication>/<Mnemonic>** field in the ConnectCIC header.
- The IOWA assigned User ID should be placed in the **Authentication>/<UserName>** field in the ConnectCIC header.

SPECIAL NOTE: **<Authentication>/<OriginatingAgencyORI>** can be used to overwrite the ORI value sent to the state by **<Authentication>/<ORI>**. This can facilitate one agency running transactions “on-behalf-of” another.

Security Requirements:

To be compliant with Trusted Server Messages for DMPP2020 Workstation and Remote Agency Interface to OpenFox the following fields are required.

1. TDAC – Each workstation is assigned a four-character terminal ID (the device from which the message was initiated) by the Iowa Technology Services Bureau (TSB). These are provided to agencies upon request.
2. Device ORI – Each workstation is assigned a nine-character device ORI by the Iowa Technology Services Bureau (TSB). These are provided upon request.
3. User ID – Each user that is granted access to the IOWA system will be assigned a User ID by the Iowa Technology Services Bureau. This will consist of the first four characters of the last name followed by the last four characters of the OLN/SOC the TSB has on file. There may be a suffix character if the person works at more than one agency - in which case they create a separate ID. Iowa will/can provide the agency will a list of the user names for their personnel.

Background Checks – Iowa requires each vendor to have any personnel who will be working with secure data (transactions) to be fingerprinted for background checks (i.e NCIC 2000 Security Policy). You will also need to complete the security paperwork (CJIS Security Addendum) using your first Iowa agency as your sponsor agency. Information can be obtained through your sponsor agency or through the Iowa Technology Services Bureau.

Logon Requirements:

None

Certification Requirements:

The vendor's first agency that requests connectivity to the IOWA system will be required to go through a fairly rigorous certification process that tests the total solution end to end. The vendor will need to coordinate this with the Iowa Technology Services Bureau. This process will include:

- Need Site Sponsor – initial communication with the state must be initiated by a state recognized agency. In order to certify an interface in Iowa, you must have a sponsor agency. The agency must request the necessary routing and connection information from the state prior to installation and configuration.
- Initial Connection Certification – the vendor will need to have the CommSys component certified proving that our product is capable of a stable TCP/IP connection and that we can manage message traffic to and from the state. Note: CommSys is fully certified in Iowa and any vendor using our ConnectCIC Server application will not need to complete this testing. Just inform the Technology Services Bureau that you are using the CommSys ConnectCIC product.
- Site Certification – the Iowa Technology Services Bureau Representative will come to the site (by appointment) and test the client screens to ensure field sizes and form requirements are met and test the solution end-to-end solution. **The vendor will need to provide the state a complete list of what queries their interface will support prior to the on-site certification.** In the ConnectCIC Basic Query Interface, we include functionality for the following queries and Iowa recommends that all be included: QA (Article), QG (Gun), QB (Boat), QQ (Drivers License Query by OLN), QD (Drivers License Query by Name), RQ (NLETS out of state Vehicle Reg), and QQ (Vehicle Reg). The QD and RQ queries allow for multiple state entries. In-house query systems may use the QXS (Sex Offender Query), and the QH (III Criminal History Query).
- Acceptance – Once the state certifies the vendor's interface, they will provide the vendor with a certification letter stating such, which will allow them to implement the interface at other agencies within the state without going through the complete testing process. However, if the interface is changed, i.e. new version, new queries, the state may require you to perform a short re-certification process.

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV(IDOT) (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Article Type Code	ArticleTypeCode	C	7	
Interface Assigned Number	InterfaceAssignedNumber	C	7	
NCIC Number	NCICNumber	C	10	
Originating Agency Case Number	OriginatingAgencyCaseNumber	C	20	
ImageIndicator	ImageIndicator	O	1	
Related Hit Search Indicator	RelatedHitSearchIndicator	O	1	
Serial Number	ArticleSerialNumber	C	20	

Possible Combinations (fields within the square brackets are optional)

1. (In/Out) ArticleTypeCode, ArticleSerialNumber [ImageIndicator, RelatedHitSearchIndicator]
2. (In) InterfaceAssignedNumber
3. (In/Out) NCICNumber [ImageIndicator, RelatedHitSearchIndicator]
4. (In) OriginatingAgencyCaseNumber

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Boat Hull Identification Number	BoatHullIdNumber	C	20	
NCIC Number	NCICNumber	C	10	
Registration Number	RegistrationNumber	C	8	
ImageIndicator	ImageIndicator	O	1	
Related Hit Search Indicator	RelatedHitSearchIndicator	O	1	
State	State	O	2	

Possible Combinations (fields within the square brackets are optional)

1. (In/Out) RegistrationNumber, [BoatHullIdNumber, ImageIndicator, RelatedHitSearchIndicator, State]
2. (In/Out) BoatHullIdNumber, [RegistrationNumber, ImageIndicator, RelatedHitSearchIndicator, State]
3. (In/Out) NCICNumber [ImageIndicator, RelatedHitSearchIndicator]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Birth Date	BirthDate	C	8	
Expanded Birth Date Search	ExpandedBirthDateSearchCode	O	1	
Expanded Name Search	ExpandedNameSearchCode	O	1	
Name	Name	C	30	
Operator License Number	OperatorLicenseNumber	C	20	
ImageIndicator	ImageIndicator	O	1	
Related Hit Search Indicator	RelatedHitSearchIndicator	O	1	
Sex Code	SexCode	O	1	
State	State	C	2	

Possible Combinations (fields within the square brackets are optional)

1. (In/Out) OperatorLicenseNumber [State, ImageIndicator, RelatedHitSearchIndicator]

2. (In) Name, [BirthDate, ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, SexCode, State, ExpandedBirthDateSearchCode]
3. (Out) Name, BirthDate, SexCode, State [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, ExpandedBirthDateSearchCode]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Gun Make	GunMake	O	23	
Gun Caliber	GunCaliber	O	4	
NCIC Number	NCICNumber	M	10	
ImageIndicator	ImageIndicator	O	1	
Related Hit Search Indicator	RelatedHitSearchIndicator	O	1	
Serial Number	GunSerialNumber	M	20	

Possible Combinations (fields within the square brackets are optional)

1. (In/Out) GunSerialNumber [GunMake, GunCaliber, ImageIndicator, RelatedHitSearchIndicator]
2. (In/Out) NCICNumber [ImageIndicator, RelatedHitSearchIndicator]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
License Plate Type Code	LicensePlateTypeCode	C	2	
License Plate Number	LicensePlateNumber	C	8	
License Plate Year	LicensePlateYear	C	4	
Multi-State	MultiState*	O	1	1 or Blank
ImageIndicator	ImageIndicator	O	1	
Related Hit Search Indicator	RelatedHitSearchIndicator	O	1	
State	State	C	2	
State 2 (second state code)	State2	O	2	
State 3 (third state code)	State3	O	2	
State 4 (fourth state code)	State4	O	2	
State 5 (fifth state code)	State5	O	2	
Vehicle Identification Number	VehicleIdentificationNumber	C	20	
Vehicle Make Code	VehicleMakeCode	O	4	
Vehicle Year	VehicleYear	C	4	

Possible Combinations (fields within the square brackets are optional)

1. (In) LicensePlateNumber, [ImageIndicator, LicensePlateYear, LicensePlateTypeCode, RelatedHitSearchIndicator]
2. (In) VehicleIdentificationNumber [ImageIndicator, RelatedHitSearchIndicator, VehicleYear, VehicleMakeCode]
3. (Out) LicensePlateNumber, State [ImageIndicator, LicensePlateYear, LicensePlateTypeCode, RelatedHitSearchIndicator]
4. (Out) VehicleIdentificationNumber, State [ImageIndicator, RelatedHitSearchIndicator, VehicleYear]
5. (Multi) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, MultiState*, State, [State2*, State3*, State4*, State5*]
6. (Multi) MultiState*, VehicleIdentificationNumber, State [ImageIndicator, RelatedHitSearchIndicator, State2*, State3*, State4*, State5*, VehicleMakeCode, VehicleYear]

*- Field MultiState must be set to 1 in order for multiple states to be queried

Transactions Supported:

Computerized Criminal History (CCH):

CCHCriminalHistoryAQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	Alphanumeric, special characters
FreeText	FreeText	M	14400	Freetext request
NletsDestination	NletsDestination	M	9	2 char state code, 4 char TDAC, or ORI of agency
NletsDestination2	NletsDestination2	O	9	2 char state code, 4 char TDAC, or ORI of agency
NletsDestination3	NletsDestination3	O	9	2 char state code, 4 char TDAC, or ORI of agency
NletsDestination4	NletsDestination4	O	9	2 char state code, 4 char TDAC, or ORI of agency
NletsDestination5	NletsDestination5	O	9	2 char state code, 4 char TDAC, or ORI of agency
PurposeCode	PurposeCode	M	1	C, E, J

Possible Combinations

1. (In/Out) Attention, FreeText, NletsDestination, PurposeCode, [NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5]

CCHCriminalHistoryARQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	Alphanumeric, special characters
FreeText	FreeText	M	14400	Freetext response
NletsDestination	NletsDestination	M	9	4 char TDAC, or ORI of agency
PurposeCode	PurposeCode	M	1	C, E, J

Possible Combinations

1. (In/Out) Attention, FreeText, NletsDestination, PurposeCode

CCHCriminalHistoryFQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address	Address	O	30	Alphanumeric
Attention	Attention	M	30	Alphanumeric, special characters
Building	Building	O	30	Alphanumeric
CityAndState	CityAndState	O	30	Alpha, comma (i.e. DETRIOT,MI).
DepartmentName	DepartmentName	O	30	Alphanumeric
PurposeCode	PurposeCode	M	1	C, E, J
State	State	M	2	2 char state code (See NCIC 2000 code manual)
StateIdNumber	StateIdNumber	M	10	10 char
ZipCode	ZipCode	O	10	5 char or 5-4 character zip or postal code

Possible Combinations

1. (Out) Attention, PurposeCode, State, StateIdNumber, [Address, Building, CityAndState, DepartmentName, ZipCode]

CCHCriminalHistoryIQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	Alphanumeric, special characters
BirthDate	BirthDate	C	8	
MiscellaneousNumber	MiscellaneousNumber	C	15	See NCIC 2000 operating manual.
Name	Name	M	30	Alphanumeric, special characters

PurposeCode	PurposeCode	M	1	C, E, J
RaceCode	RaceCode	O	1	A,B, H, I, P, U, W
SexCode	SexCode	C	1	F, M
SocialSecurityNumber	SocialSecurityNumber	C	9	Numeric
State	State	M	2	2 char state code (See NCIC 2000 code manual)
State2	State2	O	2	2 char state code (See NCIC 2000 code manual)
State3	State3	O	2	2 char state code (See NCIC 2000 code manual)
State4	State4	O	2	2 char state code (See NCIC 2000 code manual)
State5	State5	O	2	2 char state code (See NCIC 2000 code manual)

Possible Combinations

1. (Out) Attention, BirthDate, MiscellaneousNumber, Name, PurposeCode, SexCode, State, [RaceCode, State2, State3, State4, State5]
2. (Out) Attention, BirthDate, Name, PurposeCode, SexCode, SocialSecurityNumber, State, [RaceCode, State2, State3, State4, State5]
3. (Out) Attention, BirthDate, Name, PurposeCode, SexCode, State, [RaceCode, State2, State3, State4, State5]
4. (Out) Attention, MiscellaneousNumber, Name, PurposeCode, State, [RaceCode, State2, State3, State4, State5]
5. (Out) Attention, Name, PurposeCode, SocialSecurityNumber, State, [RaceCode, State2, State3, State4, State5]

CCHCriminalHistoryQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	Alphanumeric, special characters
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	Alphanumeric (See NCIC 2000 operating manual)
MiscellaneousNumber	MiscellaneousNumber	C	15	See NCIC 2000 operating manual
Name	Name	C	30	Alphanumeric, special characters
PurposeCode	PurposeCode	M	1	C, F, J
RaceCode	RaceCode	C	1	A,B, H, I, P, U, W
Redissemination	Redissemination	O	50	Alphanumeric, special characters
SexCode	SexCode	C	1	F, M
SocialSecurityNumber	SocialSecurityNumber	C	9	Numeric
StateldNumber	StateldNumber	C	10	10 char

Possible Combinations

1. (In/Out) Attention, BirthDate, Name, PurposeCode, RaceCode, SexCode, [Redissemination]
2. (In/Out) Attention, FBINumber, PurposeCode, [Redissemination]
3. (In/Out) Attention, MiscellaneousNumber, Name, PurposeCode, [Redissemination]
4. (In/Out) Attention, Name, PurposeCode, SocialSecurityNumber, [Redissemination]
5. (In/Out) Attention, Name, PurposeCode, StateldNumber, [Redissemination]
6. (In/Out) Attention, PurposeCode, StateldNumber, [Redissemination]

CCHCriminalHistoryQRIQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	Alphanumeric, special characters
FBINumber	FBINumber	M	9	Alphanumeric (See NCIC 2000 operating manual)
PurposeCode	PurposeCode	M	1	C, F, J
Redissemination	Redissemination	O	50	Alphanumeric, special characters

Possible Combinations

1. (In/Out) Attention, FBINumber, PurposeCode, [Redissemination]

CCHCriminalHistoryQRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	Alphanumeric, special characters
DCINumber	DCINumber	C	9	Alphanumeric (See IOWA operating manual)
FBINumber	FBINumber	C	9	Alphanumeric (See NCIC 2000 operating manual)
PurposeCode	PurposeCode	M	1	C, F, J
Redissemination	Redissemination	O	50	Alphanumeric, special characters

Possible Combinations

1. (In/Out) Attention, DCINumber, FBINumber, PurposeCode, [Redissemination]
2. (In/Out) Attention, DCINumber, PurposeCode, [Redissemination]
3. (In/Out) Attention, FBINumber, PurposeCode, [Redissemination]

CCHMasterNameIndexQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
DCINumber	DCINumber	C	9	Alphanumeric (See IOWA operating manual)
InquiryOptionCode	InquiryOptionCode	C	3	AKA, LVF, SDX
Name	Name	C	31	Alphanumeric, special characters
SexCode	SexCode	C		F, M
SocialSecurityNumber	SocialSecurityNumber	C	9	Numeric

Possible Combinations

1. (In/Out) BirthDate, InquiryOptionCode, Name, SexCode
2. (In/Out) DCINumber, [InquiryOptionCode]
3. (In/Out) SocialSecurityNumber

CCHRapSheetQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DCINumber	DCINumber	M	9	Alphanumeric (See IOWA operating manual)

Possible Combinations

1. (In/Out) DCINumber

Wanted Missing Persons Entry (WMPE)

WMPEDentalDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [TestIndicator]

WMPEDentalDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DentalCharacteristics	DentalCharacteristics	M	319	See NCIC Code Manual

DentalModelsAvailableIndicator	DentalModelsAvailableIndicator	M	1	Y, N
DentalXraysAvailableIndicator	DentalXraysAvailableIndicator	M	1	Y, N
DentistRemarks	DentistRemarks	O	50	
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) DentalCharacteristics, DentalModelsAvailableIndicator, DentalXraysAvailableIndicator, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [DentistRemarks, TestIndicator]

WMPEDentalDataModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DentalCharacteristics	DentalCharacteristics	O	319	See NCIC Code Manual
DentalModelsAvailableIndicator	DentalModelsAvailableIndicator	O	1	Y, N
DentalXraysAvailableIndicator	DentalXraysAvailableIndicator	O	1	Y, N
DentistRemarks	DentistRemarks	O	50	
NCICNumber	NCICNumber	M	10	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [DentistRemarks, DentalCharacteristics, DentalModelsAvailableIndicator, DentalXraysAvailableIndicator, ModifiedOriginatingAgencyORI, TestIndicator])

WMPEMissingPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
IOWANumber	IOWANumber	M	7	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ReasonCode	ReasonCode	M	1	D - OTHER DECEASED E - ERROR IN RECORD H - HOMICIDE VICTIM P - PICKED UP (NO CRIMINAL CHARGES) T - TRANSFER OF STATUS (CHANGE OF INC) U - UNFOUNDED REPORT V - VOLUNTARILY RETURNED W - WHEREABOUTS DETERMINED; PERSON NOT RETURNED Z - TEST ENTRY CANCELLATION
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, [TestIndicator]

WMPEMissingPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
IOWANumber	IOWANumber	M	7	

OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ReasonCode	ReasonCode	M	1	C - ARRESTED CRIMINAL CHARGES D - OTHER DECEASED H - HOMICIDE VICTIM P - PICKED UP (NO CRIMINAL CHARGES) T - TRANSFER OF STATUS (CHANGE OF INC) U - UNFOUNDED REPORT V - VOLUNTARILY RETURNED W - WHEREABOUTS DETERMINED; PERSON NOT RETURNED
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, [TestIndicator]

WMPEMissingPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	25	
AddressStreet	AddressStreet	O	25	
BirthDate	BirthDate	C	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyXRayCode	BodyXRayCode	O	1	See NCIC Code Manual
BroadcastMnemonicList	BroadcastMnemonicList	O	12	Up to 3x 4 char mnemonics may be entered
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	See NCIC Code Manual
ConfirmingAgencyMnemonic	ConfirmingAgencyMnemonic	O	4	
ControlField	ControlField	O	10	
DCINumber	DCINumber	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
DocumentedAddressDate	DocumentedAddressDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FaxTelephoneNumber	FaxTelephoneNumber	O	10	
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintIndicator	FootprintIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LastContactDate	LastContactDate	M	8	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	

LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
MissingPersonCircumstanceCode	MissingPersonCircumstanceCode	O	1	See NCIC Code Manual
MissingPersonCode	MissingPersonCode	M	2	See NCIC Code Manual
MissingPersonEntryType	MissingPersonEntryType	M	1	D - Disability (Physical/Mental) E - Endangered/Physical I - Involuntary Disappearance J - Juvenile K - Familial Abduction L - Lost or Wandered Away R - Other Missing (Adult) V - Castastrophe Victim
Name	Name	M	30	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PickupCode	PickupCode	M		1 - 100 Mile Radius 2 - 200 Mile Radius B - Bordering counties C - Countywide N - Nationwide S - Statewide
RaceCode	RaceCode	M	1	See NCIC Code Manual
ReleaseStatusCode	ReleaseStatusCode	M	1	I - Release of information will jeopardize investigation N - Release of information will not jeopardize investigation
ScarMarkTattooCode	ScarMarkTattooCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
TelephoneNumber	TelephoneNumber	O	14	
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, PickupCode, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, BirthDate, ReleaseStatusCode, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, PickupCode, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, FBI Number, ReleaseStatusCode, [Any optional fields]

3. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, PickupCode, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, MiscellaneousNumber, ReleaseStatusCode, [Any optional fields]
4. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, PickupCode, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, SocialSecurityNumber, ReleaseStatusCode, [Any optional fields]
5. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, PickupCode, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, ReleaseStatusCode, [Any optional fields]
6. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, PickupCode, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, LicensePlateYear, ReleaseStatusCode, [Any optional fields]
7. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, PickupCode, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, VehicleIdentificationNumber, VehicleMakeCode, VehicleYear, VehicleStyleCode, ReleaseStatusCode, [Any optional fields]
8. (In/Out) **MissingPersonEntryType = J or L**; OriginatingAgencyORI, Name, PickupCode, SexCode, RaceCode, BirthDate, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, ReleaseStatusCode, [Any optional fields]

WMPERMissingPersonLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ExtraditionCode	ExtraditionCode	M	1	Y - Extradite N - No Extradite
IOWANumber	IOWANumber	C	7	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RecoveryDate	RecoveryDate	M	8	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) ExtraditionCode, IOWANumber, OriginatingAgencyORI, RecoveryDate, [TestIndicator]
2. (In/Out) ExtraditionCode, Name, NCICNumber, OriginatingAgencyORI, RecoveryDate, [TestIndicator]

WMPERMissingPersonModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	25	
AddressStreet	AddressStreet	O	25	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyXRayCode	BodyXRayCode	O	1	See NCIC Code Manual
BroadcastMnemonicList	BroadcastMnemonicList	O	12	Up to 3x 4 char mnemonics may be entered
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual

CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	See NCIC Code Manual
ConfirmingAgencyMnemonic	ConfirmingAgencyMnemonic	O	4	
ControlField	ControlField	O	10	
DCINumber	DCINumber	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
DocumentedAddressDate	DocumentedAddressDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FaxTelephoneNumber	FaxTelephoneNumber	O	10	
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintIndicator	FootprintIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IOWANumber	IOWANumber	M	7	
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LastContactDate	LastContactDate	O	8	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
MissingPersonCircumstanceCode	MissingPersonCircumstanceCode	O	1	See NCIC Code Manual
MissingPersonCode	MissingPersonCode	O	2	See NCIC Code Manual
MissingPersonEntryType	MissingPersonEntryType	O	1	D - Disability (Physical/Mental) E - Endangered/Physical I - Involuntary Disappearance J - Juvenile K - Familial Abduction L - Lost or Wandered Away R - Other Missing (Adult) V - Castastrophe Victim
Name2	Name2	O	30	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PickupCode	PickupCode	O		1 - 100 Mile Radius 2 - 200 Mile Radius B - Bordering counties C - Countywide N - Nationwide S - Statewide

RaceCode	RaceCode	O	1	See NCIC Code Manual
ReleaseStatusCode	ReleaseStatusCode	O	1	I - Release of information will jeopardize investigation N - Release of information will not jeopardize investigation
ScarMarkTattooCode	ScarMarkTattooCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
TelephoneNumber	TelephoneNumber	O	14	
TestIndicator	TestIndicator	O	1	Y, BLANK
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	72	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyORI, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEMissingPersonPersonWithInformationCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	M	30	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [TestIndicator]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI, [TestIndicator]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [TestIndicator]

WMPEMissingPersonPersonWithInformationEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	M	500	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	

OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
TestIndicator	TestIndicator	O	1	Y, BLANK
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) Name, NCICNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]
4. (In/Out) Name, NCICNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]
5. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]
6. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonPersonWithInformationModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	M	30	
PersonWithInformationName2	PersonWithInformationName2	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
TestIndicator	TestIndicator	O	1	Y, BLANK
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]

2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonPWISupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	M	30	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonPWISupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	M	30	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreet	AddressStreet	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
IOWANumber	IOWANumber	M	7	
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPERMissingPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreet	AddressStreet	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
IOWANumber	IOWANumber	M	7	
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK

VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEProtectionOrderCancel

The IOWA Operating Manual doesn't expose a method for cancelling protective orders in the field.

WMPEProtectionOrderClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
IOWANumber	IOWANumber	M	7	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [TestIndicator]

WMPEProtectionOrderEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	25	
AddressStreet	AddressStreet	O	25	
BirthDate	BirthDate	O	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
BroadcastMnemonicList	BroadcastMnemonicList	O	12	Up to 3x 4 char mnemonics may be entered
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
DCINumber	DCINumber	O	9	

DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
DocumentedAddressDate	DocumentedAddressDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExpirationDate	ExpirationDate	M	8	
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FaxTelephoneNumber	FaxTelephoneNumber	O	10	
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IssueDate	IssueDate	M	8	
JudgeName	JudgeName	O	30	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	O	30	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	C	8	
ProtectedPersonName	ProtectedPersonName	C	30	
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	C	9	
ProtectionOrderConditionsCode	ProtectionOrderConditionsCode	M	2	See NCIC Code Manual
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	
SexCode	SexCode	M	1	See NCIC Code Manual
SightingDate	SightingDate	O	8	
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
TelephoneNumber	TelephoneNumber	O	14	
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
Weight	Weight	O	3	

Per the IOWA Operating Manual, agencies in the field may only enter EPOT - Temporary Protection Orders of type E - Emergency

Possible Combinations

1. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, BirthDate, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, FBINumber, [Any optional fields]
3. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, MiscellaneousNumber, [Any optional fields]
4. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, SocialSecurityNumber, [Any optional fields]
5. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
6. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, [Any optional fields]
7. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]
8. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, ProtectedPersonName, ProtectedPersonSocialSecurityNumber, [Any optional fields]
9. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, ProtectedPersonName, ProtectedPersonBirthDate, [Any optional fields]
10. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, BirthDate, [Any optional fields]
11. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, FBINumber, [Any optional fields]
12. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, MiscellaneousNumber, [Any optional fields]
13. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, SocialSecurityNumber, [Any optional fields]
14. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
15. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, [Any optional fields]
16. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]

17. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, ProtectedPersonName, ProtectedPersonSocialSecurityNumber, [Any optional fields]
18. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, ProtectedPersonName, ProtectedPersonBirthDate, [Any optional fields]

WMPEProtectionOrderModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	25	
AddressStreet	AddressStreet	O	25	
BirthDate	BirthDate	O	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
BroadcastMnemonicList	BroadcastMnemonicList	O	12	Up to 3x 4 char mnemonics may be entered
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
DCINumber	DCINumber	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
DocumentedAddressDate	DocumentedAddressDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExpirationDate	ExpirationDate	O	8	
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FaxTelephoneNumber	FaxTelephoneNumber	O	10	
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IOWANumber	IOWANumber	M	7	
IssueDate	IssueDate	O	8	
JudgeName	JudgeName	O	30	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name2	Name2	O	30	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	
ProtectedPersonName	ProtectedPersonName	O	30	
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual

ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	
ProtectionOrderConditionsCode	ProtectionOrderConditionsCode	O	2	See NCIC Code Manual
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	
SexCode	SexCode	O	1	See NCIC Code Manual
SightingDate	SightingDate	O	8	
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
TelephoneNumber	TelephoneNumber	O	14	
TestIndicator	TestIndicator	O	1	Y, BLANK
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
Weight	Weight	O	3	

Per the IOWA Operating Manual, agencies in the field may only enter EPOT - Temporary Protection Orders of type E - Emergency

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEProtectionOrderSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreet	AddressStreet	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should

				use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
IOWANumber	IOWANumber	M	7	
LicensePlateExpirationYear	LicensePlateExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseExpirationYear	OperatorLicenseExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonName	ProtectedPersonName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderConditionCode	ProtectionOrderConditionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEProtectionOrderSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

AddressCityState	AddressCityState	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreet	AddressStreet	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
IOWANumber	IOWANumber	M	7	
LicensePlateExpirationYear	LicensePlateExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseExpirationYear	OperatorLicenseExpirationYear	O	4	9 fields are supported. Additional identifiers should

				use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonName	ProtectedPersonName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderConditionCode	ProtectionOrderConditionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESexOffenderCancel

The IOWA Operating Manual doesn't expose a method for cancelling sex offender records in the field.

WMPESexOffenderClear

The IOWA Operating Manual doesn't expose a method for clearing sex offender records in the field.

WMPESexOffenderEntry

The IOWA Operating Manual doesn't expose a method for entering sex offender records in the field.

WMPESexOffenderModify

The IOWA Operating Manual doesn't expose a method for modifying sex offender records in the field.

WMPESexOffenderSupplementalCancel

The IOWA Operating Manual doesn't expose a method for removing supplemental data from sex offender records in the field.

WMPESexOffenderSupplementalEntry

The IOWA Operating Manual doesn't expose a method for adding supplemental data to sex offender records in the field.

WMPESupervisedReleaseCancel

The IOWA Operating Manual doesn't expose a method for cancelling supervised release records in the field.

WMPESupervisedReleaseClear

The IOWA Operating Manual doesn't expose a method for clearing supervised release records in the field.

WMPESupervisedReleaseEntry

The IOWA Operating Manual doesn't expose a method for entering supervised release records in the field.

WMPESupervisedReleaseFraudulentDataCancel

The IOWA Operating Manual doesn't expose a method for removing fraudulent data from supervised release records in the field.

WMPESupervisedReleaseFraudulentDataEntry

The IOWA Operating Manual doesn't expose a method for adding fraudulent data to supervised release records in the field.

WMPESupervisedReleaseModify

The IOWA Operating Manual doesn't expose a method for modifying supervised release records in the field.

WMPESupervisedReleaseSupplementalCancel

The IOWA Operating Manual doesn't expose a method for removing supplemental data from supervised release records in the field.

WMPESupervisedReleaseSupplementalEntry

The IOWA Operating Manual doesn't expose a method for adding supplemental data to supervised release records in the field.

WMPEUnidentifiedPersonCancel

The IOWA Operating Manual doesn't expose a method for cancelling unidentified person records in the field.

WMPEUnidentifiedPersonClear

The IOWA Operating Manual doesn't expose a method for clearing unidentified person records in the field.

WMPEUnidentifiedPersonEntry

The IOWA Operating Manual doesn't expose a method for entering unidentified person records in the field.

WMPEUnidentifiedPersonModify

The IOWA Operating Manual doesn't expose a method for modifying unidentified person records in the field.

WMPEUnidentifiedPersonSupplementalCancel

The IOWA Operating Manual doesn't expose a method for removing supplemental data from unidentified person records in the field.

WMPEUnidentifiedPersonSupplementalEntry

The IOWA Operating Manual doesn't expose a method for adding supplemental data to unidentified person records in the field.

WMPEWantedPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
IOWANumber	IOWANumber	M	7	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ReasonCode	ReasonCode	M	1	E - ERROR IN RECORD Z - TEST ENTRY R - WARRANT RECALLED
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, [TestIndicator]

WMPEWantedPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
IOWANumber	IOWANumber	M	7	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ReasonCode	ReasonCode	M	1	A - ARRESTED/BOND COLLECTED BY ENTERING AGENCY C - IN CUSTODY/BOND COLLECTED BY ANOTHER AGENCY
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, [TestIndicator]

WMPEWantedPersonDetainerCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	M	20	
IOWANumber	IOWANumber	M	7	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
TestIndicator	TestIndicator	O	1	Y, BLANK
WantedPersonType	WantedPersonType	M	1	X - Detainer Placed [Default for this transaction] B - Simple Misdemeanor Bench C - Wanted Juvenile - Charged F - Felony H - Serious or Aggravated Misdemeanor Bench M - Simple Misdemeanor N - Felony Bench P - Wanted Juvenile - Adjudged S - Serious or Aggravated Misdemeanor T - Temporary Felony Want

Possible Combinations

1. (In/Out) DetainerCaseNumber, IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, WantedPersonType, [TestIndicator]

WMPEWantedPersonDetainerEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	M	20	
DetainerDate	DetainerDate	M	8	
IncarceratingAgencyORI	IncarceratingAgencyORI	M	9	
IncarcerationPlace	IncarcerationPlace	O	50	
IncarcerationStartDate	IncarcerationStartDate	O	8	
IOWANumber	IOWANumber	M	7	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SentenceExpirationDate	SentenceExpirationDate	O	8	
TestIndicator	TestIndicator	O	1	Y, BLANK
WantedPersonType	WantedPersonType	M	1	X - Detainer Placed [Default for this transaction] B - Simple Misdemeanor Bench C - Wanted Juvenile - Charged F - Felony H - Serious or Aggravated Misdemeanor Bench M - Simple Misdemeanor N - Felony Bench P - Wanted Juvenile - Adjudged S - Serious or Aggravated Misdemeanor T - Temporary Felony Want

Possible Combinations

1. (In/Out) DetainerCaseNumber, DetainerDate, IncarceratingAgencyORI, IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, WantedPersonType, [Any optional fields]

WMPEWantedPersonDetainerModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	O	20	
DetainerDate	DetainerDate	O	8	
IncarceratingAgencyORI	IncarceratingAgencyORI	O	9	
IncarcerationPlace	IncarcerationPlace	O	50	
IncarcerationStartDate	IncarcerationStartDate	O	8	
IOWANumber	IOWANumber	M	7	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SentenceExpirationDate	SentenceExpirationDate	O	8	
TestIndicator	TestIndicator	O	1	Y, BLANK
ValidatorName	ValidatorName	O	30	

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalOffenseIndicator	AdditionalOffenseIndicator	O	1	Blank, Y
AddressCityState	AddressCityState	O	25	

AddressStreet	AddressStreet	O	25	
BirthDate	BirthDate	C	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ConfirmingAgencyMnemonic	ConfirmingAgencyMnemonic	O	4	
ControlField	ControlField	O	10	
CourtORI	CourtORI	O	9	
DCINumber	DCINumber	O	9	Alphanumeric (See IOWA operating manual)
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
DocumentedAddressDate	DocumentedAddressDate	O	8	
EmancipationDate	EmancipationDate	C	8	Mandatory for type C, P. Not used for others.
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExtraditionLimitation	ExtraditionLimitation	C	2	See NCIC Code Manual; used only when PickupCode = N
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FaxTelephoneNumber	FaxTelephoneNumber	O	10	
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	M	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
NotifyOriginatingAgency	NotifyOriginatingAgency	O	1	Blank, Y
OffenseCode	OffenseCode	M	4	
OffenseCodeDescription	OffenseCodeDescription	O	20	
OperatorLicenseYear	OperatorLicenseYear	C	4	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OriginalOffenseCode	OriginalOffenseCode	C	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PickupCode	PickupCode	M	1	1 - 100 Mile Radius 2 - 200 Mile Radius B - Bordering counties C - Countywide N - Nationwide S - Statewide
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	

TelephoneNumber	TelephoneNumber	O	10	
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	3	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
ViolationDate	ViolationDate	M	8	
WantedPersonType	WantedPersonType	M	1	B - Simple Misdemeanor Bench C - Wanted Juvenile - Charged F - Felony H - Serious or Aggravated Misdemeanor Bench M - Simple Misdemeanor N - Felony Bench P - Wanted Juvenile - Adjudged S - Serious or Aggravated Misdemeanor T - Temporary Felony Want X - Detainer Placed
WarrantDate	WarrantDate	C	8	Optional for type C, P. Mandatory for others.
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	M	3	

*Operator License fields must be entered as a set.

*License Plate fields must be entered as a set.

*VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, and VehicleStyleCode must be entered as a set.

Possible Combinations

1. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, OriginatingAgencyCaseNumber, PickupCode, TelephoneNumber, FaxTelephoneNumber, ViolationDate, WantedPersonType, BirthDate, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, OriginatingAgencyCaseNumber, PickupCode, TelephoneNumber, FaxTelephoneNumber, ViolationDate, WantedPersonType, FBINumber [Any optional fields]
3. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, OriginatingAgencyCaseNumber, PickupCode, TelephoneNumber, FaxTelephoneNumber, ViolationDate, WantedPersonType, MiscellaneousNumber [Any optional fields]
4. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, OriginatingAgencyCaseNumber, PickupCode, TelephoneNumber, FaxTelephoneNumber, ViolationDate, WantedPersonType, SocialSecurityNumber [Any optional fields]
5. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, OriginatingAgencyCaseNumber, PickupCode, TelephoneNumber, FaxTelephoneNumber, ViolationDate, WantedPersonType, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseExpirationYear, [Any optional fields]
6. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, OriginatingAgencyCaseNumber, PickupCode,

TelephoneNumber, FaxTelephoneNumber, ViolationDate , WantedPersonType, LicensePlateNumber, LicensePlateStateCode, LicensePlateExpirationYear, LicensePlateTypeCode, [Any optional fields]

7. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, OriginatingAgencyCaseNumber, PickupCode, TelephoneNumber, FaxTelephoneNumber, ViolationDate , WantedPersonType, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]

WMPEWantedPersonFraudulentDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
IOWANumber	IOWANumber	M	7	
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonFraudulentDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
IOWANumber	IOWANumber	M	7	
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ExtraditionCode	ExtraditionCode	M	1	Y - Extradite D - Detain N - No Extradite
IOWANumber	IOWANumber	C	7	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RecoveryDate	RecoveryDate	M	8	
TestIndicator	TestIndicator	O	1	Y, BLANK
WantedPersonType	WantedPersonType	C	1	T - Temporary Felony Want W - Wanted Person (Adult & Juvenile)

Possible Combinations

1. (In/Out) ExtraditionCode, IOWANumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, RecoveryDate, [TestIndicator]
2. (In/Out) ExtraditionCode, Name, NCICNumber, OriginatingAgencyORI, RecoveryDate, WantedPersonType, [TestIndicator]

WMPEWantedPersonModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalOffenseIndicator	AdditionalOffenseIndicator	O	1	Blank, Y
AddressCityState	AddressCityState	O	25	
AddressStreet	AddressStreet	O	25	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ConfirmingAgencyMnemonic	ConfirmingAgencyMnemonic	O	4	
ControlField	ControlField	O	10	
CourtORI	CourtORI	O	9	
DCINumber	DCINumber	O	9	Alphanumeric (See IOWA operating manual)
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	

DocumentedAddressDate	DocumentedAddressDate	O	8	
EmancipationDate	EmancipationDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExtraditionLimitation	ExtraditionLimitation	O	2	See NCIC Code Manual; used only when PickupCode = N
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FaxTelephoneNumber	FaxTelephoneNumber	O	10	
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IOWANumber	IOWANumber	M	7	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name2	Name2	O	30	
NotifyOriginatingAgency	NotifyOriginatingAgency	O	1	Blank, Y
OffenseCode	OffenseCode	O	4	
OffenseCodeDescription	OffenseCodeDescription	O	20	
OperatorLicenseYear	OperatorLicenseYear	O	4	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PickupCode	PickupCode	O	1	1 - 100 Mile Radius 2 - 200 Mile Radius B - Bordering counties C - Countywide N - Nationwide S - Statewide
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
TelephoneNumber	TelephoneNumber	O	10	
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
ValidatorName	ValidatorName	O	30	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	

ViolationDate	ViolationDate	O	8	
WantedPersonType	WantedPersonType	O	1	B - Simple Misdemeanor Bench C - Wanted Juvenile - Charged F - Felony H - Serious or Aggravated Misdemeanor Bench M - Simple Misdemeanor N - Felony Bench P - Wanted Juvenile - Adjudged S - Serious or Aggravated Misdemeanor T - Temporary Felony Want X - Detainer Placed
WarrantDate	WarrantDate	O	8	
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyORI, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEWantedPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreet	AddressStreet	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
IOWANumber	IOWANumber	M	7	
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyORI, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEWantedPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreet	AddressStreet	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
IOWANumber	IOWANumber	M	7	
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) IOWANumber, OriginatingAgencyORI, OriginatingAgencyCaseNumber, [Any optional fields]

Wanted Missing Person Inquiries (WMP-I)

WMPIMissingPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	M	2	
AreaCode	AreaCode	O	3	See NCIC Code Manual
EthnicityCode	EthnicityCode	M	1	See NCIC Code Manual
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Blank, Y
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
Name	Name	O	30	
RaceCode	RaceCode	M	1	See NCIC Code Manual

SexCode	SexCode	M	1	See NCIC Code Manual
TestIndicator	TestIndicator	O	1	Y, BLANK
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) Age, EthnicityCode, EyeColorCode, HairColorCode, Height, RaceCode, SexCode, Weight, [AreaCode, ExpandedNameSearchCode, Name, TestIndicator]

WMPINletsSexOffenderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Blank, Y
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
PurposeCode	PurposeCode	O	1	
SexCode	SexCode	C	1	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	M	2	
StateIdNumber	StateIdNumber	C	10	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, State, [Attention, ImageIndicator, PurposeCode, TestIndicator]
2. (In/Out) FBINumber, State, [Attention, ImageIndicator, PurposeCode, TestIndicator]
3. (In/Out) MiscellaneousNumber, State, [Attention, ImageIndicator, PurposeCode, TestIndicator]
4. (In/Out) SocialSecurityNumber, State, [Attention, ImageIndicator, PurposeCode, TestIndicator]
5. (In/Out) StateIdNumber, State, [Attention, ImageIndicator, PurposeCode, TestIndicator]

WMPINletsStateWarrantQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
RaceCode	RaceCode	O	1	
SexCode	SexCode	O	1	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	M	2	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) BirthDate, Name, State, [RaceCode, SexCode, TestIndicator]
2. (In/Out) FBINumber, Name, State, [TestIndicator]
3. (In/Out) MiscellaneousNumber, Name, State, [TestIndicator]
4. (In/Out) Name, SocialSecurityNumber, State, [TestIndicator]
5. (In/Out) Name, OperatorLicenseNumber, State, [TestIndicator]

WMPProtectionOrderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
DCINumber	DCINumber	C	9	Alphanumeric (See IOWA operating manual)
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Blank, Y
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Blank, Y
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Blank, Y
IOWANumber	IOWANumber	M	7	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
RaceCode	RaceCode	O	1	See NCIC Code Manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Blank, Y
SexCode	SexCode	O	1	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	

Possible Combinations

1. (In/Out) Name, BirthDate, [ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, RaceCode, RelatedHitSearchIndicator, SexCode, TestIndicator]
2. (In/Out) Name, OriginatingAgencyCaseNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
3. (In/Out) Name, ProtectionOrderNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
4. (In/Out) NCICNumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
5. (In/Out) IOWANumber, [TestIndicator]
6. (In/Out) DCINumber, [TestIndicator]
7. (In/Out) Name, FBINumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
8. (In/Out) Name, MiscellaneousNumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
9. (In/Out) Name, OperatorLicenseNumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
10. (In/Out) Name, SocialSecurityNumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
11. (In/Out) LicensePlateNumber, LicensePlateStateCode, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator, VehicleIdentificationNumber, VehicleMakeCode, VehicleMakeCodeDescription]
12. (In/Out) VehicleIdentificationNumber, VehicleMakeCode, [ImageIndicator, RelatedHitSearchIndicator, LicensePlateNumber, LicensePlateStateCode, TestIndicator, VehicleMakeCodeDescription]

WMPISexOffenderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

AddressCity	AddressCity	C	30	
AddressStateCode	AddressStateCode	C	2	
AddressZipCode	AddressZipCode	C	5	
Attention	Attention	M	30	
BirthDate	BirthDate	C	8	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Blank, Y
ExpandedNameSearchIndicator	ExpandedNameSearchIndicator	O	1	Blank, Y
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Blank, Y
IOWANumber	IOWANumber	C	7	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PurposeCode	PurposeCode	M	3	LAW – Request the law enforcement version of the response PUB – Request the public (abbreviated) version of the response
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SexualOffenderStatusIndicator	SexualOffenderStatusIndicator	O	1	Y,N
SocialSecurityNumber	SocialSecurityNumber	C	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Attention, Name, PurposeCode, BirthDate, [ExpandedBirthDateSearchCode, ExpandedNameSearchIndicator, ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
2. (In/Out) Attention, Name, PurposeCode, AddressCity, AddressStateCode, [TestIndicator]
3. (In/Out) Attention, PurposeCode, AddressZipCode, [SexualOffenderStatusIndicator, TestIndicator]
4. (In/Out) Attention, PurposeCode, SocialSecurityNumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
5. (In/Out) Attention, PurposeCode, MiscellaneousNumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
6. (In/Out) Attention, PurposeCode, OperatorLicenseNumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
7. (In/Out) Attention, PurposeCode, FBINumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
8. (In/Out) Attention, PurposeCode, IOWANumber, [TestIndicator]
9. (In/Out) Attention, PurposeCode, OriginatingAgencyCaseNumber, [TestIndicator]

WMPIUnidentifiedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	C	2	
AreaCode	AreaCode	O	3	See NCIC Code Manual
BodyPartsStatusCode	BodyPartsStatusCode	C	15	See NCIC Code Manual
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	C	3	See NCIC Code Manual
HairColorCode	HairColorCode	C	3	See NCIC Code Manual
Height	Height	C	3	
ImageIndicator	ImageIndicator	O	1	Blank, Y
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	C	1	See NCIC Code Manual

SexCode	SexCode	C	1	See NCIC Code Manual
TestIndicator	TestIndicator	O	1	Y, BLANK
Weight	Weight	C	3	

Possible Combinations

1. (In/Out) Age, EyeColorCode, HairColorCode, Height, RaceCode, SexCode, Weight, [AreaCode, EthnicityCode, ImageIndicator, TestIndicator]
2. (In/Out) BodyPartsStatusCode, [AreaCode, EthnicityCode, ImageIndicator, RaceCode, SexCode, TestIndicator]
3. (In/Out) NCICNumber, [ImageIndicator, TestIndicator]
4. (In/Out) OriginatingAgencyCaseNumber, [ImageIndicator, TestIndicator]

WMPIWantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	C	2	
BirthDate	BirthDate	C	8	
DCINumber	DCINumber	C	9	Alphanumeric (See IOWA operating manual)
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Blank, Y
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Blank, Y
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Blank, Y
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
MessageKeyModifier	MessageKeyModifier	O	1	BLANK - Searches wanted person file felony records regardless of extradition and misdemeanor records indicating possible extradition from the inquiring agency's location. (default message key) A - Searches all NCIC persons files without limitations. E - Searches wanted person file felony and misdemeanor records indicating possible extradition from the inquiring agency's location. All other NCIC persons files are searched without limitations. F - Searches wanted person file felony regardless of extradition. All other NCIC persons files are searched without limitations. S - Searches wanted person file felony regardless of extradition, all misdemeanor records indicating possible extradition from the inquiring agency's location, and all intrastate misdemeanor records. All other NCIC persons files are searched without limitations.
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Blank, Y
SexCode	SexCode	O	1	See NCIC Code Manual
StateIdNumber	StateIdNumber	C	7	
SocialSecurityNumber	SocialSecurityNumber	C	9	
TestIndicator	TestIndicator	O	1	

Possible Combinations

1. (In/Out) Name, BirthDate, SexCode, [ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, TestIndicator]

2. (In/Out) Name, Age, SexCode, [TestIndicator]
3. (In/Out) OriginatingAgencyCaseNumber, [TestIndicator]
4. (In/Out) BirthDate, [TestIndicator]
5. (In/Out) NCICNumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
6. (In/Out) StateIdNumber, [TestIndicator]
7. (In/Out) DCINumber, [TestIndicator]
8. (In/Out) FBINumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
9. (In/Out) MiscellaneousNumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
10. (In/Out) OperatorLicenseNumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
11. (In/Out) SocialSecurityNumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]

Expanded Transactions Supported:

The extended queries below may only be used by non-mobile users.

CriminalHistoryCheckIII

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
Birth Date	BirthDate	C	8	
FBI Number	FBINumber	C	9	
Name	Name	C	30	
Purpose Code	PurposeCode	M	1	
Race Code	RaceCode	C	1	
Re-dissemination	Redissemination	O	50	
Sex Code	SexCode	C	1	

Possible Combinations (fields within the square brackets are optional)

1. (In/Out) Attention, BirthDate, Name, PurposeCode, RaceCode, SexCode, [Redissemination]
2. (In/Out) Attention, FBINumber, PurposeCode, [Redissemination]

QuerySexOffender

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
Birth Date	BirthDate	C	8	
City	AddressCity	C	30	
Expanded Birth Date Search	ExpandedBirthDateSearchCode	O	1	
Expanded Name Search	ExpandedNameSearchCode	O	1	
FBI Number	FBINumber	C	9	
Interface Assigned Number	InterfaceAssignedNumber	C	7	
Miscellaneous Number	MiscellaneousNumber	C	15	
Name	Name	C	30	
Operator License Number	OperatorLicenseNumber	C	20	
Originating Agency Case Number	OriginatingAgencyCaseNumber	C	20	
ImageIndicator	ImageIndicator	O	1	
Related Hit Search Indicator	RelatedHitSearchIndicator	O	1	
Sex Offender Status Code	SexOffenderStatusCode	O	1	
Social Security Number	SocialSecurityNumber	C	9	
State	State	C	2	
Usage Code	UsageCode	M	3	
Zip code	AddressZipcode	C	5	

Possible Combinations (fields within the square brackets are optional)

1. (In/Out) Attention, BirthDate, Name, UsageCode, StateAbbreviation, [ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator]
2. (In/Out) AddressCity, Attention, Name, StateAbbreviation, UsageCode, [ExpandedNameSearchCode]
3. (In/Out) AddressZipcode, Attention, UsageCode, StateAbbreviation, [ImageIndicator, RelatedHitSearchIndicator, SexOffenderStatusCode]
4. (In/Out) Attention, SocialSecurityNumber, StateAbbreviation, UsageCode, [ImageIndicator, RelatedHitSearchIndicator]
5. (In/Out) Attention, MiscellaneousNumber, StateAbbreviation, UsageCode, [ImageIndicator, RelatedHitSearchIndicator]
6. (In/Out) Attention, OperatorLicenseNumber, StateAbbreviation, UsageCode [ImageIndicator, RelatedHitSearchIndicator]
7. (In/Out) Attention, FBI Number, StateAbbreviation, UsageCode, [ImageIndicator, RelatedHitSearchIndicator]
8. (In) Attention, InterfaceAssignedNumber, UsageCode
9. (In) Attention, OriginatingAgencyCaseNumber, UsageCode

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- IOWA System TCP/IP Protocol, DMPP2020
- Iowa Message Key Documentation
- Various supporting documents including NCIC 2000 message switch/implementation updates