

Illinois (IL) LEADS

[Disclaimer Statement](#)

Transport:

TCPIP

Routing and Configuration Information:

Mnemonic Routing

- The site assigned Mnemonic for a device should be placed in the <**Authentication**>/<**Mnemonic**> field in the ConnectCIC header.
- The LEADS assigned ORI for a device or agency should be placed in the <**Authentication**>/<**ORI**> field in the ConnectCIC header.
- The LEADS assigned CDC Name (maximum 8 characters) for the agency submitting the transaction should be placed in the <**Authentication**>/<**CDCName**> field in the ConnectCIC header if more than one agency is operating through the same message switch connection. If this isn't required at this particular site, set this field, CDCName, found in the "Other State Settings" drop down list to the same value as ConnectionName and ConnectCIC will populate this field in the message transaction sent to LEADS.

Security Requirements:

None known at this time

Logon Requirements:

None

Certification Requirements:

Excerpt From LEADS Administrative Rules - Section 1240.40 Connecting to LEADS

a) To connect to LEADS, an agency must have computer hardware and computer software, and be connected to a communications link to the LEADS Data Center in Springfield. For each of these requirements, there are various options. In addition, the agency must meet certain planning and administrative responsibilities.

- Notify LEADS Administrator When an agency desires to participate in LEADS and meets the qualifications described in Section 1240.30 or when an agency wishes to change its method of connecting to LEADS, it must make a written request at least 90 days in advance of the desired connection date. The request must be sent to the LEADS Administrator and must state:
 - 1) When connection to LEADS is desired; and
 - 2) What equipment and connecting options are planned by the agency.
- Arrange a Conference - The agency must arrange for a conference between its own representatives, any hardware or software vendors involved, and the Department. The LEADS Administrator may waive the requirement for a formal meeting if the vendor has previously demonstrated the ability to successfully interface with LEADS. The Department accepts no responsibility for misunderstanding of LEADS specifications and requirements that occurs between the local agency and its vendors.

b) The LEADS Administrator must approve the agency's hardware and software configuration prior to the agency connecting to LEADS.

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	
OwnerAppliedNumber	OwnerAppliedNumber	O	20	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode, [OwnerAppliedNumber]

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	M	20	

Possible Combinations

1. (In/Out) BoatHullIdNumber

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	C	1	
State	State	C	2	

Possible Combinations

1. (In) BirthDate, Name, SexCode
2. (In) OperatorLicenseNumber
3. (Out) BirthDate, Name, SexCode, State
4. (Out) OperatorLicenseNumber, State

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	O	3	
GunSerialNumber	GunSerialNumber	M	20	

Possible Combinations

1. (In/Out) GunSerialNumber, [GunCaliber, GunMake]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	O	2	
State	State	C	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In) LicensePlateNumber, [LicensePlateTypeCode]
2. (In) VehicleIdentificationNumber
3. (Out) LicensePlateNumber, State, [LicensePlateTypeCode, LicensePlateYear]
4. (Out) State, VehicleIdentificationNumber

Transactions Supported:

Computerrized Criminal History (CCH)

CriminalHistoryRecordCQR1Query

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AgencyName	AgencyName	O	30	
Attention	Attention	M	30	
BuildingInformation	BuildingInformation	O	30	
CityStateCode	CityStateCode	O	30	
FBINumber	FBINumber	C	9	
MailingAddress	MailingAddress	O	30	
OperatorInitials	OperatorInitials	O	2	
PurposeCode	PurposeCode	M	1	
Requestor	Requestor	M	30	
StateIdNumber	StateIdNumber	C	10	
ZipCode	ZipCode	O	9	

Possible Combinations

1. (In/Out) Attention, FBINumber, PurposeCode, Requestor, [AgencyName, BuildingInformation, CityStateCode, MailingAddress, OperatorInitials, ZipCode]
2. (In/Out) Attention, PurposeCode, Requestor, StateIdNumber, [AgencyName, BuildingInformation, CityStateCode, MailingAddress, OperatorInitials, ZipCode]

CCHCriminalHistoryRecordExistenceQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Alphanumeric
BirthDate	BirthDate	C	8	Numeric, YYYYMMDD
FBINumber	FBINumber	C	9	Alphanumeric
MiscellaneousNumber	MiscellaneousNumber	C	15	Alphanumeric
Name	Name	C	30	Alphanumeric, Special Characters
OperatorInitials	OperatorInitials	M	2	Alpha
PurposeCode	PurposeCode	M	1	Alpha: 'A', 'C', 'D', 'F', 'H', 'I', 'J', 'S', 'V', or 'X'
RaceCode	RaceCode	C	1	Alpha: See NCIC 200 Code Manual
Requestor	Requestor	M	30	Alpha

SexCode	SexCode	C	1	Alpha: 'M','F','X'
SocialSecurityNumber	SocialSecurityNumber	C	9	Numeric
StateIdNumber	StateIdNumber	C	10	Alphanumeric, Special Characters

Possible Combinations

1. (In/Out) BirthDate, Name, OperatorInitials, PurposeCode, RaceCode, Requestor, SexCode, [Attention]
2. (In/Out) BirthDate, FBINumber, Name, OperatorInitials, PurposeCode, RaceCode, Requestor, SexCode, [Attention]
3. (In/Out) BirthDate, MiscellaneousNumber, Name, OperatorInitials, PurposeCode, RaceCode, Requestor, SexCode, [Attention]
4. (In/Out) BirthDate, Name, OperatorInitials, PurposeCode, RaceCode, Requestor, SexCode, SocialSecurityNumber, [Attention]
5. (In/Out) BirthDate, Name, OperatorInitials, PurposeCode, RaceCode, Requestor, SexCode, StateIdNumber, [Attention]
6. (In/Out) FBINumber, Name, OperatorInitials, PurposeCode, Requestor, [Attention]
7. (In/Out) MiscellaneousNumber, Name, OperatorInitials, PurposeCode, Requestor, [Attention]
8. (In/Out) Name, OperatorInitials, PurposeCode, Requestor, SocialSecurityNumber, [Attention]
9. (In/Out) Name, OperatorInitials, PurposeCode, Requestor, StateIdNumber, [Attention]

CCHCriminalHistoryRecordQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AgencyName	AgencyName	C	30	Alphanumeric, Special Characters
Attention	Attention	M	30	Alpha
BuildingInformation	BuildingInformation	O	30	Alphanumeric, Special Characters
CityStateCode	CityStateCode	C	30	Alph and '-'
FBINumber	FBINumber	C	9	Alphanumeric
MailingAddress	MailingAddress	C	30	Alphanumeric, Special Characters
OperatorInitials	OperatorInitials	M	2	Alpha
PurposeCode	PurposeCode	M	1	Alpha: 'A', 'C', 'D', 'F', 'H', 'I', 'J', 'S', 'V', or 'X'
Requestor	Requestor	M	30	Alpha
StateIdNumber	StateIdNumber	C	10	Alphanumeric, Special Characters
ZipCode	ZipCode	C	9	US Postal ZIP Code, ZIP or ZIP+4

Possible Combinations

1. (In/Out) AgencyName, Attention, CityStateCode, FBINumber, MailingAddress, OperatorInitials, PurposeCode, Requestor, ZipCode, [BuildingInformation]
2. (In/Out) AgencyName, Attention, CityStateCode, MailingAddress, OperatorInitials, PurposeCode, Requestor, StateIdNumber, ZipCode, [BuildingInformation]
3. (In/Out) Attention, FBINumber, OperatorInitials, PurposeCode, Requestor
4. (In/Out) Attention, OperatorInitials, PurposeCode, Requestor, StateIdNumber

Expanded Transactions Supported:

AlarmExchangeResponse

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlarmResponse	AlarmResponse	M	16384	
DestinationORI	DestinationORI	M	9	
FormORI	FormORI	O	9	

Possible Combinations

1. (In/Out) AlarmResponse, DestinationORI, [FormORI]

DriverLicenseByNameQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Name	Name	M	30	

Possible Combinations

1. (In) Name

FirearmsOwnersIdQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
FirearmId	FirearmId	C	6	
Name	Name	C	30	
SexCode	SexCode	C	1	

Possible Combinations

1. (In) BirthDate, Name, SexCode
- (In) FirearmId

IILeadsAdministrativeQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AgencyLocation	AgencyLocation	O	18	
AgencyName	AgencyName	O	25	
CDC	CDC	O	3	
FormORI	FormORI	O	9	

Possible Combinations

1. (In/Out) [AgencyLocation, AgencyName, CDC, FormORI]

IILeadsBroadcastListQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdministratorLists	AdministratorLists	O	49	
CDC	CDC	O	3	
CountyLists	CountyLists	O	39	
ShowInOraList	ShowInOraList	O	3	

Possible Combinations

1. (In/Out) [AdministratorLists, CDC, CountyLists, ShowInOraList]

IILeadsDriverAbstractQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	O	1	

Possible Combinations

1. (In) Name, [BirthDate, SexCode]
2. (In) OperatorLicenseNumber

IIILeadsHandicapPlacardQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
HandicapPlacardNumber	HandicapPlacardNumber	M	20	

Possible Combinations

1. (In) HandicapPlacardNumber

IIILeadsLeadsTypeQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CDC	CDC	O	8	
DistrictCode	DistrictCode	O	2	
MessageKeyModifier	MessageKeyModifier	M	1	A – Article B – Boat G – Gun L – License M – Missing Person C – Protection Order S – Security V – Vehicle W – Wanted Person
QueryMonthDay	QueryMonthDay	M	4	MMDD

Possible Combinations

1. (In) MessageKeyModifier, QueryMonthDay, [CDC, DistrictCode]

IIILeadsRecordNumberQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
MessageKeyModifier	MessageKeyModifier	M	1	
RecordNumber	RecordNumber	M	8	

Possible Combinations

1. (In) MessageKeyModifier, RecordNumber

IIILeadsVehicleTitleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
VehicleIdentificationNumber	VehicleIdentificationNumber	M	20	

Possible Combinations

1. (In) VehicleIdentificationNumber

P1AlarmExchangeResponse

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlarmResponse	AlarmResponse	M	16384	
DestinationORI	DestinationORI	M	9	
FormORI	FormORI	O	9	

Possible Combinations

1. (In/Out) AlarmResponse, DestinationORI, [FormORI]

QueryPassThrough

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Message Data	FreeText	M		

Possible Combinations *(fields within the square brackets are optional)*

1. FreeText

*This is a message key pass through and does not require the header of the message, only the body.

Example: (Header)**QA.ORI/123456789.TYP/YTHING.SER/123456**

Bolded text would be sent to ConnectCIC server in the FreeText tag.

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

IL LEADS is not able to support driver license images at this time. They expect to roll out an image capable message switch by the end of 2016. –pw2014-07-10

References:

- NCIC 2000 Operations Manual (12/99)
- NLETS User Guide (10/1/98)
- ISP Connection Manager Technical Reference (2/2000)