

Transport:

TCPIP

Routing and Configuration Information:

Save-byte routing

- The KCJIS-assigned ORI for a device (or for the agency) should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.
- The KCJIS-assigned mnemonic for a device should be placed in the **<Authentication>/<Mnemonic>** field in the ConnectCIC header.
- The KCJIS-assigned User ID should be placed in the **<Authentication>/<UserName>** field in the ConnectCIC header.

ConnectCIC Config Option:

- CarStop. This identifier defaults to “Y” meaning if you don’t change this, the car stop transaction (KCS) will be available at this site. If change to “N” the car stop transaction is not accessible. This field is found in the “Other State Settings” drop down list. See Drivers License and Vehicle Registration Queries below for additional information.

Security Requirements:

No vendor requirements known at this time.

Logon Requirements:

The UserName is passed in the **<Authentication>/<UserName>** field is the header of each message.

OperatorPin and SecurityToken – Note: The OperatorPIN must be hidden when entered. The SecurityToken should NOT be hidden.

Example: OperatorPin: ***** SecurityToken: 1234A5

Kansas uses a Token generator. This is a physical device provided to the site by the state.

The OperatorPin is secure information (only known by each individual person).

<LogoffRequest>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

No fields other than header fields are necessary.

<LogonRequest>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Operator PIN	OperatorPin	M	8-8	
Key FOB	SecurityToken	M	8-8	

To use the <LogonRequest> to Logoff, submit LOGOFF in OperatorPin Field.

Certification Requirements:

Vendor Needs Site Sponsor; all agencies must certify as KCJIS ensures that the message flow including logon/logoff management as well as the transactions are all working properly end-to-end.

Before interface testing can occur, the agency must fax to the state helpdesk a list of queries and the dates for testing at a new site. To be considered official, this document must be on agency letterhead. The request for interface testing must then be approved by the state. Note: Be sure to plan far enough ahead (recommend a minimum of 2-4 weeks) to ensure the state has resources to support your testing request. For a new site or new vendor to the state, the state most likely will require that all queries be run against their test system before they give approval for production use. This is a lengthy process due to the fact that the state can be slow to turn around a response sometimes taking a week or more for a response.

The following queries are currently supported in Kansas if using the CarStop: Basic Inquiry Module: QA (Article); BQ, QB, ZQBO, ZQKA (Boat); DQ, QW, KCS (Driver License); QG (Gun); KCS, ZQNM (Vehicle Registration); Expanded Inquiry Module: KQ, QW, ZQ90 (Driver History); MQ (Hazmat). Note: the KCS message spawns several transactions at the message switch making this a cleaner process.

The following queries are current supported in Kansas if you are NOT using the CarStop: Basic Inquiry Module: QA (Article); BQ, QB, ZQBO, ZQKA (Boat); DQ, QW, ZA71 (Driver License); QG (Gun); RQ, QV, ZQAT, ZQBU, ZQEC, ZQEM, ZQET, ZQMB, ZQMC, ZQMH, ZQNM, ZQPC, ZQPL, ZQTK, ZQTL, ZQVN, ZQZZ (Vehicle Registration); Expanded Inquiry Module: KQ, QW, ZQ90 (Driver History); MQ (Hazmat).

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)
[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	C	20	

ArticleTypeCode	ArticleTypeCode	C	7	
ImageIndicator	ImageIndicator	O	1	
NCICNumber	NCICNumber	C	10	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode, [ImageIndicator]
2. (In/Out) NCICNumber, [ImageIndicator]

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BoatHullIdNumber	BoatHullIdNumber	C	20	
Name	Name	C	30	
RegistrationNumber	RegistrationNumber	C	8	
State	State	O	2	

Possible Combinations

1. (In) Name
2. (In) RegistrationNumber
3. (In/Out) BoatHullIdNumber
4. (In/Out) BoatHullIdNumber, [State]
5. (Out) Name, State [BirthDate]
6. (Out) RegistrationNumber, State

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	C	30	
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
PurposeCode	PurposeCode	C	1	
SexCode	SexCode	C	1	
State	State	O	2	

Possible Combinations

1. (In) BirthDate, Name
2. (In) Name
3. (In/Out) Attention, OperatorLicenseNumber, PurposeCode, [State]
4. (In/Out) BirthDate, Name, [OperatorLicenseNumber]
5. (Out) Attention, BirthDate, Name, PurposeCode, SexCode, State

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
CarStop	CarStop	O	1	Y, BLANK
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	C	1	
State	State	C	2	

Possible Combinations

1. (In) BirthDate, Name
2. (In) Name

3. (In) OperatorLicenseNumber
4. (In/Out) BirthDate, CarStop, Name, SexCode
5. (In/Out) BirthDate, Name, [OperatorLicenseNumber]
6. (In/Out) CarStop, OperatorLicenseNumber, [State]
7. (Out) BirthDate, Name, SexCode, State
8. (Out) OperatorLicenseNumber, State

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	O	23	
GunModel	GunModel	O	11	
GunSerialNumber	GunSerialNumber	C	11	
ImageIndicator	ImageIndicator	O	1	
NCICNumber	NCICNumber	C	10	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	

Possible Combinations

1. (In/Out) GunSerialNumber, [GunCaliber, GunMake, GunModel, ImageIndicator, RelatedHitSearchIndicator]
2. (In/Out) NCICNumber, [ImageIndicator]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CarStop	CarStop	O	1	Y, BLANK
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
Name	Name	C	30	
SpecialIssuedLicensePlateTypeCode	SpecialIssuedLicensePlateTypeCode	O	2	
State	State	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	24	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In) LicensePlateNumber, LicensePlateTypeCode
2. (In) Name
3. (In) VehicleIdentificationNumber
4. (In/Out) CarStop, LicensePlateNumber, [SpecialIssuedLicensePlateTypeCode, State]
5. (In/Out) CarStop, VehicleIdentificationNumber, [SpecialIssuedLicensePlateTypeCode, VehicleMakeCode, VehicleYear]
6. (In/Out) LicensePlateNumber, [State]
7. (In/Out) VehicleIdentificationNumber, [VehicleMakeCode]
8. (Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, State [VehicleMakeCode, VehicleYear]
9. (Out) VehicleIdentificationNumber, State, [VehicleMakeCode, VehicleYear]

Transactions Supported:

Computerized Criminal History (CCH)

CCHCriminalHistoryRecordQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address	Address	O	30	
Attention	Attention	M	30	
Building	Building	O	30	
CityAndState	CityAndState	O	30	
DepartmentName	DepartmentName	O	30	
FBINumber	FBINumber	C	9	
PurposeCode	PurposeCode	M	1	
Reason	Reason	M	254	
StateIDNumber	StateIDNumber	C	10	
ZipCode	ZipCode	O	9	

Possible Combinations

1. (In/Out) Attention, FBINumber, PurposeCode, Reason, [Address, Building, CityAndState, DepartmentName, ZipCode]
2. (In/Out) Attention, PurposeCode, Reason, StateIDNumber, [Address, Building, CityAndState, DepartmentName, ZipCode]

CCHFullCriminalRecordQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address	Address	O	30	
Attention	Attention	M	30	
Building	Building	O	30	
CityAndState	CityAndState	O	30	
DepartmentName	DepartmentName	O	30	
PurposeCode	PurposeCode	M	1	A – Administrative, J - Criminal Justice Employment, C - Criminal Justice Purposes, D - Domestic Violence/Stalking, X - Exigent Circumstances, I - Non-criminal Justice Employment/Licensing, F - Weapons-related Background Check
Reason	Reason	M	254	
State	State	O	2	
StateIDNumber	StateIDNumber	M	10	
ZipCode	ZipCode	O	9	

Possible Combinations

1. (In/Out) Attention, PurposeCode, Reason, StateIDNumber, [Address, Building, CityAndState, DepartmentName, State, ZipCode]

CCHIdentityInformationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	8	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
PurposeCode	PurposeCode	M	1	A – Administrative, J - Criminal Justice Employment, C - Criminal Justice Purposes, D - Domestic

				Violence/Stalking, X - Exigent Circumstances, I - Non-criminal Justice Employment/Licensing, F - Weapons-related Background Check
RaceCode	RaceCode	O	1	I = Native American, A = Asian, B = Black, W = White, U = Unknown
Reason	Reason	M	254	
SexCode	SexCode	C	1	M = Male, F = Female
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	M	2	

Possible Combinations

1. (In/Out) Attention, BirthDate, Name, PurposeCode, Reason, SexCode, State, [MiscellaneousNumber, RaceCode, SocialSecurityNumber]
2. (In/Out) Attention, MiscellaneousNumber, Name, PurposeCode, Reason, State
3. (In/Out) Attention, Name, PurposeCode, Reason, SocialSecurityNumber, State

CCHIndexRecordExistenceQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
PurposeCode	PurposeCode	M	1	
RaceCode	RaceCode	C	1	
Reason	Reason	M	254	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateIDNumber	StateIDNumber	C	10	

Possible Combinations

1. (In/Out) Attention, BirthDate, MiscellaneousNumber, Name, PurposeCode, RaceCode, Reason, SexCode
2. (In/Out) Attention, BirthDate, Name, PurposeCode, RaceCode, Reason, SexCode
3. (In/Out) Attention, BirthDate, Name, PurposeCode, RaceCode, Reason, SexCode, SocialSecurityNumber
4. (In/Out) Attention, FBINumber, Name, PurposeCode, Reason
5. (In/Out) Attention, FBINumber, PurposeCode, Reason
6. (In/Out) Attention, MiscellaneousNumber, Name, PurposeCode, Reason
7. (In/Out) Attention, Name, PurposeCode, Reason, SocialSecurityNumber
8. (In/Out) Attention, Name, PurposeCode, Reason, StateIDNumber
9. (In/Out) Attention, PurposeCode, Reason, StateIDNumber

CCHKansasCriminalRecordQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
PurposeCode	PurposeCode	M	1	
Reason	Reason	M	254	
StateIDNumber	StateIDNumber	M	10	

Possible Combinations

1. (In/Out) Attention, PurposeCode, Reason, StateIDNumber

HazardousMaterialQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Control Field	ControlField	O	11	
United Nations Number	UnitedNationsNumber	M	4	

Possible Combinations (*fields within the square brackets are optional*)

1. UnitedNationsNumber [ControlField]

QueryPassThrough

Field Name	XML Tag Name	M/C/O	Size	Possible Values
MessageData	FreeText	M		

Possible Combinations (*fields within the square brackets are optional*)

1. FreeText

This is a message key pass through and does not require the header of the message, only the body.

Example: (Header)**KANS.ZQ73.KS12390202020**

Bolded text would be sent to ConnectCIC server in the FreeText tag.

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- KCJIS Message Key Book