

Louisiana (LA) LEMS

Transport:

DMPP-2020

Routing and Configuration Information:

Save byte routing

- The LEMS assigned ORI for a device (or for the site) should be placed in the <**Authentication**>/<**ORI**> field in the ConnectCIC header.
*** The use of the OriginatingAgencyORI transaction field has been deprecated; <**Authentication**>/< **OriginatingAgencyORI**> can be used to override the <Authentication>/<ORI>.
- The LEMS assigned Mnemonic (also known as “LDI”) for a device should be placed in the <**Authentication**>/<**Mnemonic**> field in the ConnectCIC header.
- The site-assigned User ID should be placed in the <**Authentication**>/<**UserName**> field in the ConnectCIC header.

Security Requirements:

None known at this time.

Logon Requirements:

None

Certification Requirements:

None

Need sponsor agency

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName

ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	O	7	

Possible Combinations

1. (In/Out) ArticleSerialNumber, [Attention, ArticleTypeCode]

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
BoatHullIdNumber	BoatHullIdNumber	C	20	
RegistrationNumber	RegistrationNumber	C	8	
State	State	O	2	

Possible Combinations

1. (In/Out) BoatHullIdNumber, [Attention, State]
2. (In/Out) RegistrationNumber, [Attention, State]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
PurposeCode	PurposeCode	M	1	
SexCode	SexCode	C	1	
State	State	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, PurposeCode, SexCode, [State]
2. (In/Out) OperatorLicenseNumber, PurposeCode, [State]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
BirthDate	BirthDate	C	8	
ImageIndicator	ImageIndicator	O	1	Y, N (Default)
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	17	
RaceCode	RaceCode	C	1	
SexCode	SexCode	C	1	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	

Possible Combinations

1. (In) OperatorLicenseNumber, [Attention, ImageIndicator]
2. (Out) OperatorLicenseNumber, State, [ImageIndicator, State2, State3, State4, State5]
3. (In/Out) BirthDate, Name, RaceCode, SexCode, [Attention, ImageIndicator, State, State2, State3, State4, State5]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
GunMake	GunMake	O	3	
GunSerialNumber	GunSerialNumber	M	20	
GunTypeCode	GunTypeCode	O	3	

Possible Combinations

1. (In/Out) GunSerialNumber, [Attention, GunMake, GunTypeCode]

ImageQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
OperatorLicenseNumber	OperatorLicenseNumber	M	9	

Possible Combinations

1. (In/Out) Attention, OperatorLicenseNumber

LogoffRequest

*This transaction does not contain any fields.

LogonRequest

Field Name	XML Tag Name	M/C/O	Size	Possible Values
NewPassword	NewPassword	O	20	
Password	Password	C	20	
UserName	UserName	C	20	

Possible Combinations

1. (In/Out) [UserName, Password, NewPassword]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
State	State	C	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	17	

Possible Combinations

1. (In/Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, State, [Attention, State2, State3, State4, State5]
2. (In/Out) State, VehicleIdentificationNumber, [Attention, State2, State3, State4, State5]

Transactions Supported:

Agency Operations and Support (AOS)

AOSLojackQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
TypeCode	TypeCode	M	1	Q – REPLY returns the stolen vehicle information from NCIC and the LoJack system send a Speed-up message to the stolen vehicle for easier tracking. C – Check performs an emergency update to the LoJack database, if a vehicle is stolen before the information can be entered normally into the LoJack database.
LoJackReplyCode	LoJackReplyCode	M	5	

Possible Combinations

1. (In/Out) LoJackReplyCode, TypeCode

Computerized Criminal History (CCH)

CriminalHistoryAQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	32	
FreeText	FreeText	M	14400	
NletsDestination	NletsDestination	M	9	
PurposeCode	PurposeCode	M	1	

Possible Combinations

1. (In/Out) Attention, FreeText, NletsDestination, PurposeCode

CriminalHistoryARQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	32	
FreeText	FreeText	M	14400	
NletsDestination	NletsDestination	M	9	
PurposeCode	PurposeCode	M	1	

Possible Combinations

1. (In/Out) Attention, FreeText, NletsDestination, PurposeCode

CriminalHistoryC14Query

Field Name	XML Tag Name	M/C/O	Size	Possible Values
PurposeCode	PurposeCode	O	1	
Requestor	Requestor	M	30	
StateIdNumber	StateIdNumber	M	10	

Possible Combinations

1. (In/Out) Requestor, StateIdNumber, [PurposeCode]

CriminalHistoryC1Query

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthYear	BirthYear	M	4	

Name	Name	M	30	
PurposeCode	PurposeCode	O	1	
RaceCode	RaceCode	M	1	
SexCode	SexCode	M	1	

Possible Combinations

1. (In/Out) BirthYear, Name, RaceCode, SexCode, [PurposeCode]

CriminalHistoryC2Query

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M	10	Format: "MM-DD-CCYY"
Name	Name	M	30	
Nameld	Nameld	M	10	
PurposeCode	PurposeCode	O	1	
StateldNumber	StateldNumber	M	10	

Possible Combinations

1. (In/Out) BirthDate, Name, Nameld, StateldNumber, [PurposeCode]

CriminalHistoryC3Query

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M	10	Format: "MM-DD-CCYY"
BirthYear	BirthYear	M	4	
Name	Name	M	30	
Nameld	Nameld	M	10	
PurposeCode	PurposeCode	O	1	
RaceCode	RaceCode	M	1	
SexCode	SexCode	M	1	
StateldNumber	StateldNumber	M	10	

Possible Combinations

1. (In/Out) BirthDate, BirthYear, Name, Nameld, RaceCode, SexCode, StateldNumber, [PurposeCode]

CriminalHistoryC4Query

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FBINumber	FBINumber	C	9	
LocalID	LocalID	C	8	
LSPCriminalHistoryORI	LSPCriminalHistoryORI	C	4	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	
PurposeCode	PurposeCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateldNumber	StateldNumber	C	10	

Possible Combinations

1. (In/Out) FBINumber, [PurposeCode]
2. (In/Out) LocalID, LSPCriminalHistoryORI, [PurposeCode]
3. (In/Out) OperatorLicenseNumber, OperatorLicenseStateCode, [PurposeCode]
4. (In/Out) SocialSecurityNumber, [PurposeCode]
5. (In/Out) StateldNumber, [PurposeCode]

CriminalHistoryC5Query

Field Name	XML Tag Name	M/C/O	Size	Possible Values
PurposeCode	PurposeCode	O	1	
Requestor	Requestor	M	30	
StateIdNumber	StateIdNumber	M	10	
SummaryRapsheetIndicator	SummaryRapsheetIndicator	O	1	

Possible Combinations

1. (In/Out) Requestor, StateIdNumber, [PurposeCode, SummaryRapsheetIndicator]

CriminalHistoryFQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address	Address	O	30	
Attention	Attention	M	30	
Building	Building	O	30	
CityAndState	CityAndState	O	30	
DepartmentName	DepartmentName	O	30	
PurposeCode	PurposeCode	M	1	
State	State	O	2	
StateIdNumber	StateIdNumber	M	10	
ZipCode	ZipCode	O	9	

Possible Combinations

1. (In/Out) Attention, PurposeCode, StateIdNumber, [Address, Building, CityAndState, DepartmentName, State, ZipCode]

CriminalHistoryIQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	8	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
PurposeCode	PurposeCode	M	1	
RaceCode	RaceCode	O	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	M	2	

Possible Combinations

1. (In/Out) Attention, BirthDate, Name, PurposeCode, SexCode, State, [MiscellaneousNumber, RaceCode, SocialSecurityNumber]
2. (In/Out) Attention, MiscellaneousNumber, Name, PurposeCode, State
3. (In/Out) Attention, Name, PurposeCode, SocialSecurityNumber, State

CriminalHistoryQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	Defaults to the value in Authentication/UserName
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	

PurposeCode	PurposeCode	M	1	
RaceCode	RaceCode	C	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) Attention, BirthDate, MiscellaneousNumber, Name, PurposeCode, RaceCode, SexCode
2. (In/Out) Attention, BirthDate, Name, PurposeCode, RaceCode, SexCode
3. (In/Out) Attention, BirthDate, Name, PurposeCode, RaceCode, SexCode, SocialSecurityNumber
4. (In/Out) Attention, FBINumber, Name, PurposeCode
5. (In/Out) Attention, FBINumber, PurposeCode
6. (In/Out) Attention, MiscellaneousNumber, Name, PurposeCode
7. (In/Out) Attention, Name, PurposeCode, SocialSecurityNumber
 8. (In/Out) Attention, Name, PurposeCode, StateIdNumber
 9. (In/Out) Attention, PurposeCode, StateIdNumber

CriminalHistoryQRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
Address	Address	O	30	
Attention	Attention	M	30	
Building	Building	O	30	
CityAndState	CityAndState	O	30	
DepartmentName	DepartmentName	O	30	
FBINumber	FBINumber	C	9	
PurposeCode	PurposeCode	M	1	
StateIdNumber	StateIdNumber	C	10	
ZipCode	ZipCode	O	9	

Possible Combinations

1. (In/Out) Attention, FBINumber, PurposeCode, [Attention, Address, Building, CityAndState, DepartmentName, ZipCode]
2. (In/Out) Attention, PurposeCode, StateIdNumber, [Attention, Address, Building, CityAndState, DepartmentName, ZipCode]

CriminalHistoryZRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
FBINumber	FBINumber	C	9	
PurposeCode	PurposeCode	O	1	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) FBINumber, [Attention, PurposeCode]
2. (In/Out) StateIdNumber, [Attention, PurposeCode]

Wanted Missing Person Entry (WMPE)

WMPEDentalDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber

WMPEDentalDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DentalCharacteristics	DentalCharacteristics	M	319	See NCIC Code Manual
DentalModelsAvailableIndicator	DentalModelsAvailableIndicator	M	1	Y, N
DentalXraysAvailableIndicator	DentalXraysAvailableIndicator	M	1	Y, N
DentistRemarks	DentistRemarks	O	50	
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	

Possible Combinations

1. (In/Out) DentalCharacteristics, DentalModelsAvailableIndicator, DentalXraysAvailableIndicator, NCICNumber, OriginatingAgencyCaseNumber, [DentistRemarks]

WMPEDentalDataModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DentalCharacteristics	DentalCharacteristics	O	319	See NCIC Code Manual
DentalModelsAvailableIndicator	DentalModelsAvailableIndicator	O	1	Y, N
DentalXraysAvailableIndicator	DentalXraysAvailableIndicator	O	1	Y, N
DentistRemarks	DentistRemarks	O	50	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O		
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [DentistRemarks, DentalCharacteristics, DentalModelsAvailableIndicator, DentalXraysAvailableIndicator, ModifiedOriginatingAgencyORI]

WMPEMissingPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
CancellationDate	CancellationDate	M	8	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, [PersonRecordRemovalReason]
2. (In/Out) Name, NCICNumber, CancellationDate, [PersonRecordRemovalReason]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, [PersonRecordRemovalReason]

WMPEMissingPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	

ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
HitResultsIndicator	HitResultsIndicator	O	2	1-9, See NCIC Code Manual for description
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyORI	RecoveringAgencyORI	O	9	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, [RecoveringAgencyCaseNumber, RecoveringAgencyORI]
2. (In/Out) Name, NCICNumber, ClearDate, [RecoveringAgencyCaseNumber, RecoveringAgencyORI]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, [RecoveringAgencyCaseNumber, RecoveringAgencyORI]

WMPEMissingPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyXRayCode	BodyXRayCode	O	1	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	See NCIC Code Manual
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EmancipationDate	EmancipationDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintIndicator	FootprintIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LastContactDate	LastContactDate	M	8	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	

MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
MissingPersonCircumstanceCode	MissingPersonCircumstanceCode	O	1	See NCIC Code Manual
MissingPersonCode	MissingPersonCode	M	2	See NCIC Code Manual
MissingPersonEntryType	MissingPersonEntryType	M	1	D – Disability E – Endangered I – Involuntary J – Emancipated Juvenile V – Catastrophe Victim O – Other
Name	Name	M	30	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, BirthDate, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, FBI Number, [Any optional fields]
3. (In/Out) MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, MiscellaneousNumber, [Any optional fields]
4. (In/Out) MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, SocialSecurityNumber, [Any optional fields]
5. (In/Out) MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
6. (In/Out) MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, LicensePlateYear, [Any optional fields]
7. (In/Out) MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, VehicleIdentificationNumber, VehicleMakeCode, VehicleYear, VehicleStyleCode, [Any optional fields]

8. (In/Out) MissingPersonEntryType = **J**, Name, SexCode, RaceCode, BirthDate, EmancipationDate, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEMissingPersonLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
DispositionCode	DispositionCode	M	4	
HitResultsIndicator	HitResultsIndicator	O	2	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, RecoveryDate, DispositionCode, [Any optional fields]
2. (In/Out) Name, NCICNumber, RecoveryDate, DispositionCode, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, RecoveryDate, DispositionCode, [Any optional fields]

WMPEMissingPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	
BloodTypeCode	BloodTypeCode	O	5	
BodyXRayCode	BodyXRayCode	O	1	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	
CircumcisionCode	CircumcisionCode	O	1	
CitizenshipCode	CitizenshipCode	O	2	
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Y, BLANK
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	
DNAIndicator	DNAIndicator	O	1	
DNALocation	DNALocation	O	250	
EmancipationDate	EmancipationDate	O	8	
EthnicityCode	EthnicityCode	O	1	
EyeColorCode	EyeColorCode	O	3	
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	
FootprintIndicator	FootprintIndicator	O	1	
HairColorCode	HairColorCode	O	3	
Height	Height	O	3	
JewelryDescription	JewelryDescription	O	100	

JewelryTypeCode	JewelryTypeCode	O	50	
LastContactDate	LastContactDate	O	8	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	O	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
MissingPersonCircumstanceCode	MissingPersonCircumstanceCode	O	1	
MissingPersonCode	MissingPersonCode	O	2	
ModifiedMessageKey	ModifiedMessageKey	O	4	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
RaceCode	RaceCode	O	1	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	
SexCode	SexCode	O	1	
SkinToneCode	SkinToneCode	O	3	
SocialSecurityNumber	SocialSecurityNumber	O	9	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	
VehicleStyleCode	VehicleStyleCode	O	2	
VehicleYear	VehicleYear	O	4	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEMissingPersonPersonWithInformationCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PersonWithInformationName	PersonWithInformationName	M	30	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName

2. (In/Out) Name, NCICNumber, PersonWithInformationName
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName

WMPEMissingPersonPersonWithInformationEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	M	500	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PersonWithInformationName	PersonWithInformationName	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, [Any optional fields]
3. (In/Out) Name, NCICNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, [Any optional fields]
4. (In/Out) Name, NCICNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, [Any optional fields]
5. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, [Any optional fields]
6. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, [Any optional fields]

WMPEMissingPersonPersonWithInformationModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PersonWithInformationName	PersonWithInformationName	M	30	
PersonWithInformationName2	PersonWithInformationName2	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual

SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, [Any optional fields]

WMPEMissingPersonPWISupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PersonWithInformationName	PersonWithInformationName	M	30	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, [Any optional fields]

WMPEMissingPersonPWISupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PersonWithInformationName	PersonWithInformationName	M	30	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
----------------------	----------------------	---	---	--

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, [Any optional fields]

WMPEMissingPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEMissingPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual.

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEProtectionOrderCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Protection Order
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, [Any optional fields]
2. (In/Out) Name, ProtectionOrderNumber, CancellationDate, [Any optional fields]
3. (In/Out) Name, NCICNumber, CancellationDate, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, [Any optional fields]

WMPEProtectionOrderClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Protection Order
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, [Any optional fields]
2. (In/Out) Name, ProtectionOrderNumber, ClearDate, [Any optional fields]
3. (In/Out) Name, NCICNumber, ClearDate, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, [Any optional fields]

WMPEProtectionOrderEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
BradyIndicator	BradyIndicator	O	1	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y

DNALocation	DNALocation	O	250	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExpirationDate	ExpirationDate	M	8	
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IssueDate	IssueDate	M	8	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Protection Order
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	O	30	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	C	8	
ProtectedPersonName	ProtectedPersonName	C	30	
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	C	9	
ProtectionOrderConditionsCode	ProtectionOrderConditionsCode	M	2	See NCIC Code Manual
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	
ServiceCode	ServiceCode	O	1	See NCIC Code Manual
ServiceDate	ServiceDate	O	8	
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, BirthDate, [Any optional fields]

2. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, FBINumber, [Any optional fields]
3. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, MiscellaneousNumber, [Any optional fields]
4. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, SocialSecurityNumber, [Any optional fields]
5. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
6. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, [Any optional fields]
7. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]
8. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, ProtectedPersonName, ProtectedPersonSocialSecurityNumber, [Any optional fields]
9. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, ProtectedPersonName, ProtectedPersonBirthDate, [Any optional fields]
10. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, BirthDate, [Any optional fields]
11. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, FBINumber, [Any optional fields]
12. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, MiscellaneousNumber, [Any optional fields]
13. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, SocialSecurityNumber, [Any optional fields]
14. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
15. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, [Any optional fields]
16. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]
17. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, ProtectedPersonName, ProtectedPersonSocialSecurityNumber, [Any optional fields]
18. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, ProtectedPersonName, ProtectedPersonBirthDate, [Any optional fields]

WMPEProtectionOrderModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
BradyIndicator	BradyIndicator	O	1	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	

DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExpirationDate	ExpirationDate	O	8	
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IssueDate	IssueDate	O	8	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Protection Order
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	EPO ETO EPOC ETOC
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	
ProtectedPersonName	ProtectedPersonName	O	30	
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	
ProtectionOrderConditionsCode	ProtectionOrderConditionsCode	O	2	See NCIC Code Manual
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
ProtectionOrderNumber2	ProtectionOrderNumber2	O	15	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
ServiceCode	ServiceCode	O	1	
ServiceDate	ServiceDate	O	8	
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual

VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, ProtectionOrderNumber, [Any optional fields]
3. (In/Out) Name, NCICNumber, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEProtectionOrderSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateExpirationYear	LicensePlateExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonName	ProtectedPersonName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderConditionCode	ProtectionOrderConditionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderNumber	ProtectionOrderNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEProtectionOrderSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateExpirationYear	LicensePlateExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonName	ProtectedPersonName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderConditionCode	ProtectionOrderConditionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderNumber	ProtectionOrderNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESexOffenderCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	

Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, [Any optional fields]
2. (In/Out) Name, NCICNumber, CancellationDate, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, [Any optional fields]

WMPESexOffenderClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, [Any optional fields]
2. (In/Out) Name, NCICNumber, ClearDate, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, [Any optional fields]

WMPESexOffenderEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	M	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	M	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BoatColorCode	BoatColorCode	O	7	See NCIC Code Manual
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual
BoatHullNumber	BoatHullNumber	O	20	
BoatHullShapeCode	BoatHullShapeCode	O	2	
BoatLength	BoatLength	O	2	See NCIC Code Manual
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual
BoatModelName	BoatModelName	O	20	
BoatModelYear	BoatModelYear	O	4	
BoatName	BoatName	O	20	
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	
ConvictionDate	ConvictionDate	M	8	
ConvictionOffenseCode	ConvictionOffenseCode	M	4	See NCIC Code Manual
CrimeLocation	CrimeLocation	O	2	See NCIC Code Manual, State Code
DNALocation	DNALocation	O	250	
DNAIndicator	DNAIndicator	O	1	Blank, N, Y
EmailAddress	EmailAddress	O	80	

EmployerName	EmployerName	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
HomePort	HomePort	O	20	
InternetId	InternetId	O	80	
JuvenileOffenderIndicator	JuvenileOffenderIndicator	O	1	Blank, N, Y
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	C	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	M	30	
NCICNumber	NCICNumber	O	10	
Occupation	Occupation	O	80	
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	
RaceCode	RaceCode	M	1	See NCIC Code Manual
RegistrationEndDate	RegistrationEndDate	M	8	
RegistrationNumber	RegistrationNumber	O	8	
RegistrationStartDate	RegistrationStartDate	M	8	
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual
ResidenceBeginDate	ResidenceBeginDate	O	8	
ResidenceEndDate	ResidenceEndDate	O	8	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SchoolName	SchoolName	O	80	
SexCode	SexCode	M	1	See NCIC Code Manual
SexOffenderTier	SexOffenderTier	O	1	See NCIC Code Manual
SexualPredatorIndicator	SexualPredatorIndicator	O	1	Blank, N, Y
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
StateIdNumber	StateIdNumber	O	10	
TelephoneNumber	TelephoneNumber	O	12	
TelephoneType	TelephoneType	C	1	See NCIC Code Manual
RegistrationExpirationYear	RegistrationExpirationYear	O	2	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	

VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleOwnershipCode	VehicleOwnershipCode	O	2	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
VictimAge	VictimAge	O	2	
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) Name, SexCode, RaceCode, BirthDate, RegistrationStartDate, RegistrationEndDate, Height, Weight, HairColorCode, EyeColorCode, ConvictionOffenseCode, ConvictionDate, OriginatingAgencyCaseNumber, AddressStateCode, [Any optional fields]

WMPESexOffenderModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BoatColorCode	BoatColorCode	O	7	See NCIC Code Manual
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual
BoatHullNumber	BoatHullNumber	O	20	
BoatHullShapeCode	BoatHullShapeCode	O	2	
BoatLength	BoatLength	O	2	See NCIC Code Manual
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual
BoatModelName	BoatModelName	O	20	
BoatModelYear	BoatModelYear	O	4	
BoatName	BoatName	O	20	
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	
ConvictionDate	ConvictionDate	O	8	
ConvictionOffenseCode	ConvictionOffenseCode	O	4	See NCIC Code Manual
CrimeLocation	CrimeLocation	O	2	See NCIC Code Manual, State Code
DNALocation	DNALocation	O	250	
DNAIndicator	DNAIndicator	O	1	Blank, N, Y
EmailAddress	EmailAddress	O	80	
EmployerName	EmployerName	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual

HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
HomePort	HomePort	O	20	
InternetId	InternetId	O	80	
JuvenileOffenderIndicator	JuvenileOffenderIndicator	O	1	Blank, N, Y
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	O	10	
Occupation	Occupation	O	80	
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
RegistrationEndDate	RegistrationEndDate	O	8	
RegistrationNumber	RegistrationNumber	O	8	
RegistrationStartDate	RegistrationStartDate	O	8	
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual
ResidenceBeginDate	ResidenceBeginDate	O	8	
ResidenceEndDate	ResidenceEndDate	O	8	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SchoolName	SchoolName	O	80	
SexCode	SexCode	O	1	See NCIC Code Manual
SexOffenderTier	SexOffenderTier	O	1	See NCIC Code Manual
SexualPredatorIndicator	SexualPredatorIndicator	O	1	Blank, N, Y
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
StateIdNumber	StateIdNumber	O	10	
TelephoneNumber	TelephoneNumber	O	12	
TelephoneType	TelephoneType	O	1	See NCIC Code Manual
RegistrationExpirationYear	RegistrationExpirationYear	O	2	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual

VehicleOwnershipCode	VehicleOwnershipCode	O	2	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
VictimAge	VictimAge	O	2	
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESexOffenderSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullNumber	BoatHullNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullShapeCode	BoatHullShapeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatLength	BoatLength	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelName	BoatModelName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelYear	BoatModelYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatName	BoatName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
EmailAddress	EmailAddress	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Employer	Employer	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
InternetId	InternetId	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
Occupation	Occupation	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProfessionalLicenseNumberType	ProfessionalLicenseNumberType	O	80	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationExpirationYear	RegistrationExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

RegistrationNumber	RegistrationNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SchoolName	SchoolName	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
StateIdNumber	StateIdNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumber	TelephoneNumber	O	12	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumberType	TelephoneNumberType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleOwnershipCode	VehicleOwnershipCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimAge	VictimAge	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
---------------	---------------	---	---	--

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESexOffenderSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullNumber	BoatHullNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullShapeCode	BoatHullShapeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatLength	BoatLength	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelName	BoatModelName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelYear	BoatModelYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatName	BoatName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
EmailAddress	EmailAddress	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Employer	Employer	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
InternetId	InternetId	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
Occupation	Occupation	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProfessionalLicenseNumberType	ProfessionalLicenseNumberType	O	80	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationExpirationYear	RegistrationExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationNumber	RegistrationNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SchoolName	SchoolName	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
StateIdNumber	StateIdNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumber	TelephoneNumber	O	12	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumberType	TelephoneNumberType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleOwnershipCode	VehicleOwnershipCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimAge	VictimAge	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
--	--	--	--	--

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESupervisedReleaseCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, [Any optional fields]
2. (In/Out) Name, NCICNumber, CancellationDate, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, [Any optional fields]

WMPESupervisedReleaseClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, [Any optional fields]
2. (In/Out) Name, NCICNumber, ClearDate, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, [Any optional fields]

WMPESupervisedReleaseEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArrestDate	ArrestDate	O	8	
ArrestingAgencyORI	ArrestingAgencyORI	O	9	
BirthDate	BirthDate	C	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EmailAddress	EmailAddress	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	
FraudulentBirthDate	FraudulentBirthDate	O	8	
FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	
FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	O	20	

FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	O	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	O	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
IncarcerationPlace	IncarcerationPlace	O	50	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ReleaseDate	ReleaseDate	O	8	
ReleaseLocation	ReleaseLocation	O	50	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SentencingCourtORI	SentencingCourtORI	O	9	
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
SupervisingOfficerName	SupervisingOfficerName	M	30	
SupervisingOfficerTelephone	SupervisingOfficerTelephone	M	12	
SupervisionStartDate	SupervisionStartDate	M	8	
SupervisionExpirationDate	SupervisionExpirationDate	M	8	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
WarrantCourtORI	WarrantCourtORI	O	9	
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, BirthDate, [Any optional fields]
2. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, FBI Number, [Any optional fields]
3. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate,

- SupervisingOfficerName, SupervisingOfficerTelephone, MiscellaneousNumber, [Any optional fields]
4. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, SocialSecurityNumber, [Any optional fields]
 5. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
 6. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, [Any optional fields]
 7. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]

WMPESupervisedReleaseFraudulentDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESupervisedReleaseFraudulentDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESupervisedReleaseModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArrestDate	ArrestDate	O	8	
ArrestingAgencyORI	ArrestingAgencyORI	O	9	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EmailAddress	EmailAddress	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FraudulentBirthDate	FraudulentBirthDate	O	8	
FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	
FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	O	20	
FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	O	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	O	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IncarcerationPlace	IncarcerationPlace	O	50	

LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	EC EC-C
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
ProbationParoleExpirationDate	ProbationParoleExpirationDate	O	8	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ReleaseLocation	ReleaseLocation	O	50	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SentencingCourtORI	SentencingCourtORI	O	9	
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
SupervisingOfficerName	SupervisingOfficerName	O	30	
SupervisingOfficerTelephone	SupervisingOfficerTelephone	O	12	
SupervisionStartDate	SupervisionStartDate	O	8	
SupervisionReleaseDate	SupervisionReleaseDate	O	5	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
WarrantCourtORI	WarrantCourtORI	O	9	
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESupervisedReleaseSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESupervisedReleaseSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEUnidentifiedPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	

NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
RecordRemovalReason	RecordRemovalReason	O	21	

Possible Combinations

1. (In/Out) CancellationDate, NCICNumber, OriginatingAgencyCaseNumber, [RecordRemovalReason]

WMPEUnidentifiedPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
RecordRemovalReason	RecordRemovalReason	O	21	

Possible Combinations

1. (In/Out) ClearDate, NCICNumber, OriginatingAgencyCaseNumber, [RecordRemovalReason]

WMPEUnidentifiedPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyFoundDate	BodyFoundDate	M	8	
BodyPartsStatusCode	BodyPartsStatusCode	C	15	See NCIC Code Manual
CauseOfDeath	CauseOfDeath	O	30	
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EstimatedBirthYear	EstimatedBirthYear	C	9	
EstimatedDeathDate	EstimatedDeathDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintAvailableIndicator	FootprintAvailableIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	7	Range of values Ex. 000-000
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MedicalExaminerAgencyAndCaseNumber	MedicalExaminerAgencyAndCaseNumber	O	50	
MedicalExaminerLocality	MedicalExaminerLocality	O	30	
MedicalExaminerTelephoneNumber	MedicalExaminerTelephoneNumber	O	12	
MessageKeyModifier	MessageKeyModifier	M	1	D – Deceased L – Living V – Catastrophe Victim
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual

SexCode	SexCode	M	1	See NCIC Code Manual
Weight	Weight	M	7	Range of values Ex. 000-000
XraysAvailableIndicator	XraysAvailableIndicator	M	1	Blank, Y

Possible Combinations

1. (In/Out) MessageKeyModifier=**D** or **V**, BodyPartsStatusCode, SexCode, RaceCode, EstimatedDeathDate, BodyFoundDate, Height, Weight, EyeColorCode, HairColorCode, OriginatingAgencyCaseNumber, XraysAvailableIndicator, CauseOfDeath, [BloodTypeCode, CircumcisionCode, CorrectiveVisionPerscriptionCode, DNAIndicator, DNALocation, EstimatedBirthYear, EthnicityCode, FingerprintClassificationCode, FootprintAvailableIndicator, JewelryDescription, JewelryTypeCode, LinkageAgencyIdentifier, LinkageCaseNumber, MedicalExaminerAgencyAndCaseNumber, MedicalExaminerLocality, MedicalExaminerTelephoneNumber, MiscellaneousDescriptiveText, NotifyOriginatingAgencyIndicator, ScarsMarksTattoosCode]
2. (In/Out) MessageKeyModifier=**L**, SexCode, RaceCode, BodyFoundDate, Height, Weight, EyeColorCode, HairColorCode, FingerprintClassificationCode, OriginatingAgencyCaseNumber, XraysAvailableIndicator, [BloodTypeCode, CircumcisionCode, CorrectiveVisionPerscriptionCode, DNAIndicator, DNALocation, EstimatedBirthYear, EthnicityCode, FootprintAvailableIndicator, JewelryDescription, JewelryTypeCode, LinkageAgencyIdentifier, LinkageCaseNumber, MedicalExaminerAgencyAndCaseNumber, MedicalExaminerLocality, MedicalExaminerTelephoneNumber, MiscellaneousDescriptiveText, NotifyOriginatingAgencyIndicator, ScarsMarksTattoosCode]

WMPEUnidentifiedPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyFoundDate	BodyFoundDate	O	8	
BodyPartsStatusCode	BodyPartsStatusCode	O	15	See NCIC Code Manual
CauseOfDeath	CauseOfDeath	O	30	
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EstimatedBirthYear	EstimatedBirthYear	O	9	
EstimatedDeathDate	EstimatedDeathDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintAvailableIndicator	FootprintAvailableIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MedicalExaminerAgencyAndCaseNumber	MedicalExaminerAgencyAndCaseNumber	O	50	
MedicalExaminerLocality	MedicalExaminerLocality	O	30	
MedicalExaminerTelephoneNumber	MedicalExaminerTelephoneNumber	O	12	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
ModifiedMessageKey	ModifiedMessageKey	O	4	EUD - Deceased EUL - Living EUV - Catastrophe Victim

ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
NCICNumber	NCICNumber	M	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
ValidatorName	ValidatorName	O	30	
VisionPrescription	VisionPrescription	O	40	
Weight	Weight	O	3	
XraysAvailableIndicator	XraysAvailableIndicator	O	1	Blank, Y

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEUnidentifiedPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [ImageNCICNumber, ImageNCICNumber2, ImageNCICNumber3, ImageNCICNumber4, ImageType, ImageType2, ImageType3, ImageType4, ScarsMarksTattoosCode, ScarsMarksTattoosCode2, ScarsMarksTattoosCode3, ScarsMarksTattoosCode4]

WMPEUnidentifiedPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [ImageNCICNumber, ImageNCICNumber2, ImageNCICNumber3, ImageNCICNumber4, ImageType, ImageType2,

ImageType3, ImageType4, ScarsMarksTattoosCode, ScarsMarksTattoosCode2,
ScarsMarksTattoosCode3, ScarsMarksTattoosCode4]

WMPEWantedPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
CancellationDate	CancellationDate	M	8	

Possible Combinations

1. (In/Out) Name, NCICNumber, CancellationDate, [MessageKeyModifier, NCICNumber, OriginatingAgencyCaseNumber, PersonRecordRemovalReason]
2. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, [MessageKeyModifier, NCICNumber, OriginatingAgencyCaseNumber, PersonRecordRemovalReason]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, [MessageKeyModifier, NCICNumber, OriginatingAgencyCaseNumber, PersonRecordRemovalReason]

WMPEWantedPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
HitResultsIndicator	HitResultsIndicator	O	2	See NCIC Code Manual
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	Blank, Y
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyORI	RecoveringAgencyORI	O	9	

Possible Combinations

1. (In/Out) Name, NCICNumber, ClearDate, [ContrabandRecoveredValue, HitResultsIndicator, MessageKeyModifier, NumberMissingPersonsFound, NumberPersonsApprehended, OtherRecoveredPropertyValue, PersonArmedIndicator, PersonRecordRemovalReason, PropertyRecoveredValue, RecoveringAgencyCaseNumber, RecoveringAgencyORI]
2. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, [ContrabandRecoveredValue, HitResultsIndicator, MessageKeyModifier, NumberMissingPersonsFound, NumberPersonsApprehended, OtherRecoveredPropertyValue, PersonArmedIndicator, PersonRecordRemovalReason, PropertyRecoveredValue, RecoveringAgencyCaseNumber, RecoveringAgencyORI]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, [ContrabandRecoveredValue, HitResultsIndicator, MessageKeyModifier, NumberMissingPersonsFound, NumberPersonsApprehended, OtherRecoveredPropertyValue,

PersonArmedIndicator, PersonRecordRemovalReason, PropertyRecoveredValue,
RecoveringAgencyCaseNumber, RecoveringAgencyORI]

WMPEWantedPersonDetainerCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	M	20	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	

Possible Combinations

1. (In/Out) Name, NCICNumber, DetainerCaseNumber
2. (In/Out) Name, OriginatingAgencyCaseNumber, DetainerCaseNumber
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, DetainerCaseNumber

WMPEWantedPersonDetainerEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	M	20	
DetainerDate	DetainerDate	M	8	
IncarceratingAgencyORI	IncarceratingAgencyORI	M	9	
IncarcerationPlace	IncarcerationPlace	O	50	
IncarcerationStartDate	IncarcerationStartDate	O	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
SentenceExpirationDate	SentenceExpirationDate	O	8	

Possible Combinations

1. (In/Out) Name, NCICNumber, DetainerCaseNumber, IncarceratingAgencyORI, [IncarcerationPlace, IncarcerationStartDate, SentenceExpirationDate]
2. (In/Out) Name, OriginatingAgencyCaseNumber, DetainerCaseNumber, IncarceratingAgencyORI, [IncarcerationPlace, IncarcerationStartDate, SentenceExpirationDate]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, DetainerCaseNumber, IncarceratingAgencyORI, [IncarcerationPlace, IncarcerationStartDate, SentenceExpirationDate]

WMPEWantedPersonDetainerModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	O	20	
DetainerDate	DetainerDate	O	8	
IncarceratingAgencyORI	IncarceratingAgencyORI	O	9	
IncarcerationPlace	IncarcerationPlace	O	50	
IncarcerationStartDate	IncarcerationStartDate	O	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
SentenceExpirationDate	SentenceExpirationDate	O	8	
ValidatorName	ValidatorName	O	30	

Possible Combinations

1. (In/Out) Name, NCICNumber, [DetainerCaseNumber, IncarceratingAgencyORI, IncarcerationPlace, ValidatorName]

2. (In/Out) Name, OriginatingAgencyCaseNumber, [DetainerCaseNumber, IncarceratingAgencyORI, IncarcerationPlace, ValidatorName]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [DetainerCaseNumber, IncarceratingAgencyORI, IncarcerationPlace, ValidatorName]

WMPEWantedPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalOffenseIndicator	AdditionalOffenseIndicator	O	1	Blank, Y
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	C	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
DocumentedAddressDate	DocumentedAddressDate	O	8	
EmancipationDate	EmancipationDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExtraditionLimitation	ExtraditionLimitation	M	2	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FraudulentBirthDate	FraudulentBirthDate	O	8	
FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	
FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	C	20	
FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	C	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	C	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
IncidentDate	IncidentDate	M	8	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	

NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OffenseCode	OffenseCode	M	24	
OperatorLicenseYear	OperatorLicenseYear	C	4	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OriginalOffenseCode	OriginalOffenseCode	C	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	3	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
WantedPersonType	WantedPersonType	O	1	Blank, J – Wanted Juvenile
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	M	3	

*Operator License fields must be entered as a set.

*License Plate fields must be entered as a set.

*VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, and VehicleStyleCode must be entered as a set.

Possible Combinations

1. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, BirthDate, [Any optional fields]
2. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FBI Number [Any optional fields]
3. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, MiscellaneousNumber [Any optional fields]
4. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, SocialSecurityNumber [Any optional fields]
5. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
6. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, LicensePlateNumber, LicensePlateStateCode, LicensePlateExpirationYear, LicensePlateTypeCode, [Any optional fields]
7. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]

8. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentName, FraudulentBirthDate, [Any optional fields]
9. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentMiscellaneousNumber, [Any optional fields]
10. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentSocialSecurityNumber, [Any optional fields]
11. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentOperatorLicenseNumber, FraudulentOperatorLicenseStateCode, FraudulentOperatorLicenseYear, [Any optional fields]
12. (In/Out) WantedPersonType, Name, SexCode, RaceCode, BrithDate, EmancipationDate, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, [Any optional fields]

WMPEWantedPersonFraudulentDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEWantedPersonFraudulentDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEWantedPersonLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
Extradition	Extradition	M	4	See NCIC Code Manual
HitResultsIndicator	HitResultsIndicator	O	2	See NCIC Code Manual
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	Blank, Y
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	

Possible Combinations

1. (In/Out) Name, NCICNumber, Extradition, RecoveryDate, [ContrabandRecoveredValue, HitResultsIndicator, MessageKeyModifier, NumberMissingPersonsFound, NumberPersonsApprehended, OtherRecoveredPropertyValue, PersonArmedIndicator, PersonRecordRemovalReason, PropertyRecoveredValue, RecoveringAgencyCaseNumber]
2. (In/Out) Name, OriginatingAgencyCaseNumber, Extradition, RecoveryDate, [ContrabandRecoveredValue, HitResultsIndicator, MessageKeyModifier, NumberMissingPersonsFound, NumberPersonsApprehended, OtherRecoveredPropertyValue,

- PersonArmedIndicator, PersonRecordRemovalReason, PropertyRecoveredValue, RecoveringAgencyCaseNumber]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, Extradition, RecoveryDate, [ContrabandRecoveredValue, HitResultsIndicator, MessageKeyModifier, NumberMissingPersonsFound, NumberPersonsApprehended, OtherRecoveredPropertyValue, PersonArmedIndicator, PersonRecordRemovalReason, PropertyRecoveredValue, RecoveringAgencyCaseNumber]

WMPEWantedPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalOffenseIndicator	AdditionalOffenseIndicator	O	1	Blank, Y
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	
DNALocation	DNALocation	O	250	Blank, Y
DocumentedAddressDate	DocumentedAddressDate	O	8	
EmancipationDate	EmancipationDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExtraditionLimitation	ExtraditionLimitation	O	2	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IncidentDate	IncidentDate	O	8	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	Blank EW – Wanted Person EWJ – Wanted Juvenile ET – Temporary Felony EW-C – Wanted Person with Caution EWJC – Wanted Juvenile with Caution

				ET-C – Temporary Felony with Caution
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OffenseCode	OffenseCode	O	24	See NCIC Code Manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	
OperatorLicenseYear	OperatorLicenseYear	O	4	See NCIC Code Manual
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
ValidatorNameName	ValidatorNameName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEWantedPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressCounty	AddressCounty	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetName	AddressStreetName	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetNumber	AddressStreetNumber	O	7	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressTypeCode	AddressTypeCode	O	2	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressZipCode	AddressZipCode	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	

ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]
4. [Any optional fields]

WMPEWantedPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressCounty	AddressCounty	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetName	AddressStreetName	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetNumber	AddressStreetNumber	O	7	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressTypeCode	AddressTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

AddressZipCode	AddressZipCode	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

*Operator License fields must be entered as a set.

*License Plate fields must be entered as a set.

*VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, and VehicleStyleCode must be entered as a set.

*Address fields must be entered as a set.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

Wanted Missing Person Inquiries (WMP-I)

WMPIMissingPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
Age	Age	M	2	
AreaCode	AreaCode	O	3	See NCIC Code Manual
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Blank, Y
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
Name	Name	O	30	
RaceCode	RaceCode	M	1	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual

Weight	Weight	M	3	
--------	--------	---	---	--

Possible Combinations

1. (In/Out) Age, EyeColorCode, HairColorCode, Height, RaceCode, SexCode, Weight, [Attention, AreaCode, EthnicityCode, ExpandedNameSearchCode, Name]

WMPIProtectionOrderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
BirthDate	BirthDate	C	8	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Blank, Y
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Blank, Y
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Blank, Y
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
RaceCode	RaceCode	O	1	See NCIC Code Manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Blank, Y
SexCode	SexCode	O	1	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	

Possible Combinations

1. (In/Out) Name, BirthDate, [Attention, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, RaceCode, RelatedHitSearchIndicator, SexCode]
2. (In/Out) Name, OriginatingAgencyCaseNumber, [Attention, ExpandedNameSearchCode, ImageIndicator, RaceCode, RelatedHitSearchIndicator, SexCode]
3. (In/Out) Name, ProtectionOrderNumber, [Attention, ExpandedNameSearchCode, ImageIndicator, RaceCode, RelatedHitSearchIndicator, SexCode]
4. (In/Out) NCICNumber, [Attention, ImageIndicator, RelatedHitSearchIndicator]
5. (In/Out) Name, FBINumber, [Attention, ImageIndicator, RelatedHitSearchIndicator]
6. (In/Out) Name, MiscellaneousNumber, [Attention, ImageIndicator, RelatedHitSearchIndicator]
7. (In/Out) Name, OperatorLicenseNumber, [Attention, ImageIndicator, RelatedHitSearchIndicator]
8. (In/Out) Name, SocialSecurityNumber, [Attention, ImageIndicator, RelatedHitSearchIndicator]
9. (In/Out) LicensePlateNumber, LicensePlateStateCode, [ImageIndicator, RelatedHitSearchIndicator, VehicleIdentificationNumber, VehicleMakeCode]
10. (In/Out) VehicleIdentificationNumber, VehicleMakeCode, [Attention, VehicleMakeCodeDescription, ImageIndicator, RelatedHitSearchIndicator, LicensePlateNumber, LicensePlateStateCode]

WMPISexOffenderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName

BirthDate	BirthDate	C	8	
BoatHullNumber	BoatHullNumber	C	20	
BoatRegistrationNumber	BoatRegistrationNumber	C	10	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Blank, Y
ExpandedNameSearchIndicator	ExpandedNameSearchIndicator	O	1	Blank, Y
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Blank, Y
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	O	1	See NCIC Code Manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SexCode	SexCode	O	1	See NCIC Code Manual
SexualOffenderStatusIndicator	SexualOffenderStatusIndicator	O	1	Y,N
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
ZipCode	ZipCode	C	10	

Possible Combinations

1. (In/Out) Name, **and at least one** BirthDate, BoatHullNumber, FBINumber, LicensePlateNumber, MiscellaneousNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, RegistrationNumber, SocialSecurityNumber, VehicleIdentificationNumber, [Attention, VehicleMakeCodeDescription, ExpandedBirthDateSearchCode, ExpandedNameSearchIndicator, ImageIndicator, LicensePlateStateCode, RaceCode, RelatedHitSearchIndicator, SexCode, VehicleMakeCode]
2. (In/Out) ZipCode, [Attention, SexualOffenderStatusIndicator, ImageIndicator]

WMPIUnidentifiedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
Age	Age	C	2	
AreaCode	AreaCode	O	3	See NCIC Code Manual
BodyPartsStatusCode	BodyPartsStatusCode	C	15	See NCIC Code Manual
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	C	3	See NCIC Code Manual
HairColorCode	HairColorCode	C	3	See NCIC Code Manual
Height	Height	C	3	
ImageIndicator	ImageIndicator	O	1	Blank, Y
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	C	1	See NCIC Code Manual
SexCode	SexCode	C	1	See NCIC Code Manual
Weight	Weight	C	3	

Possible Combinations

1. (In/Out) Age, EyeColorCode, HairColorCode, Height, RaceCode, SexCode, Weight [Attention, AreaCode, EthnicityCode, ImageIndicator]

2. (In/Out) BodyPartsStatusCode, [Attention, AreaCode, ImageIndicator, RaceCode, SexCode]
3. (In/Out) NCICNumber, [Attention]
4. (In/Out) OriginatingAgencyCaseNumber, [Attention]

WMPIWantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
BirthDate	BirthDate	C	8	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Blank, Y
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Blank, Y
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Blank, Y
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	
MessageKeyModifier	MessageKeyModifier	O	1	Blank, A, E, F, S See NCIC Wanted Person File for additional information on different message keys available.
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	O	1	See NCIC Code Manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Blank, Y
SexCode	SexCode	O	1	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	

Possible Combinations

1. (In/Out) Name, BirthDate, [Attention, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, MessageKeyModifier, RaceCode, RelatedHitSearchIndicator, SexCode]
2. (In/Out) Name, OriginatingAgencyCaseNumber, [Attention, ExpandedNameSearchCode, ImageIndicator, MessageKeyModifier, RelatedHitSearchIndicator]
3. (In/Out) NCICNumber, [Attention, ImageIndicator, MessageKeyModifier, RelatedHitSearchIndicator]
4. (In/Out) Name, FBINumber, [Attention, ImageIndicator, MessageKeyModifier, RelatedHitSearchIndicator]
5. (In/Out) Name, MiscellaneousNumber, [Attention, ImageIndicator, MessageKeyModifier, RelatedHitSearchIndicator]
6. (In/Out) Name, OperatorLicenseNumber, [Attention, ImageIndicator, MessageKeyModifier, RelatedHitSearchIndicator]
7. (In/Out) Name, SocialSecurityNumber, [Attention, ImageIndicator, MessageKeyModifier, RelatedHitSearchIndicator]
8. (In/Out) LicensePlateNumber, LicensePlateStateCode, [Attention, ImageIndicator, MessageKeyModifier, RelatedHitSearchIndicator, VehicleIdentificationNumber, VehicleMakeCode]
9. (In/Out) VehicleIdentificationNumber, VehicleMakeCode, [Attention, VehicleMakeCodeDescription, ImageIndicator, MessageKeyModifier, RelatedHitSearchIndicator, LicensePlateNumber, LicensePlateStateCode]

Expanded Transactions Supported:

AFISPhotoQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Requestor	Requestor	M	30	
StateIdNumber	StateIdNumber	M	10	

Possible Combinations

1. (In/Out) Requestor, StateIdNumber

InsuranceQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	C	4	
MessageKeyModifier	MessageKeyModifier	O	1	V – Real-Time Insurance Check
VehicleIdentificationNumber	VehicleIdentificationNumber	C	17	

Possible Combinations

1. (In/Out) LicensePlateNumber, [Attention, LicensePlateTypeCode, LicensePlateYear, MessageKeyModifier]
2. (In/Out) VehicleIdentificationNumber, [Attention, MessageKeyModifier]

LaLemsRqsDins

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	8	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	17	

Possible Combinations

1. (In/Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, State, [Attention, State2, State3, State4, State5]
2. (In/Out) VehicleIdentificationNumber, State, [Attention, State2, State3, State4, State5]

MissingPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

Attention	Attention	O	30	Defaults to the value in Authentication/UserName
Age	Age	M	2	
Area	Area	O	3	
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	
EyeColorCode	EyeColorCode	M	3	
HairColorCode	HairColorCode	M	3	
Height	Height	M	3	
ImageIndicator	ImageIndicator	O	1	
Name	Name	O	30	
RaceCode	RaceCode	M	1	
SexCode	SexCode	M	1	
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) Age, EyeColorCode, HairColorCode, Height, RaceCode, SexCode, Weight, [Area, ExpandedNameSearchCode, ImageIndicator, Name]

QueryPassThrough

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Message Data	FreeText	M	400	

Possible Combinations *(fields within the square brackets are optional)*

1. FreeText

*This is a message key pass through and does not require the header of the message, only the body.

Example: (Header)**QA.ORI/123456789.TYP/YTHING.SER/123456**

Bolded text would be sent to ConnectCIC server in the FreeText tag.

PICustomVehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
ImageIndicator	ImageIndicator	O	1	Y, BLANK
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	17	

Possible Combinations

1. (In) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, [Attention, ImageIndicator]
2. (In) VehicleIdentificationNumber, [Attention, ImageIndicator]

UnidentifiedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
Area	Area	O	3	
BodyPartsStatusCode	BodyPartsStatusCode	M	15	
ImageIndicator	ImageIndicator	O	1	

RaceCode	RaceCode	O	1	
SexCode	SexCode	O	1	

Possible Combinations

1. (In/Out) BodyPartsStatusCode, [Attention, Area, ImageIndicator, RaceCode, SexCode]

WantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Defaults to the value in Authentication/UserName
BirthDate	BirthDate	O	8	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	
FBINumber	FBINumber	O	9	
ImageIndicator	ImageIndicator	O	1	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	O	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SexCode	SexCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	24	

** An inquiry of the Wanted Person File may be made by name and one, more than one, or all of the following alphanumeric identifiers: DOB, FBI, MNU, SOC, and OLN. Additionally, inquiries may be made using vehicle data (LIC, LIS, and/or VIN and VMA); NAM and OCA only; or NIC only.

Possible Combinations

1. (In/Out) Name and an additional identifier, [Attention, BirthDate, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, MiscellaneousNumber, OperatorLicenseNumber, RaceCode, RelatedHitSearchIndicator, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
2. (In/Out) Name, OriginatingAgencyCaseNumber, [Attention]
3. (In/Out) NCICNumber, [Attention]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- Louisiana State (LEMS) Documentation