

Massachusetts (MA) LEAPS XML V2

[Disclaimer Statement](#)

Transport:

Web Services (SOAP over HTTP). Requires TCP level network access to the state.

Routing and Configuration Information:

Save byte routing.

- The LEAPS assigned ORI for a device (or for the site) should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.*
- The LEAPS assigned Mnemonic for a device should be placed in the **<Authentication>/<Mnemonic>** field in the ConnectCIC header.*
- A User ID should be placed in the **<Authentication>/<UserName>** field in the ConnectCIC header. The User ID is assigned by LEAPS.*
- A password should be placed in the **<Authentication>/<Password>** field in the ConnectCIC header. Passwords are assigned by LEAPS.*

*If using Device or User Alias Tables, this information would be stored in these tables instead of included in each message transaction. The UserName and Password values must be unique and at the time of this writing can be assigned by the vendor. In the future these will be assigned by the LEAPS.

Security Requirements:

Massachusetts requires that information for background checks be provided to the agency on all vendor employees who may have access to CJIS data. Vendors must meet FBI Security Policy requirements.

Logon Requirements:

No login is required.

Certification Requirements:

Need Site Sponsor

Agencies must complete the paperwork requesting CHSB to testing a vendor's product. Once approved, vendors must follow the steps outlined in the document "Guidelines for Evaluation and Testing of Non-Standard Equipment/Software" which includes vendors passing software certification testing. Further information can be found at :

<http://www.mass.gov/eopss/law-enforce-and-cj/cjis/massachusetts-cjis-guidelines-for-vendors.html>.

CHSB requires additional transactions beyond our defined Basic Query. ConnectCIC's Basic Query set for MA LEAPS XML has been altered to support the requirements of CHSB. All transactions listed under Basic Query are required to pass CHSB's certification process. Additionally, CHSB requires the ability to drill down a transaction based on candidate list information. For more information about ConnectCIC's built-in drill down support available with data mining, please see [Drill Down Processing](#).

Data-Mined Transactions & Fields:

LEAPS returns all responses in the state-specific XML format, not in the typical block format. Therefore, by default in Massachusetts, ConnectCIC will pass you the response in this XML format (non-human readable XML with state tags). If you would like to receive the Massachusetts data in the CommSys mined (parsed) fields using our consistent XML tags (same across all interfaces), you would need to purchase the data-mining module.

NCIC (QA, QB, QG, QWA) and DMV(RMV) (Person and Vehicle)
[Tags returned from Data mining](#)

Furthermore, if you also would like to receive the return response in a standard block format, CommSys offers an optional ConnectCIC module for Massachusetts called "Response Reassembly" that provides a block-type return.

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	20	
RegistrationNumber	RegistrationNumber	C	8	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	

Possible Combinations

1. (In/Out) BoatHullIdNumber, [State, State2, State3, State4, State5]
2. (In/Out) RegistrationNumber, [State, State2, State3, State4, State5]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
ImageIndicator	ImageIndicator	O	5	true
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
PurposeCode	PurposeCode	O	1	C,F,E,D,J,S
SexCode	SexCode	C	1	M,F,U
State	State	O	2	
BirthDate	BirthDate	C	10	
Name	Name	C	30	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, State, [Attention, ImageIndicator, PurposeCode]
2. (In/Out) OperatorLicenseNumber, State, [Attention, ImageIndicator, PurposeCode]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	10	
ImageIndicator*	ImageIndicator*	O	5	true
Name	Name	C	30	
NextAlias	NextAlias	O	8	
NextName	NextName	O	8	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	

SexCode	SexCode	C	1	M,F,U
State	State	C	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	

Possible Combinations

1. (In) Name,[BirthDate,NextAlias,NextName]
2. (In) OperatorLicenseNumber
3. (In) OperatorLicenseNumber,State,[ImageIndicator*,State3,State4,State5]
4. (In) Name,BirthDate,SexCode,State,[ImageIndicator*,State3,State4,State5]
5. (Out) OperatorLicenseNumber,[ImageIndicator*,State2,State3,State4,State5]
6. (Out) Name,BirthDate,SexCode,[ImageIndicator*,State2,State3,State4,State5]

Footnote(s)

* ImageIndicator is required to conduct image queries in triggered secondary transaction. Assure the user password save setting has been enabled. Please see checklist.

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	O	23	
GunSerialNumber	GunSerialNumber	C	20	
ImageIndicator	ImageIndicator	O	1	Y, N, or Blank
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Y, N, or Blank

Possible Combinations

1. (In/Out) GunSerialNumber, [GunCaliber, GunMake, ImageIndicator, RelatedHitSearchIndicator]

ImageQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageId	ImageId	M	8	

Possible Combinations

1. (In) ImageId

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	4	
LicensePlateColorCode	LicensePlateColorCode	C	1	
LicensePlateYear	LicensePlateYear	C	4	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	
VehicleYear	VehicleYear	C	4	

Possible Combinations

1. (In) LicensePlateNumber, LicensePlateTypeCode, LicensePlateColorCode
2. (In) VehicleIdentificationNumber
3. (Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, State, [State2,State3,State4,State5]
4. (Out) VehicleIdentificationNumber, VehicleMakeCode, VehicleYear, State, [State2,State3,State4,State5]

Transactions Supported:

Agency Operations and Support (AOS)

AOSHazardousMaterialQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
UnitedNationsNumber	UnitedNationsNumber	M	4	

Possible Combinations

1. (In/Out) [UnitedNationsNumber]

Canadian Basic Query Package (CBI)

CBIArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	23	
ArticleTypeCode	ArticleTypeCode	M	2	AA – Domestic appliances BI – Non-motorized vehicles BU - -Bulk entries HH – Household property JE – Jewelry MI – Musical instruments MT – Machinery and Tools OM – Office machines PA – Personal Accessories PE Photographic equipment PH – Phones and wireless communication RA – Radio, TV, sound reproducing SC – Scientific, optical and measuring SP – Sporting goods OT - Other
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	O	1	Y or N
ReasonCode	ReasonCode	O	1	N – Narcotics F – Fraud V – Violent Crimes T – Traffic violations S – Theft H - Humanitarian

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode, [PersonPropertyInSightIndicator, ReasonCode]

CBIBoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	12	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	O	1	Y or N

ReasonCode	ReasonCode	O	1	N – Narcotics F – Fraud V – Violent Crimes T – Traffic violations S – Theft H – Humanitarian
RegistrationNumber	RegistrationNumber	C	7	

Possible Combinations

1. (In/Out) BoatHullIdNumber, [PersonPropertyInSightIndicator, ReasonCode]
2. (In/Out) RegistrationNumber, [PersonPropertyInSightIndicator, ReasonCode]

CBIDriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M	10	
Name	Name	M	30	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	O	1	Y or N
ReasonCode	ReasonCode	O	1	N – Narcotics F – Fraud V – Violent Crimes T – Traffic violations S – Theft H - Humanitarian
SexCode	SexCode	M	1	F, M
State	State	M	2	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, State, [PersonPropertyInSightIndicator, ReasonCode, OperatorLicenseNumber]

CBIGunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunSerialNumber	GunSerialNumber	M	23	
GunTypeCode	GunTypeCode	M	2	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	O	1	Y or N
ReasonCode	ReasonCode	O	1	N – Narcotics F – Fraud V – Violent Crimes T – Traffic violations S – Theft H - Humanitarian

Possible Combinations

1. (In/Out) GunSerialNumber, GunTypeCode, [PersonPropertyInSightIndicator, ReasonCode]

CBIVehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	10	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	O	1	Y or N
ReasonCode	ReasonCode	O	1	N – Narcotics F – Fraud V – Violent Crimes T – Traffic violations S – Theft

				H - Humanitarian
State	State	M	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	17	

Possible Combinations

1. (In/Out) LicensePlateNumber, State, [PersonPropertyInSightIndicator, ReasonCode]
2. (In/Out) VehicleIdentificationNumber, State, [PersonPropertyInSightIndicator, ReasonCode]

Computerized Criminal History (CCH)

CCHCriminalHistoryAQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
FreeText	FreeText	M	14400	
ImageIndicator	ImageIndicator	O	1	
NletsDestination	NletsDestination	M	9	
NletsDestination2	NletsDestination2	O	9	
NletsDestination3	NletsDestination3	O	9	
NletsDestination4	NletsDestination4	O	9	
NletsDestination5	NletsDestination5	O	9	
PurposeCode	PurposeCode	O	1	

Possible Combinations

1. (In/Out) FreeText, NletsDestination, [Attention, ImageIndicator, NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, PurposeCode]

CCHCriminalHistoryARQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	AQ Attention value if present
FreeText	FreeText	M	14400	
Name	Name	M	30	
NletsDestination	NletsDestination	M	9	
PurposeCode	PurposeCode	O	1	AQ Purpose code if present

Possible Combinations

1. (In/Out) FreeText, Name, NletsDestination, [Attention, PurposeCode]

CCHCriminalHistoryFQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	
AddressStateCode	AddressStateCode	O	2	
AddressStreet	AddressStreet	O	30	
AddressZipCode	AddressZipCode	O	10	
Attention	Attention	O	30	
DepartmentName	DepartmentName	O	30	
ImageIndicator	ImageIndicator	O	1	
PurposeCode	PurposeCode	O	1	
State	State	M		
StateIdNumber	StateIdNumber	M	10	

Possible Combinations

1. (In/Out) StateIdNumber, State, [AddressCity, AddressStateCode, AddressStreet, AddressZipCode, Attention, DepartmentName, ImageIndicator, PurposeCode]

CCHCriminalHistoryIQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	M	10	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	M	30	
PurposeCode	PurposeCode	O	1	
RaceCode	RaceCode	O	1	
SexCode	SexCode	M	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
State	State	M	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, State, [Attention, MiscellaneousNumber, PurposeCode, RaceCode, SocialSecurityNumber, State2, State3, State4, State5]

CCHCriminalHistoryQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	10	
FBINumber	FBINumber	C	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
PurposeCode	PurposeCode	M	1	
RaceCode	RaceCode	C	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) FBINumber, PurposeCode, [Name]
2. (In/Out) Name, PurposeCode, MiscellaneousNumber
3. (In/Out) Name, PurposeCode, SocialSecurityNumber
4. (In/Out) Name, BirthDate, PurposeCode, RaceCode, SexCode, [MiscellaneousNumber, SocialSecurityNumber]
5. (In/Out) PurposeCode, StateIdNumber, [Name]

CCHCriminalHistoryQRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
FBINumber	FBINumber	C	9	
Name	Name	O	30	
PurposeCode	PurposeCode	M	1	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) FBI Number, PurposeCode, [Attention, Name]
2. (In/Out) StateIdNumber, PurposeCode, [Attention, Name]

CCHCriminalHistoryQWIQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	10	
EnhancedNameSearchIndicator	EnhancedNameSearchIndicator	O	1	Y, N, or Blank
ImageIndicator	ImageIndicator	O	1	Y, N, or Blank
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
PurposeCode	PurposeCode	M	1	
RaceCode	RaceCode	O	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Y, N, or Blank
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	

Possible Combinations

1. (In/Out) Name, BirthDate, SexCode, PurposeCode, [Attention, EnhancedNameSearchIndicator, ImageIndicator, MiscellaneousNumber, RaceCode, RelatedHitSearchIndicator, SocialSecurityNumber]
2. (In/Out) Name, MiscellaneousNumber, PurposeCode, [Attention, EnhancedNameSearchIndicator, ImageIndicator, RelatedHitSearchIndicator]
3. (In/Out) Name, SocialSecurityNumber, PurposeCode, [Attention, EnhancedNameSearchIndicator, ImageIndicator, RelatedHitSearchIndicator]

Wanted Missing Person Inquiries (WMP-I)

WMPISexOffenderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	C	20	
AddressStateCode	AddressStateCode	O	2	
AddressStreetName	AddressStreetName	C	30	
AddressStreetNameSecond	AddressStreetNameSecond	O	10	
AddressStreetNumber	AddressStreetNumber	O	6	
AddressZipCode	AddressZipCode	C	10	
Attention	Attention	O	30	
BirthDate	BirthDate	O	10	
ImageIndicator	ImageIndicator	O	1	
Name	Name	C	30	
PurposeCode	PurposeCode	O	1	
SexCode	SexCode	C	1	
SexOffenderNumber	SexOffenderNumber	C	6	
State	State	C	2	

Possible Combinations

1. (In) AddressStreetName, AddressCity, AddressZipCode, [AddressStateCode, AddressStreetNameSecond, AddressStreetNumber]
2. (In) Name, [BirthDate]
3. (In) SexOffenderNumber
4. (Out) BirthDate, Name, SexCode, State, [Attention, ImageIndicator, PurposeCode]

WMPIWantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	10	
FBINumber	FBINumber	C	9	
LicensePlateNumber	LicensePlateNumber	C	10	
MiscellaneousNumber	MiscellaneousNumber	C	15	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	O	1	
SexCode	SexCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	C	2	
Name	Name	C	30	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	

Possible Combinations

1. (In/Out) Name, plus one or more (BirthDate, FBINumber, MiscellaneousNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, SocialSecurityNumber), [RaceCode, SexCode]
2. (In/Out) NCICNumber
3. (In/Out) LicensePlateNumber, State
4. (In/Out) VehicleIdentificationNumber, VehicleMakeCode

Expanded Transactions Supported:

AlarmExchangeResponse

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlarmResponse	AlarmResponse	M	16384	
DestinationORI	DestinationORI	M	9	
FormORI	FormORI	O	9	

Possible Combinations

1. (In/Out) AlarmResponse, DestinationORI, [FormORI]

MaLeapsXmlBop1

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M		
Name	Name	M		

Possible Combinations

1. (In/Out) BirthDate, Name

MaLeapsXmlConcealedWeaponsQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address	Address	C		
BirthDate	BirthDate	C		
Name	Name	C		

SurrogateIdNumber	SurrogateIdNumber	C		
-------------------	-------------------	---	--	--

Possible Combinations

1. (In) Address
2. (In) BirthDate, Name
3. (In) SurrogateIdNumber

MaLeapsXmlDriverLicenseNoR3Query

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	10	
ImageIndicator	ImageIndicator	O	5	true
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	C	1	M,F,U
State	State	C	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	

Possible Combinations

1. (In) Name, BirthDate
2. (In) OperatorLicenseNumber
3. (Out) OperatorLicenseNumber, State, [ImageIndicator,State2,State3,State4,State5]
4. (Out) Name, BirthDate, SexCode,State, [ImageIndicator,State2,State3,State4,State5]

MaLeapsXmlFirearmsOwnersIdQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address	Address	C	160	
BirthDate	BirthDate	C	10	
GunCaliber	GunCaliber	O	20	
GunMake	GunMake	O	50	
Name	Name	C	100	
FirearmId	FirearmId	C	20	Numbers only

Possible Combinations

1. (In) Address
2. (In) BirthDate, Name
3. (In) GunSerialNumber, [GunCaliber, GunMake]
4. (In) FirearmId

MaLeapsXmlQs

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Denomination	Denomination	C	9	
Issuer	Issuer	O	15	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
Owner	Owner	C	40	
NCICNumber	NCICNumber	C	10	
ImageIndicator	ImageIndicator	O	1	Y, N, or Blank
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Y, N, or Blank
SecurityDate	SecurityDate	O	8	
SecuritySerialNumber	SecuritySerialNumber	C	20	

SecurityTypeCode	SecurityTypeCode	C	2	
SocialSecurityNumber	SocialSecurityNumber	C	9	

Possible Combinations

1. (In/Out) Denomination, SecuritySerialNumber, SecurityTypeCode, [ImageIndicator, Issuer, RelatedHitSearchIndicator, SecurityDate]
2. (In/Out) Owner, [ImageIndicator, RelatedHitSearchIndicator, SecurityDate]
3. (In/Out) Owner, SecurityTypeCode, [ImageIndicator, RelatedHitSearchIndicator, SecurityDate]
4. (In/Out) OriginatingAgencyCaseNumber, Owner, [ImageIndicator, RelatedHitSearchIndicator, SecurityDate]
5. (In/Out) Owner, SocialSecurityNumber, [ImageIndicator, RelatedHitSearchIndicator, SecurityDate]
6. (In/Out) SocialSecurityNumber, [ImageIndicator, Owner, RelatedHitSearchIndicator, SecurityDate]
7. (In/Out) NCICNumber, [ImageIndicator, RelatedHitSearchIndicator, SecurityDate]

MaLeapsXmlSrr

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	M		
DateOfDocumentCoverage	DateOfDocumentCoverage	M		

Possible Combinations

1. (In/Out) AddressCity, DateOfDocumentCoverage

MaLeapsXmlSui1

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M		
Name	Name	M		

Possible Combinations

1. (In/Out) BirthDate, Name

MaLeapsXmlSui2

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O		
CJISReferenceID	CJISReferenceID	M		
Name	Name	O		

Possible Combinations

1. (In/Out) CJISReferenceID, [BirthDate, Name]

MaLeapsXmlVehicleRegistrationR6Query

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C		
LicensePlateTypeCode	LicensePlateTypeCode	O		
LicensePlateColorCode	LicensePlateColorCode	O		
RegistrationStatusCode	RegistrationStatusCode	O		
SurrogateIdNumber	SurrogateIdNumber	C		

Possible Combinations

1. (In) LicensePlateNumber, [LicensePlateColorCode, LicensePlateTypeCode, RegistrationStatusCode]
2. (In) SurrogateIdNumber

MaLeapsXmlVehicleRegistrationR7Query

Field Name	XML Tag Name	M/C/O	Size	Possible Values
VehicleIdentificationNumber	VehicleIdentificationNumber	C		
RegistrationStatusCode	RegistrationStatusCode	O		
SurrogateIdNumber	SurrogateIdNumber	C		

Possible Combinations

1. (In) VehicleIdentificationNumber, [RegistrationStatusCode]
2. (In) SurrogateIdNumber

MaLeapsXmlVehicleRegistrationR8Query

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O		
DatabaseldNumber	DatabaseldNumber	C		
Name	Name	C		
RegistrationStatusCode	RegistrationStatusCode	O		
SurrogateIdNumber	SurrogateIdNumber	C		

Possible Combinations

1. (In) Name, [BirthDate, RegistrationStatusCode]
2. (In) DatabaseldNumber, [RegistrationStatusCode]
3. (In) SurrogateIdNumber, [RegistrationStatusCode]

MaLeapsXmlVehicleRegistrationR9Query

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	M		
LicensePlateTypeCode	LicensePlateTypeCode	O		
RegistrationStatusCode	RegistrationStatusCode	O		

Possible Combinations

1. (In) LicensePlateNumber, [LicensePlateTypeCode, RegistrationStatusCode]

MaLeapsXmlVehicleRqfQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	10	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In/Out) LicensePlateNumber
2. (In/Out) VehicleIdentificationNumber

MaLeapsXmlWarrantDetailQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CourtId	CourtId	M		
DocketId	DocketId	M		

Possible Combinations

- (In) CourtId, DocketId

P1AlarmExchangeResponse

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlarmResponse	AlarmResponse	M	16384	

DestinationORI	DestinationORI	M	9	
FormORI	FormORI	O	9	

Possible Combinations

1. (In/Out) AlarmResponse, DestinationORI, [FormORI]

ProbationSummaryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M		
Name	Name	M		

Possible Combinations

1. (In) BirthDate, Name

ProbationSummaryDrilldown

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M		
Name	Name	M		
ProbationId	ProbationId	M		

Possible Combinations

1. (In) BirthDate, Name, ProbationId

StolenSecuritiesQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Denomination	Denomination	C	9	
ImageIndicator	ImageIndicator	O	1	Y or Blank
Issuer	Issuer	C	15	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
Owner	Owner	C	30	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Y or Blank
SecurityDate	SecurityDate	C	9	
SecuritySerialNumber	SecuritySerialNumber	C	18	
SecurityTypeCode	SecurityTypeCode	C	2	
SocialSecurityNumber	SocialSecurityNumber	C		

Possible Combinations

1. (In/Out) [Denomination, ImageIndicator, Issuer, OriginatingAgencyCaseNumber, RelatedHitSearchIndicator, SecurityDate, SecuritySerialNumber, SecurityTypeCode, SocialSecurityNumber]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

- ConnectCIC will return response information from LEAPS to vendors in the state-defined XML (non-human readable) as our basic product always returns to you what the interface returns to us. This is not the ConnectCIC Data-

Mining/Parsed XML tags but the state-specific tags. If our Data-Mining Module is purchased, then we will provide our consistent XML tags as well. Also, if you would like to receive the information in a formatted block-type return as well (much like how many of the other state/regional interfaces return the data), ConnectCIC offers an optional module for such. The module is called Response Reassembly. See the ConnectCIC Master Price Book for module and pricing information.

- ConnectCIC will need to connect to an HTTP server and thus has more specific Windows Operating System requirements. Be sure to verify the Operating System requirements; these are located in the “Hardware/Software Requirements” Section above.

References:

- NCIC 2000 Operations Manual
- NLETS User Guide CJIS-XML Web service documentation