

Transport:

DMPP2020

Routing and Configuration Information:

Save byte routing

- The DPSCS assigned ORI for a device (or for the site) should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.
- The DPSCS assigned PID for a device should be placed in the **<Authentication>/<DeviceId>** field in the ConnectCIC header.
- The DPSCS assigned User ID for a user should be placed in the **<Authentication>/<UserName>** field in the ConnectCIC header.

Security Requirements:

Each site must request DPSCS access for the vendor and application and complete the necessary paperwork, which will include a network diagram and information about the application's purpose and use. The physical and application security is addressed. This paperwork is necessary to gain approval for DPSCS connectivity. This paperwork must be completed by the site before DPSCS will release any documentation or provide any connectivity or assistance to vendors.

Logon Requirements:

UserName and Password

Certification Requirements:

When the local agency has determined that their testing is complete and they are ready to cut their new system in production DPSCS will need the following items.

- 1) DPSCS will need an email from the individual in charge of the agency stating that the agency's testing has been completed and the agency is ready to move to production.
 - a. This letter will need to contain the IP address of the agency's connection to DPSCS (Ed Nabors will be able to provide this).
 - b. The cut over date must also be at least two weeks in advance of the send date of the email.
 - c. All other items which follow must be completed.

- d. Upon receipt of this letter and approval from Jillian Watts, Ed Nabors will send the local agency the production IP address and port number.
- 2) Dalene Drum will need a letter for the agency TAC officer with a list of all of the new PID numbers which need to be configured for the new system.
 - a. It is recommended to include half a dozen PID at the top of the list and clearly marked for testing. This way the production connection may be tested before a full roll out.
 - 3) If a new ORI is needed for the RMDT/CAD system then the ORI request process must be completed before the cut over to production can be started.

If the system is a new CAD system DPSCS and MSP must perform an onsite inspection of the system before the system can be cut over to production.

Data-Mined Transactions:

None

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	20	
RegistrationNumber	RegistrationNumber	C	8	

Possible Combinations

1. (In/Out) BoatHullIdNumber
2. (In/Out) BoatHullIdNumber, RegistrationNumber
3. (In/Out) RegistrationNumber

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C		
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	

Possible Combinations

1. (In) BirthDate, Name

2. (In) OperatorLicenseNumber

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C		
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	C	1	
RaceCode	RaceCode	C	1	
State	State	O	2	

Possible Combinations

1. (In) Name, SexCode, RaceCode, BirthDate, [State]
2. (In) Name, SexCode, RaceCode, OperatorLicenseNumber, OperatorLicenseExpirationYear, [State]
3. (Out) Name, SexCode, BirthDate, [State]
4. (In/Out) OperatorLicenseNumber, [State]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	M	4	
GunMake	GunMake	M	23	
GunSerialNumber	GunSerialNumber	M	20	

Possible Combinations

1. (In/Out) GunCaliber, GunMake, GunSerialNumber

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
State	State	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	24	

Possible Combinations

1. (In) VehicleIdentificationNumber, [VehicleMakeCode]
2. (In/Out) VehicleIdentificationNumber, [State]
3. (In) LicensePlateNumber
4. (In/Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, [State]

Transactions Supported:

None

Expanded Transactions Supported:

LogoffRequest

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Password	Password	O		

Possible Combinations

1. (In/Out) [Password]

LogonRequest

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Password	Password	M		

Possible Combinations

1. (In/Out) Password

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Hardware

Edge Checkpoint Device

Notes:

None

References:

- Maryland Department of Public Safety and Correctional Services (Mobile Data Terminal Interface Specifications)
- NCIC 2000 Operations Manual
- NLETS User Guide
- RMDTS Specifications Document
- RMDT Info Sheet