

Michigan (MI) LEIN

[Disclaimer Statement](#)

Transport:

TCP/IP CPI (SimpleFrame)

Routing and Configuration Information:

Save byte routing

- The LEIN assigned ORI for a device (or for the site) should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.
- The LEIN assigned UserName for a User should be placed in the **<Authentication>/<UserName>** field in the ConnectCIC header.
- The site (agency name) may be placed in the **<Authentication>/<Agency>** field in the ConnectCIC header. If not specified, the **AddressDepartment** field becomes required in all transactions in which it is specified.

Security Requirements:

Follow state mandated agency-level security policy complete with background checks for vendors; follow NCIC 2000 policy for site security (firewalls, secure access, network security, etc.)

Logon Requirements:

None

Certification Requirements:

None

Need Site Sponsor

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Query Transactions Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	

FormORI	FormORI	O	9	
Requestor	Requestor	O	15	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode, [Requestor, AddressDepartment, FormORI]

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BoatHullIdNumber	BoatHullIdNumber	C	20	
BoatYear	BoatYear	C	6	
FormORI	FormORI	O	9	
RegistrationNumber	RegistrationNumber	C	10	
Requestor	Requestor	O	15	
State	State	C	2	

Possible Combinations

1. (In) BoatHullIdNumber, [Requestor, AddressDepartment, FormORI]
2. (In) RegistrationNumber, [Requestor, AddressDepartment, FormORI]
3. (In/Out) BoatHullIdNumber, [Requestor, AddressDepartment, FormORI]
4. (In/Out) BoatHullIdNumber, RegistrationNumber, [Requestor, AddressDepartment, FormORI]
5. (In/Out) RegistrationNumber, [Requestor, AddressDepartment, FormORI]
6. (Out) BoatHullIdNumber, State, [Requestor, AddressDepartment, FormORI]
7. (Out) BoatYear, RegistrationNumber, State, [Requestor, AddressDepartment, FormORI]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	8	
FormORI	FormORI	O	9	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	15	
RaceCode	RaceCode	C	1	
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	

Possible Combinations

1. (In/Out) BirthDate, Name, RaceCode, SexCode, [OperatorLicenseNumber, AddressDepartment, FormORI, Requestor]
2. (In/Out) OperatorLicenseNumber, [AddressDepartment, FormORI, Requestor]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	8	
FormORI	FormORI	O	9	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	15	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	
RaceCode	RaceCode	C	1	A, B, I, U, W
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	F, M, U

State	State	C	2	
-------	-------	---	---	--

Possible Combinations

1. (In) BirthDate, Name, RaceCode, SexCode, [Requestor, AddressDepartment, FormORI]
2. (In) BirthDate, Name, OperatorLicenseStateCode, RaceCode, SexCode, [Requestor, AddressDepartment, FormORI]
3. (In) OperatorLicenseNumber, [Requestor, AddressDepartment, FormORI]
4. (Out) BirthDate, Name, RaceCode, SexCode, State, [Requestor, AddressDepartment, FormORI]
5. (Out) OperatorLicenseNumber, State, [Requestor, AddressDepartment, FormORI]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
FormORI	FormORI	O	9	
FreeText	FreeText	O	22	
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	M	3	
GunSerialNumber	GunSerialNumber	M	20	
GunTypeCode	GunTypeCode	O	2	
Requestor	Requestor	O	15	

Possible Combinations

1. (In/Out) GunMake, GunSerialNumber, [Requestor, AddressDepartment, FormORI, FreeText, GunCaliber, GunTypeCode]

SnowmobileBoatOperatorQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	8	
FormORI	FormORI	O	9	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	15	
RaceCode	RaceCode	C	1	A, B, I, U, W
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	F, M, U

Possible Combinations

1. (In) BirthDate, Name, RaceCode, SexCode, [Requestor, AddressDepartment, FormORI]
2. (In) OperatorLicenseNumber, [Requestor, AddressDepartment, FormORI]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
AddressStreetNumber	AddressStreetNumber	O	8	
FormORI	FormORI	O	9	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
Name	Name	C	30	
PageCode	PageCode	C	8	
Requestor	Requestor	O	15	

State	State	C	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In) LicensePlateNumber, [Requestor, AddressDepartment, FormORI, LicensePlateTypeCode]
2. (In) VehicleIdentificationNumber, [Requestor, AddressDepartment, FormORI]
3. (In/Out) Name, [AddressStreetNumber, Requestor, AddressDepartment, FormORI]
4. (In/Out) PageCode, [Requestor, AddressDepartment, FormORI]
5. (Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, State, [Requestor, AddressDepartment, FormORI]
6. (Out) State, VehicleIdentificationNumber, [Requestor, AddressDepartment, FormORI]

Transactions Supported:

Agency Operations and Support (AOS):

AOSAdministrativeMessage

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ControlNumber	ControlNumber	O	10	10 character unique alphanumeric identifier
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
FreeText	FreeText	M	14000	
FromAgencyName	FromAgencyName	M	63	
MessageNumber	MessageNumber	M	63	Unique agency assigned message number
MessageTime	MessageTime	M	10	Message sent time, i.e. 1830 EST
NletsDestination	NletsDestination	M	9	ORI, mnemonic, or broadcast list code
NletsDestination2	NletsDestination2	O	9	ORI, mnemonic, or broadcast list code
NletsDestination3	NletsDestination3	O	9	ORI, mnemonic, or broadcast list code
NletsDestination4	NletsDestination4	O	9	ORI, mnemonic, or broadcast list code
NletsDestination5	NletsDestination5	O	9	ORI, mnemonic, or broadcast list code
OperatorName	OperatorName	M	25	Operator's name or initials
SignatureLine	SignatureLine	M	35	Signature line as per LEIN operations manual
Subject	Subject	O	70	Subject of message
ToAgencyName	ToAgencyName	M	200	

Possible Combinations

1. (In/Out) FreeText, FromAgencyName, MessageNumber, MessageTime, NletsDestination, OperatorName, SignatureLine, ToAgencyName, [ControlNumber, FormORI, NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, Subject]

AOSAircraftRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
AircraftSightedIndicator	AircraftSightedIndicator	C	1	Y, N, blank
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
RegistrationNumber	RegistrationNumber	C	6	
Requestor	Requestor	O	15	
SerialNumber	SerialNumber	C	20	
SightingDate	SightingDate	O	8	

Possible Combinations

1. (In/Out) AircraftSightedIndicator, RegistrationNumber, [AddressDepartment, FormORI, Requestor, SightingDate]
2. (In/Out) SerialNumber, [AddressDepartment, FormORI, Requestor]

AOSHazardousMaterialsQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
UnitedNationsNumber	UnitedNationsNumber	M	4	

Possible Combinations

1. (In/Out) UnitedNationsNumber, [FormORI]

AOSLeinORIModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ChangeRequestText	ChangeRequestText	C	14000	Specific ORI change request for LEIN
ControlNumber	ControlNumber	O	10	10 character unique alphanumeric identifier
FaxTelephoneNumber	FaxTelephoneNumber	O	12	
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
FromAgencyName	FromAgencyName	C	63	
MessageNumber	MessageNumber	C	63	Unique agency assigned message number
MessageTime	MessageTime	C	10	Message sent time, i.e. 1830 EST
MobileTerminalsNumber	MobileTerminalsNumber	O	4	Number of mobile terminals
OperatorName	OperatorName	C	25	
PrimaryTelephoneNumber	PrimaryTelephoneNumber	O	12	
SecondaryTelephoneNumber	SecondaryTelephoneNumber	O	12	Second phone number, or TAC phone number
SignatureLine	SignatureLine	C	35	
StationaryTerminalsNumber	StationaryTerminalsNumber	O	4	Number of mobile terminals
TACName	TACName	O	30	
TACName2	TACName2	O	30	

Possible Combinations

1. (In/Out) [FaxTelephoneNumber, FormORI, MobileTerminalsNumber, PrimaryTelephoneNumber, SecondaryTelephoneNumber, StationaryTerminalsNumber, TACName, TACName2]
2. (In/Out) ChangeRequestText, FromAgencyName, MessageNumber, MessageTime, OperatorName, SignatureLine, [ControlNumber, FormORI]

AOSLeinORIQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AgencyType	AgencyType	C	2	
FederalAgency	FederalAgency	C	3	
Location	Location	C	20	
LookupORI	LookupORI	C	9	
State	State	C	20	

Possible Combinations

1. (In) LookupORI
2. (In/Out) AgencyType, Location, [State]
3. (In/Out) FederalAgency, [Location, State]
4. (Out) LookupORI, State

AOSLoJackQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other

LojackId	LojackId	M	5	
Requestor	Requestor	O	15	

Possible Combinations

1. (In/Out) LojackId, [AddressDepartment, FormORI, Requestor]

AOSNletsHitConfirmationRequest

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleBrand	ArticleBrand	O	6	
ArticleSerialNumber	ArticleSerialNumber	C	20	
ArticleTypeCode	ArticleTypeCode	C	7	
BirthDate	BirthDate	C	8	
BoatHullIdNumber	BoatHullIdNumber	O	20	
BoatMakeCode	BoatMakeCode	O	24	
Brand	Brand	O	4	
Category	Category	O	2	
ControlNumber	ControlNumber	O	10	10 character unique alphanumeric identifier
CourtOrderNumber	CourtOrderNumber	O	20	
Denomination	Denomination	O	9	
ExtensionNumber	ExtensionNumber	O	4	
FaxNumber	FaxNumber	O	10	
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
FromAgencyName	FromAgencyName	C	63	
GunCaliber	GunCaliber	C	4	
GunMake	GunMake	C	24	
GunModel	GunModel	O	20	
GunSerialNumber	GunSerialNumber	C	20	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	O	4	
MessageNumber	MessageNumber	C	63	Unique agency assigned message number
MessageTime	MessageTime	C	10	Message sent time, i.e. 1830 EST
Name	Name	C	30	
NCICNumber	NCICNumber	O	10	
NletsDestination	NletsDestination	C	9	Destination agency ORI only
NletsDestination2	NletsDestination2	O	9	Destination agency ORI only
NletsDestination3	NletsDestination3	O	9	Destination agency ORI only
NletsDestination4	NletsDestination4	O	9	Destination agency ORI only
NletsDestination5	NletsDestination5	O	9	Destination agency ORI only
OperatorName	OperatorName	C	25	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PhoneNumber	PhoneNumber	O	10	
PriorityDestinationCode	PriorityDestinationCode	C	1	R,U
RegistrationNumber	RegistrationNumber	O	8	
Remarks	Remarks	O	250	
RequesterName	RequesterName	C	30	
RequestingAgency	RequestingAgency	C	30	
RequestNumber	RequestNumber	C	2	1, 2, 3
RequestTypeCode	RequestTypeCode	C	2	SA,SB,SG,SL,SP,SS,SV,WP

SecuritySerialNumber	SecuritySerialNumber	C	18	
SecurityTypeCode	SecurityTypeCode	C	2	
SerialNumber	SerialNumber	C	20	
SexCode	SexCode	O	1	
SignatureLine	SignatureLine	C	35	
ToAgencyName	ToAgencyName	C	200	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	24	
VehicleYear	VehicleYear	O	4	
WarrantNumber	WarrantNumber	O	20	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode, FromAgencyName, MessageNumber, MessageTime, NletsDestination, OperatorName, OriginatingAgencyCaseNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, SignatureLine, ToAgencyName, [ArticleBrand, ControlNumber, CourtOrderNumber, ExtensionNumber, FaxNumber, FormORI, NCICNumber, NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, PhoneNumber, Remarks, WarrantNumber]
2. (In/Out) BirthDate, FromAgencyName, MessageNumber, MessageTime, Name, NletsDestination, OperatorName, OriginatingAgencyCaseNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, SignatureLine, ToAgencyName, [ControlNumber, CourtOrderNumber, ExtensionNumber, FaxNumber, FormORI, NCICNumber, NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, PhoneNumber, Remarks, SexCode, WarrantNumber]
3. (In/Out) BirthDate, FromAgencyName, MessageNumber, MessageTime, Name, NletsDestination, OperatorName, OriginatingAgencyCaseNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, SignatureLine, ToAgencyName, [ControlNumber, CourtOrderNumber, ExtensionNumber, FaxNumber, FormORI, NCICNumber, NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, PhoneNumber, Remarks, SexCode, WarrantNumber]
4. (In/Out) FromAgencyName, GunCaliber, GunMake, GunSerialNumber, MessageNumber, MessageTime, NletsDestination, OperatorName, OriginatingAgencyCaseNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, SignatureLine, ToAgencyName, [ControlNumber, CourtOrderNumber, ExtensionNumber, FaxNumber, FormORI, GunModel, NCICNumber, NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, PhoneNumber, Remarks, WarrantNumber]
5. (In/Out) FromAgencyName, LicensePlateNumber, LicensePlateStateCode, MessageNumber, MessageTime, NletsDestination, OperatorName, OriginatingAgencyCaseNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, SignatureLine, ToAgencyName, [ControlNumber, CourtOrderNumber, ExtensionNumber, FaxNumber, FormORI, LicensePlateTypeCode, LicensePlateYear, NCICNumber, NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, PhoneNumber, Remarks, WarrantNumber]
6. (In/Out) FromAgencyName, MessageNumber, MessageTime, NletsDestination, OperatorName, OriginatingAgencyCaseNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, SecuritySerialNumber, SecurityTypeCode, SignatureLine, ToAgencyName, [ControlNumber, CourtOrderNumber, Denomination, ExtensionNumber, FaxNumber, FormORI, NCICNumber, NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, PhoneNumber, Remarks, WarrantNumber]
7. (In/Out) FromAgencyName, MessageNumber, MessageTime, NletsDestination, OperatorName, OriginatingAgencyCaseNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, SerialNumber, SignatureLine,

ToAgencyName, [Brand, Category, ControlNumber, CourtOrderNumber, ExtensionNumber, FaxNumber, FormORI, NCICNumber, NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, PhoneNumber, Remarks, WarrantNumber]

8. (In/Out) FromAgencyName, MessageNumber, MessageTime, NletsDestination, OperatorName, OriginatingAgencyCaseNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, SignatureLine, [ControlNumber, CourtOrderNumber, ExtensionNumber, FaxNumber, FormORI, LicensePlateNumber, NCICNumber, NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, PhoneNumber, Remarks, ToAgencyName, VehicleIdentificationNumber, VehicleMakeCode, VehicleYear, WarrantNumber]
9. (In/Out) FromAgencyName, MessageNumber, MessageTime, NletsDestination, OperatorName, OriginatingAgencyCaseNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, SignatureLine, ToAgencyName, [BoatHullIdNumber, BoatMakeCode, ControlNumber, CourtOrderNumber, ExtensionNumber, FaxNumber, FormORI, NCICNumber, NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, PhoneNumber, RegistrationNumber, Remarks, WarrantNumber]

AOSNletsHitConfirmationResponse

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleBrand	ArticleBrand	O	6	
ArticleSerialNumber	ArticleSerialNumber	O	20	
ArticleTypeCode	ArticleTypeCode	O	7	
BirthDate	BirthDate	O	8	
BoatHullIdNumber	BoatHullIdNumber	O	20	
BoatMakeCode	BoatMakeCode	O	24	
BoatRegistrationNumber	BoatRegistrationNumber	O	8	
ConfirmationStatusCode	ConfirmationStatusCode	M	1	E,N,P,Y
ConfirmingAgency	ConfirmingAgency	M	30	
ConfirmingName	ConfirmingName	M	30	
ControlNumber	ControlNumber	O	10	10 character unique alphanumeric identifier
CourtOrderNumber	CourtOrderNumber	O	20	
Denomination	Denomination	O	9	
ExtensionNumber	ExtensionNumber	O	4	
FaxNumber	FaxNumber	O	10	
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
FromAgencyName	FromAgencyName	M	63	
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	O	24	
GunModel	GunModel	O	20	
GunSerialNumber	GunSerialNumber	O	20	
HoursForConfirmation	HoursForConfirmation	M	3	The number of hours needed to confirm, i.e. 2
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	O	4	
MessageNumber	MessageNumber	M	63	Unique agency assigned message number
MessageTime	MessageTime	M	10	Message sent time, i.e. 1830 EST
Name	Name	O	30	
NCICNumber	NCICNumber	M	10	
NletsDestination	NletsDestination	M	9	Destination Agency ORI only

OperatorName	OperatorName	M	25	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
PartBrand	PartBrand	O	4	
PartCategoryCode	PartCategoryCode	O	2	
PartSerialNumber	PartSerialNumber	O	20	
PhoneNumber	PhoneNumber	O	10	
Remarks	Remarks	O	250	
RequestTypeCode	RequestTypeCode	M	2	SA,SB,SG,SL,SP,SS,SV,WP
SecuritySerialNumber	SecuritySerialNumber	O	20	
SecurityTypeCode	SecurityTypeCode	O	2	
SexCode	SexCode	O	1	
SignatureLine	SignatureLine	M	35	
ToAgencyName	ToAgencyName	M	200	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	24	
VehicleYear	VehicleYear	O	4	
WarrantNumber	WarrantNumber	O	20	

Possible Combinations

1. (In/Out) ConfirmationStatusCode, ConfirmingAgency, ConfirmingName, FromAgencyName, HoursForConfirmation, MessageNumber, MessageTime, NCICNumber, NletsDestination, OperatorName, OriginatingAgencyCaseNumber, RequestTypeCode, SignatureLine, ToAgencyName, [ArticleBrand, ArticleSerialNumber, ArticleTypeCode, BirthDate, BoatHullIdNumber, BoatMakeCode, BoatRegistrationNumber, ControlNumber, CourtOrderNumber, Denomination, ExtensionNumber, FaxNumber, FormORI, GunCaliber, GunMake, GunModel, GunSerialNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, LicensePlateYear, Name, PartBrand, PartCategoryCode, PartSerialNumber, PhoneNumber, Remarks, SecuritySerialNumber, SecurityTypeCode, SexCode, VehicleIdentificationNumber, VehicleMakeCode, VehicleYear, WarrantNumber]

Computerized Criminal History (CCH):

CCHCriminalHistoryAQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ControlNumber	ControlNumber	O	10	10 character unique alphanumeric identifier
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
FreeText	FreeText	M	14000	
FromAgencyName	FromAgencyName	M	63	
MessageNumber	MessageNumber	M	63	Unique agency assigned message number
MessageTime	MessageTime	M	10	Message sent time, i.e. 1830 EST
NletsDestination	NletsDestination	M	9	Destination agency ORI only
NletsDestination2	NletsDestination2	O	9	Destination agency ORI only
NletsDestination3	NletsDestination3	O	9	Destination agency ORI only
NletsDestination4	NletsDestination4	O	9	Destination agency ORI only
NletsDestination5	NletsDestination5	O	9	Destination agency ORI only
OperatorName	OperatorName	M	25	
SignatureLine	SignatureLine	M	35	
Subject	Subject	O	70	Subject of message
ToAgencyName	ToAgencyName	M	200	

Possible Combinations

2. (In/Out) FreeText, FromAgencyName, MessageNumber, MessageTime, NletsDestination, OperatorName, SignatureLine, ToAgencyName, [ControlNumber, FormORI, NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, Subject]

CCHCriminalHistoryARQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ControlNumber	ControlNumber	O	10	10 character unique alphanumeric identifier
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
FreeText	FreeText	M	14000	
FromAgencyName	FromAgencyName	M	63	
MessageNumber	MessageNumber	M	63	Unique agency assigned message number
MessageTime	MessageTime	M	10	Message sent time, i.e. 1830 EST
NletsDestination	NletsDestination	M	9	Destination agency ORI only
OperatorName	OperatorName	M	25	
SignatureLine	SignatureLine	M	35	
Subject	Subject	O	70	Subject of message
ToAgencyName	ToAgencyName	M	200	

Possible Combinations

1. (In/Out) FreeText, FromAgencyName, MessageNumber, MessageTime, NletsDestination, OperatorName, SignatureLine, ToAgencyName, [ControlNumber, FormORI, Subject]

CCHCriminalHistoryOutOfStateOnlyQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	8	
CriminalTrackingNumber	CriminalTrackingNumber	C	12	
FBINumber	FBINumber	C	9	
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	C	200	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C		
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PrisonNumber	PrisonNumber	C	11	
PurposeCode	PurposeCode	C	17	See LEIN operating manual for valid codes
RaceCode	RaceCode	C	1	
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	
State	State	M	2	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations *** Must enter either MiscellaneousDescriptiveText or OriginatingAgencyCaseNumber for all combinations ***

1. (In/Out) BirthDate, Name, PurposeCode, RaceCode, SexCode, State, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
2. (In/Out) CriminalTrackingNumber, PurposeCode, State, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
3. (In/Out) FBINumber, PurposeCode, State, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]

4. (In/Out) MiscellaneousNumber, PurposeCode, State, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
5. (In/Out) OperatorLicenseNumber, PurposeCode, State, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
6. (In/Out) PrisonNumber, PurposeCode, State, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
7. (In/Out) PurposeCode, State, StateIdNumber, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]

CCHCriminalHistoryQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	8	
CriminalTrackingNumber	CriminalTrackingNumber	C	12	
FBINumber	FBINumber	C	9	
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	C	200	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C		
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PrisonNumber	PrisonNumber	C	11	
PurposeCode	PurposeCode	C	17	See LEIN operating manual for valid codes
RaceCode	RaceCode	C	1	
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations* Must enter either MiscellaneousDescriptiveText or OriginatingAgencyCaseNumber for all combinations *****

1. (In/Out) BirthDate, Name, PurposeCode, RaceCode, SexCode, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
2. (In/Out) CriminalTrackingNumber, PurposeCode, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
3. (In/Out) FBINumber, PurposeCode, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
4. (In/Out) MiscellaneousNumber, PurposeCode, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
5. (In/Out) OperatorLicenseNumber, PurposeCode, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
6. (In/Out) PrisonNumber, PurposeCode, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
7. (In/Out) PurposeCode, StateIdNumber, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]

CCHCriminalHistoryQHWQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	8	
CriminalTrackingNumber	CriminalTrackingNumber	C	12	
FBINumber	FBINumber	C	9	

FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	C	200	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C		
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PrisonNumber	PrisonNumber	C	11	
PurposeCode	PurposeCode	C	17	See LEIN operating manual for valid codes
RaceCode	RaceCode	C	1	
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations* Must enter either MiscellaneousDescriptiveText or OriginatingAgencyCaseNumber for all combinations *****

1. (In/Out) BirthDate, Name, PurposeCode, RaceCode, SexCode, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
2. (In/Out) CriminalTrackingNumber, PurposeCode, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
3. (In/Out) FBINumber, PurposeCode, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
4. (In/Out) MiscellaneousNumber, PurposeCode, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
5. (In/Out) OperatorLicenseNumber, PurposeCode, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
6. (In/Out) PrisonNumber, PurposeCode, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
7. (In/Out) PurposeCode, StateIdNumber, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]

CCHCriminalHistoryQRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
FBINumber	FBINumber	C	9	
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	C	200	
NICSTransactionNumber	NICSTransactionNumber	O	9	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PurposeCode	PurposeCode	M	17	See LEIN operating manual for valid codes
Requestor	Requestor	O	15	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations* Must enter either MiscellaneousDescriptiveText or OriginatingAgencyCaseNumber for all combinations *****

1. (In/Out) FBINumber, PurposeCode, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, NICSTransactionNumber, OriginatingAgencyCaseNumber, Requestor]
2. (In/Out) PurposeCode, StateIdNumber, [AddressDepartment, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]

Canadian Basic Inquiries (CBI)

CanadianArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	
ArticleTypeCode2	ArticleTypeCode2	M	2	
FormORI	FormORI	O	9	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	
ReasonCode	ReasonCode	M	1	
Requestor	Requestor	O	15	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode, ArticleTypeCode2, PersonPropertyInSightIndicator, ReasonCode, [AddressDepartment, FormORI, Requestor]

CanadianBoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BoatHullIdNumber	BoatHullIdNumber	C	20	
BoatTypeCode	BoatTypeCode	M	2	
FormORI	FormORI	O	9	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	
ReasonCode	ReasonCode	M	1	
RegistrationNumber	RegistrationNumber	C	20	
Requestor	Requestor	O	15	

Possible Combinations

1. (In/Out) BoatHullIdNumber, BoatTypeCode, PersonPropertyInSightIndicator, ReasonCode, [AddressDepartment, FormORI, Requestor]
2. (In/Out) BoatTypeCode, PersonPropertyInSightIndicator, ReasonCode, RegistrationNumber, Requestor, [AddressDepartment, FormORI, Requestor]

CanadianDriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	M	8	
FormORI	FormORI	O	9	
Name	Name	M	30	
OperatorLicenseNumber	OperatorLicenseNumber	M	15	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	
RaceCode	RaceCode	M	1	A, B, I, U, W
ReasonCode	ReasonCode	M	1	
Requestor	Requestor	O	15	
SexCode	SexCode	M	1	F, M, U
State	State	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, OperatorLicenseNumber, PersonPropertyInSightIndicator, RaceCode, ReasonCode, SexCode, [AddressDepartment, FormORI, Requestor, State]

CanadianGunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
FormORI	FormORI	O	9	
GunCaliber	GunCaliber	M	4	
GunMake	GunMake	M	3	
GunSerialNumber	GunSerialNumber	M	20	
GunTypeCode	GunTypeCode	M	2	
GunTypeCode2	GunTypeCode2	M	2	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	
ReasonCode	ReasonCode	M	1	
Requestor	Requestor	O	15	

Possible Combinations

1. (In/Out) GunCaliber, GunMake, GunSerialNumber, GunTypeCode, GunTypeCode2, PersonPropertyInSightIndicator, ReasonCode, [AddressDepartment, FormORI, Requestor]

CanadianVehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
FormORI	FormORI	O	9	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateYear	LicensePlateYear	C	4	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	
ReasonCode	ReasonCode	M	15	
Requestor	Requestor	O	15	
State	State	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In/Out) LicensePlateNumber, LicensePlateYear, PersonPropertyInSightIndicator, ReasonCode, [AddressDepartment, FormORI, Requestor, State]
2. (In/Out) PersonPropertyInSightIndicator, ReasonCode, VehicleIdentificationNumber, [AddressDepartment, FormORI, Requestor, State]

Expanded Transactions Supported:

BatchArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
ArticleSerialNumber	ArticleSerialNumber	C	20	
ArticleSerialNumber2	ArticleSerialNumber2	C	20	
ArticleSerialNumber3	ArticleSerialNumber3	C	20	
ArticleSerialNumber4	ArticleSerialNumber4	C	20	
ArticleSerialNumber5	ArticleSerialNumber5	C	20	
ArticleTypeCode	ArticleTypeCode	C	7	
ArticleTypeCode2	ArticleTypeCode2	C	7	
ArticleTypeCode3	ArticleTypeCode3	C	7	
ArticleTypeCode4	ArticleTypeCode4	C	7	
ArticleTypeCode5	ArticleTypeCode5	C	7	
FormORI	FormORI	O	9	

Requestor	Requestor	O	15	
-----------	-----------	---	----	--

Possible Combinations (Up to 5 combinations may be sent at once)

1. (In/Out) ArticleSerialNumber, ArticleTypeCode, [AddressDepartment, FormORI, Requestor]
2. (In/Out) ArticleSerialNumber2, ArticleTypeCode2, [AddressDepartment, FormORI, Requestor]
3. (In/Out) ArticleSerialNumber3, ArticleTypeCode3, [AddressDepartment, FormORI, Requestor]
4. (In/Out) ArticleSerialNumber4, ArticleTypeCode4, [AddressDepartment, FormORI, Requestor]
5. (In/Out) ArticleSerialNumber5, ArticleTypeCode5, [AddressDepartment, FormORI, Requestor]

BatchGunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	M	15	Defaults to Authentication/Agency.
FormORI	FormORI	O	9	
FreeText	FreeText	O	22	
FreeText2	FreeText2	O	22	
FreeText3	FreeText3	O	22	
FreeText4	FreeText4	O	22	
FreeText5	FreeText5	O	22	
GunCaliber	GunCaliber	O	4	
GunCaliber2	GunCaliber2	O	4	
GunCaliber3	GunCaliber3	O	4	
GunCaliber4	GunCaliber4	O	4	
GunCaliber5	GunCaliber5	O	4	
GunMake	GunMake	C	3	
GunMake2	GunMake2	C	3	
GunMake3	GunMake3	C	3	
GunMake4	GunMake4	C	3	
GunMake5	GunMake5	C	3	
GunSerialNumber	GunSerialNumber	C	20	
GunSerialNumber2	GunSerialNumber2	C	20	
GunSerialNumber3	GunSerialNumber3	C	20	
GunSerialNumber4	GunSerialNumber4	C	20	
GunSerialNumber5	GunSerialNumber5	C	20	
GunTypeCode	GunTypeCode	O	2	
GunTypeCode2	GunTypeCode2	O	2	
GunTypeCode3	GunTypeCode3	O	2	
GunTypeCode4	GunTypeCode4	O	2	
GunTypeCode5	GunTypeCode5	O	2	
Requestor	Requestor	O	15	

Possible Combinations (Up to 5 combinations may be sent at once)

1. (In/Out) GunSerialNumber, FreeText, GunCaliber, GunMake, GunTypeCode, [AddressDepartment, FormORI, Requestor]
2. (In/Out) GunSerialNumber2, GunMake2, GunCaliber2, GunTypeCode2, [AddressDepartment, FormORI, Requestor, FreeText2]
3. (In/Out) GunSerialNumber3, GunMake3, GunCaliber3, GunTypeCode3, [AddressDepartment, FormORI, Requestor, FreeText3]
4. (In/Out) GunSerialNumber4, GunMake4, GunCaliber4, GunTypeCode4, [AddressDepartment, FormORI, Requestor, FreeText4]
5. (In/Out) GunSerialNumber5, GunMake5, GunCaliber5, GunTypeCode5, [AddressDepartment, FormORI, Requestor, FreeText5]

BatchPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	10	
BirthDate2	BirthDate2	C	10	
BirthDate3	BirthDate3	C	10	
BirthDate4	BirthDate4	C	10	
BirthDate5	BirthDate5	C	10	
FormORI	FormORI	O	9	
Name	Name	C		
Name2	Name2	C		
Name3	Name3	C		
Name4	Name4	C		
Name5	Name5	C		
OperatorLicenseNumber	OperatorLicenseNumber	C	15	
OperatorLicenseNumber2	OperatorLicenseNumber2	C	15	
OperatorLicenseNumber3	OperatorLicenseNumber3	C	15	
OperatorLicenseNumber4	OperatorLicenseNumber4	C	15	
OperatorLicenseNumber5	OperatorLicenseNumber5	C	15	
RaceCode	RaceCode	C	1	
RaceCode2	RaceCode2	C	1	
RaceCode3	RaceCode3	C	1	
RaceCode4	RaceCode4	C	1	
RaceCode5	RaceCode5	C	1	
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	
SexCode2	SexCode2	C	1	
SexCode3	SexCode3	C	1	
SexCode4	SexCode4	C	1	
SexCode5	SexCode5	C	1	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	

Possible Combinations (Up to 5 combinations may be sent at once)

- (In/Out) BirthDate, Name, RaceCode, SexCode, [State, AddressDepartment, FormORI, Requestor]
OR
 OperatorLicenseNumber, [State, AddressDepartment, FormORI, Requestor]
- (In/Out) BirthDate2, Name2, RaceCode2, SexCode2, [State2, AddressDepartment, FormORI, Requestor]
OR
 OperatorLicenseNumber2, [State2, AddressDepartment, FormORI, Requestor]
- (In/Out) BirthDate3, Name3, RaceCode3, SexCode3, [State3, AddressDepartment, FormORI, Requestor]
OR
 OperatorLicenseNumber3, [State3, AddressDepartment, FormORI, Requestor]

4. (In/Out) BirthDate4, Name4, RaceCode4, SexCode4, [State4, AddressDepartment, FormORI, Requestor]

OR

OperatorLicenseNumber4, [State4, AddressDepartment, FormORI, Requestor]

5. (In/Out) BirthDate5, Name5, RaceCode5, SexCode5, [State5, AddressDepartment, FormORI, Requestor]

OR

OperatorLicenseNumber5, [State5, AddressDepartment, FormORI, Requestor]

BatchVehicleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
FormORI	FormORI	O	9	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateNumber2	LicensePlateNumber2	C	10	
LicensePlateNumber3	LicensePlateNumber3	C	10	
LicensePlateNumber4	LicensePlateNumber4	C	10	
LicensePlateNumber5	LicensePlateNumber5	C	10	
LicensePlateNumber6	LicensePlateNumber6	C	10	
LicensePlateNumber7	LicensePlateNumber7	C	10	
LicensePlateNumber8	LicensePlateNumber8	C	10	
LicensePlateNumber9	LicensePlateNumber9	C	10	
LicensePlateNumber10	LicensePlateNumber10	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateTypeCode2	LicensePlateTypeCode2	C	2	
LicensePlateTypeCode3	LicensePlateTypeCode3	C	2	
LicensePlateTypeCode4	LicensePlateTypeCode4	C	2	
LicensePlateTypeCode5	LicensePlateTypeCode5	C	2	
LicensePlateTypeCode6	LicensePlateTypeCode6	C	2	
LicensePlateTypeCode7	LicensePlateTypeCode7	C	2	
LicensePlateTypeCode8	LicensePlateTypeCode8	C	2	
LicensePlateTypeCode9	LicensePlateTypeCode9	C	2	
LicensePlateTypeCode10	LicensePlateTypeCode10	C	2	
LicensePlateYear	LicensePlateYear	C	4	
LicensePlateYear2	LicensePlateYear2	C	4	
LicensePlateYear3	LicensePlateYear3	C	4	
LicensePlateYear4	LicensePlateYear4	C	4	
LicensePlateYear5	LicensePlateYear5	C	4	
LicensePlateYear6	LicensePlateYear6	C	4	
LicensePlateYear7	LicensePlateYear7	C	4	
LicensePlateYear8	LicensePlateYear8	C	4	
LicensePlateYear9	LicensePlateYear9	C	4	
LicensePlateYear10	LicensePlateYear10	C	4	
Requestor	Requestor	O	15	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	
State6	State6	O	2	
State7	State7	O	2	

State8	State8	O	2	
State9	State9	O	2	
State10	State10	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleIdentificationNumber2	VehicleIdentificationNumber2	C	20	
VehicleIdentificationNumber3	VehicleIdentificationNumber3	C	20	
VehicleIdentificationNumber4	VehicleIdentificationNumber4	C	20	
VehicleIdentificationNumber5	VehicleIdentificationNumber5	C	20	
VehicleIdentificationNumber6	VehicleIdentificationNumber6	C	20	
VehicleIdentificationNumber7	VehicleIdentificationNumber7	C	20	
VehicleIdentificationNumber8	VehicleIdentificationNumber8	C	20	
VehicleIdentificationNumber9	VehicleIdentificationNumber9	C	20	
VehicleIdentificationNumber10	VehicleIdentificationNumber10	C	20	

Possible Combinations (Up to 5 combinations may be sent at once)

* License information must be entered as a set for out of state inquiries

1. (In/Out) LicensePlateNumber, [LicensePlateTypeCode, LicensePlateYear, LicensePlateTypeCode, State, AddressDepartment, FormORI, Requestor]

OR

VehicleIdentificationNumber, [State, AddressDepartment, FormORI, Requestor]

2. (In/Out) LicensePlateNumber2, [LicensePlateTypeCode2, LicensePlateYear2, LicensePlateTypeCode2, State2, AddressDepartment, FormORI, Requestor]

OR

VehicleIdentificationNumber2, [State2, AddressDepartment, FormORI, Requestor]

3. (In/Out) LicensePlateNumber3, [LicensePlateTypeCode3, LicensePlateYear3, LicensePlateTypeCode3, State3, AddressDepartment, FormORI, Requestor]

OR

VehicleIdentificationNumber3, [State3, AddressDepartment, FormORI, Requestor]

4. (In/Out) LicensePlateNumber4, [LicensePlateTypeCode4, LicensePlateYear4, LicensePlateTypeCode4, State4, FormORI]

OR

VehicleIdentificationNumber4, [State4, AddressDepartment, FormORI, Requestor]

5. (In/Out) LicensePlateNumber5, [LicensePlateTypeCode5, LicensePlateYear5, LicensePlateTypeCode5, State5, AddressDepartment, FormORI, Requestor]

OR

VehicleIdentificationNumber5, [State5, AddressDepartment, FormORI, Requestor]

6. (In/Out) LicensePlateNumber6, [LicensePlateTypeCode6, LicensePlateYear6, LicensePlateTypeCode6, State6, AddressDepartment, FormORI, Requestor]

OR

VehicleIdentificationNumber6, [State6, AddressDepartment, FormORI, Requestor]

7. (In/Out) LicensePlateNumber7 [LicensePlateTypeCode7, LicensePlateYear7, LicensePlateTypeCode7, State7, AddressDepartment, FormORI, Requestor]

OR

VehicleIdentificationNumber7, [State7, AddressDepartment, FormORI, Requestor]

8. (In/Out) LicensePlateNumber8, [LicensePlateTypeCode8, LicensePlateYear8, LicensePlateTypeCode8, State8, AddressDepartment, FormORI, Requestor]

OR

VehicleIdentificationNumber8, [State8, AddressDepartment, FormORI, Requestor]

9. (In/Out) LicensePlateNumber9, [LicensePlateTypeCode9, LicensePlateYear9, LicensePlateTypeCode9, State9, AddressDepartment, FormORI, Requestor]

OR

VehicleIdentificationNumber9, [State9, AddressDepartment, FormORI, Requestor]

10. (In/Out) LicensePlateNumber10, [LicensePlateTypeCode10, LicensePlateYear10, LicensePlateTypeCode10, State10, FormORI]

OR

VehicleIdentificationNumber10, [State10, AddressDepartment, FormORI, Requestor]

BoatRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BoatHullIdNumber	BoatHullIdNumber	C	20	
BoatYear	BoatYear	C	6	
FormORI	FormORI	O	9	
RegistrationNumber	RegistrationNumber	C	10	
Requestor	Requestor	O	15	
State	State	C	2	

Possible Combinations

1. (In) BoatHullIdNumber, [AddressDepartment, FormORI, Requestor]
2. (In) RegistrationNumber, [AddressDepartment, FormORI, Requestor]
3. (Out) BoatHullIdNumber, State, [AddressDepartment, FormORI, Requestor]
4. (Out) BoatYear, RegistrationNumber, State, [AddressDepartment, FormORI, Requestor]

BoatStolenQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BoatHullIdNumber	BoatHullIdNumber	C	20	
FormORI	FormORI	O	9	
RegistrationNumber	RegistrationNumber	C	10	
Requestor	Requestor	O	15	

Possible Combinations

1. (In/Out) BoatHullIdNumber, [AddressDepartment, FormORI, Requestor]
2. (In/Out) BoatHullIdNumber, RegistrationNumber, [AddressDepartment, FormORI, Requestor]
3. (In/Out) RegistrationNumber, [AddressDepartment, FormORI, Requestor]

CPLCanadianDriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	M	8	
ConcealedAttestCode	ConcealedAttestCode	O	1	
ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
FormORI	FormORI	O	9	
Name	Name	M	30	
OperatorLicenseNumber	OperatorLicenseNumber	M	15	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	
RaceCode	RaceCode	M	1	A, B, I, U, W
ReasonCode	ReasonCode	M	1	
Requestor	Requestor	O	15	
SexCode	SexCode	M	1	F, M, U
State	State	M	2	

Possible Combinations

1. (In/Out) BirthDate, Name, OperatorLicenseNumber, PersonPropertyInSightIndicator, RaceCode, ReasonCode, SexCode, State, [AddressDepartment, Requestor, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI]

CPLCCHCriminalHistoryQHWQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	8	
ConcealedAttestCode	ConcealedAttestCode	O	1	
ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
CriminalTrackingNumber	CriminalTrackingNumber	C	12	
FBINumber	FBINumber	C	9	
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	C	200	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C		
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PrisonNumber	PrisonNumber	C	11	
PurposeCode	PurposeCode	C	17	See LEIN operating manual for valid codes
RaceCode	RaceCode	C	1	
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	
StateldNumber	StateldNumber	C	10	

Possible Combinations* Must enter either MiscellaneousDescriptiveText or OriginatingAgencyCaseNumber for all combinations *****

1. (In/Out) BirthDate, Name, PurposeCode, RaceCode, SexCode, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
2. (In/Out) CriminalTrackingNumber, PurposeCode, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
3. (In/Out) FBINumber, PurposeCode, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
4. (In/Out) MiscellaneousNumber, PurposeCode, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
5. (In/Out) OperatorLicenseNumber, PurposeCode, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
6. (In/Out) PrisonNumber, PurposeCode, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]
7. (In/Out) PurposeCode, StateldNumber, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, Requestor]

CPLDriverConvictionHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	8	
ConcealedAttestCode	ConcealedAttestCode	O	1	

ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
FormORI	FormORI	O	9	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	15	
RaceCode	RaceCode	C	1	
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	

Possible Combinations

1. (In/Out) BirthDate, Name, RaceCode, SexCode, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]
2. (In/Out) OperatorLicenseNumber, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]

CPLDriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	8	
ConcealedAttestCode	ConcealedAttestCode	O	1	
ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
FormORI	FormORI	O	9	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	15	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	
RaceCode	RaceCode	C	1	A, B, I, U, W
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	F, M, U
State	State	C	2	

Possible Combinations

1. (In) BirthDate, Name, Requestor, SexCode, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, RaceCode]
2. (In) BirthDate, Name, OperatorLicenseStateCode, RaceCode, SexCode, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]
3. (In) OperatorLicenseNumber, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]
4. (Out) BirthDate, Name, RaceCode, SexCode, State, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]
5. (Out) OperatorLicenseNumber, Requestor, State, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]

CPLLicenseInformationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	8	
ConcealedAttestCode	ConcealedAttestCode	O	1	
ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
FormORI	FormORI	O	9	
Name	Name	C	30	

OperatorLicenseNumber	OperatorLicenseNumber	C	15	
RaceCode	RaceCode	C	1	
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	

Possible Combinations

1. (In/Out) BirthDate, Name, RaceCode, SexCode, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI]
2. (In/Out) OperatorLicenseNumber, Requestor, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]

CPLLICENSEInformationSOSOnlyQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
ConcealedAttestCode	ConcealedAttestCode	O	1	
ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
FormORI	FormORI	O	9	
OperatorLicenseNumber	OperatorLicenseNumber	M	15	
Requestor	Requestor	O	15	

Possible Combinations

1. (In/Out) OperatorLicenseNumber, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]

CPLLICENSEQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
ConcealedAttestCode	ConcealedAttestCode	O	1	
ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
ConvictedIndicator	ConvictedIndicator	O	1	Y, N
FormORI	FormORI	O	9	
OperatorLicenseNumber	OperatorLicenseNumber	M	15	
Requestor	Requestor	O	15	
State	State	C	2	

Possible Combinations

1. (In) ConvictedIndicator, OperatorLicenseNumber, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]
2. (Out) OperatorLicenseNumber, State, AddressDepartment, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]

CPLPartialNameSearchQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
Age	Age	C	2	
BirthDate	BirthDate	C	8	
ConcealedAttestCode	ConcealedAttestCode	O	1	
ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
FormORI	FormORI	O	9	

Name	Name	C	30	
RaceCode	RaceCode	C	1	
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	

Possible Combinations

1. (In/Out) Age, Name, RaceCode, SexCode, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]
2. (In/Out) BirthDate, Name, RaceCode, SexCode, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]

CPLPersonalIdentificationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	8	
ConcealedAttestCode	ConcealedAttestCode	O	1	
ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
FormORI	FormORI	O	9	
Name	Name	C	30	
PersonalIdentificationNumber	PersonalIdentificationNumber	C	15	
RaceCode	RaceCode	C	1	A, B, I, U, W
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	F, M, U

Possible Combinations

1. (In) BirthDate, Name, PersonalIdentificationNumber, RaceCode, SexCode, [AddressDepartment, FormORI, Requestor]
2. (In) BirthDate, Name, RaceCode, SexCode, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]
3. (In) PersonalIdentificationNumber, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]

CPLSnowmobileRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	
ConcealedAttestCode	ConcealedAttestCode	O	1	
ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
FormORI	FormORI	O	9	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateYear	LicensePlateYear	C	4	
Requestor	Requestor	O	15	
State	State	C	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In) LicensePlateNumber, AddressDepartment, [ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]
2. (In) VehicleIdentificationNumber, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]
3. (Out) LicensePlateNumber, LicensePlateYear, State, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]

4. (Out) State, VehicleIdentificationNumber, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]

CPLVehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
AddressStreetNumber	AddressStreetNumber	O	8	
ConcealedAttestCode	ConcealedAttestCode	O	1	
ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
FormORI	FormORI	O	9	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
Name	Name	C	30	
PageCode	PageCode	C	8	
Requestor	Requestor	O	15	
State	State	C	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In) LicensePlateNumber [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, LicensePlateTypeCode, Requestor]
2. (In) VehicleIdentificationNumber, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]
3. (In/Out) Name, [AddressDepartment, AddressStreetNumber, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]
4. (In/Out) PageCode, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]
5. (Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, State, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]
6. (Out) State, VehicleIdentificationNumber, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, Requestor]

CPLWantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	
BirthDate	BirthDate	C	8	
ConcealedAttestCode	ConcealedAttestCode	O	1	
ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
FBINumber	FBINumber	O	20	
FormORI	FormORI	O	9	
LicensePlateNumber	LicensePlateNumber	O	15	
MiscellaneousNumber	MiscellaneousNumber	O	20	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	O	17	
OwnerAppliedNumber	OwnerAppliedNumber	O	20	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	O	1	
PurposeCode	PurposeCode	O	1	

RaceCode	RaceCode	O	1	A, B, I, U, W
Requestor	Requestor	O	15	
SexCode	SexCode	O	1	F, M, U
SocialSecurityNumber	SocialSecurityNumber	O	9	
State	State	C	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	17	

Possible Combinations

1. (In) [AddressDepartment, BirthDate, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FBINumber, FormORI, LicensePlateNumber, MiscellaneousNumber, Name, OperatorLicenseNumber, OwnerAppliedNumber, RaceCode, SexCode, SocialSecurityNumber, VehicleIdentificationNumber]
2. (Out) Requestor, State, [AddressDepartment, BirthDate, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FBINumber, FormORI, LicensePlateNumber, MiscellaneousNumber, Name, OperatorLicenseNumber, OwnerAppliedNumber, PersonPropertyInSightIndicator, PurposeCode, RaceCode, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, Requestor]

DisabilityParkingPermitQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
FormORI	FormORI	O	9	
PermitNumber	PermitNumber	M	10	
Requestor	Requestor	O	15	

Possible Combinations

1. (In/Out) PermitNumber, [AddressDepartment, FormORI, Requestor]

DriverConvictionHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	8	
FormORI	FormORI	O	9	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	15	
RaceCode	RaceCode	C	1	
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	

Possible Combinations

1. (In/Out) BirthDate, Name, RaceCode, SexCode, [AddressDepartment, FormORI, Requestor]
2. (In/Out) OperatorLicenseNumber, [AddressDepartment, FormORI, Requestor]

DriverLicenseCCWQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	8	
ConcealedAttestCode	ConcealedAttestCode	O	1	
ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
FormORI	FormORI	O	9	
Name	Name	C	30	

OperatorLicenseNumber	OperatorLicenseNumber	C	15	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	
RaceCode	RaceCode	C	1	A, B, I, U, W
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	F, M, U
State	State	C	2	

Possible Combinations

1. (In) BirthDate, Name, RaceCode, SexCode, [AddressDepartment, FormORI, Requestor, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText]
2. (In) BirthDate, Name, OperatorLicenseStateCode, RaceCode, SexCode, [AddressDepartment, FormORI, Requestor, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText]
3. (In) OperatorLicenseNumber, [AddressDepartment, FormORI, Requestor, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText]
4. (Out) BirthDate, Name, RaceCode, SexCode, State, [AddressDepartment, FormORI, Requestor, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText]
5. (Out) AddressDepartment, OperatorLicenseNumber, State, [AddressDepartment, FormORI, Requestor, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText]

HazmatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FormORI	FormORI	O	9	
UnitedNationsNumber	UnitedNationsNumber	M	4	

Possible Combinations

1. (In/Out) UnitedNationsNumber, [FormORI]

LicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
ConvictedIndicator	ConvictedIndicator	O	1	Y, N
FormORI	FormORI	O	9	
OperatorLicenseNumber	OperatorLicenseNumber	M	15	
Requestor	Requestor	O	15	
State	State	C	2	

Possible Combinations

1. (In) OperatorLicenseNumber, [AddressDepartment, FormORI, Requestor, ConvictedIndicator]
2. (Out) OperatorLicenseNumber, State, [AddressDepartment, FormORI, Requestor]

LicenseInformationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	
BirthDate	BirthDate	C	8	
FormORI	FormORI	O	9	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	15	
RaceCode	RaceCode	C	1	
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	

Possible Combinations

1. (In/Out) BirthDate, Name, RaceCode, SexCode, [AddressDepartment, FormORI, Requestor]

2. (In/Out) OperatorLicenseNumber, [AddressDepartment, FormORI, Requestor]

LicenseInformationSOSOnlyQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
FormORI	FormORI	O	9	
OperatorLicenseNumber	OperatorLicenseNumber	M	15	
Requestor	Requestor	O	15	

Possible Combinations

1. (In/Out) OperatorLicenseNumber, [AddressDepartment, FormORI, Requestor]

MiDriverLicense35Query

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	10	
FormORI	FormORI	O	9	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	15	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	
RaceCode	RaceCode	C	1	
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	
State	State	C	2	
SubCode	SubCode	O	7	
UserName	UserName	C	15	

Possible Combinations

1. (In) BirthDate, Name, RaceCode, SexCode, UserName, [AddressDepartment, FormORI, OperatorLicenseStateCode, Requestor]
2. (In) BirthDate, Name, RaceCode, SexCode, UserName, [AddressDepartment, FormORI, Requestor]
3. (In) OperatorLicenseNumber, UserName, [AddressDepartment, FormORI, Requestor, SubCode]
4. (Out) BirthDate, Name, RaceCode, SexCode, State, UserName, [AddressDepartment, FormORI, Requestor]
5. (Out) OperatorLicenseNumber, State, UserName, [AddressDepartment, FormORI, Requestor]

MiDriverQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	10	
ConcealedAttestCode	ConcealedAttestCode	O	1	
ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
FormORI	FormORI	O	9	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	

RaceCode	RaceCode	C	1	
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	
State	State	O	2	
UserName	UserName	C	15	

Possible Combinations

1. (In/Out) BirthDate, Name, RaceCode, SexCode, UserName, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, OperatorLicenseNumber, OperatorLicenseStateCode, Requestor, State]
2. (In/Out) OperatorLicenseNumber, UserName, [AddressDepartment, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, OperatorLicenseStateCode, Requestor, State]

MopedQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
FormORI	FormORI	O	9	
LicensePlateNumber	LicensePlateNumber	C	10	
Requestor	Requestor	O	15	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In/Out) LicensePlateNumber, [AddressDepartment, FormORI, Requestor]
2. (In/Out) Requestor, VehicleIdentificationNumber, [AddressDepartment, FormORI, Requestor]

MultiUseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
Age	Age	O	3	
BirthDate	BirthDate	C	8	
CriminalTrackingNumber	CriminalTrackingNumber	O	12	
ConcealedAttestCode	ConcealedAttestCode	O	1	
ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
FormORI	FormORI	O	9	
FBINumber	FBINumber	C	9	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	O	4	
LojackId	LojackId	O	10	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	200	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	C	30	
NICSTransactionNumber	NICSTransactionNumber	O	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	15	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	
OwnerAppliedNumber	OwnerAppliedNumber	O	20	
PersonEntryNumber	PersonEntryNumber	O	10	

PersonShowCanceledRecordsIndicator	PersonShowCanceledRecordsIndicator	O	1	Y
PersonSOSCode	PersonSOSCode	C	8	
PrisonNumber	PrisonNumber	O	10	
PurposeCode	PurposeCode	C	5	
PurposeDetails	PurposeDetails	O	15	
RaceCode	RaceCode	O	1	
Requestor	Requestor	O	15	
SendToMDOCIndicator	SendToMDOCIndicator	O	1	Y
SexCode	SexCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
SOSOnlyIndicator	SOSOnlyIndicator	O	1	Y
State	State	O	2	
StateIdNumber	StateIdNumber	C	10	
VehicleEntryNumber	VehicleEntryNumber	O	10	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	24	
VehicleModelCode	VehicleModelCode	O	3	
VehicleShowCanceledRecordsIndicator	VehicleShowCanceledRecordsIndicator	O	1	Y
VehicleSOSCode	VehicleSOSCode	C	3	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In) BirthDate, Name, PurposeCode, [Age, AddressDepartment, FormORI, Requestor, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, PurposeDetails, RaceCode, SexCode, ConcealedAttestCode, ConcealedAttestCode, ConcealedReasonText]
2. (In/Out) FBINumber, PurposeCode, [AddressDepartment, FormORI, Requestor, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, PurposeDetails, ConcealedAttestCode, ConcealedAttestCode, ConcealedReasonText]
3. (In/Out) PersonSOSCode, [Age, CriminalTrackingNumber, FBINumber, AddressDepartment, FormORI, Requestor, MiscellaneousDescriptiveText, MiscellaneousNumber, NICSTransactionNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, PersonEntryNumber, PersonShowCanceledRecordsIndicator, PrisonNumber, PurposeCode, PurposeDetails, RaceCode, SendToMDOCIndicator, SexCode, SocialSecurityNumber, SOSOnlyIndicator, State, StateIdNumber, VehicleEntryNumber, ConcealedAttestCode, ConcealedAttestCode, ConcealedReasonText]
4. (In/Out) PurposeCode, StateIdNumber, [AddressDepartment, FormORI, Requestor, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, PurposeDetails, ConcealedAttestCode, ConcealedAttestCode, ConcealedReasonText]
5. (In/Out) VehicleSOSCode, [AddressDepartment, FormORI, Requestor, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, LicensePlateYear, LojackId, OperatorLicenseNumber, OriginatingAgencyCaseNumber, OwnerAppliedNumber, PersonEntryNumber, State, VehicleEntryNumber, VehicleIdentificationNumber, VehicleMakeCode, VehicleModelCode, VehicleShowCanceledRecordsIndicator, VehicleYear, ConcealedAttestCode, ConcealedAttestCode, ConcealedReasonText]
6. (Out) BirthDate, Name, PurposeCode, State, [Age, AddressDepartment, FormORI, Requestor, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, PurposeDetails, RaceCode, SexCode, ConcealedAttestCode, ConcealedAttestCode, ConcealedReasonText]

NFPDisabilityParkingPermitQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
PermitNumber	PermitNumber	M	10	

Requestor	Requestor	O	15	
-----------	-----------	---	----	--

Possible Combinations

1. (In/Out) PermitNumber, [AddressDepartment, FormORI, Requestor]

NFPMedicalMarijuanaNameQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
MedicalMarijuanaIdNumber	MedicalMarijuanaIdNumber	M	14	Medical Marijuana ID Card Number
Requestor	Requestor	O	15	

*** NFPMedicalMarijuanaStatusQuery must be run before NFPMedicalMarijuanaNameQuery ***

Possible Combinations

1. (In/Out) MedicalMarijuanaIdNumber, [AddressDepartment, FormORI, Requestor]

NFPMedicalMarijuanaStatusQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
MedicalMarijuanaIdNumber	MedicalMarijuanaIdNumber	M	14	Medical Marijuana ID Card Number
Requestor	Requestor	O	15	

*** This query must be run before NFPMedicalMarijuanaNameQuery ***

Possible Combinations

1. (In/Out) MedicalMarijuanaIdNumber, [AddressDepartment, FormORI, Requestor]

PartialNameSearchQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
Age	Age	C	2	
BirthDate	BirthDate	C	8	
FormORI	FormORI	O	9	
Name	Name	C	30	
RaceCode	RaceCode	C	1	
Requestor	Requestor	O	15	
SexCode	SexCode	C	1	

Possible Combinations

1. (In/Out) Age, Name, RaceCode, SexCode, [AddressDepartment, FormORI, Requestor]
2. (In/Out) BirthDate, Name, RaceCode, SexCode, [AddressDepartment, FormORI, Requestor]

PersonalIdentificationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	8	
FormORI	FormORI	O	9	
Name	Name	C	30	
PersonalIdentificationNumber	PersonalIdentificationNumber	C	15	
RaceCode	RaceCode	C	1	A, B, I, U, W

Requestor	Requestor	O	15	
SexCode	SexCode	C	1	F, M, U

Possible Combinations

1. (In) BirthDate, Name, PersonalIdentificationNumber, RaceCode, Requestor, SexCode, [AddressDepartment, FormORI, Requestor]
2. (In) BirthDate, Name, RaceCode, Requestor, SexCode, [AddressDepartment, FormORI, Requestor]
3. (In) PersonalIdentificationNumber, Requestor, [AddressDepartment, FormORI, Requestor]

SnowmobileRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
FormORI	FormORI	O	9	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateYear	LicensePlateYear	C	4	
Requestor	Requestor	O	15	
State	State	C	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In) LicensePlateNumber, [AddressDepartment, FormORI, Requestor]
2. (In) Requestor, VehicleIdentificationNumber, [AddressDepartment, FormORI, Requestor]
3. (Out) LicensePlateNumber, LicensePlateYear, State, [AddressDepartment, FormORI, Requestor]
4. (Out) State, VehicleIdentificationNumber, [AddressDepartment, FormORI, Requestor]

VehicleRegistrationAlphaQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
AddressStreet	AddressStreet	O	24	Registered owner's street address ex: 123 PARK AVE
FormORI	FormORI	O	9	Enter to change originating ori from terminal to other
Name	Name	C	30	Person's name (first and last at least)
PageCode	PageCode	C	8	Unique code generated in response to combination 1 or 3 to allow viewing of next page by running combination 2.
Requestor	Requestor	O	15	
SingleName	SingleName	C	30	Person's last name, or single company name

Possible Combinations

1. (In/Out) Name, [AddressDepartment, AddressStreet, FormORI, Requestor]
2. (In/Out) PageCode, [AddressDepartment, FormORI, Requestor]
3. (In/Out) SingleName, [AddressDepartment, AddressStreet, FormORI, Requestor]

WantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency.
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	O	20	
FormORI	FormORI	O	9	
LicensePlateNumber	LicensePlateNumber	O	15	
MiscellaneousNumber	MiscellaneousNumber	O	20	
Name	Name	C	30	

OperatorLicenseNumber	OperatorLicenseNumber	O	17	
OwnerAppliedNumber	OwnerAppliedNumber	O	20	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	O	1	
PurposeCode	PurposeCode	O	1	
RaceCode	RaceCode	O	1	A, B, I, U, W
Requestor	Requestor	O	15	
SexCode	SexCode	O	1	F, M, U
SocialSecurityNumber	SocialSecurityNumber	O	9	
State	State	C	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	17	

Possible Combinations

1. (In) AddressDepartment, Requestor, [BirthDate, FBINumber, FormORI, LicensePlateNumber, MiscellaneousNumber, Name, OperatorLicenseNumber, OwnerAppliedNumber, RaceCode, SexCode, SocialSecurityNumber, VehicleIdentificationNumber]
2. (Out) AddressDepartment, Requestor, State, [BirthDate, FBINumber, FormORI, LicensePlateNumber, MiscellaneousNumber, Name, OperatorLicenseNumber, OwnerAppliedNumber, PersonPropertyInSightIndicator, PurposeCode, RaceCode, SexCode, SocialSecurityNumber, VehicleIdentificationNumber]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

Michigan LEIN will only work with agencies, not directly with vendors. You must go through the agency for any communication necessary for installation, configuration, documentation, security requirements from LEIN.

Each Michigan transactions requires the following fields: UserName, For, and Department.

- UserName -- Name assigned the person who is actually using the application and entering the information. This field will be populated with the value in Authentication/UserName by default.
- For – Name of the individual who someone is performing a transaction for. For example, a dispatcher may be running an inquiry for an officer (Off. John Doe) or a detective (Det. Jane Joe). This field will be populated with the value in Authentication/UserName by default. It can be overwritten with the Requestor field.
- Department – Name of the agency the transaction is being run for. For example a dispatch center may perform services for multi-agencies so the agency the inquiry is being entered for would be entered here (ABC123 Police Department). This field will be populated with the value in Authentication/Agency by default. It can be overwritten with the AddressDepartment field.

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- LEIN Operations Manual