

Michigan (MI) TALON

[Disclaimer Statement](#)

Transport:

TCP/IP CPI (SimpleFrame)

Routing and Configuration Information:

Save byte routing

- The LEIN assigned ORI for a device (or for the site) should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.
- A valid user name on the agency system should be placed in the **<Authentication>/<UserName>** field in the ConnectCIC header.
- A valid password on the agency system should be placed in the **<Authentication>/<Password>** field in the ConnectCIC header.
- The site (agency name) may be placed in the **<Authentication>/<Agency>** field in the ConnectCIC header. If not specified, the **AddressDepartment** field becomes required in all transactions in which it is specified.

Security Requirements:

Follow state mandated agency-level security policy complete with background checks for vendors; follow NCIC 2000 policy for site security (firewalls, secure access, network security, etc.)

Logon Requirements:

Mobile access to LEIN must include a password log on and automatic log off after 30 minutes of inactivity. Compliance to this requirement must be met by Jan 1, 2005.
(Controlled at Client – Sever level)

Note: LEIN does not have a logon or logoff query so to meet this requirement the Vendor must implement logon/logoff functionality in their application with a timer to trigger the expiration (logoff) of connectivity if no activity has happened in a 30-minute time frame and then provide a way for the user to log back on.

Certification Requirements:

None

Need Site Sponsor

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	
FormORI	FormORI	O	9	
Requestor	Requestor	M	15	
UserName	UserName	M	15	

Possible Combinations

1. (In/Out)ArticleSerialNumber, ArticleTypeCode, Requestor, UserName, [AddressDepartment, FormORI]

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
BoatHullIdNumber	BoatHullIdNumber	C	20	
BoatYear	BoatYear	C	6	
FormORI	FormORI	O	9	
RegistrationNumber	RegistrationNumber	C	10	
Requestor	Requestor	C	15	
State	State	C	2	
UserName	UserName	M	15	

Possible Combinations

1. (In) BoatHullIdNumber, Requestor, UserName, [AddressDepartment, FormORI]
2. (In) RegistrationNumber, Requestor, UserName, [AddressDepartment, FormORI]
3. (In/Out) UserName, [AddressDepartment, FormORI, Requestor]
4. (In/Out) RegistrationNumber, UserName, [AddressDepartment, FormORI, Requestor]
5. (In/Out) RegistrationNumber, UserName, [AddressDepartment, FormORI, Requestor]
6. (Out) BoatHullIdNumber, Requestor, State, UserName, [AddressDepartment, FormORI]
7. (Out) BoatYear, RegistrationNumber, Requestor, State, UserName, [AddressDepartment, FormORI]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
BirthDate	BirthDate	C	8	
FormORI	FormORI	O	9	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	15	
RaceCode	RaceCode	C	1	A, B, I, U, W
Requestor	Requestor	M	15	
SexCode	SexCode	C	1	F, M, U
State	State	C	2	
UserName	UserName	M	15	

Possible Combinations

1. (In) BirthDate, Name, RaceCode, Requestor, SexCode, UserName, [AddressDepartment, FormORI]
2. (In) OperatorLicenseNumber, Requestor, UserName, [AddressDepartment, FormORI]
3. (Out) BirthDate, Name, RaceCode, Requestor, SexCode, State, UserName, [AddressDepartment, FormORI]
4. (Out) OperatorLicenseNumber, Requestor, State, UserName, [AddressDepartment, FormORI]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
FormORI	FormORI	O	9	
FreeText	FreeText	O	22	
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	M	3	
GunSerialNumber	GunSerialNumber	M	20	
GunTypeCode	GunTypeCode	O	2	
Requestor	Requestor	M	15	
UserName	UserName	M	15	

Possible Combinations

1. (In/Out) GunMake, GunSerialNumber, Requestor, UserName, [AddressDepartment, FormORI, FreeText, GunCaliber, GunTypeCode]

SnowmobileBoatOperatorQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
BirthDate	BirthDate	C	8	
FormORI	FormORI	O	9	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	15	
RaceCode	RaceCode	C	1	A, B, I, U, W
Requestor	Requestor	M	15	
SexCode	SexCode	C	1	F, M, U
UserName	UserName	M	15	

Possible Combinations

1. (In) BirthDate, Name, RaceCode, Requestor, SexCode, UserName, [AddressDepartment, FormORI]
2. (In) OperatorLicenseNumber, Requestor, UserName, [AddressDepartment, FormORI]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
AddressStreetNumber	AddressStreetNumber	O	8	
FormORI	FormORI	O	9	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
Name	Name	C	30	
PageCode	PageCode	C	8	
Requestor	Requestor	C	15	

State	State	C	2	
UserName	UserName	C	15	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In) LicensePlateNumber, Requestor, UserName, [AddressDepartment, FormORI, LicensePlateTypeCode]
2. (In) Requestor, UserName, VehicleIdentificationNumber, [AddressDepartment, FormORI]
3. (In/Out) Name, Requestor, UserName, [AddressStreetNumber, FormORI]
4. (In/Out) PageCode, Requestor, UserName, [AddressDepartment, FormORI]
5. (Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, Requestor, State, UserName, [AddressDepartment, FormORI]
6. (Out) Requestor, State, UserName, VehicleIdentificationNumber, [AddressDepartment, FormORI]

Transactions Supported:

Canadian Basic Inquiries (CBI)

CanadianArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	
ArticleTypeCode2	ArticleTypeCode2	M	2	
FormORI	FormORI	O	9	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	
ReasonCode	ReasonCode	M	1	
Requestor	Requestor	M	15	
UserName	UserName	M	15	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode, ArticleTypeCode2, PersonPropertyInSightIndicator, ReasonCode, Requestor, UserName, [AddressDepartment, FormORI]

CanadianBoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
BoatHullIdNumber	BoatHullIdNumber	C	20	
BoatTypeCode	BoatTypeCode	M	2	
FormORI	FormORI	O	9	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	
ReasonCode	ReasonCode	M	1	
RegistrationNumber	RegistrationNumber	C	20	
Requestor	Requestor	M	15	
UserName	UserName	M	15	

Possible Combinations

1. (In/Out) BoatHullIdNumber, BoatTypeCode, PersonPropertyInSightIndicator, ReasonCode, Requestor, UserName, [AddressDepartment, FormORI]
2. (In/Out) BoatTypeCode, PersonPropertyInSightIndicator, ReasonCode, RegistrationNumber, Requestor, UserName, [AddressDepartment, FormORI]

CanadianDriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
BirthDate	BirthDate	M	8	
FormORI	FormORI	O	9	
Name	Name	M	30	
OperatorLicenseNumber	OperatorLicenseNumber	M	15	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	
RaceCode	RaceCode	M	1	A, B, I, U, W
ReasonCode	ReasonCode	M	1	
Requestor	Requestor	M	15	
SexCode	SexCode	M	1	F, M, U
State	State	O	2	
UserName	UserName	M	15	

Possible Combinations

1. (In/Out) BirthDate, Name, OperatorLicenseNumber, PersonPropertyInSightIndicator, RaceCode, ReasonCode, Requestor, SexCode, UserName, [AddressDepartment, FormORI, State]

CanadianGunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
FormORI	FormORI	O	9	
GunCaliber	GunCaliber	M	4	
GunMake	GunMake	M	3	
GunSerialNumber	GunSerialNumber	M	20	
GunTypeCode	GunTypeCode	M	2	
GunTypeCode2	GunTypeCode2	M	2	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	
ReasonCode	ReasonCode	M	1	
Requestor	Requestor	M	15	
UserName	UserName	M	15	

Possible Combinations

1. (In/Out) GunCaliber, GunMake, GunSerialNumber, GunTypeCode, GunTypeCode2, PersonPropertyInSightIndicator, ReasonCode, Requestor, UserName, [AddressDepartment, FormORI]

CanadianVehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
FormORI	FormORI	O	9	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateYear	LicensePlateYear	C	4	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	
ReasonCode	ReasonCode	M	15	
Requestor	Requestor	M	15	
State	State	O	2	
UserName	UserName	M	15	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In/Out) LicensePlateNumber, LicensePlateYear, PersonPropertyInSightIndicator, ReasonCode, Requestor, UserName, [AddressDepartment, FormORI, State]
2. (In/Out) PersonPropertyInSightIndicator, ReasonCode, Requestor, UserName, VehicleIdentificationNumber, [AddressDepartment, FormORI, State]

Expanded Transactions Supported:

AddressQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address	Address	M		

Possible Combinations

1. (In/Out) Address

BoatRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agncy
BoatHullIdNumber	BoatHullIdNumber	C	20	
BoatYear	BoatYear	C	6	
FormORI	FormORI	O	9	
RegistrationNumber	RegistrationNumber	C	10	
Requestor	Requestor	M	15	
State	State	C	2	
UserName	UserName	M	15	

Possible Combinations

1. (In) BoatHullIdNumber, Requestor, UserName, [AddressDepartment, FormORI]
2. (In) RegistrationNumber, Requestor, UserName, [AddressDepartment, FormORI]
3. (Out) BoatHullIdNumber, Requestor, State, UserName, [AddressDepartment, FormORI]
4. (Out) BoatYear, RegistrationNumber, Requestor, State, UserName, [AddressDepartment, FormORI]

BoatStolenQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agncy
BoatHullIdNumber	BoatHullIdNumber	C	20	
FormORI	FormORI	O	9	
RegistrationNumber	RegistrationNumber	C	10	
Requestor	Requestor	O	15	
UserName	UserName	O	15	

Possible Combinations

1. (In/Out) BoatHullIdNumber, [AddressDepartment, FormORI, Requestor, UserName]
2. (In/Out) BoatHullIdNumber, RegistrationNumber, [AddressDepartment, FormORI, Requestor, UserName]
3. (In/Out) RegistrationNumber, [AddressDepartment, FormORI, Requestor, UserName]

DestinationListQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

Possible Combinations

- simply send "DestinationListQuery" in the MessageType tag in the request to ConnectCIC and ConnectCIC will provide a list of destinations

DisabilityParkingPermitQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
FormORI	FormORI	O	9	
PermitNumber	PermitNumber	M	10	
Requestor	Requestor	M	15	
UserName	UserName	M	15	

Possible Combinations

1. (In/Out) PermitNumber, Requestor, UserName, [AddressDepartment, FormORI]

DriverConvictionHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
BirthDate	BirthDate	C	8	
FormORI	FormORI	O	9	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	15	
RaceCode	RaceCode	C	1	
Requestor	Requestor	C	15	
SexCode	SexCode	C	1	
UserName	UserName	C	15	

Possible Combinations

1. (In/Out) BirthDate, Name, RaceCode, Requestor, SexCode, UserName, [AddressDepartment, FormORI]
2. (In/Out) OperatorLicenseNumber, Requestor, UserName, [AddressDepartment, FormORI]

HazmatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FormORI	FormORI	O	9	
UnitedNationsNumber	UnitedNationsNumber	M	4	

Possible Combinations

1. (In/Out) UnitedNationsNumber, [FormORI]

ImageDrilldown

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageId	ImageId	M		

Possible Combinations

1. (In/Out) ImageId

LicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
FormORI	FormORI	O	9	
OperatorLicenseNumber	OperatorLicenseNumber	M	15	

Requestor	Requestor	M	15	
State	State	C	2	
UserName	UserName	M	15	

Possible Combinations

1. (In) ConvictedIndicator, OperatorLicenseNumber, Requestor, UserName, [AddressDepartment, FormORI]
2. (Out) OperatorLicenseNumber, Requestor, State, UserName, [AddressDepartment, FormORI]

LicenseInformationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
BirthDate	BirthDate	C	8	
FormORI	FormORI	O	9	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	15	
RaceCode	RaceCode	C	1	
Requestor	Requestor	C	15	
SexCode	SexCode	C	1	
UserName	UserName	C	15	

Possible Combinations

1. (In/Out) BirthDate, Name, RaceCode, Requestor, SexCode, UserName, [AddressDepartment, FormORI]
2. (In/Out) OperatorLicenseNumber, Requestor, UserName, [AddressDepartment, FormORI]

LicenseInformationSOSOnlyQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
FormORI	FormORI	O	9	
OperatorLicenseNumber	OperatorLicenseNumber	M	15	
Requestor	Requestor	M	15	
UserName	UserName	M	15	

Possible Combinations

1. (In/Out) OperatorLicenseNumber, Requestor, UserName, [AddressDepartment, FormORI]

LocationAddressQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ApartmentNumber	ApartmentNumber	O	10	Defaults to Authentication/Agency
City	City	O	50	
Destination	Destination	O	30	LocalTest, Demo Image, OTIS, TRACVIEW, LocatePLUS, MIDRS, Kent County Sheriff RMS
Destination	Destination	O	30	
Destination	Destination	O	30	
Destination	Destination	O	30	
Destination	Destination	O	30	
Destination	Destination	O	30	
Destination	Destination	O	30	
Destination	Destination	O	30	
Destination	Destination	O	30	

Destination	Destination	O	30	
Destination	Destination	O	30	
Destination	Destination	O	30	
Destination	Destination	O	30	
Destination	Destination	O	30	
Location	Location	M	100	
StateCode	StateCode	O	2	
ZipCode	ZipCode	O	10	

Possible Combinations

1. (In/Out) Location, [ApartmentNumber, City, Destination, StateCode, ZipCode]

MopedQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
FormORI	FormORI	O	9	
LicensePlateNumber	LicensePlateNumber	C	10	
Requestor	Requestor	M	15	
UserName	UserName	M	15	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In/Out) LicensePlateNumber, Requestor, UserName, [AddressDepartment, FormORI]
2. (In/Out) Requestor, UserName, VehicleIdentificationNumber, [AddressDepartment, FormORI]

MultiUseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	M	15	Defaults to Authentication/Agency
Age	Age	O	3	
BirthDate	BirthDate	C	8	
ConcealedAttestCode	ConcealedAttestCode	O	1	
ConcealedPurposeCode	ConcealedPurposeCode	O	1	
ConcealedReasonText	ConcealedReasonText	O	50	
CriminalTrackingNumber	CriminalTrackingNumber	O	12	
FBI Number	FBI Number	C	9	
FormORI	FormORI	O	9	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	O	4	
LojackId	LojackId	O	10	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	200	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	C	30	
NICSTransactionNumber	NICSTransactionNumber	O	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	15	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	
OwnerAppliedNumber	OwnerAppliedNumber	O	20	
PersonEntryNumber	PersonEntryNumber	O	10	
PersonShowCanceledRecordsIndicator	PersonShowCanceledRecordsIndicator	O	1	Y
PersonSOSCode	PersonSOSCode	C	8	

PrisonNumber	PrisonNumber	O	10	
PurposeCode	PurposeCode	C	5	
PurposeDetails	PurposeDetails	O	15	
RaceCode	RaceCode	O	1	
Requestor	Requestor	M	15	
SendToMDOCIndicator	SendToMDOCIndicator	O	1	Y
SexCode	SexCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
SOSOnlyIndicator	SOSOnlyIndicator	O	1	Y
State	State	O	2	
StateIdNumber	StateIdNumber	C	10	
UserName	UserName	M	15	
VehicleEntryNumber	VehicleEntryNumber	O	10	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	24	
VehicleModelCode	VehicleModelCode	O	3	
VehicleShowCanceledRecordsIndicator	VehicleShowCanceledRecordsIndicator	O	1	Y
VehicleSOSCode	VehicleSOSCode	C	3	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In) BirthDate, Name, PurposeCode, Requestor, UserName, [Age, FormORI, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, PurposeDetails, RaceCode, SexCode]
2. (In/Out) FBINumber, PurposeCode, Requestor, UserName, [ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, PurposeDetails]
3. (In/Out) PersonSOSCode, Requestor, UserName, [Age, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, CriminalTrackingNumber, FBINumber, FormORI, MiscellaneousDescriptiveText, MiscellaneousNumber, NICSTransactionNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, PersonEntryNumber, PersonShowCanceledRecordsIndicator, PrisonNumber, PurposeCode, PurposeDetails, RaceCode, SendToMDOCIndicator, SexCode, SocialSecurityNumber, SOSOnlyIndicator, State, StateIdNumber, VehicleEntryNumber]
4. (In/Out) PurposeCode, Requestor, StateIdNumber, UserName, [ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, PurposeDetails]
5. (In/Out) Requestor, UserName, VehicleSOSCode, [ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, LicensePlateYear, LojackId, OperatorLicenseNumber, OriginatingAgencyCaseNumber, OwnerAppliedNumber, PersonEntryNumber, State, VehicleEntryNumber, VehicleIdentificationNumber, VehicleMakeCode, VehicleModelCode, VehicleShowCanceledRecordsIndicator, VehicleYear]
6. (Out) BirthDate, Name, PurposeCode, Requestor, State, UserName, [Age, ConcealedAttestCode, ConcealedPurposeCode, ConcealedReasonText, FormORI, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, PurposeDetails, RaceCode, SexCode]

NameSearchQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M	8	

Destination	Destination	O	20	LocalTest, Demo Image, OTIS, TRACVIEW, LocatePLUS, MIDRS
Destination	Destination	O	20	
Destination	Destination	O	20	
Destination	Destination	O	20	
Destination	Destination	O	20	
Destination	Destination	O	20	
Destination	Destination	O	20	
Destination	Destination	O	20	
Destination	Destination	O	20	
Destination	Destination	O	20	
Destination	Destination	O	20	
Destination	Destination	O	20	
Destination	Destination	O	20	
Destination	Destination	O	20	
Name	Name	M	30	
RaceCode	RaceCode	M	1	A, B, I, U, W
SexCode	SexCode	M	1	F, M, U

Possible Combinations

1. (In/Out) BirthDate, Name, RaceCode, SexCode, [Destination]

PartialNameSearchQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agncy
Age	Age	C	2	
BirthDate	BirthDate	C	8	
FormORI	FormORI	O	9	
Name	Name	C	30	
RaceCode	RaceCode	C	1	
Requestor	Requestor	C	15	
SexCode	SexCode	C	1	
UserName	UserName	C	15	

Possible Combinations

1. (In/Out) Age, Name, RaceCode, Requestor, SexCode, UserName, [AddressDepartment, FormORI]
2. (In/Out) BirthDate, Name, RaceCode, Requestor, SexCode, UserName, [AddressDepartment, FormORI]

PersonalIdentificationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agncy
BirthDate	BirthDate	C	8	
FormORI	FormORI	O	9	
Name	Name	C	30	
PersonalIdentificationNumber	PersonalIdentificationNumber	C	15	
RaceCode	RaceCode	C	1	A, B, I, U, W
Requestor	Requestor	C	15	
SexCode	SexCode	C	1	F, M, U
UserName	UserName	C	15	

Possible Combinations

1. (In) BirthDate, Name, PersonalIdentificationNumber, RaceCode, Requestor, SexCode, UserName, [AddressDepartment, FormORI]
2. (In) BirthDate, Name, RaceCode, Requestor, SexCode, UserName, [AddressDepartment, FormORI]
3. (In) PersonalIdentificationNumber, Requestor, UserName, [AddressDepartment, FormORI]

SnowmobileRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
FormORI	FormORI	O	9	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateYear	LicensePlateYear	C	4	
Requestor	Requestor	M	15	
State	State	C	2	
UserName	UserName	M	15	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In) LicensePlateNumber, Requestor, UserName, [AddressDepartment, FormORI]
2. (In) Requestor, UserName, VehicleIdentificationNumber, [AddressDepartment, FormORI]
3. (Out) LicensePlateNumber, LicensePlateYear, Requestor, State, UserName, [AddressDepartment, FormORI]
4. (Out) Requestor, State, UserName, VehicleIdentificationNumber, [AddressDepartment, FormORI]

WantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressDepartment	AddressDepartment	O	15	Defaults to Authentication/Agency
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	O	20	
FormORI	FormORI	O	9	
LicensePlateNumber	LicensePlateNumber	O	15	
MiscellaneousNumber	MiscellaneousNumber	O	20	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	O	17	
OwnerAppliedNumber	OwnerAppliedNumber	O	20	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	O	1	
PurposeCode	PurposeCode	O	1	
RaceCode	RaceCode	O	1	A, B, I, U, W
Requestor	Requestor	C	15	
SexCode	SexCode	O	1	F, M, U
SocialSecurityNumber	SocialSecurityNumber	O	9	
State	State	C	2	
UserName	UserName	C	15	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	17	

Possible Combinations

1. (In) Requestor, UserName, [BirthDate, FBINumber, FormORI, LicensePlateNumber, MiscellaneousNumber, Name, OperatorLicenseNumber, OwnerAppliedNumber, RaceCode, SexCode, SocialSecurityNumber, VehicleIdentificationNumber]
2. (Out) Requestor, State, UserName, [BirthDate, FBINumber, FormORI, LicensePlateNumber, MiscellaneousNumber, Name, OperatorLicenseNumber, OwnerAppliedNumber,

PersonPropertyInSightIndicator, PurposeCode, RaceCode, SexCode, SocialSecurityNumber, VehicleIdentificationNumber]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

Michigan LEIN will only work with agencies, not directly with vendors. You must go through the agency for any communication necessary for installation, configuration, documentation, security requirements from LEIN.

Each Michigan transactions requires the following fields: UserName, Requestor, and AddressDepartment.

- UserName -- Name assigned the person who is actually using the application and entering the information.
- Requestor -- Name of the individual who someone is performing a transaction for. For example, a dispatcher may be running an inquiry for an officer (Off. John Doe) or a detective (Det. Jane Joe).
- AddressDepartment -- Name of the agency the transaction is being run for. For example a dispatch center may perform services for multi-agencies so the agency the inquiry is being entered for would be entered here (ABC123 Police Department).

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- LEIN Operations Manual