

Missouri (MO) REJIS

[Disclaimer Statement](#)

Transport:

TCPIP/WEB Services

Routing and Configuration Information:

Mnemonic Routing

- The REJIS assigned LTERM for a device should be placed in the **<Authentication>/<Mnemonic>** field in the ConnectCIC header.
- The REJIS assigned ORI for a device should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.
- The REJIS assigned Username should be placed in the **<Authentication>/<UserName>** field in the ConnectCIC header.
- The REJIS assigned Password should be placed in the **<Authentication>/<Password>** field in the ConnectCIC header.

Security Requirements:

Each CAD user that runs REJIS inquiries through the CAD interface must have a valid REJIS User ID (ConnectCIC UserName) and associated password. In addition, the CAD user must have a current REJIS certification authorizing the user to run law enforcement inquiries and the user's corresponding REJIS User ID must be granted the necessary system permissions. The CAD user's client workstation will be required to have a static IP address and LTERM defined to the REJIS system. Any violation of these standards may result in termination of service for the agency.

Logon Requirements:

The REJIS law enforcement inquiry system is stateless as far as security is concerned. There is no concept of a REJIS logon session.

Certification Requirements:

Each CAD user must have a current REJIS certification authorizing the user to run law enforcement inquiries and the user's corresponding REJIS User ID must be granted the necessary system permissions.

Data-Mined Transactions:

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	20	
RegistrationNumber	RegistrationNumber	C	8	
State	State	O	2	

Possible Combinations

1. (In/Out) BoatHullIdNumber, [State]
2. (In/Out) RegistrationNumber, [State]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
PurposeCode	PurposeCode	C	1	'C' – Criminal Justice 'J' – Criminal Justice Employment 'H' - Housing Authority 'S' = SCIA Agencies
RaceCode	RaceCode	O	1	
RegionCode	RegionCode	O	1	"K" – Kansas City "S" – Saint Louis "A" " " – These values indicate all regions Default: All Regions
ResponseFormat	ResponseFormat	O	1	'I' – index 'F' – Full 'B' – Both. Default: F
SexCode	SexCode	C	1	
State	State	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, RaceCode, SexCode, [PurposeCode, RegionCode, ResponseFormat, State]
2. (In/Out) OperatorLicenseNumber, [RegionCode, ResponseFormat, State]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	O	23	
GunModel	GunModel	O	11	
GunSerialNumber	GunSerialNumber	M	20	
ImageIndicator	ImageIndicator	O	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	

Possible Combinations

1. (In/Out) GunSerialNumber, [GunCaliber, GunMake, GunModel, ImageIndicator, RelatedHitSearchIndicator]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	C	4	
State	State	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In) VehicleIdentificationNumber, [VehicleMakeCode]
2. (In/Out) LicensePlateNumber, [LicensePlateTypeCode, LicensePlateYear, State]
3. (In/Out) LicensePlateNumber, [State]
4. (In/Out) LicensePlateNumber, LicensePlateYear
5. (Out) VehicleIdentificationNumber, State, [VehicleMakeCode]

Transactions Supported:

Computerized Criminal History (CCH)

CCHNameQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	15	
PurposeCode	PurposeCode	M	1	'C' – Criminal Justice 'J' – Criminal Justice Employment 'H' – Housing Authority 'S' – SCIA Agencies
RaceCode	RaceCode	M	1	
ReasonCode	ReasonCode	M	5	
ResponseFormat	ResponseFormat	O	1	'I' – index 'F' – Full 'B' – Both. Default: F
SexCode	SexCode	M	1	
BirthDate	BirthDate	M	8	
Name	Name	M	30	

Possible Combinations

1. (In/Out) BirthDate, Name, PurposeCode, RaceCode, SexCode, Attention, ReasonCode, {ResponseFormat}

Expanded Queries Supported:

ChangePassword

Field Name	XML Tag Name	M/C/O	Size	Possible Values
NewPassword	NewPassword	M	20	
Password	Password	M	20	
UserName	UserName	M	8	

Possible Combinations

1. (In/Out) NewPassword, Password, UserName

ValidateUser

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

Possible Combinations

1. (In/Out) No fields are used with this transaction. Just execute this transaction and the user will be notified of password expiration days.

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- MO REJIS Transport, Protocol, and Message Key Documentation