

Mississippi (MS) MCHS

[Disclaimer Statement](#)

Transport:

TCPIP

DMPP2020 Extended

Routing Information:

Mnemonic Routing

- The MCHS assigned ORI for a device (or for the site) should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.
- The MCHS assigned Mnemonic for a device should be placed in the **<Authentication>/<Mnemonic>** field in the ConnectCIC header.

Logon Requirements:

To logoff, use the Logon transaction and pass the word “LOGOFF” in the UserName field. No password is required.

<LogonRequest>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
User Name	UserName	M	20	
Password	Password	M	6	
New Password	NewPassword	O	6	
Retype New Password	ReTypeNewPassword	O	6	

1. Logon -- To logon use the UserName and Password fields in the header.
2. Change Password -- To logon and change password provide Password, NewPassword, and RetypeNewPassword fields.
3. Logoff -- To logoff, use the Logon transaction and pass the word “LOGOFF” in the UserName field. No password is required.

<LogoffRequest>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

No fields are required; Just send <LogoffRequest> form.

Certification Requirements:

Need Site Sponsor.

State-Level Certification – every vendor must certify with the state before installing at an agency

CommSys has certified ConnectCIC; however, if you have not certified as a vendor, you will need to do so prior to installing your solution at a MS agency.

Data mined Queries:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Article Type Code	ArticleTypeCode	C	7	
NCIC Number	NCICNumber	C	10	
Owner Applied Number	OwnerAppliedNumber	O	20	
Serial Number	ArticleSerialNumber	C	20	

Possible Combinations (fields within the square brackets are optional)

1. ArticleSerialNumber, ArticleTypeCode [OwnerAppliedNumber]
2. NCICNumber

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Boat Hull Number	BoatHullIdNumber	C	20	
NCIC Number	NCICNumber	C	10	
Registration Number	RegistrationNumber	C	8	

Possible Combinations (fields within the square brackets are optional)

1. BoatHullIdNumber
2. BoatHullIdNumber, RegistrationNumber
3. NCICNumber
4. RegistrationNumber

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Birth Date	BirthDate	C	8	
ImageIndicator	ImageIndicator	O	1	Y
Name	Name	C	30	
Operator License Number	OperatorLicenseNumber	C	20	
Sex Code	SexCode	C	1	
State	State	M	2	Default = MS
State 2	State2	O	2	
State 3	State3	O	2	
State 4	State4	O	2	
State 5	State5	O	2	

Possible Combinations (fields within the square brackets are optional)

1. BirthDate, Name, SexCode, State [ImageIndicator, State2, State3, State4, State5]
2. OperatorLicenseNumber, State [ImageIndicator, State2, State3, State4, State5]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

Attention	Attention	C	30	
Birth Date	BirthDate	C	8	
Name	Name	C	30	
Operator License Number	OperatorLicenseNumber	C	20	
Purpose Code	PurposeCode	C	1	
State	State	C	2	Default = MS
Sex Code	SexCode	C	1	

Possible Combinations

1. (In) OperatorLicenseNumber, PurposeCode, Attention
2. (In) SexCode, BirthDate, Name
3. (Out) OperatorLicenseNumber, PurposeCode, Attention, State
4. (Out) SexCode, BirthDate, Name, State

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Gun Make	GunMake	O	23	
Gun Caliber	GunCaliber	O	4	
NCIC Number	NCICNumber	C	10	
Serial Number	GunSerialNumber	C	11	

Possible Combinations (fields within the square brackets are optional)

1. GunSerialNumber, [GunMake, GunCaliber]
2. NCICNumber

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
License Plate Number	LicensePlateNumber	C	10	
License Plate Year	LicensePlateYear	O	4	
License Plate Type Code	LicensePlateTypeCode	O	2	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	
Title Number	TitleNumber	C	7	
Vehicle Identification Number	VehicleIdentificationNumber	C	20	
Vehicle Make Code	VehicleMakeCode	O	4	
Vehicle Year	VehicleYear	O	4	

Possible Combinations (fields within the square brackets are optional)

1. (In) TitleNumber
2. LicensePlateNumber, [LicensePlateYear, LicensePlateTypeCode, State, State2, State3, State4, State5]
3. VehicleIdentificationNumber, [State, State2, State3, State4, State5, VehicleMakeCode, VehicleYear]

VehicleStolenQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
License Plate Number	LicensePlateNumber	C	8	

NCIC Number	NCICNumber	C	10	
State	State	O	2	
Vehicle Identification Number	VehicleIdentificationNumber	C	20	
Vehicle Identification Number 2	VehicleIdentificationNumber2	O	20	
Vehicle Identification Number 3	VehicleIdentificationNumber3	O	20	

Possible Combinations (fields within the square brackets are optional)

1. LicensePlateNumber, [State, VehicleIdentificationNumber, VehicleIdentificationNumber2, VehicleIdentificationNumber3]
2. NCICNumber
3. VehicleIdentificationNumber, [VehicleIdentificationNumber2, VehicleIdentificationNumber3]

Transactions Supported:

Computerized Criminal History (CCH)

CCHCriminalHistoryAQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
DestinationORI	DestinationORI	M	9	
FreeText	FreeText	O	14400	
PurposeCode	PurposeCode	M	1	

Possible Combinations

1. (In/Out) Attention, DestinationORI, PurposeCode, [FreeText]

CCHCriminalHistoryFQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address	Address	O	30	
Attention	Attention	M	30	
Building	Building	O	30	
CityAndState	CityAndState	O	30	
DepartmentName	DepartmentName	O	30	
ImageIndicator	ImageIndicator	O	1	
PurposeCode	PurposeCode	M	1	
State	State	M	2	
StateIDNumber	StateIDNumber	M	10	
ZipCode	ZipCode	O	9	

Possible Combinations

1. (In/Out) Attention, PurposeCode, State, StateIDNumber, [Address, Building, CityAndState, DepartmentName, ImageIndicator, ZipCode]

CCHCriminalHistoryIQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	8	
ImageIndicator	ImageIndicator	O	1	
MiscellaneousNumber	MiscellaneousNumber	C	15	

Name	Name	M	30	
PurposeCode	PurposeCode	M	1	
RaceCode	RaceCode	O	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	M	2	

Possible Combinations

1. (In/Out) Attention, BirthDate, Name, PurposeCode, SexCode, State, [ImageIndicator, MiscellaneousNumber, RaceCode]
2. (In/Out) Attention, BirthDate, Name, PurposeCode, SexCode, State, [ImageIndicator, RaceCode, SocialSecurityNumber]
3. (In/Out) Attention, MiscellaneousNumber, Name, PurposeCode, State, [ImageIndicator]
4. (In/Out) Attention, Name, PurposeCode, SocialSecurityNumber, State, [ImageIndicator]

CCHCriminalHistoryLQ1Query

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	8	
DepartmentCorrectionsNumber	DepartmentCorrectionsNumber	O	10	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
PurposeCode	PurposeCode	M	1	
RaceCode	RaceCode	C	4	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateIDNumber	StateIDNumber	O	10	

Possible Combinations

1. (In/Out) Attention, BirthDate, MiscellaneousNumber, Name, PurposeCode, RaceCode, SexCode, [DepartmentCorrectionsNumber, OperatorLicenseNumber, StateIDNumber]
2. (In/Out) Attention, BirthDate, Name, PurposeCode, RaceCode, SexCode, [DepartmentCorrectionsNumber, OperatorLicenseNumber, StateIDNumber]
3. (In/Out) Attention, BirthDate, Name, PurposeCode, RaceCode, SexCode, SocialSecurityNumber, [DepartmentCorrectionsNumber, OperatorLicenseNumber, StateIDNumber]
4. (In/Out) Attention, MiscellaneousNumber, Name, PurposeCode, [DepartmentCorrectionsNumber, OperatorLicenseNumber, StateIDNumber]
5. (In/Out) Attention, Name, PurposeCode, SocialSecurityNumber, [DepartmentCorrectionsNumber, OperatorLicenseNumber, StateIDNumber]

CCHCriminalHistoryQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
PurposeCode	PurposeCode	M	1	
RaceCode	RaceCode	C	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	

StateIDNumber	StateIDNumber	C	10	
---------------	---------------	---	----	--

Possible Combinations

1. (In/Out) BirthDate, MiscellaneousNumber, Name, PurposeCode, RaceCode, SexCode, [Attention]
2. (In/Out) BirthDate, Name, PurposeCode, RaceCode, SexCode, [Attention]
3. (In/Out) BirthDate, Name, PurposeCode, RaceCode, SexCode, SocialSecurityNumber, [Attention]
4. (In/Out) FBINumber, PurposeCode, [Attention, Name]
5. (In/Out) MiscellaneousNumber, Name, PurposeCode, [Attention]
6. (In/Out) Name, PurposeCode, SocialSecurityNumber, [Attention]
7. (In/Out) PurposeCode, StateIDNumber, [Attention, Name]

CCHCriminalHistoryQRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address	Address	O	30	
Attention	Attention	O	30	
Building	Building	O	30	
CityAndState	CityAndState	O	30	
DepartmentName	DepartmentName	O	30	
FBINumber	FBINumber	C	9	
Name	Name	O	30	
PurposeCode	PurposeCode	M	1	
StateIDNumber	StateIDNumber	C	10	
ZipCode	ZipCode	O	9	

Possible Combinations

1. (In/Out) FBINumber, PurposeCode, [Address, Attention, Building, CityAndState, DepartmentName, Name, ZipCode]
2. (In/Out) PurposeCode, StateIDNumber, [Address, Attention, Building, CityAndState, DepartmentName, Name, ZipCode]

CCHCriminalHistoryQWIQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	
FBINumber	FBINumber	O	9	
ImageIndicator	ImageIndicator	O	1	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	M	30	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	
PurposeCode	PurposeCode	M	1	
RaceCode	RaceCode	O	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SexCode	SexCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
StateIDNumber	StateIDNumber	O	10	

Possible Combinations

1. (In/Out) Name, PurposeCode, [BirthDate, ExpandedNameSearchCode, FBINumber, ImageIndicator, MiscellaneousNumber, OriginatingAgencyCaseNumber, RaceCode, RelatedHitSearchIndicator, SexCode, SocialSecurityNumber, StateIDNumber]

CCHCriminalHistoryZRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FBINumber	FBINumber	C	9	
PurposeCode	PurposeCode	O	1	
StateIDNumber	StateIDNumber	C	10	

Possible Combinations

1. (In/Out) FBINumber, [PurposeCode]
2. (In/Out) StateIDNumber, [PurposeCode]

Wanted Missing Person Inquiries (WMP-I)

WMPIMissingPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	M	2	
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	
EyeColorCode	EyeColorCode	M	3	
HairColorCode	HairColorCode	M	3	
Height	Height	M	3	
Name	Name	O	30	
RaceCode	RaceCode	M	1	
SexCode	SexCode	M	1	
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) Age, EyeColorCode, HairColorCode, Height, RaceCode, SexCode, Weight, [ExpandedNameSearchCode, Name]

WMPIWantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	
FBINumber	FBINumber	O	9	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	O	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SexCode	SexCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	24	

**** An inquiry of the Wanted Person File may be made by name and one, more than one, or all of the following alphanumeric identifiers: DOB, FBI, MNU, SOC, and OLN. Additionally, inquiries may be made using vehicle data (LIC, LIS, and/or VIN and VMA); NAM and OCA only; or NIC only.**

Possible Combinations

1. (In/Out) Name and an additional identifier, [BirthDate, ExpandedNameSearchCode, FBINumber, LicensePlateNumber, LicensePlateStateCode, MiscellaneousNumber, OperatorLicenseNumber, RaceCode, RelatedHitSearchIndicator, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
2. (In/Out) Name, OriginatingAgencyCaseNumber
3. (In/Out) NCICNumber

Expanded Transactions Supported:***WantedPersonQuery***

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
FBINumber	FBINumber	O	9	
LicensePlateNumber	LicensePlateNumber	O	8	
LicensePlateStateCode	LicensePlateStateCode	O	2	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	O	1	
SexCode	SexCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	

Possible Combinations

1. (In/Out) Name, [BirthDate, FBINumber, LicensePlateNumber, LicensePlateStateCode, MiscellaneousNumber, NCICNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, RaceCode, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
2. (In/Out) Name, OriginatingAgencyCaseNumber
3. (In/Out) NCICNumber

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

Reference:

- NCIC 2000 Operations Manual
- NLETS User Guide
- Mississippi State Document

