

Montana (MT) CJIN

[Disclaimer Statement](#)

Transport:

TCPIP DMPP2020

Routing and Configuration Information:

Mnemonic Routing

- The CJIN assigned ORI for a device (or for the site) should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.
- The CJIN assigned Mnemonic for a device should be placed in the **<Authentication>/<Mnemonic>** field in the ConnectCIC header.

Requestor and Reason Code – Definition and Usage:

The **Requestor Initials** field must identify the user making a transaction. The **Reason Code** field identifies the reason for the CJIN transaction. A reason code as follows could be used.

INV - Investigation

RCT - Recertification Workbook

ENT - Record Entry

TST - Test

VAL - Validations

WBK - Workbook Certification

*A Badge number could be automatically inserted in the case of the mobile units, where the transactions are routine.

These codes are examples. CJIN does not dictate what codes must be used. The user agency can use any code up to 3 characters, as long as they can explain them if audited.

Security Requirements:

None known at this time.

Logon Requirements:

CJIN requires a user login transaction for non-trusted CJIN connections.

Certification Requirements:

Agency sponsor is required.

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Article Type Code	ArticleTypeCode	C	4-7	
Article Serial Number	ArticleSerialNumber	C	20	
Image Indicator	ImageIndicator	O	1	Y,N
NCIC Number	NCICNumber	C	10	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Related Hit Search	RelatedHitSearchIndicator	O	1	Y, N
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations (fields within the square brackets are optional)

1. Requestor, ReasonCode, NCICNumber, [ImageIndicator, RelatedHitSearchIndicator]
2. Requestor, ReasonCode, ArticleTypeCode, ArticleSerialNumber, [ImageIndicator, RelatedHitSearchIndicator]

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Boat Hull Number	BoatHullIdNumber	C	20	
Image Indicator	ImageIndicator	O	1	Y,N
NCIC Number	NCICNumber	C	10	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Related Hit Search	RelatedHitSearchIndicator	O	1	Y, N
Requestor Initials	Requestor	M	3	See Definition and Usage above
Registration Number	RegistrationNumber	C	8	

Possible Combinations (fields within the square brackets are optional)

1. Requestor, ReasonCode, NCICNumber, [ImageIndicator, RelatedHitSearchIndicator]
2. Requestor, ReasonCode, RegistrationNumber, [BoatHullIdNumber, ImageIndicator, RelatedHitSearchIndicator]
3. Requestor, ReasonCode, BoatHullIdNumber, [ImageIndicator, RelatedHitSearchIndicator]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
ImageIndicator	ImageIndicator	O	1	Y
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
PurposeCode	PurposeCode	O	1	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
SexCode	SexCode	C	1	

State	State	O	2	
-------	-------	---	---	--

Possible Combinations

1. (In/Out) Requestor, ReasonCode, BirthDate, Name, SexCode, [Attention, ImageIndicator, PurposeCode, State]
2. (In/Out) Requestor, ReasonCode, OperatorLicenseNumber, [Attention, ImageIndicator, PurposeCode, State]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Birth Date	BirthDate	C	10	
Expanded Birth Date Search	ExpandedBirthDateSearchCode	O	1	1,0
ImageIndicator	ImageIndicator	O	1	Y
Name	Name	C	30	
Operator License Number	OperatorLicenseNumber	C	20	
Reason	Reason	O	200	Freetext description of reason inquiry was made
Reason Code	ReasonCode	M	3	See Definition and Usage above
Related Hit Search	RelatedHitSearchIndicator	O	1	Y
Requestor Initials	Requestor	M	3	See Definition and Usage above
Sex Code	SexCode	C	1	F, M, U
State	State	O	2	
State 2	State2	O	2	
State 3	State3	O	2	
State 4	State4	O	2	
State 5	State5	O	2	

Possible Combinations (fields within the square brackets are optional)

1. Requestor, ReasonCode, OperatorLicenseNumber, [ImageIndicator, State, State2, State3, State4, State5, RelatedHitSearchIndicator, ExpandedBirthDateSearchCode, Reason]
2. Requestor, ReasonCode, Name, BirthDate, SexCode, [ImageIndicator, State, State2, State3, State4, State5, RelatedHitSearchIndicator, ExpandedBirthDateSearchCode, Reason]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Gun Caliber	GunCaliber	O	4	
Gun Make	GunMake	O	23	
Image Indicator	ImageIndicator	O	1	Y
NCIC Number	NCICNumber	C	10	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Related Hit Search	RelatedHitSearchIndicator	O	1	Y
Requestor Initials	Requestor	M	3	See Definition and Usage above
Serial Number	GunSerialNumber	M	20	

Possible Combinations (fields within the square brackets are optional)

1. Requestor, ReasonCode, NCICNumber, [ImageIndicator, RelatedHitSearchIndicator]
2. Requestor, ReasonCode, GunSerialNumber, [GunMake, GunCaliber, ImageIndicator, RelatedHitSearchIndicator]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
License Plate Number	LicensePlateNumber	C	10	
License Plate Year	LicensePlateYear	C	4	
License Plate Type	LicensePlateTypeCode	C	2	
Reason	Reason	O	200	Freetext description of reason inquiry was made
Reason Code	ReasonCode	M	3	See Definition and Usage above
Related Hit Search	RelatedHitSearchIndicator	O	1	Y
Requestor Initials	Requestor	M	3	See Definition and Usage above
State	State	O	2	
State 2	State2	O	2	
State 3	State3	O	2	
State 4	State4	O	2	
State 5	State5	O	2	
Vehicle Identification Number	VehicleIdentificationNumber	C	20	
Vehicle Make Code	VehicleMakeCode	O	4	
Vehicle Year	VehicleYear	O	4	

Possible Combinations (fields within the square brackets are optional)

1. Requestor, ReasonCode, LicensePlateNumber, LicensePlateYear, LicensePlateTypeCode, [State, State2, State3, State4, State5, RelatedHitSearchIndicator, Reason]
2. Requestor, ReasonCode, VehicleIdentificationNumber, [VehicleMakeCode, VehicleYear, State, State2, State3, State4, State5, RelatedHitSearchIndicator, Reason]

Transactions Supported:

Agency Operations and Support (AOS)

AOSAircraftRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
Name	Name	C	40	
ReasonCode	ReasonCode	O	3	See Definition and Usage above
RegistrationNumber	RegistrationNumber	C	6	
Requestor	Requestor	O	3	See Definition and Usage above
SerialNumber	SerialNumber	C	16	

Possible Combinations

1. (In/Out) Attention, Name, [ReasonCode, Requestor]
2. (In/Out) Attention, SerialNumber, [ReasonCode, Requestor]
3. (In/Out) Attention, RegistrationNumber, [ReasonCode, Requestor]

AOSHazardousMaterialQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ReasonCode	ReasonCode	O	3	See Definition and Usage above
Requestor	Requestor	O	3	See Definition and Usage above
UnitedNationsNumber	UnitedNationsNumber	M	4	

Possible Combinations

1. (In/Out) UnitedNationsNumber, [ReasonCode, Requestor]

AOSNIletsAdministrativeMessage

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Destination	Destination	M	9	
Destination2	Destination2	O	9	
Destination3	Destination3	O	9	
Destination4	Destination4	O	9	
Destination5	Destination5	O	9	
FreeText	FreeText	M	1000	
ReasonCode	ReasonCode	O	3	See Definition and Usage above
Requestor	Requestor	O	3	See Definition and Usage above

Possible Combinations

1. (In/Out) Destination, FreeText, [Destination2, Destination3, Destination4, Destination5, ReasonCode, Requestor]

AOSNIletsHitConfirmationRequest

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleBrand	ArticleBrand	O	6	
ArticleSerialNumber	ArticleSerialNumber	C	20	
ArticleTypeCode	ArticleTypeCode	C	7	
BirthDate	BirthDate	C	10	
BoatHullIdNumber	BoatHullIdNumber	O	20	
BoatMakeCode	BoatMakeCode	O	24	
Brand	Brand	O	4	
Category	Category	O	2	
CourtOrderNumber	CourtOrderNumber	O	20	
Denomination	Denomination	O	9	
Destination	Destination	C	9	
Destination2	Destination2	O	9	
Destination3	Destination3	O	9	
ExtensionNumber	ExtensionNumber	O	4	
FaxNumber	FaxNumber	O	10	
GunCaliber	GunCaliber	C	4	
GunMake	GunMake	C	24	
GunModel	GunModel	O	20	
GunSerialNumber	GunSerialNumber	C	20	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	O	4	
Name	Name	C	30	
NCICNumber	NCICNumber	O	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PhoneNumber	PhoneNumber	O	10	
PriorityDestinationCode	PriorityDestinationCode	C	1	
ReasonCode	ReasonCode	O	3	See Definition and Usage above
RegistrationNumber	RegistrationNumber	O	8	
Remarks	Remarks	O	500	

RequesterName	RequesterName	C	30	
RequestingAgency	RequestingAgency	C	30	
RequestNumber	RequestNumber	C	1	
Requestor	Requestor	O	3	See Definition and Usage above
RequestTypeCode	RequestTypeCode	C	2	
SecuritySerialNumber	SecuritySerialNumber	C	18	
SecurityTypeCode	SecurityTypeCode	C	2	
SerialNumber	SerialNumber	C	20	
SexCode	SexCode	O	1	F, M, U
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	24	
VehicleYear	VehicleYear	O	4	
WarrantNumber	WarrantNumber	O	20	

Possible Combinations

1. (In) ArticleSerialNumber, ArticleTypeCode, Destination, OriginatingAgencyCaseNumber, PhoneNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, [ArticleBrand, CourtOrderNumber, Destination2, Destination3, ExtensionNumber, FaxNumber, NCICNumber, ReasonCode, Remarks, Requestor, WarrantNumber]
2. (In) BirthDate, Destination, Name, OriginatingAgencyCaseNumber, PhoneNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, [CourtOrderNumber, Destination2, Destination3, ExtensionNumber, FaxNumber, NCICNumber, ReasonCode, Remarks, Requestor, SexCode, WarrantNumber]
3. (In) BirthDate, Destination, Name, OriginatingAgencyCaseNumber, PhoneNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, [CourtOrderNumber, Destination2, Destination3, ExtensionNumber, FaxNumber, NCICNumber, ReasonCode, Remarks, Requestor, SexCode, WarrantNumber]
4. (In) Destination, GunCaliber, GunMake, GunSerialNumber, OriginatingAgencyCaseNumber, PhoneNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, [CourtOrderNumber, Destination2, Destination3, ExtensionNumber, FaxNumber, GunModel, NCICNumber, ReasonCode, Remarks, Requestor, WarrantNumber]
5. (In) Destination, LicensePlateNumber, LicensePlateStateCode, OriginatingAgencyCaseNumber, PhoneNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, [CourtOrderNumber, Destination2, Destination3, ExtensionNumber, FaxNumber, LicensePlateTypeCode, LicensePlateYear, NCICNumber, ReasonCode, Remarks, Requestor, WarrantNumber]
6. (In) Destination, OriginatingAgencyCaseNumber, PhoneNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, [BoatHullIdNumber, BoatMakeCode, CourtOrderNumber, Destination2, Destination3, ExtensionNumber, FaxNumber, NCICNumber, ReasonCode, RegistrationNumber, Remarks, Requestor, WarrantNumber]
7. (In) Destination, OriginatingAgencyCaseNumber, PhoneNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, [CourtOrderNumber, Destination2, Destination3, ExtensionNumber, FaxNumber, LicensePlateNumber, NCICNumber, ReasonCode, Remarks, Requestor, VehicleIdentificationNumber, VehicleMakeCode, VehicleYear, WarrantNumber]
8. (In) Destination, OriginatingAgencyCaseNumber, PhoneNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, SecuritySerialNumber, SecurityTypeCode, [CourtOrderNumber, Denomination, Destination2, Destination3, ExtensionNumber, FaxNumber, NCICNumber, ReasonCode, Remarks, Requestor, WarrantNumber]
9. (In) Destination, OriginatingAgencyCaseNumber, PhoneNumber, PriorityDestinationCode, RequesterName, RequestingAgency, RequestNumber, RequestTypeCode, SerialNumber,

[Brand, Category, CourtOrderNumber, Destination2, Destination3, ExtensionNumber, FaxNumber, NCICNumber, ReasonCode, Remarks, Requestor, WarrantNumber]

AOSNletsHitConfirmationResponse

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleBrand	ArticleBrand	O	6	
ArticleSerialNumber	ArticleSerialNumber	O	20	
ArticleTypeCode	ArticleTypeCode	O	7	
BirthDate	BirthDate	O	10	
BoatHullIdNumber	BoatHullIdNumber	O	20	
BoatMakeCode	BoatMakeCode	O	24	
BoatRegistrationNumber	BoatRegistrationNumber	O	8	
ConfirmationStatusCode	ConfirmationStatusCode	M	1	Y, N, P, E
ConfirmingAgency	ConfirmingAgency	M	30	
ConfirmingName	ConfirmingName	M	30	
CourtOrderNumber	CourtOrderNumber	O	20	
Denomination	Denomination	O	9	
Destination	Destination	M	9	
ExtensionNumber	ExtensionNumber	O	4	
FaxNumber	FaxNumber	O	10	
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	O	24	
GunModel	GunModel	O	20	
GunSerialNumber	GunSerialNumber	O	20	
HoursForConfirmation	HoursForConfirmation	C	3	Mandatory ConfirmationStatusCode is E or P
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	O	4	
Name	Name	O	30	
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
PartBrand	PartBrand	O	4	
PartCategoryCode	PartCategoryCode	O	2	
PartSerialNumber	PartSerialNumber	O	20	
PhoneNumber	PhoneNumber	O	10	
ReasonCode	ReasonCode	O	3	See Definition and Usage above
Remarks	Remarks	O	500	
Requestor	Requestor	O	3	See Definition and Usage above
RequestTypeCode	RequestTypeCode	M	2	SV, WP, PO, MP, SL, SG, SA, SS, SB, SP
SecuritySerialNumber	SecuritySerialNumber	O	20	
SecurityTypeCode	SecurityTypeCode	O	2	
SexCode	SexCode	O	1	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	24	
VehicleYear	VehicleYear	O	4	
WarrantNumber	WarrantNumber	O	20	

Possible Combinations

1. (In/Out code¹=SA) ConfirmationStatusCode, ConfirmingAgency, ConfirmingName, Destination, HoursForConfirmation, NCICNumber, OriginatingAgencyCaseNumber, RequestTypeCode,

- ArticleSerialNumber, ArticleTypeCode, [ArticleBrand, PhoneNumber, ExtensionNumber, FaxNumber, ReasonCode, Remarks, Requestor]
2. (In/Out code¹=SV) ConfirmationStatusCode, ConfirmingAgency, ConfirmingName, Destination, HoursForConfirmation, NCICNumber, OriginatingAgencyCaseNumber, RequestTypeCode, LicensePlateNumber [PhoneNumber, ExtensionNumber, FaxNumber, ReasonCode, Remarks, Requestor]
 3. (In/Out code¹=SV) ConfirmationStatusCode, ConfirmingAgency, ConfirmingName, Destination, HoursForConfirmation, NCICNumber, OriginatingAgencyCaseNumber, RequestTypeCode, VehicleIdentificationNumber, [VehicleYear, VehicleMakeCode, PhoneNumber, ExtensionNumber, FaxNumber, ReasonCode, Remarks, Requestor]
 4. (In/Out code¹=WP,PO,MP) ConfirmationStatusCode, ConfirmingAgency, ConfirmingName, Destination, HoursForConfirmation, NCICNumber, OriginatingAgencyCaseNumber, RequestTypeCode, Name, BirthDate, [SexCode, PhoneNumber, ExtensionNumber, FaxNumber, ReasonCode, Remarks, Requestor]
 5. (In/Out code¹=SL) ConfirmationStatusCode, ConfirmingAgency, ConfirmingName, Destination, HoursForConfirmation, NCICNumber, OriginatingAgencyCaseNumber, RequestTypeCode, LicensePlateNumber, LicensePlateStateCode, [LicensePlateYear, LicensePlateTypeCode, PhoneNumber, ExtensionNumber, FaxNumber, ReasonCode, Remarks, Requestor]
 6. (In/Out code¹=SG) ConfirmationStatusCode, ConfirmingAgency, ConfirmingName, Destination, HoursForConfirmation, NCICNumber, OriginatingAgencyCaseNumber, RequestTypeCode, GunSerialNumber, GunCaliber, GunMake, [GunModel, PhoneNumber, ExtensionNumber, FaxNumber, ReasonCode, Remarks, Requestor]
 7. (In/Out code¹=SS) ConfirmationStatusCode, ConfirmingAgency, ConfirmingName, Destination, HoursForConfirmation, NCICNumber, OriginatingAgencyCaseNumber, RequestTypeCode, SecuritySerialNumber, SecurityTypeCode, [Denomination, PhoneNumber, ExtensionNumber, FaxNumber, ReasonCode, Remarks, Requestor]
 8. (In/Out code¹=SB) ConfirmationStatusCode, ConfirmingAgency, ConfirmingName, Destination, HoursForConfirmation, NCICNumber, OriginatingAgencyCaseNumber, RequestTypeCode, BoatRegistrationNumber, [PhoneNumber, ExtensionNumber, FaxNumber, ReasonCode, Remarks, Requestor]
 9. (In/Out code¹=SB) ConfirmationStatusCode, ConfirmingAgency, ConfirmingName, Destination, HoursForConfirmation, NCICNumber, OriginatingAgencyCaseNumber, RequestTypeCode, BoatHullIdNumber, [BoatMakeCode, PhoneNumber, ExtensionNumber, FaxNumber, ReasonCode, Remarks, Requestor]
 10. (In/Out code¹=SP) ConfirmationStatusCode, ConfirmingAgency, ConfirmingName, Destination, HoursForConfirmation, NCICNumber, OriginatingAgencyCaseNumber, RequestTypeCode, PartSerialNumber, [PartBrand, PartCategoryCode, PhoneNumber, ExtensionNumber, FaxNumber, ReasonCode, Remarks, Requestor]
- ¹code = RequestTypeCode value

AOSOrion

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AgencyTypeCode	AgencyTypeCode	O	2	
DestinationORI	DestinationORI	C	9	
FederalAgencyOrLocation	FederalAgencyOrLocation	C	30	
Location	Location	C	20	
ReasonCode	ReasonCode	O	3	See Definition and Usage above
Requestor	Requestor	O	3	See Definition and Usage above
State	State	O	2	

Possible Combinations

1. (In/Out) DestinationORI, [ReasonCode, Requestor, State]
2. (In/Out) FederalAgencyOrLocation, [ReasonCode, Requestor, State]
3. (In/Out) Location, [AgencyTypeCode, ReasonCode, Requestor, State]

AOSORIQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DestinationORI	DestinationORI	M	9	
ReasonCode	ReasonCode	O	3	See Definition and Usage above
Requestor	Requestor	O	3	See Definition and Usage above

Possible Combinations

- (In/Out) DestinationORI, [ReasonCode, Requestor]

Canadian Basic Inquiries (CBI)

CBIArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	23	
ArticleTypeCode	ArticleTypeCode	M	2	AA- domestic appliances, e.g. stoves, washers. BI- non-motorized bicycles, e.g. mountain bikes, tandems, 10-speeds. NOTE: Motorized bikes are in the Vehicle File. HH- Household property, e.g. rugs, furniture. JE- jewelry, e.g. watches, rings. MI- musical instruments, e.g. violins, guitars. MT- machinery and tools, e.g. electrical motors, lawn mowers. NOTE: Lawn mowers capable of carrying an operator are in the Vehicle File. OM- office machines and equipment, e.g. computers. PA- personal accessories, e.g. hearing aids, luggage. PE- photographic equipment, e.g. camera, enlargers. RA- radio, TV, sound-reproducing equipment, e.g. VCR's. SC- scientific, optical and measuring devices, e.g. binoculars. SP- sporting goods, hobby equipment, e.g. skis, model aircraft, scuba equipment. OT- all other articles, e.g. animals, vending machines, precious metals such as gold bars, uniquely identifiable gun barrels
NletsReasonCode	NletsReasonCode	M	1	N - Narcotics F - Fraud (includes counterfeit documents) V - Violent crimes (incl. robbery, murder, rape, bombing, etc.) T - Traffic violations S - Theft H - Humanitarian
PersonPropertyInSiteIndicator	PersonPropertyInSiteIndicator	M	1	Y
ReasonCode	ReasonCode	M	3	See Definition and Usage above
Requestor	Requestor	M	3	See Definition and Usage above

Possible Combinations

- (In/Out) ArticleSerialNumber, ArticleTypeCode, NletsReasonCode, PersonPropertyInSiteIndicator, ReasonCode, Requestor

CBIBoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

BoatHullIdNumber	BoatHullIdNumber	C	12	
BoatHullSerialNumber	BoatHullSerialNumber	C	18	
BoatName	BoatName	C	13	
BoatRegistrationNumber	BoatRegistrationNumber	C	7	
LicensePlateNumber	LicensePlateNumber	C	10	
MotorTypeCode	MotorTypeCode	O	5	INB, OUTB, INOUT, OT
NletsReasonCode	NletsReasonCode	M	1	N - Narcotics F - Fraud (includes counterfeit documents) V - Violent crimes (incl. robbery, murder, rape, bombing, etc.) T - Traffic violations S - Theft H - Humanitarian
PersonPropertyInSiteIndicator	PersonPropertyInSiteIndicator	M	1	Y, N
ReasonCode	ReasonCode	M	3	See Definition and Usage above
Requestor	Requestor	M	3	See Definition and Usage above
State	State	M	2	For VIN inquiries only "CN" is allowed. For LIC inquiries, a providence or territory code must be used.

Possible Combinations

1. (In/Out) BoatHullIdNumber, NletsReasonCode, PersonPropertyInSiteIndicator, ReasonCode, Requestor, State
2. (In/Out) BoatHullSerialNumber, NletsReasonCode, PersonPropertyInSiteIndicator, ReasonCode, Requestor, State, [MotorTypeCode]
3. (In/Out) BoatName, NletsReasonCode, PersonPropertyInSiteIndicator, ReasonCode, Requestor, State
4. (In/Out) BoatRegistrationNumber, NletsReasonCode, PersonPropertyInSiteIndicator, ReasonCode, Requestor, State
5. (In/Out) LicensePlateNumber, NletsReasonCode, PersonPropertyInSiteIndicator, ReasonCode, Requestor, State

CBIDriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M	10	
Name	Name	M	30	
NletsReasonCode	NletsReasonCode	M	1	N – Narcotics F - Fraud (includes counterfeit documents) V - Violent crimes (incl. robbery, murder, rape, bombing, etc.) T - Traffic violations S - Theft H - Humanitarian
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
PersonPropertyInSiteIndicator	PersonPropertyInSiteIndicator	M	1	Y, N
ReasonCode	ReasonCode	M	3	See Definition and Usage above
Requestor	Requestor	M	3	See Definition and Usage above
SexCode	SexCode	M	1	
State	State	M	2	2 character province/territory code

Possible Combinations

1. (In/Out) BirthDate, Name, NletsReasonCode, PersonPropertyInSiteIndicator, ReasonCode, Requestor, SexCode, State, [OperatorLicenseNumber]

CBIGunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

GunSerialNumber	GunSerialNumber	M	23	
GunTypeCode	GunTypeCode	M	2	SG - shotgun RI - rifle RW - restricted weapon OT - other only
NletsReasonCode	NletsReasonCode	M	1	N - Narcotics F - Fraud (includes counterfeit documents) V - Violent crimes (incl. robbery, murder, rape, bombing, etc.) T - Traffic violations S - Theft H - Humanitarian
PersonPropertyInSiteIndicator	PersonPropertyInSiteIndicator	M	1	Y, N
ReasonCode	ReasonCode	M	3	See Definition and Usage above
Requestor	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) GunSerialNumber, GunTypeCode, NletsReasonCode, PersonPropertyInSiteIndicator, ReasonCode, Requestor

CBIVehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	10	
NletsReasonCode	NletsReasonCode	M	1	N - Narcotics F - Fraud (includes counterfeit documents) V - Violent crimes (incl. robbery, murder, rape, bombing, etc.) T - Traffic violations S - Theft H - Humanitarian
PersonPropertyInSiteIndicator	PersonPropertyInSiteIndicator	M	1	Y, N
ReasonCode	ReasonCode	M	3	See Definition and Usage above
Requestor	Requestor	M	3	See Definition and Usage above
State	State	M	2	2 character province/territory code
VehicleIdentificationNumber	VehicleIdentificationNumber	C	17	

Possible Combinations

1. (In/Out) LicensePlateNumber, NletsReasonCode, PersonPropertyInSiteIndicator, ReasonCode, Requestor, State
2. (In/Out) NletsReasonCode, PersonPropertyInSiteIndicator, ReasonCode, Requestor, State, VehicleIdentificationNumber

Computerized Criminal History Package (CCH):

CCHCriminalHistoryAQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
FreeText	FreeText	M	14400	
NletsDestination	NletsDestination	M	9	
NletsDestination2	NletsDestination2	O	9	
NletsDestination3	NletsDestination3	O	9	
NletsDestination4	NletsDestination4	O	9	
PurposeCode	PurposeCode	M	1	
Reason	Reason	O	200	Freetext description of reason inquiry was made
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) Attention, FreeText, NletsDestination, PurposeCode, ReasonCode, Requestor, [NletsDestination2, NletsDestination3, NletsDestination4, Reason]

CCHCriminalHistoryARQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
FreeText	FreeText	M	14400	
NletsDestination	NletsDestination	M	9	
PurposeCode	PurposeCode	M	1	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) Attention, FreeText, NletsDestination, PurposeCode, ReasonCode, Requestor

CCHCriminalHistoryFQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	30	
AddressStreet	AddressStreet	O	30	
AddressZipCode	AddressZipCode	O	9	
Attention	Attention	M	30	
BuildingName	BuildingName	O	30	
DepartmentName	DepartmentName	O	30	
ImageIndicator	ImageIndicator	O	1	
PurposeCode	PurposeCode	M	1	
Reason	Reason	O	200	Freetext description of reason inquiry was made
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
State	State	C	2	
StateIdNumber	StateIdNumber	M	10	

Possible Combinations

1. (In) AddressCityState, AddressStreet, AddressZipCode, Attention, PurposeCode, Reason, ReasonCode, Requestor, StateIdNumber, [BuildingName, DepartmentName, ImageIndicator]
2. (Out) AddressCityState, AddressStreet, AddressZipCode, Attention, PurposeCode, Reason, ReasonCode, Requestor, StateIdNumber, State [BuildingName, DepartmentName, ImageIndicator]

CCHCriminalHistoryIQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	C	30	
BirthDate	BirthDate	C	8	
ImageIndicator	ImageIndicator	O	1	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	C	30	
PurposeCode	PurposeCode	C	1	
RaceCode	RaceCode	O	1	
Reason	Reason	O	200	Freetext description of reason inquiry was made
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
State	State	O	2	

Possible Combinations

1. (In) Attention, BirthDate, Name, PurposeCode, ReasonCode, Requestor, SexCode, [ImageIndicator, MiscellaneousNumber, RaceCode, Reason, SocialSecurityNumber]
2. (Out) Attention, BirthDate, Name, PurposeCode, ReasonCode, Requestor, SexCode, State, [ImageIndicator, MiscellaneousNumber, RaceCode, Reason, SocialSecurityNumber]

CCHCriminalHistoryQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
PurposeCode	PurposeCode	C	1	
RaceCode	RaceCode	C	1	
Reason	Reason	O	200	Freetext description of reason inquiry was made
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateldNumber	StateldNumber	C	10	

Possible Combinations

1. (In/Out) BirthDate, Name, PurposeCode, ReasonCode, Requestor, RaceCode, SexCode, [Attention, Reason]
2. (In/Out) BirthDate, MiscellaneousNumber, Name, PurposeCode, ReasonCode, Requestor, RaceCode, SexCode, [Attention, Reason]
3. (In/Out) BirthDate, Name, PurposeCode, ReasonCode, Requestor, RaceCode, SexCode, SocialSecurityNumber, [Attention, Reason]
4. (In/Out) Name, PurposeCode, ReasonCode, Requestor, SocialSecurityNumber, [Attention, Reason]
5. (In/Out) MiscellaneousNumber, Name, PurposeCode, ReasonCode, Requestor, [Attention, Reason]
6. (In/Out) PurposeCode, ReasonCode, Requestor, StateldNumber, [Attention, Name, Reason]
7. (In/Out) FBINumber, PurposeCode, ReasonCode, Requestor, [Attention, Name, Reason]

CCHCriminalHistoryQRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	30	
AddressStreet	AddressStreet	O	30	
AddressZipCode	AddressZipCode	O	9	
Attention	Attention	M	30	
BuildingName	BuildingName	O	30	
DepartmentName	DepartmentName	O	30	
FBINumber	FBINumber	C	10	
PurposeCode	PurposeCode	M	1	
Reason	Reason	O	200	Freetext description of reason inquiry was made
Reason Code	ReasonCode	M	3	See Definition and Usage above

Requestor Initials	Requestor	M	3	See Definition and Usage above
StateIdNumber	StateIdNumber	C	10	
Name	Name	O	30	

Possible Combinations

1. (In/Out) Attention, FBINumber, PurposeCode, ReasonCode, Requestor, [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName, Name, Reason]
2. (In/Out) Attention, PurposeCode, ReasonCode, Requestor, StateIdNumber, [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName, Name, Reason]

CCHCriminalHistoryQWIQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
EnhancedNameSearchIndicator	EnhancedNameSearchIndicator	O	1	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	
ImageIndicator	ImageIndicator	O	1	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
PurposeCode	PurposeCode	C	1	
RaceCode	RaceCode	C	1	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	

Possible Combinations

1. (In/Out) BirthDate, MiscellaneousNumber, Name, PurposeCode, ReasonCode, Requestor, RaceCode, SexCode, [Attention, EnhancedNameSearchIndicator, ExpandedBirthDateSearchCode, ImageIndicator, RelatedHitSearchIndicator]
2. (In/Out) BirthDate, Name, PurposeCode, ReasonCode, Requestor, RaceCode, SexCode, [Attention, EnhancedNameSearchIndicator, ExpandedBirthDateSearchCode, ImageIndicator, RelatedHitSearchIndicator]
3. (In/Out) BirthDate, Name, PurposeCode, ReasonCode, Requestor, RaceCode, SexCode, SocialSecurityNumber, [Attention, EnhancedNameSearchIndicator, ExpandedBirthDateSearchCode, ImageIndicator, RelatedHitSearchIndicator]
4. (In/Out) MiscellaneousNumber, Name, PurposeCode, ReasonCode, Requestor, [Attention, EnhancedNameSearchIndicator, ImageIndicator, RelatedHitSearchIndicator]
5. (In/Out) Name, PurposeCode, ReasonCode, Requestor, SocialSecurityNumber, [Attention, EnhancedNameSearchIndicator, ImageIndicator, RelatedHitSearchIndicator]

CCHCriminalHistoryZRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	30	
AddressStreet	AddressStreet	O	30	
AddressZipCode	AddressZipCode	O	9	
Attention	Attention	M	30	
BuildingName	BuildingName	O	30	
DepartmentName	DepartmentName	O	30	
FBINumber	FBINumber	C	10	
PurposeCode	PurposeCode	M	1	
Reason Code	ReasonCode	M	3	See Definition and Usage above

Requestor Initials	Requestor	M	3	See Definition and Usage above
StateIdNumber	StateIdNumber	C	10	
Name	Name	O	30	

Possible Combinations

1. (In/Out) Attention, FBINumber, PurposeCode, ReasonCode, Requestor, [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName, Name]
2. (In/Out) Attention, PurposeCode, ReasonCode, Requestor, StateIdNumber, [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName, Name]

Wanted Missing Person Entry (WMPE)

WMPEDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [MontanaSpecificIndicator]

WMPEDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DentalCharacteristics	DentalCharacteristics	M	319	See NCIC Code Manual
DentalModelsAvailableIndicator	DentalModelsAvailableIndicator	M	1	Y, N
DentalXraysAvailableIndicator	DentalXraysAvailableIndicator	M	1	Y, N
DentistRemarks	DentistRemarks	O	50	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) DentalCharacteristics, DentalModelsAvailableIndicator, DentalXraysAvailableIndicator, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor [DentistRemarks, MontanaSpecificIndicator]

WMPEDataModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DentalCharacteristics	DentalCharacteristics	O	319	See NCIC Code Manual
DentalModelsAvailableIndicator	DentalModelsAvailableIndicator	O	1	Y, N
DentalXraysAvailableIndicator	DentalXraysAvailableIndicator	O	1	Y, N
DentistRemarks	DentistRemarks	O	50	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above

NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out, NCICNumber, OriginatingAgencyCaseNumber, [DentistRemarks, DentalCharacteristics, DentalModelsAvailableIndicator, OriginatingAgencyORI, DentalXraysAvailableIndicator, MontanaSpecificIndicator, ReasonCode, Requestor])

WMPEMissingPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, ReasonCode, Requestor, [MontanaSpecificIndicator, PersonRecordRemovalReason]
2. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI, ReasonCode, Requestor, [MontanaSpecificIndicator, PersonRecordRemovalReason]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, ReasonCode, Requestor, [MontanaSpecificIndicator, PersonRecordRemovalReason]

WMPEMissingPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
HitResultsIndicator	HitResultsIndicator	O	2	1-9, See NCIC Code Manual for description
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
Reason Code	ReasonCode	M	3	See Definition and Usage above
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyORI	RecoveringAgencyORI	O	9	

Requestor Initials	Requestor	M	3	See Definition and Usage above
--------------------	-----------	---	---	--------------------------------

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI , ReasonCode, Requestor, [MontanaSpecificIndicator, RecoveringAgencyCaseNumber, RecoveringAgencyORI]
2. (In/Out) Name, NCICNumber, ClearDate, OriginatingAgencyORI , ReasonCode, Requestor, [MontanaSpecificIndicator, RecoveringAgencyCaseNumber, RecoveringAgencyORI]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI , ReasonCode, Requestor, [MontanaSpecificIndicator, RecoveringAgencyCaseNumber, RecoveringAgencyORI]

WMPEMissingPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyXRayCode	BodyXRayCode	O	1	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	See NCIC Code Manual
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EmancipationDate	EmancipationDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FBI Number	FBI Number	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintIndicator	FootprintIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LastContactDate	LastContactDate	M	8	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
MissingPersonCircumstanceCode	MissingPersonCircumstanceCode	O	1	See NCIC Code Manual
MissingPersonCode	MissingPersonCode	M	2	See NCIC Code Manual
MissingPersonEntryType	MissingPersonEntryType	M	1	D – Disability E – Endangered I – Involuntary J – Emancipated Juvenile V – Catastrophe Victim O – Other

MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	M	30	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	M	1	See NCIC Code Manual
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarMarkTattooCode	ScarMarkTattooCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, BirthDate , ReasonCode, Requestor, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, FBI Number , ReasonCode, Requestor, [Any optional fields]
3. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, MiscellaneousNumber , ReasonCode, Requestor, [Any optional fields]
4. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, SocialSecurityNumber , ReasonCode, Requestor, [Any optional fields]
5. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear , ReasonCode, Requestor, [Any optional fields]
6. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, LicensePlateYear , ReasonCode, Requestor, [Any optional fields]
7. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate,

- OriginatingAgencyCaseNumber, VehicleIdentificationNumber, VehicleMakeCode, VehicleYear, VehicleStyleCode , ReasonCode, Requestor, [Any optional fields]
8. (In/Out) OriginatingAgencyORI, MissingPersonEntryType = J, Name, SexCode, RaceCode, BirthDate, EmancipationDate, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber , ReasonCode, Requestor, [Any optional fields]

WMPEMissingPersonLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
DispositionCode	DispositionCode	M	4	
HitResultsIndicator	HitResultsIndicator	O	2	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
Reason Code	ReasonCode	M	3	See Definition and Usage above
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, RecoveryDate, DispositionCode, OriginatingAgencyORI , ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, RecoveryDate, DispositionCode, OriginatingAgencyORI , ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, RecoveryDate, DispositionCode, OriginatingAgencyORI , ReasonCode, Requestor, [Any optional fields]

WMPEMissingPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	
BloodTypeCode	BloodTypeCode	O	5	
BodyXRayCode	BodyXRayCode	O	1	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	
CircumcisionCode	CircumcisionCode	O	1	
CitizenshipCode	CitizenshipCode	O	2	
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	
DNAIndicator	DNAIndicator	O	1	
DNALocation	DNALocation	O	250	
EmancipationDate	EmancipationDate	O	8	
EthnicityCode	EthnicityCode	O	1	

EyeColorCode	EyeColorCode	O	3	
FBI Number	FBI Number	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	
FootprintIndicator	FootprintIndicator	O	1	
HairColorCode	HairColorCode	O	3	
Height	Height	O	3	
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	
LastContactDate	LastContactDate	O	8	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	O	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
MissingPersonCircumstanceCode	MissingPersonCircumstanceCode	O	1	
MissingPersonCode	MissingPersonCode	O	2	
ModifiedMessageKey	ModifiedMessageKey	O	6	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	O	1	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarMarkTattooCode	ScarMarkTattooCode	O	10	
SexCode	SexCode	O	1	
SkinToneCode	SkinToneCode	O	3	
SocialSecurityNumber	SocialSecurityNumber	O	9	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	
VehicleStyleCode	VehicleStyleCode	O	2	
VehicleYear	VehicleYear	O	4	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPEMissingPersonPersonWithInformationCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	M	30	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI , ReasonCode, Requestor, [MontanaSpecificIndicator]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI , ReasonCode, Requestor, [MontanaSpecificIndicator]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI , ReasonCode, Requestor, [MontanaSpecificIndicator]

WMPEMissingPersonPersonWithInformationEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	M	500	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) Name, NCICNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
4. (In/Out) Name, NCICNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
5. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
6. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPERMissingPersonPersonWithInformationModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	M	30	
PersonWithInformationName2	PersonWithInformationName2	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPERMissingPersonPWISupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	M	30	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPERMissingPersonPWISupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	M	30	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
----------------------	----------------------	---	---	--

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPEMissingPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual.

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPEMissingPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual.

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPEProtectionOrderCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Protection Order
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, ProtectionOrderNumber, CancellationDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPEProtectionOrderClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

ClearDate	ClearDate	M	8	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Protection Order
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, ProtectionOrderNumber, ClearDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) Name, NCICNumber, ClearDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPEProtectionOrderEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
BradyIndicator	BradyIndicator	O	1	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExpirationDate	ExpirationDate	M	8	
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IssueDate	IssueDate	M	8	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Protection Order
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	

MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	O	30	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	C	8	
ProtectedPersonName	ProtectedPersonName	C	30	
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	C	9	
ProtectionOrderConditionsCode	ProtectionOrderConditionsCode	M	2	See NCIC Code Manual
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
RaceCode	RaceCode	M	1	See NCIC Code Manual
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	
ServiceCode	ServiceCode	O	1	See NCIC Code Manual
ServiceDate	ServiceDate	O	8	
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, BirthDate, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, FBINumber, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, MiscellaneousNumber, ReasonCode, Requestor, [Any optional fields]
4. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, SocialSecurityNumber, ReasonCode, Requestor, [Any optional fields]
5. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, ReasonCode, Requestor, [Any optional fields]

6. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, ReasonCode, Requestor, [Any optional fields]
7. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, ReasonCode, Requestor, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]
8. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, ProtectedPersonName, ProtectedPersonSocialSecurityNumber, ReasonCode, Requestor, [Any optional fields]
9. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, ProtectedPersonName, ProtectedPersonBirthDate, ReasonCode, Requestor, [Any optional fields]
10. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, BirthDate, ReasonCode, Requestor, [Any optional fields]
11. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, FBINumber, ReasonCode, Requestor, [Any optional fields]
12. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, MiscellaneousNumber, ReasonCode, Requestor, [Any optional fields]
13. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, SocialSecurityNumber, ReasonCode, Requestor, [Any optional fields]
14. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, ReasonCode, Requestor, [Any optional fields]
15. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, ReasonCode, Requestor, [Any optional fields]
16. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, ReasonCode, Requestor, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]
17. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, ProtectedPersonName, ProtectedPersonSocialSecurityNumber, ReasonCode, Requestor, [Any optional fields]
18. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, ProtectedPersonName, ProtectedPersonBirthDate, ReasonCode, Requestor, [Any optional fields]

WMPEProtectionOrderModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
BradyIndicator	BradyIndicator	O	1	See NCIC Code Manual

CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExpirationDate	ExpirationDate	O	8	
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBI Number	FBI Number	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IssueDate	IssueDate	O	8	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Protection Order
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	6	EPO ETO EPOC ETOC M* can be prepended to indicate MT specific
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	
ProtectedPersonName	ProtectedPersonName	O	30	
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	
ProtectionOrderConditionsCode	ProtectionOrderConditionsCode	O	2	See NCIC Code Manual
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
ProtectionOrderNumber2	ProtectionOrderNumber2	O	15	
RaceCode	RaceCode	O	1	See NCIC Code Manual

Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
ServiceCode	ServiceCode	O	1	
ServiceDate	ServiceDate	O	8	
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, ProtectionOrderNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPEProtectionOrderSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should

				use the XML tag name with the number 2-9 appended.
LicensePlateExpirationYear	LicensePlateExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonName	ProtectedPersonName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should

				use the XML tag name with the number 2-9 appended.
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderConditionCode	ProtectionOrderConditionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderNumber	ProtectionOrderNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPEProtectionOrderSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateExpirationYear	LicensePlateExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	9 fields are supported. Additional identifiers should

				use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonName	ProtectedPersonName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderConditionCode	ProtectionOrderConditionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderNumber	ProtectionOrderNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPESexOffenderCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPESexOffenderClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, ClearDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPESexOffenderEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	M	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	M	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BoatColorCode	BoatColorCode	O	7	See NCIC Code Manual
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual
BoatHullNumber	BoatHullNumber	O	20	
BoatHullShapeCode	BoatHullShapeCode	O	2	
BoatLength	BoatLength	O	2	See NCIC Code Manual
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual
BoatModelName	BoatModelName	O	20	
BoatModelYear	BoatModelYear	O	4	
BoatName	BoatName	O	20	
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	
ConvictionDate	ConvictionDate	M	8	
ConvictionOffenseCode	ConvictionOffenseCode	M	4	See NCIC Code Manual
CrimeLocation	CrimeLocation	O	2	See NCIC Code Manual, State Code
DNALocation	DNALocation	O	250	
DNAIndicator	DNAIndicator	O	1	Blank, N, Y
EmailAddress	EmailAddress	O	80	

EmployerName	EmployerName	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
HomePort	HomePort	O	20	
InternetId	InternetId	O	80	
JuvenileOffenderIndicator	JuvenileOffenderIndicator	O	1	Blank, N, Y
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	C	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	M	30	
NCICNumber	NCICNumber	O	10	
Occupation	Occupation	O	80	
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	
RaceCode	RaceCode	M	1	See NCIC Code Manual
Reason Code	ReasonCode	M	3	See Definition and Usage above
RegistrationEndDate	RegistrationEndDate	M	8	
RegistrationNumber	RegistrationNumber	O	8	
RegistrationStartDate	RegistrationStartDate	M	8	
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual
Requestor Initials	Requestor	M	3	See Definition and Usage above
ResidenceBeginDate	ResidenceBeginDate	O	8	
ResidenceEndDate	ResidenceEndDate	O	8	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SchoolName	SchoolName	O	80	
SexCode	SexCode	M	1	See NCIC Code Manual
SexOffenderTier	SexOffenderTier	O	1	See NCIC Code Manual
SexualPredatorIndicator	SexualPredatorIndicator	O	1	Blank, N, Y
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
StateIdNumber	StateIdNumber	O	10	
TelephoneNumber	TelephoneNumber	O	12	
TelephoneType	TelephoneType	C	1	See NCIC Code Manual
RegistrationExpirationYear	RegistrationExpirationYear	O	2	

ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleOwnershipCode	VehicleOwnershipCode	O	2	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
VictimAge	VictimAge	O	2	
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) Name, SexCode, RaceCode, BirthDate, RegistrationStartDate, RegistrationEndDate, Height, Weight, HairColorCode, EyeColorCode, ConvictionOffenseCode, ConvictionDate, OriginatingAgencyCaseNumber, AddressStateCode, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPESexOffenderModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BoatColorCode	BoatColorCode	O	7	See NCIC Code Manual
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual
BoatHullNumber	BoatHullNumber	O	20	
BoatHullShapeCode	BoatHullShapeCode	O	2	
BoatLength	BoatLength	O	2	See NCIC Code Manual
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual
BoatModelName	BoatModelName	O	20	
BoatModelYear	BoatModelYear	O	4	
BoatName	BoatName	O	20	
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	
ConvictionDate	ConvictionDate	O	8	
ConvictionOffenseCode	ConvictionOffenseCode	O	4	See NCIC Code Manual
CrimeLocation	CrimeLocation	O	2	See NCIC Code Manual, State Code
DNALocation	DNALocation	O	250	
DNAIndicator	DNAIndicator	O	1	Blank, N, Y

EmailAddress	EmailAddress	O	80	
EmployerName	EmployerName	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
HomePort	HomePort	O	20	
InternetId	InternetId	O	80	
JuvenileOffenderIndicator	JuvenileOffenderIndicator	O	1	Blank, N, Y
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	6	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	O	10	
Occupation	Occupation	O	80	
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
Reason Code	ReasonCode	M	3	See Definition and Usage above
RegistrationEndDate	RegistrationEndDate	O	8	
RegistrationNumber	RegistrationNumber	O	8	
RegistrationStartDate	RegistrationStartDate	O	8	
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual
Requestor Initials	Requestor	M	3	See Definition and Usage above
ResidenceBeginDate	ResidenceBeginDate	O	8	
ResidenceEndDate	ResidenceEndDate	O	8	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SchoolName	SchoolName	O	80	
SexCode	SexCode	O	1	See NCIC Code Manual
SexOffenderTier	SexOffenderTier	O	1	See NCIC Code Manual
SexualPredatorIndicator	SexualPredatorIndicator	O	1	Blank, N, Y
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual

SocialSecurityNumber	SocialSecurityNumber	O	9	
StateIdNumber	StateIdNumber	O	10	
TelephoneNumber	TelephoneNumber	O	12	
TelephoneType	TelephoneType	O	1	See NCIC Code Manual
RegistrationExpirationYear	RegistrationExpirationYear	O	2	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleOwnershipCode	VehicleOwnershipCode	O	2	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
VictimAge	VictimAge	O	2	
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPESexOffenderSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullNumber	BoatHullNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullShapeCode	BoatHullShapeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatLength	BoatLength	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelName	BoatModelName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

BoatModelYear	BoatModelYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatName	BoatName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
EmailAddress	EmailAddress	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Employer	Employer	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
InternetId	InternetId	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
Occupation	Occupation	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProfessionalLicenseNumberType	ProfessionalLicenseNumberType	O	80	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Reason Code	ReasonCode	M	3	See Definition and Usage above
RegistrationExpirationYear	RegistrationExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationNumber	RegistrationNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SchoolName	SchoolName	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
StateldNumber	StateldNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumber	TelephoneNumber	O	12	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumberType	TelephoneNumberType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleOwnershipCode	VehicleOwnershipCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimAge	VictimAge	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPESexOffenderSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullNumber	BoatHullNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullShapeCode	BoatHullShapeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatLength	BoatLength	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelName	BoatModelName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelYear	BoatModelYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatName	BoatName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
EmailAddress	EmailAddress	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Employer	Employer	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
InternetId	InternetId	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	

Occupation	Occupation	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProfessionalLicenseNumberType	ProfessionalLicenseNumberType	O	80	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Reason Code	ReasonCode	M	3	See Definition and Usage above
RegistrationExpirationYear	RegistrationExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationNumber	RegistrationNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SchoolName	SchoolName	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
StateldNumber	StateldNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumber	TelephoneNumber	O	12	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumberType	TelephoneNumberType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleOwnershipCode	VehicleOwnershipCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimAge	VictimAge	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPESupervisedReleaseCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

2. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPESupervisedReleaseClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, ClearDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPESupervisedReleaseEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArrestDate	ArrestDate	O	8	
ArrestingAgencyORI	ArrestingAgencyORI	O	9	
BirthDate	BirthDate	C	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EmailAddress	EmailAddress	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	
FraudulentBirthDate	FraudulentBirthDate	O	8	
FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	
FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	O	20	
FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	O	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	O	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
IncarcerationPlace	IncarcerationPlace	O	50	
LicensePlateNumber	LicensePlateNumber	C	10	

LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	M	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	M	1	See NCIC Code Manual
Reason Code	ReasonCode	M	3	See Definition and Usage above
ReleaseDate	ReleaseDate	O	8	
ReleaseLocation	ReleaseLocation	O	50	
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SentencingCourtORI	SentencingCourtORI	O	9	
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
SupervisingOfficerName	SupervisingOfficerName	M	30	
SupervisingOfficerTelephone	SupervisingOfficerTelephone	M	12	
SupervisionStartDate	SupervisionStartDate	M	8	
SupervisionExpirationDate	SupervisionExpirationDate	M	8	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
WarrantCourtORI	WarrantCourtORI	O	9	
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, ReasonCode, Requestor, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, BirthDate, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, ReasonCode, Requestor, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, FBINumber, [Any optional fields]
3. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, ReasonCode, Requestor,

- SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, MiscellaneousNumber, [Any optional fields]
4. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, ReasonCode, Requestor, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, SocialSecurityNumber, [Any optional fields]
 5. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, ReasonCode, Requestor, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
 6. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, ReasonCode, Requestor, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, [Any optional fields]
 7. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, ReasonCode, Requestor, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]

WMPESupervisedReleaseFraudulentDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPESupervisedReleaseFraudulentDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPESupervisedReleaseModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArrestDate	ArrestDate	O	8	
ArrestingAgencyORI	ArrestingAgencyORI	O	9	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual

CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EmailAddress	EmailAddress	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FraudulentBirthDate	FraudulentBirthDate	O	8	
FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	
FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	O	20	
FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	O	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	O	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IncarcerationPlace	IncarcerationPlace	O	50	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	6	EC EC-C M* can be prepended to indicate MT specific
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProbationParoleExpirationDate	ProbationParoleExpirationDate	O	8	
RaceCode	RaceCode	O	1	See NCIC Code Manual
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ReleaseLocation	ReleaseLocation	O	50	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SentencingCourtORI	SentencingCourtORI	O	9	

SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
SupervisingOfficerName	SupervisingOfficerName	O	30	
SupervisingOfficerTelephone	SupervisingOfficerTelephone	O	12	
SupervisionStartDate	SupervisionStartDate	O	8	
SupervisionReleaseDate	SupervisionReleaseDate	O	5	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
WarrantCourtORI	WarrantCourtORI	O	9	
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPESupervisedReleaseSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPESupervisedReleaseSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPEUnidentifiedPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
RecordRemovalReason	RecordRemovalReason	O	21	
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [MontanaSpecificIndicator, RecordRemovalReason]

WMPEUnidentifiedPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
RecordRemovalReason	RecordRemovalReason	O	21	
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [MontanaSpecificIndicator, RecordRemovalReason]

WMPEUnidentifiedPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyFoundDate	BodyFoundDate	M	8	
BodyPartsStatusCode	BodyPartsStatusCode	C	15	See NCIC Code Manual
CauseOfDeath	CauseOfDeath	O	30	
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EstimatedBirthYear	EstimatedBirthYear	C	9	
EstimatedDeathDate	EstimatedDeathDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintAvailableIndicator	FootprintAvailableIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	7	Range of values Ex. 000-000
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MedicalExaminerAgencyAndCaseNumber	MedicalExaminerAgencyAndCaseNumber	O	50	
MedicalExaminerLocality	MedicalExaminerLocality	O	30	
MedicalExaminerTelephoneNumber	MedicalExaminerTelephoneNumber	O	12	
MessageKeyModifier	MessageKeyModifier	M	1	D – Deceased L – Living V – Catastrophe Victim
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above

NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	M	1	See NCIC Code Manual
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
Weight	Weight	M	7	Range of values Ex. 000-000
XraysAvailableIndicator	XraysAvailableIndicator	M	1	Blank, Y

Possible Combinations

1. (In/Out) MessageKeyModifier=**D** or **V**, BodyPartsStatusCode, SexCode, RaceCode, EstimatedDeathDate, BodyFoundDate, Height, Weight, EyeColorCode, HairColorCode, OriginatingAgencyCaseNumber, XraysAvailableIndicator, CauseOfDeath, OriginatingAgencyORI, ReasonCode, Requestor, [BloodTypeCode, CircumcisionCode, CorrectiveVisionPerscriptionCode, DNAIndicator, DNALocation, EstimatedBirthYear, EthnicityCode, FingerprintClassificationCode, FootprintAvailableIndicator, JewelryDescription, JewelryTypeCode, LinkageAgencyIdentifier, LinkageCaseNumber, MedicalExaminerAgencyAndCaseNumber, MedicalExaminerLocality, MedicalExaminerTelephoneNumber, MiscellaneousDescriptiveText, MontanaSpecificIndicator, NotifyOriginatingAgencyIndicator, ScarsMarksTattoosCode]
2. (In/Out) MessageKeyModifier=**L**, SexCode, RaceCode, BodyFoundDate, Height, Weight, EyeColorCode, HairColorCode, FingerprintClassificationCode, OriginatingAgencyCaseNumber, XraysAvailableIndicator, OriginatingAgencyORI, , ReasonCode, Requestor, [BloodTypeCode, CircumcisionCode, CorrectiveVisionPerscriptionCode, DNAIndicator, DNALocation, EstimatedBirthYear, EthnicityCode, FootprintAvailableIndicator, JewelryDescription, JewelryTypeCode, LinkageAgencyIdentifier, LinkageCaseNumber, MedicalExaminerAgencyAndCaseNumber, MedicalExaminerLocality, MedicalExaminerTelephoneNumber, MiscellaneousDescriptiveText, MontanaSpecificIndicator, NotifyOriginatingAgencyIndicator, ScarsMarksTattoosCode]

WMPEUnidentifiedPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyFoundDate	BodyFoundDate	O	8	
BodyPartsStatusCode	BodyPartsStatusCode	O	15	See NCIC Code Manual
CauseOfDeath	CauseOfDeath	O	30	
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EstimatedBirthYear	EstimatedBirthYear	O	9	
EstimatedDeathDate	EstimatedDeathDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintAvailableIndicator	FootprintAvailableIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	

JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MedicalExaminerAgencyAndCaseNumber	MedicalExaminerAgencyAndCaseNumber	O	50	
MedicalExaminerLocality	MedicalExaminerLocality	O	30	
MedicalExaminerTelephoneNumber	MedicalExaminerTelephoneNumber	O	12	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
ModifiedMessageKey	ModifiedMessageKey	O	6	EUD - Deceased EUL - Living EUV – Catastrophe Victim M* can be prepended to indicate MT specific
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
NCICNumber	NCICNumber	M	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	O	1	See NCIC Code Manual
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
ValidatorName	ValidatorName	O	30	
VisionPrescription	VisionPrescription	O	40	
Weight	Weight	O	3	
XraysAvailableIndicator	XraysAvailableIndicator	O	1	Blank, Y

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPEUnidentifiedPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
-----------------------	-----------------------	---	----	--

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [ImageNCICNumber, ImageNCICNumber2, ImageNCICNumber3, ImageNCICNumber4, ImageType, ImageType2, ImageType3, ImageType4, MontanaSpecificIndicator, ScarsMarksTattoosCode, ScarsMarksTattoosCode2, ScarsMarksTattoosCode3, ScarsMarksTattoosCode4]

WMPEUnidentifiedPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [ImageNCICNumber, ImageNCICNumber2, ImageNCICNumber3, ImageNCICNumber4, ImageType, ImageType2, ImageType3, ImageType4, MontanaSpecificIndicator, ScarsMarksTattoosCode, ScarsMarksTattoosCode2, ScarsMarksTattoosCode3, ScarsMarksTattoosCode4]

WMPEWantedPersonCancel

Field Name	XML Tag Name	MKE	M/C/O	Size	Possible Values
Cancellation Date	CancellationDate	DOC	M	8	
Message Key	MessageKeyModifier	MKE	O	1	Default to CW. See State and NCIC manuals for full definitions. XW WANTED PERSON XT TEMPORARY FELONY
Montana Specific Indicator	MontanaSpecificIndicator	MKE	O	1	Blank, Y This field will prepend the message key with "M*" for state specific transactions
Name	Name	NAM	M	30	
Originating Agency Case Number	OriginatingAgencyCaseNumber	OCA	M	20	
ORI	OriginatingAgencyORI	ORI	M	9	

Reason for Person Record Removal	PersonRecordRemovalReason	RPS	O	21	
Reason Code	ReasonCode	RSN	M	3	See Definition and Usage above
Requestor Initials	Requestor	REQ	M	3	See Definition and Usage above

Usage:

- MKE will be defaulted to “XW” if not provided. The available message keys with descriptions can be found in the NCIC Operating Manual and CJIN Interface Guide.
- Montana only entries are designated with the MontanaSpecificIndicator field (part of MKE). If sent as “Y”, the message key will be prepended with “M*” for the Montana specific key. Ex: M*XW.
- NAM and OCA are required for record identification.
- The ORI used to cancel the record must match the entry ORI

WMPEWantedPersonClear

Field Name	XML Tag Name	MFC	M/C/O	Size	Possible Values
Date of Clear	ClearDate	DCL	M	8	
Value of Recovered Contraband	ContrabandRecoveredValue	VRC	O	8	
Wanted/Missing Person Hit Results	HitResultsIndicator	HIT	O	2	See NCIC Code Manual
Message Key	MessageKey		O	1	Default to CW. See State and NCIC manuals for full definitions. CW WANTED PERSON CT TEMPORARY FELONY
Montana Specific Indicator	MontanaSpecificIndicator	MKE	O	1	Blank, Y This field will prepend the message key with “M*” for state specific transactions
Name	Name	NAM	M	30	
Number of Missing Persons Found	NumberMissingPersonsFound	NPF	O	20	
Number of Persons Apprehended	NumberPersonsApprehended	NPA	O	3	
Originating Agency Case Number	OriginatingAgencyCaseNumber	OCA	M	20	
ORI	OriginatingAgencyORI	ORI	M	9	
Value of Other Recovered Property	OtherRecoveredPropertyValue	VOR	O	8	
Person Armed Indicator	PersonArmedIndicator	PAR	O	1	Blank, Y
Reason for Person Record Removal	PersonRecordRemovalReason	RPS	O	21	
Value of Recovered Property	PropertyRecoveredValue	VNP	O	8	
Reason Code	ReasonCode	RSN	M	3	See Definition and Usage above
Recovering Agency Case Number	RecoveringAgencyCaseNumber	RCA	O	20	
Recovering Agency ORI	RecoveringAgencyORI	RRI	O	9	
Requestor Initials	Requestor	REQ	M	3	See Definition and Usage above

Usage:

- MKE will be defaulted to “CW” if not provided. The available message keys with descriptions can be found in the NCIC Operating Manual and CJIN Interface Guide.
- Montana only entries are designated with the MontanaSpecificIndicator field (part of MKE). If sent as “Y”, the message key will be prepended with “M*” for the Montana specific key. Ex: M*CW.
- NAM and OCA are required for record identification.
- The ORI used to clear the record must match the entry ORI

WMPEWantedPersonDetainerCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	M	20	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above

Possible Combinations

1. (In/Out) Name, NCICNumber, DetainerCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [MontanaSpecificIndicator]
2. (In/Out) Name, OriginatingAgencyCaseNumber, DetainerCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [MontanaSpecificIndicator]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, DetainerCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [MontanaSpecificIndicator]

WMPEWantedPersonDetainerEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	M	20	
DetainerDate	DetainerDate	M	8	
IncarceratingAgencyORI	IncarceratingAgencyORI	M	9	
IncarcerationPlace	IncarcerationPlace	O	50	
IncarcerationStartDate	IncarcerationStartDate	O	8	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
SentenceExpirationDate	SentenceExpirationDate	O	8	

Possible Combinations

1. (In/Out) Name, NCICNumber, DetainerCaseNumber, IncarceratingAgencyORI, OriginatingAgencyORI, ReasonCode, Requestor, [IncarcerationPlace, IncarcerationStartDate, MontanaSpecificIndicator, SentenceExpirationDate]
2. (In/Out) Name, OriginatingAgencyCaseNumber, DetainerCaseNumber, IncarceratingAgencyORI, OriginatingAgencyORI, ReasonCode, Requestor,

- [IncarcerationPlace, IncarcerationStartDate, MontanaSpecificIndicator, SentenceExpirationDate]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, DetainerCaseNumber, IncarceratingAgencyORI, OriginatingAgencyORI, ReasonCode, Requestor, [IncarcerationPlace, IncarcerationStartDate, MontanaSpecificIndicator, SentenceExpirationDate]

WMPEWantedPersonDetainerModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	O	20	
DetainerDate	DetainerDate	O	8	
IncarceratingAgencyORI	IncarceratingAgencyORI	O	9	
IncarcerationPlace	IncarcerationPlace	O	50	
IncarcerationStartDate	IncarcerationStartDate	O	8	
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
SentenceExpirationDate	SentenceExpirationDate	O	8	
ValidatorName	ValidatorName	O	30	

Possible Combinations

1. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [DetainerCaseNumber, IncarceratingAgencyORI, IncarcerationPlace, MontanaSpecificIndicator, ValidatorName]
2. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [DetainerCaseNumber, IncarceratingAgencyORI, IncarcerationPlace, MontanaSpecificIndicator, ValidatorName]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [DetainerCaseNumber, IncarceratingAgencyORI, IncarcerationPlace, MontanaSpecificIndicator, ValidatorName]

WMPEWantedPersonEntry

Field Name	XML Tag Name	MFC	M/C/O	Size	Possible Values
Additional Offense	AdditionalOffenseIndicator	ADO	O	1	Blank, Y
City Name	AddressCity	CTY	O	20	
County	AddressCounty	COU	O	20	
State	AddressStateCode	STA	O	2	See NCIC Code Manual
Street Name	AddressStreetName	SNA	O	25	
Street Number	AddressStreetNumber	SNU	O	7	
Address Type	AddressType	ADD	O	2	See NCIC Code Manual
Zip Code	AddressZipCode	ZIP	O	10	
Date of Birth	BirthDate	DOB	C	8	
Place of Birth	BirthPlaceCode	POB	O	2	See NCIC Code Manual
Caution and Medical Conditions	CautionMedicalConditionsCode	CAU	O	2	See NCIC Code Manual
Citizenship	CitizenshipCode	CTZ	O	2	See NCIC Code Manual
Court ORI	CourtORI	CTI	O	9	
DNA Profile Indicator	DNAIndicator	DNA	O	1	Blank, Y

DNA Location	DNALocation	DLO	O	250	
Date of Documented Address	DocumentedAddressDate	DDA	O	8	
Date of Emancipation	EmancipationDate	DOE	C	8	
Ethnicity	EthnicityCode	ETN	O	1	See NCIC Code Manual
Extradition Limitation	ExtraditionLimitation	EXL	M	2	See NCIC Code Manual
Eye Color	EyeColorCode	EYE	O	3	See NCIC Code Manual
FBI Number	FBINumber	FBI	C	9	
Fingerprint Classification	FingerprintClassificationCode	FPC	O	20	See NCIC Code Manual
S/F BirthDate	FraudulentBirthDate	DOB	O	8	
S/F MiscellaneousNumber	FraudulentMiscellaneousNumber	MNU	O	15	
S/F Name	FraudulentName	NAM	O	30	
S/F OperatorLicenseNumber	FraudulentOperatorLicenseNumber	OLN	C	20	
S/F OperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	OLS	C	2	See NCIC Code Manual
S/F OperatorLicenseYear	FraudulentOperatorLicenseYear	OLY	C	4	
S/F SocialSecurityNumber	FraudulentSocialSecurityNumber	SSN	O	9	
Hair Color	HairColorCode	HAI	M	3	See NCIC Code Manual
Height	Height	HGT	M	3	
Warrant or Violation Date	IncidentDate	DOW DOV	M	8	
License Plate Number	LicensePlateNumber	LIC	C	10	
License Plate State	LicensePlateStateCode	LIS	C	2	See NCIC Code Manual
License Plate Year	LicensePlateYear	LIY	C	4	
License Plate Type	LicensePlateTypeCode	LIT	C	2	See NCIC Code Manual
Linking Agency Identifier	LinkageAgencyIdentifier	LKI	O	9	
Linking Case Number	LinkageCaseNumber	LKA	O	20	
Message Key	MessageKey	MKE	C	6	Default to EW. See State and NCIC manuals for full definitions. EW WANTED PERSON EW-C WANTED PERSON - CAUTION ET TEMPORARY FELONY ET-C TEMPORARY FELONY/CAUTION EWJ JUVENILE DELINQUENT EWJC JUVENILE DELINQUENT - CAUTION
Miscellaneous Descriptive Text	MiscellaneousDescriptiveText	MIS	O	500	
Miscellaneous Number	MiscellaneousNumber	MNU	C	15	
Montana Specific Indicator	MontanaSpecificIndicator	MKE	O	1	Blank, Y This field will prepend the message key with "M*" for state specific transactions.
Watch List Indicator	MontanaWatchListIndicator	WWL	M	1	Y, N
Name	Name	NAM	M	30	
Notify Originating Agency	NotifyOriginatingAgency	NOA	O	1	Blank, Y
Offense Code	OffenseCode	OFF	M	4	
Offense Description	OffenseCodeDescription	OFF	C	20	
Operator License Year	OperatorLicenseYear	OLY	C	4	
Operator License Number	OperatorLicenseNumber	OLN	C	20	

Operator License State	OperatorLicenseStateCode	OLS	C	2	See NCIC Code Manual
Original Offense Code	OriginalOffenseCode	OOC	C	4	See NCIC Code Manual
Originating Agency Case Number	OriginatingAgencyCaseNumber	OCA	M	20	
ORI	OriginatingAgencyORI	ORI	M	9	
Race Code	RaceCode	RAC	M	1	See NCIC Code Manual
Reason Code	ReasonCode	RSN	M	3	See Definition and Usage above
Requestor Initials	Requestor	REQ	M	3	See Definition and Usage above
Scars Marks Tattoos	ScarsMarksTattoosCode	SMT	O	10	See NCIC Code Manual
Sex Code	SexCode	SEX	M	1	See NCIC Code Manual
Skin Tone	SkinToneCode	SKN	O	3	See NCIC Code Manual
Social Security Number	SocialSecurityNumber	SSN	C	9	
State ID Number	StateIdNumber	SID	O	10	
Vehicle Color	VehicleColorCode	VCO	O	7	See NCIC Code Manual
Vehicle Identification Number	VehicleIdentificationNumber	VIN	C	20	
Vehicle Make	VehicleMakeCode	VMA	C	4	See NCIC Code Manual
Vehicle Make Description	VehicleMakeCodeDescription	VMA	O	20	
Vehicle Model	VehicleModelCode	VMO	O	3	See NCIC Code Manual
Vehicle Style	VehicleStyleCode	VST	C	3	See NCIC Code Manual
Vehicle Year	VehicleYear	VYR	C	4	
Warrant Number	WarrantNumber	WNO	O	15	
Weight	Weight	WGT	M	3	

Usage:

- MKE will be defaulted to “EW” if not provided. The available message keys with descriptions can be found in the NCIC Operating Manual and CJIN Interface Guide.
- Montana only entries are designated with the MontanaSpecificIndicator field (part of MKE). If sent as “Y”, the message key will be prepended with “M*” for the Montana specific key. Ex: M*EW.
- Adult Montana records require at minimum: ORI, NAM, SEX, RAC, HGT, WGT, HAI, OFF, DOW, OCA, WWL, and at least one numeric identifier: DOB; FBI; MNU; SOC; OLN with OLS and OLY; LIC with LIS, LIY, and LIT, VIN with VYR, VMA, and VST; S/F NAM and S/F DOB, S/F MNU, S/F SOC, or S/F OLN with S/F OLS and S/F OLY.
- NCIC records will additionally require EXL.
- Juvenile records will additionally require DOE and DOV
- The following fields must be entered as a set
 - OLN, OLS, and OLY
 - LIC, LIT, LIY, LIS
 - VIN, VMA, VST, VYR

WMPEWantedPersonFraudulentDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPEWantedPersonFraudulentDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	

OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPEWantedPersonLocate

Field Name	XML Tag Name	MKE	M/C/O	Size	Possible Values
Value of Recovered Contraband	ContrabandRecoveredValue	VRC	O	8	
Extradition	Extradition	EXT	M	4	See NCIC Code Manual
Wanted/Missing Person Hit Results	HitResultsIndicator	HIT	O	2	See NCIC Code Manual
Message Key	MessageKey	MKE	O	1	Default to LW. See State and NCIC manuals for full definitions. LW WANTED PERSON LT TEMPORARY FELONY
Montana Specific Indicator	MontanaSpecificIndicator	MKE	O	1	Blank, Y This field will prepend the message key with "M*" for state specific transactions
Name	Name	NAM	M	30	
Number of Missing Persons Found	NumberMissingPersonsFound	NPF	O	20	
Number of Persons Apprehended	NumberPersonsApprehended	NPA	O	3	
Originating Agency Case Number	OriginatingAgencyCaseNumber	OCA	M	20	
ORI	OriginatingAgencyORI	ORI			
Value of Other Recovered Property	OtherRecoveredPropertyValue	VOR	O	8	
Person Armed Indicator	PersonArmedIndicator	PAR	O	1	Blank, Y
Reason for Person Record Removal	PersonRecordRemovalReason	RPS	O	21	
Value of Recovered Property	PropertyRecoveredValue	VNP	O	8	
Reason Code	ReasonCode	RSN	M	3	See Definition and Usage above
Recovering Agency Case Number	RecoveringAgencyCaseNumber	RCA	O	20	
RecoveryDate	RecoveryDate	DOR	M	8	
Requestor Initials	Requestor	REQ	M	3	See Definition and Usage above

Usage:

- MKE will be defaulted to "LW" if not provided. The available message keys with descriptions can be found in the NCIC Operating Manual and CJIN Interface Guide.

- Montana only entries are designated with the MontanaSpecificIndicator field (part of MKE). If sent as “Y”, the message key will be prepended with “M*” for the Montana specific key. Ex: M***LW**.
- A Montana wanted person record modification requires NAM and OCA for identification.
- NCIC records can be identified with NAM and NIC, NAM and OCA, or NIC and OCA.
- The ORI must be that of the locating agency, not the entering agency.

WMPEWantedPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	MFC	M/C/O	Size	Possible Values
Additional Offense	AdditionalOffenseIndicator	ADO	O	1	Blank, Y
City Name	AddressCity	CTY	O	20	
County	AddressCounty	COU	O	20	
State	AddressStateCode	STA	O	2	See NCIC Code Manual
Street Name	AddressStreetName	SNA	O	25	
Street Number	AddressStreetNumber	SNU	O	7	
Address Type	AddressType	ADD	O	2	See NCIC Code Manual
Zip Code	AddressZipCode	ZIP	O	10	
Date of Birth	BirthDate	DOB	O	8	
Place of Birth	BirthPlaceCode	POB	O	2	See NCIC Code Manual
Caution and Medical Conditions	CautionMedicalConditionsCode	CAU	O	2	See NCIC Code Manual
Citizenship	CitizenshipCode	CTZ	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	LIC-VCO	O	1	Blank, Y
Court ORI	CourtORI	CTI	O	9	
DNA Profile Indicator	DNAIndicator	DNA	O	1	
DNA Location	DNALocation	DLO	O	250	Blank, Y
Date of Documented Address	DocumentedAddressDate	DDA	O	8	
Date of Emancipation	EmancipationDate	DOE	O	8	
Ethnicity	EthnicityCode	ETN	O	1	See NCIC Code Manual
Extradition Limitation	ExtraditionLimitation	EXL	O	2	See NCIC Code Manual
Eye Color	EyeColorCode	EYE	O	3	See NCIC Code Manual
FBI Number	FBINumber	FBI	O	9	
Fingerprint Classification	FingerprintClassificationCode	FPC	O	20	See NCIC Code Manual
Hair Color	HairColorCode	HAI	O	3	See NCIC Code Manual
Height	Height	HGT	O	3	
Warrant Date	WarrantDate	DOW	O	8	
Violation Date	ViolationDate	DOV	O	8	
License Plate Number	LicensePlateNumber	LIC	O	10	
License Plate State	LicensePlateStateCode	LIS	O	2	
License Plate Year	LicensePlateTypeCode	LIY	O	2	See NCIC Code Manual
License Plate Type	LicensePlateYear	LIT	O	4	See NCIC Code Manual
Linking Agency Identifier	LinkageAgencyIdentifier	LKI	O	9	
Linking Case Number	LinkageCaseNumber	LKA	O	20	
Message Key	MessageKey	MKE	O	1	Default to MW. See State and NCIC manuals for full definitions. MW WANTED PERSON

					MT TEMPORARY FELONY
Miscellaneous Descriptive Text	MiscellaneousDescriptiveText	MIS	O	500	
Miscellaneous Number	MiscellaneousNumber	MNU	O	15	
Modified Entry Key	ModifiedMessageKey	MKE	O	6	See State and NCIC manuals for full definitions. EW WANTED PERSON EW-C WANTED PERSON - CAUTION ET TEMPORARY FELONY ET-C TEMPORARY FELONY/CAUTION EWJ JUVENILE DELINQUENT EWJC JUVENILE DELINQUENT - CAUTION
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	ORI	O	9	
MontanaSpecificIndicator	MontanaSpecificIndicator		O	1	Blank, Y This field will prepend the message key with "M*" for state specific transactions.
Watch List Indicator	MontanaWatchListIndicator	WWL	O	1	Y,N
Name	Name	NAM	C	30	
Modified Name	Name2	NAM	O	30	
NCIC Number	NCICNumber	NIC	C	10	
Notify Originating Agency	NotifyOriginatingAgency	NOA	O	1	Blank, Y
Offense Code	OffenseCode	OFF	O	4	See NCIC Code Manual
Offense Description	OffenseCodeDescription	OFF	O	20	
Operator License Number	OperatorLicenseNumber	OLN	O	20	
Operator License State	OperatorLicenseStateCode	OLS	O	2	
Operator License Year	OperatorLicenseYear	OLY	O	4	See NCIC Code Manual
Original Offense Code	OriginalOffenseCode	OOC	O	4	See NCIC Code Manual
Record OCA	OriginatingAgencyCaseNumber	OCA	C	20	
Modified OCA	OriginatingAgencyCaseNumber2	OCA	O	20	
ORI	OriginatingAgencyORI	ORI	M	9	
Race Code	RaceCode	RAC	O	1	See NCIC Code Manual
Reason Code	ReasonCode	RSN	M	3	See Definition and Usage above
Requestor Initials	Requestor	REQ	M	3	See Definition and Usage above
Scars Marks Tattoos	ScarsMarksTattoosCode	SMT	O	10	See NCIC Code Manual
Sex Code	SexCode	SEX	O	1	See NCIC Code Manual
Skin Tone	SkinToneCode	SKN	O	3	See NCIC Code Manual
Social Security Number	SocialSecurityNumber	SSN	O	9	
Validator Name	ValidatorName	VLN	O	30	
Vehicle Color	VehicleColorCode	VCO	O	7	See NCIC Code Manual
Vehicle Identification Number	VehicleIdentificationNumber	VIN	O	20	
Vehicle Make	VehicleMakeCode	VMA	O	4	See NCIC Code Manual
Vehicle Make Description	VehicleMakeCodeDescription	VMA	O	20	
Vehicle Model	VehicleModelCode	VMO	O	3	See NCIC Code Manual
Vehicle Style	VehicleStyleCode	VST	O	3	See NCIC Code Manual
Vehicle Year	VehicleYear	VYR	O	4	
Warrant Number	WarrantNumber	WNO	O	15	

Weight	Weight	WGT	O	3	
--------	--------	-----	---	---	--

Usage:

- MKE will be defaulted to “MW” if not provided. The available message keys with descriptions can be found in the NCIC Operating Manual and CJIN Interface Guide.
- Montana only entries are designated with the MontanaSpecificIndicator field (part of MKE). If sent as “Y”, the message key will be prepended with “M*” for the Montana specific key. Ex: M*MW.
- A Montana wanted person record modification requires NAM and OCA for identification.
- NCIC records can be identified with NAM and NIC, NAM and OCA, or NIC and OCA.
- The following fields must be entered as a set
 - OLN, OLS, and OLY
 - LIC, LIT, LIY, LIS
 - VIN, VMA, VST, VYR

WMPEWantedPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressCounty	AddressCounty	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetName	AddressStreetName	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetNumber	AddressStreetNumber	O	7	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressTypeCode	AddressTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressZipCode	AddressZipCode	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
StateldNumber	StateldNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

WMPEWantedPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressCounty	AddressCounty	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetName	AddressStreetName	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetNumber	AddressStreetNumber	O	7	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressTypeCode	AddressTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressZipCode	AddressZipCode	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MontanaSpecificIndicator	MontanaSpecificIndicator	O	1	Y or BLANK. See Definition and Usage above
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
StateIdNumber	StateIdNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

*Operator License fields must be entered as a set.

*License Plate fields must be entered as a set.

*VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, and VehicleStyleCode must be entered as a set.

*Address fields must be entered as a set.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, ReasonCode, Requestor, [Any optional fields]

Wanted Missing Person Inquiries (WMP-I)

WMPIMissingPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	C	2	
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Y
EyeColorCode	EyeColorCode	C	3	
HairColorCode	HairColorCode	C	3	
Height	Height	C	3	
ImageIndicator	ImageIndicator	O	1	Y
Name	Name	O	30	
RaceCode	RaceCode	C	1	A, I, B, W, U

ReasonCode	ReasonCode	O	3	See Definition and Usage above
Requestor	Requestor	O	3	See Definition and Usage above
SexCode	SexCode	C	1	F, M, U
Weight	Weight	C	3	

Possible Combinations

1. (In/Out) Age, EyeColorCode, HairColorCode, Height, RaceCode, SexCode, Weight, [Name, ExpandedNameSearchCode, ImageIndicator, ReasonCode, Requestor]

WMPIProtectionOrderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	10	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Y
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Y
FBINumber	FBINumber	O	9	
ImageIndicator	ImageIndicator	O	1	Y
LicensePlateNumber	LicensePlateNumber	O	10	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	O	30	
NCICNumber	NCICNumber	O	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	
ProtectionOrderNumber	ProtectionOrderNumber	O	15	
RaceCode	RaceCode	O	1	A, I, B, W, U
ReasonCode	ReasonCode	O	3	See Definition and Usage above
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Y
Requestor	Requestor	O	3	See Definition and Usage above
SexCode	SexCode	O	1	F, M, U
SocialSecurityNumber	SocialSecurityNumber	O	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	

Possible Combinations

1. (In/Out) Name, BirthDate, [ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, MiscellaneousNumber, OperatorLicenseNumber, RaceCode, ReasonCode, RelatedHitSearchIndicator, Requestor, SexCode, SocialSecurityNumber, VehicleIdentificationNumber]
2. (In/Out) Name, FBINumber, [BirthDate, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, LicensePlateNumber, MiscellaneousNumber, OperatorLicenseNumber, RaceCode, ReasonCode, RelatedHitSearchIndicator, Requestor, SexCode, SocialSecurityNumber, VehicleIdentificationNumber]
3. (In/Out) Name, MiscellaneousNumber, [BirthDate, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, OperatorLicenseNumber, RaceCode, ReasonCode, RelatedHitSearchIndicator, Requestor, SexCode, SocialSecurityNumber, VehicleIdentificationNumber]
4. (In/Out) Name, SocialSecurityNumber, [BirthDate, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, MiscellaneousNumber, OperatorLicenseNumber, RaceCode, ReasonCode, RelatedHitSearchIndicator, Requestor, SexCode, VehicleIdentificationNumber]

5. (In/Out) Name, OperatorLicenseNumber, [BirthDate ,ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, MiscellaneousNumber, RaceCode, ReasonCode, RelatedHitSearchIndicator, Requestor, SocialSecurityNumber, SexCode, VehicleIdentificationNumber]
6. (In/Out) Name, OriginatingAgencyCaseNumber, [ImageIndicator, ReasonCode, RelatedHitSearchIndicator, Requestor]
7. (In/Out) Name, ProtectionOrderNumber, [ImageIndicator, ReasonCode, RelatedHitSearchIndicator, Requestor]
8. (In/Out) NCICNumber, [ImageIndicator, ReasonCode, RelatedHitSearchIndicator, Requestor]

WMPISexualOffenderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	10	
BoatHullIdNumber	BoatHullIdNumber	O	20	
BoatRegistrationNumber	BoatRegistrationNumber	O	8	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Y
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Y
FBINumber	FBINumber	O	9	
ImageIndicator	ImageIndicator	O	1	Y
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	10	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	
RaceCode	RaceCode	O	1	A, I, B, W, U
ReasonCode	ReasonCode	O	3	See Definition and Usage above
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Y
Requestor	Requestor	O	3	See Definition and Usage above
SexCode	SexCode	O	1	F, M, U
SexualOffenderActiveStatusIndicator	SexualOffenderActiveStatusIndicator	O	1	Y
SocialSecurityNumber	SocialSecurityNumber	O	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	24	
ZipCode	ZipCode	C	10	

Possible Combinations

1. (In/Out) Name, BirthDate, [BoatHullIdNumber, BoatRegistrationNumber, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, MiscellaneousNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, RaceCode, ReasonCode, RelatedHitSearchIndicator, Requestor, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
2. (In/Out) Name, FBINumber, [BirthDate, BoatHullIdNumber, BoatRegistrationNumber, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, MiscellaneousNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, RaceCode, ReasonCode,

- RelatedHitSearchIndicator, Requestor, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
3. (In/Out) Name, MiscellaneousNumber, [BirthDate, BoatHullIdNumber, BoatRegistrationNumber, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, OperatorLicenseNumber, OriginatingAgencyCaseNumber, RaceCode, ReasonCode, RelatedHitSearchIndicator, Requestor, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
 4. (In/Out) Name, SocialSecurityNumber, [BirthDate, BoatHullIdNumber, BoatRegistrationNumber, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, MiscellaneousNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, RaceCode, ReasonCode, RelatedHitSearchIndicator, Requestor, SexCode, VehicleIdentificationNumber, VehicleMakeCode]
 5. (In/Out) Name, OperatorLicenseNumber, [BirthDate, BoatHullIdNumber, BoatRegistrationNumber, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, MiscellaneousNumber, OriginatingAgencyCaseNumber, RaceCode, ReasonCode, RelatedHitSearchIndicator, Requestor, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
 6. (In/Out) Name, LicensePlateNumber, [BirthDate, BoatHullIdNumber, BoatRegistrationNumber, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateStateCode, MiscellaneousNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, RaceCode, ReasonCode, RelatedHitSearchIndicator, Requestor, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
 7. (In/Out) Name, VehicleIdentificationNumber, [BirthDate, BoatHullIdNumber, BoatRegistrationNumber, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, MiscellaneousNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, RaceCode, ReasonCode, RelatedHitSearchIndicator, Requestor, SexCode, SocialSecurityNumber, VehicleMakeCode]
 8. (In/Out) Name, BoatRegistrationNumber, [BirthDate, BoatHullIdNumber, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, MiscellaneousNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, RaceCode, ReasonCode, RelatedHitSearchIndicator, Requestor, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
 9. (In/Out) Name, BoatHullIdNumber, [BirthDate, BoatRegistrationNumber, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, MiscellaneousNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, RaceCode, ReasonCode, RelatedHitSearchIndicator, Requestor, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
 10. (In/Out) ZipCode, [ImageIndicator, ReasonCode, Requestor, SexualOffenderActiveStatusIndicator]

WMPIUnidentifiedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	C	2	
AreaCode	AreaCode	O	3	
BodyPartsStatus	BodyPartsStatus	C	15	
EthnicityCode	EthnicityCode	O	1	H, N
EyeColorCode	EyeColorCode	C	3	

HairColorCode	HairColorCode	C	3	
Height	Height	C	3	
ImageIndicator	ImageIndicator	O	1	Y
RaceCode	RaceCode	C	1	A, I, B, W, U
ReasonCode	ReasonCode	O	3	See Definition and Usage above
Requestor	Requestor	O	3	See Definition and Usage above
SexCode	SexCode	C	1	F, M, U
Weight	Weight	C	3	

Possible Combinations

1. (In/Out) Age, EyeColorCode, HairColorCode, Height, RaceCode, SexCode, Weight, [AreaCode, EthnicityCode, ImageIndicator, ReasonCode, Requestor]
2. (In/Out) BodyPartsStatus, [AreaCode, ImageIndicator, RaceCode, ReasonCode, Requestor, SexCode]

WMPIWantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	10	
EnhancedNameSearchIndicator	EnhancedNameSearchIndicator	O	1	Y
ExpandedBirthDateSearchIndicator	ExpandedBirthDateSearchIndicator	O	1	Y
FBINumber	FBINumber	O	9	
ImageIndicator	ImageIndicator	O	1	Y
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
MessageKey	MessageKey	O	3	Defaults QW: QWA QWE QWF QWS
MiscellaneousNumber	MiscellaneousNumber	O	15	
MontanaRecordNumber	MontanaRecordNumber	C	7	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	
RaceCode	RaceCode	O	1	A, I, B, W, U
ReasonCode	ReasonCode	O	3	See Definition and Usage above
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Y
Requestor	Requestor	O	3	See Definition and Usage above
SexCode	SexCode	O	1	F, M, U
SocialSecurityNumber	SocialSecurityNumber	O	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	24	

Possible Combinations

1. (In/Out) LicensePlateNumber, [ImageIndicator, LicensePlateStateCode, MessageKey, ReasonCode, RelatedHitSearchIndicator, Requestor]
2. (In/Out) MontanaRecordNumber, [MessageKey, ReasonCode, Requestor]
3. (In/Out) Name, [EnhancedNameSearchIndicator, ExpandedBirthDateSearchIndicator, FBINumber, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, MessageKey, MiscellaneousNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, RaceCode,

- ReasonCode, RelatedHitSearchIndicator, Requestor, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
- (In/Out) NCICNumber, [ImageIndicator, MessageKey, ReasonCode, RelatedHitSearchIndicator, Requestor]
 - (In/Out) OperatorLicenseNumber, [ImageIndicator, MessageKey, ReasonCode, RelatedHitSearchIndicator, Requestor]
 - (In/Out) VehicleIdentificationNumber, [ImageIndicator, MessageKey, ReasonCode, RelatedHitSearchIndicator, Requestor, VehicleMakeCode]

Extended Queries Supported:

ImageQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Boat Length	BoatLength	C	2	
Boat Make Code	BoatMakeCode	C	24	
Boat Type Code	BoatTypeCode	C	3	
Boat Year	BoatYear	O	4	
Image Id	ImageId	C	10	
Image Indicator	ImageIndicator	O	1	Y
NCIC Number	NCICNumber	C	10	
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
Vehicle Make Code	VehicleMakeCode	O	4	
Vehicle Model Code	VehicleModelCode	C	3	
Vehicle Style Code	VehicleStyleCode	C	2	
Vehicle Year	VehicleYear	C	4	

Possible Combinations (fields within the square brackets are optional)

- Requestor, ReasonCode, NCICNumber, [ImageIndicator]
- Requestor, ReasonCode, ImageId, [ImageIndicator]
- Requestor, ReasonCode, BoatMakeCode, BoatTypeCode, BoatLength, [BoatYear, ImageIndicator]
- Requestor, ReasonCode, VehicleMakeCode, VehicleStyleCode, VehicleYear, VehicleModelCode, [ImageIndicator]

LogonRequest

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Password	Password	M	6+	
New Password	NewPassword	O	6+	
User Name	UserName	M	1+	

Possible Combinations (fields within the square brackets are optional)

- UserName, Password, [NewPassword]

MtCjinCdIisQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	10	
Name	Name	O	30	
OperatorLicenseNumber	OperatorLicenseNumber	M	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	M	2	
ReasonCode	ReasonCode	M	3	
Requestor	Requestor	M	3	
SexCode	SexCode	O	1	

Possible Combinations

1. (In/Out) OperatorLicenseNumber, OperatorLicenseStateCode, ReasonCode, Requestor, [BirthDate, Name, SexCode]

MtCjinDriverLicenseNameQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
City	City	O	20	
County	County	O	20	
Name	Name	M	30	
NextPage	NextPage	O	20	See Nlets Wiki
PersonAge	PersonAge	O	2	See Nlets Wiki
Reason	Reason	O	200	Freetext description of reason inquiry was made
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
SexCode	SexCode	O	1	
State	State	O	2	See Nlets Wiki

Possible Combinations

1. (In/Out) Name, ReasonCode, Requestor, [City, County, NextPage, PersonAge, Reason, SexCode, State]

MtCjinVehicleRegistrationNameQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
Name	Name	M	30	
Reason	Reason	O	200	Freetext description of reason inquiry was made
Reason Code	ReasonCode	M	3	See Definition and Usage above
Requestor Initials	Requestor	M	3	See Definition and Usage above
State	State	O	2	See Nlets Wiki

Possible Combinations

1. (In/Out) Name, ReasonCode, Requestor, [BirthDate, Reason, State]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- CJIN Documentation