

Nebraska (NE*) CJIS OFML

[Disclaimer Statement](#)

*May also see Nebraska referred to as NB

Transport:

TCPIP (DMPP-2020)

Routing and Configuration Information:

Mnemonic Routing

- The Nebraska assigned ORI for a device (or for the site) should be placed in the <Authentication>/<ORI> field in the ConnectCIC header.
- The Nebraska assigned mnemonic or terminal id for a device should be placed in the <Authentication>/<Mnemonic> field in the ConnectCIC header.
- The Nebraska assigned user id for a person should be placed in the <Authentication>/<UserName> field in the ConnectCIC header.

Security Requirements:

None known at this time.

Logon Requirements:

None known at this time.

Certification Requirements:

Agency sponsor is required.

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode, TestIndicator

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	20	
RegistrationNumber	RegistrationNumber	C	8	
State	State	O	2	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) BoatHullIdNumber, [State, TestIndicator]
2. (In/Out) RegistrationNumber, [State, TestIndicator]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
ImageIndicator	ImageIndicator	C	1	Y, N, BLANK
PurposeCode	PurposeCode	O	1	
SexCode	SexCode	C	1	
State	State	O	2	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, [Attention, PurposeCode, State, TestIndicator]
2. (In/Out) ImageIndicator, OperatorLicenseNumber, [Attention, PurposeCode, State, TestIndicator]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	C	1	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	
ImageIndicator	ImageIndicator	C	1	Y, N, BLANK
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, [State, State2, State3, State4, State5, TestIndicator]
2. (In/Out) ImageIndicator, OperatorLicenseNumber, [State, State2, State3, State4, State5, TestIndicator]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	O	10	

GunModel	GunModel	O	20	
GunSerialNumber	GunSerialNumber	M	20	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) GunSerialNumber, [GunCaliber, GunMake, GunModel, TestIndicator]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	20	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In/Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, [State, State2, State3, State4, State5, TestIndicator]
2. (In/Out) VehicleIdentificationNumber, [State, State2, State3, State4, State5, TestIndicator, VehicleMakeCode, VehicleYear]

Transactions Supported:

Agency Operations And Support (AOS)

AOSAdministrativeMessage

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FreeText	FreeText	M	14400	Alphanumeric, special chars; See NLETS manual
NletsDestination	NletsDestination	M	9	ORI, mnemonic, distribution list, etc.
NletsDestination2	NletsDestination2	O	9	ORI, mnemonic, distribution list, etc.
NletsDestination3	NletsDestination3	O	9	ORI, mnemonic, distribution list, etc.
NletsDestination4	NletsDestination4	O	9	ORI, mnemonic, distribution list, etc.
NletsDestination5	NletsDestination5	O	9	ORI, mnemonic, distribution list, etc.
MessageKeyModifier	MessageKeyModifier	O	1	Enter L for law enforcement only; blank if not
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) FreeText, MessageKeyModifier, NletsDestination [NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, TestIndicator]

AOSAircraftRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AircraftSerialNumber	AircraftSerialNumber	C	16	Alphanumeric; See NLETS manual

AircraftSightedDate	AircraftSightedDate	O	8	Numeric-Date. See NLETS manual
AircraftSightedFlag	AircraftSightedFlag	O	1	'Y', 'N', or BLANK. See NLETS manual
Attention	Attention	M	30	Alphanumeric; See NLETS manual
Name	Name	C	40	Alphanumeric; See NLETS manual
TailNumber	TailNumber	C	8	Alphanumeric; See NLETS manual
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Attention, TailNumber, [AircraftSightedDate, AircraftSightedFlag, TestIndicator]
2. (In/Out) Attention, AircraftSerialNumber, [TestIndicator]
3. (In/Out) Attention, Name, [TestIndicator]

AOSHazardousMaterialsQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
UnitedNationsNumber	UnitedNationsNumber	M	4	Numeric; See NLETS manual
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) UnitedNationsNumber, [TestIndicator]

AOSImageCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	O	8	Alphanumeric; See NCIC manual
ImageNCICNumber	ImageNCICNumber	M	10	Numeric-Date. See NCIC manual
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) ImageNCICNumber, [CancellationDate, TestIndicator]

AOSImageEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageData	ImageData	M	16000	Alphanumeric and Binary. See NCIC manual
ImageDate	ImageDate	O	8	Numeric-Date. See NCIC manual
ImageType	ImageType	M	1	Alphabetic: M,S,I,B,V. See NCIC manual
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	240	Alphanumeric,special chars. See NCIC manual
NCICNumber	NCICNumber	M	10	Alphanumeric; See NCIC manual
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) ImageData, ImageType, NCICNumber, [ImageDate ,MiscellaneousDescriptiveText, TestIndicator]

AOSImageModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageData	ImageData	O	16000	Alphanumeric and Binary. See NCIC manual
ImageDate	ImageDate	O	8	Numeric-Date. See NCIC manual
ImageNCICNumber	ImageNCICNumber	M	10	Alphanumeric; See NCIC manual
ImageType	ImageType	M	1	Alphabetic: M,S,I,B,V. See NCIC manual

MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	240	Alphanumeric,special chars. See NCIC manual
NCICNumber	NCICNumber	O	10	Alphanumeric; See NCIC manual
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) ImageNCICNumber, ImageType, [ImageData, MiscellaneousDescriptiveText, NCICNumber, TestIndicator]

AOSImageQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatLength	BoatLength	C	2	Numeric. See NCIC manual
BoatMakeCode	BoatMakeCode	C	24	Alphanumeric; See NCIC manual
BoatTypeCode	BoatTypeCode	C	3	Alphabetic. See NCIC manual
BoatYear	BoatYear	C	4	Numeric-Year. See NCIC manual
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y, N, or BLANK
ImageNCICNumber	ImageNCICNumber	C	10	Alphanumeric; See NCIC manual
NCICNumber	NCICNumber	C	10	Alphanumeric; See NCIC manual
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleMakeCode	VehicleMakeCode	C	24	Alphanumeric; See NCIC manual
VehicleModelCode	VehicleModelCode	C	3	Alphanumeric; See NCIC manual
VehicleStyleCode	VehicleStyleCode	C	2	Alphanumeric; See NCIC manual
VehicleYear	VehicleYear	C	4	Numeric-Year. See NCIC manual

Possible Combinations

1. (In/Out) ImageNCICNumber, [ImageIndicator, TestIndicator]
2. (In/Out) NCICNumber, [ImageIndicator, TestIndicator]
3. (In/Out) BoatLength, BoatMakeCode, BoatTypeCode, [ImageIndicator, TestIndicator]
4. (In/Out) VehicleMakeCode, VehicleModelCode, VehicleStyleCode, [ImageIndicator, TestIndicator]

AOSORIQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FormORI	FormORI	M	9	Alphanumeric; See NCIC manual
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) FormORI, [TestIndicator]

AOSHitConfirmationRequest

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleBrand	ArticleBrand	O	6	Alphanumeric,special chars. See NCIC manual
ArticleSerialNumber	ArticleSerialNumber	O	20	Alphanumeric; See NCIC manual
ArticleTypeCode	ArticleTypeCode	O	7	Alphabetic. See NCIC code manual
BirthDate	BirthDate	O	8	Numeric-Date. See NCIC manual
BoatHullIdNumber	BoatHullIdNumber	O	20	Alphanumeric; See NCIC manual
BoatMakeCode	BoatMakeCode	O	24	Alphanumeric; See NCIC code manual
BoatRegistrationNumber	BoatRegistrationNumber	O	8	Alphanumeric; See NCIC manual
CourtOrderNumber	CourtOrderNumber	O	20	Alphanumeric,special chars;See NLETS manual

CourtORI	CourtORI	O	9	Valid 9-digit ORI
Denomination	Denomination	O	9	Alphanumeric,special chars;See NCIC manual
DestinationORI	DestinationORI	M	9	Valid 9-digit ORI
ExtensionNumber	ExtensionNumber	O	4	Numeric; See NLETS manual
FaxNumber	FaxNumber	O	10	Numeric; See NLETS manual
GunCaliber	GunCaliber	O	4	Numeric; See NCIC manual
GunMake	GunMake	O	24	Alphabetic. See NCIC code manual
GunModel	GunModel	O	20	Alphanumeric.See NCIC manual
GunSerialNumber	GunSerialNumber	O	20	Alphanumeric.See NCIC manual
LicensePlateNumber	LicensePlateNumber	O	10	Alphanumeric.See NCIC manual
LicensePlateStateCode	LicensePlateStateCode	O	2	Alphanumeric; See NCIC code manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	Alphanumeric; See NCIC code manual
LicensePlateYear	LicensePlateYear	O	4	Numeric-Year. See NCIC manual
Name	Name	O	30	Alphanumeric,special chars. See NCIC manual
NCICNumber	NCICNumber	M	10	Alphanumeric.See NLETS/NCIC manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	Alphanumeric, '-' – See NCIC manual
OriginatingAgencyORI	OriginatingAgencyORI	M	9	Alphanumeric; See NCIC manual
PartBrand	PartBrand	O	4	Alphanumeric; See NCIC code manual
PartCategoryCode	PartCategoryCode	O	2	Alphanumeric; See NCIC code manual
PartSerialNumber	PartSerialNumber	O	20	Alphanumeric.See NCIC manual
PhoneNumber	PhoneNumber	O	10	Numeric; See NLETS manual
PriorityDestinationCode	PriorityDestinationCode	M	1	Alphabetic: U, R. See NLETS manual
Remarks	Remarks	O	500	Alphanumeric,special chars.See NLETS manual
RequesterName	RequesterName	M	30	Alphanumeric,special chars.See NLETS manual
RequestingAgency	RequestingAgency	M	30	Alphanumeric,special chars.See NLETS manual
RequestNumber	RequestNumber	M	1	Numeric: 1,2,3. See NLETS manual
RequestTypeCode	RequestTypeCode	M	2	Alphabetic: See NLETS manual
SecuritySerialNumber	SecuritySerialNumber	O	20	Alphanumeric; See NCIC code manual
SecurityTypeCode	SecurityTypeCode	O	2	Alphabetic: See NCIC code manual
SexCode	SexCode	O	1	Alphabetic: M, F, U. See NCIC manual
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	Alphanumeric, See NCIC manual
VehicleMakeCode	VehicleMakeCode	O	24	Alphanumeric; See NCIC code manual
VehicleYear	VehicleYear	O	4	Numeric-Year. See NCIC manual
WarrantNumber	WarrantNumber	O	20	Alphanumeric, '-' – See NCIC manual

Possible Combinations

1. (In/Out) DestinationORI, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, RequestNumber, RequesterName, RequestingAgency, RequestTypeCode, [ArticleBrand, ArticleSerialNumber, ArticleTypeCode, BirthDate, BoatHullIdNumber, BoatMakeCode, BoatRegistrationNumber, CourtOrderNumber, CourtORI, Denomination, ExtensionNumber, FaxNumber, GunCaliber, GunMake, GunModel, GunSerialNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, LicensePlateYear, Name, PartBrand, PartCategoryCode, PartSerialNumber, PhoneNumber, Remarks, SecuritySerialNumber, SecurityTypeCode, SexCode, TestIndicator, VehicleIdentificationNumber, VehicleMakeCode, VehicleYear, WarrantNumber]

AOSHitConfirmationResponse

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleBrand	ArticleBrand	O	6	Alphanumeric,special chars. See NCIC manual
ArticleSerialNumber	ArticleSerialNumber	O	20	Alphanumeric; See NCIC manual
ArticleTypeCode	ArticleTypeCode	O	7	Alphabetic. See NCIC code manual
BirthDate	BirthDate	O	8	Numeric-Date. See NCIC manual
BoatHullIdNumber	BoatHullIdNumber	O	20	Alphanumeric; See NCIC manual
BoatMakeCode	BoatMakeCode	O	24	Alphanumeric; See NCIC code manual
BoatRegistrationNumber	BoatRegistrationNumber	O	8	Alphanumeric; See NCIC manual
ConfirmationStatusCode	ConfirmationStatusCode	M	1	Alphabetic: Y,N,P,E. See NLETS manual
ConfirmerName	ConfirmerName	M	30	Alphanumeric,special chars.See NLETS manual
ConfirmingAgency	ConfirmingAgency	M	30	Alphanumeric,special chars.See NLETS manual
CourtOrderNumber	CourtOrderNumber	O	20	Alphanumeric,special chars;See NLETS manual
Denomination	Denomination	O	9	Alphanumeric,special chars;See NCIC manual
DestinationORI	DestinationORI	M	9	Valid 9-digit ORI
ExtensionNumber	ExtensionNumber	O	4	Numeric; See NLETS manual
FaxNumber	FaxNumber	O	10	Numeric; See NLETS manual
GunCaliber	GunCaliber	O	4	Numeric; See NCIC manual
GunMake	GunMake	O	24	Alphabetic. See NCIC code manual
GunModel	GunModel	O	20	Alphanumeric.See NCIC manual
GunSerialNumber	GunSerialNumber	O	20	Alphanumeric.See NCIC manual
HoursForConfirmation	HoursForConfirmation	O	3	Numeric; See NLETS manual
LicensePlateNumber	LicensePlateNumber	O	10	Alphanumeric.See NCIC manual
LicensePlateStateCode	LicensePlateStateCode	O	2	Alphanumeric; See NCIC code manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	Alphanumeric; See NCIC code manual
LicensePlateYear	LicensePlateYear	O	4	Numeric-Year. See NCIC manual
Name	Name	O	30	Alphanumeric,special chars. See NCIC manual
NCICNumber	NCICNumber	M	10	Alphanumeric.See NLETS/NCIC manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	Alphanumeric, '-' – See NCIC manual
OriginatingAgencyORI	OriginatingAgencyORI	M	9	Alphanumeric; See NCIC manual

PartBrand	PartBrand	O	4	Alphanumeric; See NCIC code manual
PartCategoryCode	PartCategoryCode	O	2	Alphanumeric; See NCIC code manual
PartSerialNumber	PartSerialNumber	O	20	Alphanumeric. See NCIC manual
PhoneNumber	PhoneNumber	O	10	Numeric; See NLETS manual
Remarks	Remarks	O	500	Alphanumeric, special chars. See NLETS manual
RequestTypeCode	RequestTypeCode	M	2	Alphabetic: See NLETS manual
SecuritySerialNumber	SecuritySerialNumber	O	20	Alphanumeric; See NCIC code manual
SecurityTypeCode	SecurityTypeCode	O	2	Alphabetic: See NCIC code manual
SexCode	SexCode	O	1	Alphabetic: M, F, U. See NCIC manual
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	Alphanumeric, See NCIC manual
VehicleMakeCode	VehicleMakeCode	O	24	Alphanumeric; See NCIC code manual
VehicleYear	VehicleYear	O	4	Numeric-Year. See NCIC manual
WarrantNumber	WarrantNumber	O	20	Alphanumeric, '-' – See NCIC manual

Possible Combinations

(In/Out) ConfirmationStatusCode, ConfirmerName, ConfirmingAgency, DestinationORI, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, RequestTypeCode, [ArticleBrand, ArticleSerialNumber, ArticleTypeCode, BirthDate, BoatHullIdNumber, BoatMakeCode, BoatRegistrationNumber, CourtOrderNumber, Denomination, DestinationORI, ExtensionNumber, FaxNumber, GunCaliber, GunMake, GunModel, GunSerialNumber, HoursForConfirmation, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, LicensePlateYear, Name, PartBrand, PartCategoryCode, PartSerialNumber, PhoneNumber, Remarks, SecuritySerialNumber, SecurityTypeCode, SexCode, TestIndicator, VehicleIdentificationNumber, VehicleMakeCode, VehicleYear, WarrantNumber]

AOSOrionQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AgencyTypeCode	AgencyTypeCode	C	2	Alphabetic: See NLETS manual
FederalAgencyOrLocation	FederalAgencyOrLocation	C	30	Alphanumeric. See NLETS/NCIC manual
FormORI	FormORI	C	9	Valid 9-digit ORI
Location	Location	C	20	Alphanumeric. See NLETS/NCIC manual
State	State	O	2	Alphabetic: See NLETS/NCIC code manual
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) FormORI, [State]
2. (In/Out) Location, AgencyTypeCode, [State, TestIndicator]
3. (In/Out) FederalAgencyOrLocation, [State, TestIndicator]

Computerized Criminal History (CCH)

CCHCriminalHistoryQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Alphanumeric, Special chars, See NCIC code manual
BirthDate	BirthDate	C	8	Numeric-Date. See NCIC manual

FBINumber	FBINumber	C	9	Alphanumeric. See NCIC manual
MiscellaneousNumber	MiscellaneousNumber	C	15	Alphanumeric,Special chars,See NCIC code manual
Name	Name	C	30	Alphanumeric,Special chars,See NCIC code manual
PurposeCode	PurposeCode	M	1	Alphabetic: C,D,E,F,J,S. See NCIC code manual
RaceCode	RaceCode	C	1	Alphabetic: I, A, B, W, U. See NCIC code manual
SexCode	SexCode	C	1	Alphabetic: M, F, U. See NCIC code manual
SocialSecurityNumber	SocialSecurityNumber	C	9	Numeric
StateIdNumber	StateIdNumber	C	10	Alphanumeric. See NCIC manual
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) BirthDate , Name, PurposeCode, RaceCode, SexCode, [Attention, TestIndicator]
2. (In/Out) BirthDate , Name, PurposeCode, RaceCode, SexCode, SocialSecurityNumber, [Attention, TestIndicator]
3. (In/Out) BirthDate , Name, PurposeCode, RaceCode, SexCode, MiscellaneousNumber, [Attention, TestIndicator]
4. (In/Out) Name, PurposeCode, SocialSecurityNumber, [Attention, TestIndicator]
5. (In/Out) Name, MiscellaneousNumber, PurposeCode, [Attention, TestIndicator]
6. (In/Out) PurposeCode, StateIdNumber, [Attention, Name, TestIndicator]
7. (In/Out) FBINumber, PurposeCode, [Attention, Name, TestIndicator]

CCHCriminalHistoryQRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	30	Alphanumeric,Special chars,See NCIC manual
AddressStreet	AddressStreet	O	30	Alphanumeric,Special chars,See NCIC manual
AddressZipCode	AddressZipCode	O	9	Numeric
Attention	Attention	M	30	Alphanumeric,Special chars,See NCIC code manual
BuildingName	BuildingName	O	30	Alphanumeric,Special chars,See NCIC code manual
DepartmentName	DepartmentName	O	30	Alphanumeric,Special chars,See NCIC code manual
FBINumber	FBINumber	C	9	Alphanumeric. See NCIC manual
Name	Name	O	30	Alphanumeric,Special chars,See NCIC code manual
PurposeCode	PurposeCode	M	1	Alphabetic: C,D,E,F,J,S. See NCIC code manual
StateIdNumber	StateIdNumber	C	10	Alphanumeric,Special chars,See NCIC code manual
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Attention, FBINumber, PurposeCode, [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName, Name, TestIndicator]
2. (In/Out) Attention, PurposeCode, StateIdNumber [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName, Name, TestIndicator]

CCHCriminalHistoryQWQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Alphanumeric,Special chars,See NCIC code manual
BirthDate	BirthDate	C	8	Numeric-Date. See NCIC manual
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Numeric: 0, 1, 2, 3 – See NCIC manual
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Alphabetic: Y, N, or blank
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y, N, or blank
MiscellaneousNumber	MiscellaneousNumber	C	15	Alphanumeric,Special chars,See NCIC code manual
Name	Name	M	30	Alphanumeric,Special chars,See NCIC code manual
PurposeCode	PurposeCode	M	1	Alphabetic: C,D,E,F,J,S. See NCIC code manual
RaceCode	RaceCode	C	1	Alphabetic: I, A, B, W, U. See NCIC code manual

RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Alphabetic: Y, N, or blank
SexCode	SexCode	C	1	Alpha: M, F, U
SocialSecurityNumber	SocialSecurityNumber	C	9	Numeric
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) BirthDate , Name, PurposeCode, RaceCode, SexCode, [Attention, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
2. (In/Out) BirthDate , Name, PurposeCode, RaceCode, SexCode, SocialSecurityNumber, [Attention, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
3. (In/Out) BirthDate , Name, PurposeCode, RaceCode, SexCode, MiscellaneousNumber, [Attention, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
4. (In/Out) Name, PurposeCode, SocialSecurityNumber, [Attention, ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
5. (In/Out) Name, MiscellaneousNumber, PurposeCode, [Attention, ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, TestIndicator]

CCHCriminalHistoryAQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	Alphanumeric; See NLETS manual
FreeText	FreeText	M	14400	Alphanumeric, special chars; See NLETS manual
NletsDestination	NletsDestination	M	9	2- or 9-character destination ORI
NletsDestination2	NletsDestination2	O	9	2- or 9-character destination ORI
NletsDestination3	NletsDestination3	O	9	2- or 9-character destination ORI
NletsDestination4	NletsDestination4	O	9	2- or 9-character destination ORI
NletsDestination5	NletsDestination5	O	9	2- or 9-character destination ORI
PurposeCode	PurposeCode	M	1	Alphabetic: C,D,E,F,J,I,S. See NLETS manual
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Attention, FreeText, NletsDestination, PurposeCode, [NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, TestIndicator]

CCHCriminalHistoryARQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Alphanumeric; See NLETS manual
FreeText	FreeText	O	14400	Alphanumeric, special chars; See NLETS manual
NletsDestination	NletsDestination	O	9	9-character destination ORI
PurposeCode	PurposeCode	O	1	Alphabetic: C,D,E,F,J,I,S. See NLETS manual
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Attention, FreeText, NletsDestination, PurposeCode, [TestIndicator]

CCHCriminalHistoryFQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	30	Alphanumeric, Special chars, See NCIC manual
AddressStreet	AddressStreet	O	30	Alphanumeric, Special chars, See NCIC manual
AddressZipCode	AddressZipCode	O	9	Numeric
Attention	Attention	M	30	Alphanumeric, Special chars, See NCIC manual

BuildingName	BuildingName	O	30	Alphanumeric,Special chars,See NCIC manual
DepartmentName	DepartmentName	O	30	Alphanumeric,Special chars,See NCIC manual
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y, N, or blank
PurposeCode	PurposeCode	M	1	Alpahbetic: C,D,E,F,J,I,S. See NLETS manual
State	State	O	2	2 alphanumeric character NLETS state/province code
StateIdNumber	StateIdNumber	M	10	Alphanumeric,Special chars,See NCIC code manual
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Attention, PurposeCode, StateIdNumber, [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName, ImageIndicator, State, TestIndicator]

CCHCriminalHistoryIQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	Alphanumeric,Special chars,See NCIC manual
BirthDate	BirthDate	M	8	Numeric-Date. See NCIC/NLETS manual
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y, N, or blank
MiscellaneousNumber	MiscellaneousNumber	O	15	Alphanumeric,Special chars,See NCIC code manual
Name	Name	M	30	Alphanumeric,Special chars,See NCIC/NLETS manual
PurposeCode	PurposeCode	M	1	Alpahbetic: C,D,E,F,J,I,S. See NLETS manual
RaceCode	RaceCode	O	1	Alphabetic: I, A, B, W, U. See NCIC code manual
SexCode	SexCode	M	1	Alpha: M, F, U
SocialSecurityNumber	SocialSecurityNumber	O	9	Numeric
State	State	O	2	2 alphanumeric character NLETS state/province code
State2	State2	O	2	2 alphanumeric character NLETS state/province code
State3	State3	O	2	2 alphanumeric character NLETS state/province code
State4	State4	O	2	2 alphanumeric character NLETS state/province code
State5	State5	O	2	2 alphanumeric character NLETS state/province code
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Attention, BirthDate, Name, PurposeCode, SexCode, [ImageIndicator, MiscellaneousNumber, RaceCode, SocialSecurityNumber, State, State2, State3, State4, State5, TestIndicator]

Wanted Missing Person Entry (WMPE)

WMPEDentalDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [TestIndicator]

WMPEDentalDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

DentalCharacteristics	DentalCharacteristics	M	319	See NCIC Code Manual
DentalModelsAvailableIndicator	DentalModelsAvailableIndicator	M	1	Y, N
DentalXraysAvailableIndicator	DentalXraysAvailableIndicator	M	1	Y, N
DentistRemarks	DentistRemarks	O	50	
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) DentalCharacteristics, DentalModelsAvailableIndicator, DentalXraysAvailableIndicator, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [DentistRemarks, TestIndicator]

WMPEDentalDataModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DentalCharacteristics	DentalCharacteristics	O	319	See NCIC Code Manual
DentalModelsAvailableIndicator	DentalModelsAvailableIndicator	O	1	Y, N
DentalXraysAvailableIndicator	DentalXraysAvailableIndicator	O	1	Y, N
DentistRemarks	DentistRemarks	O	50	
NCICNumber	NCICNumber	M	10	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [DentistRemarks, DentalCharacteristics, DentalModelsAvailableIndicator, DentalXraysAvailableIndicator, ModifiedOriginatingAgencyORI, TestIndicator])

WMPEMissingPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
CancellationDate	CancellationDate	M	8	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [PersonRecordRemovalReason, TestIndicator]
2. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI, [PersonRecordRemovalReason, TestIndicator]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [PersonRecordRemovalReason, TestIndicator]

WMPEMissingPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	

ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
HitResultsIndicator	HitResultsIndicator	O	2	1-9, See NCIC Code Manual for description
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyORI	RecoveringAgencyORI	O	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [HitResultsIndicator, NumberMissingPersonsFound, NumberPersonsApprehended, OtherRecoveredPropertyValue, PersonArmedIndicator, PropertyRecoveredValue, RecoveringAgencyCaseNumber, RecoveringAgencyORI, TestIndicator]
2. (In/Out) Name, NCICNumber, ClearDate, OriginatingAgencyORI, [HitResultsIndicator, NumberMissingPersonsFound, NumberPersonsApprehended, OtherRecoveredPropertyValue, PersonArmedIndicator, PropertyRecoveredValue, RecoveringAgencyCaseNumber, RecoveringAgencyORI, TestIndicator]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [HitResultsIndicator, NumberMissingPersonsFound, NumberPersonsApprehended, OtherRecoveredPropertyValue, PersonArmedIndicator, PropertyRecoveredValue, RecoveringAgencyCaseNumber, RecoveringAgencyORI, TestIndicator]

WMPEMissingPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyXRayCode	BodyXRayCode	O	1	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	See NCIC Code Manual
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EmancipationDate	EmancipationDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintIndicator	FootprintIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
JewelryDescription	JewelryDescription	O	100	

JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LastContactDate	LastContactDate	M	8	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
MissingPersonCircumstanceCode	MissingPersonCircumstanceCode	O	1	See NCIC Code Manual
MissingPersonCode	MissingPersonCode	M	2	See NCIC Code Manual
MissingPersonEntryType	MissingPersonEntryType	M	1	D – Disability E – Endangered I – Involuntary J – Emancipated Juvenile V – Catastrophe Victim O – Other
Name	Name	M	30	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarMarkTattooCode	ScarMarkTattooCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, BirthDate, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, FBI Number, [Any optional fields]
3. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, MiscellaneousNumber, [Any optional fields]
4. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, SocialSecurityNumber, [Any optional fields]

5. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
6. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, LicensePlateYear, [Any optional fields]
7. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, VehicleIdentificationNumber, VehicleMakeCode, VehicleYear, VehicleStyleCode, [Any optional fields]
8. (In/Out) **MissingPersonEntryType = J**; OriginatingAgencyORI, Name, SexCode, RaceCode, BirthDate, EmancipationDate, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEMissingPersonLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
DispositionCode	DispositionCode	M	4	
HitResultsIndicator	HitResultsIndicator	O	2	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, RecoveryDate, DispositionCode, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, RecoveryDate, DispositionCode, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, RecoveryDate, DispositionCode, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	
BloodTypeCode	BloodTypeCode	O	5	
BodyXRayCode	BodyXRayCode	O	1	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	
CircumcisionCode	CircumcisionCode	O	1	

CitizenshipCode	CitizenshipCode	O	2	
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	
DNAIndicator	DNAIndicator	O	1	
DNALocation	DNALocation	O	250	
EmancipationDate	EmancipationDate	O	8	
EthnicityCode	EthnicityCode	O	1	
EyeColorCode	EyeColorCode	O	3	
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	
FootprintIndicator	FootprintIndicator	O	1	
HairColorCode	HairColorCode	O	3	
Height	Height	O	3	
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	
LastContactDate	LastContactDate	O	8	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	O	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
MissingPersonCircumstanceCode	MissingPersonCircumstanceCode	O	1	
MissingPersonCode	MissingPersonCode	O	2	
ModifiedMessageKey	ModifiedMessageKey	O	4	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	O	1	
ScarMarkTattooCode	ScarMarkTattooCode	O	10	
SexCode	SexCode	O	1	
SkinToneCode	SkinToneCode	O	3	
SocialSecurityNumber	SocialSecurityNumber	O	9	
TestIndicator	TestIndicator	O	1	Y, BLANK
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	
VehicleStyleCode	VehicleStyleCode	O	2	
VehicleYear	VehicleYear	O	4	

Weight	Weight	O	3	
--------	--------	---	---	--

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonPersonWithInformationCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	M	30	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [TestIndicator]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI, [TestIndicator]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [TestIndicator]

WMPEMissingPersonPersonWithInformationEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	M	500	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
TestIndicator	TestIndicator	O	1	Y, BLANK
SocialSecurityNumber	SocialSecurityNumber	C	9	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]

3. (In/Out) Name, NCICNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]
4. (In/Out) Name, NCICNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]
5. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]
6. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonPersonWithInformationModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	M	30	
PersonWithInformationName2	PersonWithInformationName2	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
TestIndicator	TestIndicator	O	1	Y, BLANK
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonPWISupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	

PersonWithInformationName	PersonWithInformationName	M	30	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonPWISupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	M	30	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual.

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual.

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPENebraskaWantedPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NBICNumber	NBICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
CancellationDate	CancellationDate	M	8	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, NBICNumber, CancellationDate, OriginatingAgencyORI, [MessageKeyModifier, OriginatingAgencyCaseNumber, PersonRecordRemovalReason, TestIndicator]
2. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [MessageKeyModifier, NBICNumber, PersonRecordRemovalReason, TestIndicator]
3. (In/Out) NBICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [MessageKeyModifier, Name, PersonRecordRemovalReason, TestIndicator]

WMPENebraskaWantedPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
HitResultsIndicator	HitResultsIndicator	O	2	See NCIC Code Manual
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NBICNumber	NBICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	Blank, Y
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyORI	RecoveringAgencyORI	O	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, NBICNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NBICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]

WMPENebraskaWantedPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

AdditionalOffenseIndicator	AdditionalOffenseIndicator	O	1	Blank, Y
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	C	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
DocumentedAddressDate	DocumentedAddressDate	O	8	
EmancipationDate	EmancipationDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExtraditionLimitation	ExtraditionLimitation	M	2	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FraudulentBirthDate	FraudulentBirthDate	O	8	
FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	
FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	C	20	
FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	C	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	C	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
IncidentDate	IncidentDate	C	8	Warrant or violation date
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
NotifyOriginatingAgency	NotifyOriginatingAgency	O	1	Blank, Y
OffenseCode	OffenseCode	M	4	
OffenseCodeDescription	OffenseCodeDescription	O	20	
OperatorLicenseYear	OperatorLicenseYear	C	4	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OriginalOffenseCode	OriginalOffenseCode	C	4	See NCIC Code Manual

OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	3	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
WantedPersonType	WantedPersonType	O	1	Blank, J – Wanted Juvenile
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	M	3	

*Operator License fields must be entered as a set.

*License Plate fields must be entered as a set.

*VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, and VehicleStyleCode must be entered as a set.

Possible Combinations

1. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, BirthDate, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FBINumber [Any optional fields]
3. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, MiscellaneousNumber [Any optional fields]
4. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, SocialSecurityNumber [Any optional fields]
5. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseExpirationYear, [Any optional fields]
6. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, LicensePlateNumber, LicensePlateStateCode, LicensePlateExpirationYear, LicensePlateTypeCode, [Any optional fields]
7. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]
8. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentName, FraudulentBirthDate, [Any optional fields]

9. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentMiscellaneousNumber, [Any optional fields]
10. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentSocialSecurityNumber, [Any optional fields]
11. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentOperatorLicenseNumber, FraudulentOperatorLicenseStateCode, FraudulentOperatorLicenseExpirationYear, [Any optional fields]
12. (In/Out) OriginatingAgencyORI, WantedPersonType, Name, SexCode, RaceCode, BrithDate, EmancipationDate, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, [Any optional fields]

WMPENebraskaWantedPersonLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
Extradition	Extradition	M	4	See NCIC Code Manual
HitResultsIndicator	HitResultsIndicator	O	2	See NCIC Code Manual
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NBICNumber	NBICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	Blank, Y
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, NBICNumber, Extradition, RecoveryDate, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, Extradition, RecoveryDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NBICNumber, OriginatingAgencyCaseNumber, Extradition, RecoveryDate, OriginatingAgencyORI, [Any optional fields]

WMPENebraskaWantedPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalOffenseIndicator	AdditionalOffenseIndicator	O	1	Blank, Y
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	

AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	
DNALocation	DNALocation	O	250	Blank, Y
DocumentedAddressDate	DocumentedAddressDate	O	8	
EmancipationDate	EmancipationDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExtraditionLimitation	ExtraditionLimitation	O	2	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IncidentDate	IncidentDate	C	8	Warrant or violation date
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	Blank EW – Wanted Person EWJ – Wanted Juvenile ET – Temporary Felony EW-C – Wanted Person with Caution EWJC – Wanted Juvenile with Caution ET-C – Temporary Felony with Caution
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NBICNumber	NBICNumber	C	10	
NotifyOriginatingAgency	NotifyOriginatingAgency	O	1	Blank, Y
OffenseCode	OffenseCode	O	4	See NCIC Code Manual
OffenseCodeDescription	OffenseCodeDescription	O	20	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	
OperatorLicenseYear	OperatorLicenseYear	O	4	See NCIC Code Manual
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual

SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
TestIndicator	TestIndicator	O	1	Y, BLANK
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NBICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NBICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPENebraskaWantedPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressCounty	AddressCounty	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetName	AddressStreetName	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetNumber	AddressStreetNumber	O	7	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressTypeCode	AddressTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressZipCode	AddressZipCode	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NBICNumber	NBICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual.

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NBICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NBICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPENebraskaWantedPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressCounty	AddressCounty	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetName	AddressStreetName	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetNumber	AddressStreetNumber	O	7	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressTypeCode	AddressTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressZipCode	AddressZipCode	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NBICNumber	NBICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual.

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

*Operator License fields must be entered as a set.

*License Plate fields must be entered as a set.

*VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, and VehicleStyleCode must be entered as a set.

*Address fields must be entered as a set.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NBICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NBICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEProtectionOrderCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
MessageKeyModifier	MessageKeyModifier	O	1	Blank or P – Protection Order T – Temporary Protection Order
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, ProtectionOrderNumber, CancellationDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [Any optional fields]

WMPEProtectionOrderClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

ClearDate	ClearDate	M	8	
MessageKeyModifier	MessageKeyModifier	O	1	Blank or P – Protection Order T – Temporary Protection Order
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, ProtectionOrderNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) Name, NCICNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]

WMPEProtectionOrderEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
BradyIndicator	BradyIndicator	O	1	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExpirationDate	ExpirationDate	M	8	
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IssueDate	IssueDate	M	8	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MessageKeyModifier	MessageKeyModifier	O	1	Blank or P – Protection Order T – Temporary Protection Order
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	O	30	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	C	20	

OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	C	8	
ProtectedPersonName	ProtectedPersonName	C	30	
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	C	9	
ProtectionOrderConditionsCode	ProtectionOrderConditionsCode	M	2	See NCIC Code Manual
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	
ServiceCode	ServiceCode	O	1	See NCIC Code Manual
ServiceDate	ServiceDate	O	8	
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, BirthDate, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, FBINumber, [Any optional fields]
3. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, MiscellaneousNumber, [Any optional fields]
4. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, SocialSecurityNumber, [Any optional fields]
5. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
6. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, [Any optional fields]
7. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]

8. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, ProtectedPersonName, ProtectedPersonSocialSecurityNumber, [Any optional fields]
9. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, ProtectedPersonName, ProtectedPersonBirthDate, [Any optional fields]
10. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, BirthDate, [Any optional fields]
11. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, FBINumber, [Any optional fields]
12. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, MiscellaneousNumber, [Any optional fields]
13. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, SocialSecurityNumber, [Any optional fields]
14. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
15. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, [Any optional fields]
16. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]
17. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, ProtectedPersonName, ProtectedPersonSocialSecurityNumber, [Any optional fields]
18. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, ProtectedPersonName, ProtectedPersonBirthDate, [Any optional fields]

WMPEProtectionOrderModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
BradyIndicator	BradyIndicator	O	1	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExpirationDate	ExpirationDate	O	8	
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual

Height	Height	O	3	
IssueDate	IssueDate	O	8	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MessageKeyModifier	MessageKeyModifier	O	1	Blank or P – Protection Order T – Temporary Protection Order
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	EPO ETO EPOC ETOC
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	
ProtectedPersonName	ProtectedPersonName	O	30	
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	
ProtectionOrderConditionsCode	ProtectionOrderConditionsCode	O	2	See NCIC Code Manual
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
ProtectionOrderNumber2	ProtectionOrderNumber2	O	15	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
ServiceCode	ServiceCode	O	1	
ServiceDate	ServiceDate	O	8	
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
TestIndicator	TestIndicator	O	1	Y, BLANK
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	

Weight	Weight	O	3	
--------	--------	---	---	--

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, ProtectionOrderNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEProtectionOrderSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateExpirationYear	LicensePlateExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	

NCICNumber	NCICNumber	C	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonName	ProtectedPersonName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderConditionCode	ProtectionOrderConditionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderNumber	ProtectionOrderNumber	C	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should

				use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) Name, ProtectionOrderNumber, OriginatingAgencyORI, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEProtectionOrderSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should

				use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateExpirationYear	LicensePlateExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonName	ProtectedPersonName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderConditionCode	ProtectionOrderConditionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderNumber	ProtectionOrderNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) Name, ProtectionOrderNumber, OriginatingAgencyORI, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESexOffenderCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [TestIndicator]
2. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI, [TestIndicator]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [TestIndicator]

WMPESexOffenderClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [TestIndicator]
2. (In/Out) Name, NCICNumber, ClearDate, OriginatingAgencyORI, [TestIndicator]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [TestIndicator]

WMPESexOffenderEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	M	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	M	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BoatColorCode	BoatColorCode	O	7	See NCIC Code Manual
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual
BoatHullNumber	BoatHullNumber	O	20	
BoatHullShapeCode	BoatHullShapeCode	O	2	

BoatLength	BoatLength	O	2	See NCIC Code Manual
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual
BoatModelName	BoatModelName	O	20	
BoatModelYear	BoatModelYear	O	4	
BoatName	BoatName	O	20	
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	
ConvictionDate	ConvictionDate	M	8	
ConvictionOffenseCode	ConvictionOffenseCode	M	4	See NCIC Code Manual
CrimeLocation	CrimeLocation	O	2	See NCIC Code Manual, State Code
DNALocation	DNALocation	O	250	
DNAIndicator	DNAIndicator	O	1	Blank, N, Y
EmailAddress	EmailAddress	O	80	
EmployerName	EmployerName	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
HomePort	HomePort	O	20	
InternetId	InternetId	O	80	
JuvenileOffenderIndicator	JuvenileOffenderIndicator	O	1	Blank, N, Y
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	C	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	M	30	
NCICNumber	NCICNumber	O	10	
Occupation	Occupation	O	80	
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	
RaceCode	RaceCode	M	1	See NCIC Code Manual
RegistrationEndDate	RegistrationEndDate	M	8	
RegistrationNumber	RegistrationNumber	O	8	
RegistrationStartDate	RegistrationStartDate	M	8	
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual
ResidenceBeginDate	ResidenceBeginDate	O	8	

ResidenceEndDate	ResidenceEndDate	O	8	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SchoolName	SchoolName	O	80	
SexCode	SexCode	M	1	See NCIC Code Manual
SexOffenderTier	SexOffenderTier	O	1	See NCIC Code Manual
SexualPredatorIndicator	SexualPredatorIndicator	O	1	Blank, N, Y
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
StateIdNumber	StateIdNumber	O	10	
TelephoneNumber	TelephoneNumber	O	12	
TelephoneType	TelephoneType	C	1	See NCIC Code Manual
TestIndicator	TestIndicator	O	1	Y, BLANK
RegistrationExpirationYear	RegistrationExpirationYear	O	2	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleOwnershipCode	VehicleOwnershipCode	O	2	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
VictimAge	VictimAge	O	2	
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) Name, SexCode, RaceCode, BirthDate, RegistrationStartDate, RegistrationEndDate, Height, Weight, HairColorCode, EyeColorCode, ConvictionOffenseCode, ConvictionDate, OriginatingAgencyCaseNumber, AddressStateCode, OriginatingAgencyORI, [Any optional fields]

WMPESexOffenderModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BoatColorCode	BoatColorCode	O	7	See NCIC Code Manual
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual
BoatHullNumber	BoatHullNumber	O	20	
BoatHullShapeCode	BoatHullShapeCode	O	2	
BoatLength	BoatLength	O	2	See NCIC Code Manual
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual
BoatModelName	BoatModelName	O	20	

BoatModelYear	BoatModelYear	O	4	
BoatName	BoatName	O	20	
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	
ConvictionDate	ConvictionDate	O	8	
ConvictionOffenseCode	ConvictionOffenseCode	O	4	See NCIC Code Manual
CrimeLocation	CrimeLocation	O	2	See NCIC Code Manual, State Code
DNALocation	DNALocation	O	250	
DNAIndicator	DNAIndicator	O	1	Blank, N, Y
EmailAddress	EmailAddress	O	80	
EmployerName	EmployerName	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
HomePort	HomePort	O	20	
InternetId	InternetId	O	80	
JuvenileOffenderIndicator	JuvenileOffenderIndicator	O	1	Blank, N, Y
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	O	10	
Occupation	Occupation	O	80	
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
RegistrationEndDate	RegistrationEndDate	O	8	
RegistrationNumber	RegistrationNumber	O	8	
RegistrationStartDate	RegistrationStartDate	O	8	
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual

RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual
ResidenceBeginDate	ResidenceBeginDate	O	8	
ResidenceEndDate	ResidenceEndDate	O	8	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SchoolName	SchoolName	O	80	
SexCode	SexCode	O	1	See NCIC Code Manual
SexOffenderTier	SexOffenderTier	O	1	See NCIC Code Manual
SexualPredatorIndicator	SexualPredatorIndicator	O	1	Blank, N, Y
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
StateIdNumber	StateIdNumber	O	10	
TelephoneNumber	TelephoneNumber	O	12	
TelephoneType	TelephoneType	O	1	See NCIC Code Manual
TestIndicator	TestIndicator	O	1	Y, BLANK
RegistrationExpirationYear	RegistrationExpirationYear	O	2	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleOwnershipCode	VehicleOwnershipCode	O	2	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
VictimAge	VictimAge	O	2	
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESexOffenderSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullNumber	BoatHullNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullShapeCode	BoatHullShapeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

BoatLength	BoatLength	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelName	BoatModelName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelYear	BoatModelYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatName	BoatName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
EmailAddress	EmailAddress	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Employer	Employer	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
InternetId	InternetId	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	

NCICNumber	NCICNumber	C	10	
Occupation	Occupation	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProfessionalLicenseNumberType	ProfessionalLicenseNumberType	O	80	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationExpirationYear	RegistrationExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationNumber	RegistrationNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SchoolName	SchoolName	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
StateldNumber	StateldNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumber	TelephoneNumber	O	12	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumberType	TelephoneNumberType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK

VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleOwnershipCode	VehicleOwnershipCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimAge	VictimAge	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESexOffenderSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullNumber	BoatHullNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullShapeCode	BoatHullShapeCode	O	2	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatLength	BoatLength	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelName	BoatModelName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelYear	BoatModelYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatName	BoatName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
EmailAddress	EmailAddress	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Employer	Employer	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
InternetId	InternetId	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
Occupation	Occupation	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProfessionalLicenseNumberType	ProfessionalLicenseNumberType	O	80	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationExpirationYear	RegistrationExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationNumber	RegistrationNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SchoolName	SchoolName	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
StateIdNumber	StateIdNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumber	TelephoneNumber	O	12	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumberType	TelephoneNumberType	O	1	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleOwnershipCode	VehicleOwnershipCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimAge	VictimAge	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESupervisedReleaseCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [Any optional fields]

WMPESupervisedReleaseClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]

WMPESupervisedReleaseEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArrestDate	ArrestDate	O	8	
ArrestingAgencyORI	ArrestingAgencyORI	O	9	
BirthDate	BirthDate	C	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EmailAddress	EmailAddress	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	
FraudulentBirthDate	FraudulentBirthDate	O	8	
FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	
FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	O	20	
FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	O	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	O	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
IncarcerationPlace	IncarcerationPlace	O	50	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual

LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ReleaseDate	ReleaseDate	O	8	
ReleaseLocation	ReleaseLocation	O	50	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SentencingCourtORI	SentencingCourtORI	O	9	
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
SupervisingOfficerName	SupervisingOfficerName	M	30	
SupervisingOfficerTelephone	SupervisingOfficerTelephone	M	12	
SupervisionStartDate	SupervisionStartDate	M	8	
SupervisionExpirationDate	SupervisionExpirationDate	M	8	
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
WarrantCourtORI	WarrantCourtORI	O	9	
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, BirthDate, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, FBINumber, [Any optional fields]
3. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, MiscellaneousNumber, [Any optional fields]
4. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate,

- SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, SocialSecurityNumber, [Any optional fields]
5. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
 6. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, [Any optional fields]
 7. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]

WMPESupervisedReleaseFraudulentDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESupervisedReleaseFraudulentDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESupervisedReleaseModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArrestDate	ArrestDate	O	8	
ArrestingAgencyORI	ArrestingAgencyORI	O	9	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EmailAddress	EmailAddress	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FraudulentBirthDate	FraudulentBirthDate	O	8	

FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	
FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	O	20	
FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	O	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	O	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IncarcerationPlace	IncarcerationPlace	O	50	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	EC EC-C
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProbationExpirationDate	ProbationExpirationDate	O	8	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ReleaseLocation	ReleaseLocation	O	50	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SentencingCourtORI	SentencingCourtORI	O	9	
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
SupervisingOfficerName	SupervisingOfficerName	O	30	
SupervisingOfficerTelephone	SupervisingOfficerTelephone	O	12	
SupervisionStartDate	SupervisionStartDate	O	8	
SupervisionReleaseDate	SupervisionReleaseDate	O	5	
TestIndicator	TestIndicator	O	1	Y, BLANK
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	

WarrantCourtORI	WarrantCourtORI	O	9	
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESupervisedReleaseSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESupervisedReleaseSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual.

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEUnidentifiedPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RecordRemovalReason	RecordRemovalReason	O	21	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) CancellationDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [RecordRemovalReason, TestIndicator]

WMPEUnidentifiedPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RecordRemovalReason	RecordRemovalReason	O	21	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) ClearDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [RecordRemovalReason, TestIndicator]

WMPEUnidentifiedPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyFoundDate	BodyFoundDate	M	8	
BodyPartsStatusCode	BodyPartsStatusCode	C	15	See NCIC Code Manual
CauseOfDeath	CauseOfDeath	O	30	
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual

CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EstimatedBirthYear	EstimatedBirthYear	C	9	
EstimatedDeathDate	EstimatedDeathDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintAvailableIndicator	FootprintAvailableIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	7	Range of values Ex. 000-000
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MedicalExaminerAgencyAndCaseNumber	MedicalExaminerAgencyAndCaseNumber	O	50	
MedicalExaminerLocality	MedicalExaminerLocality	O	30	
MedicalExaminerTelephoneNumber	MedicalExaminerTelephoneNumber	O	12	
MessageKeyModifier	MessageKeyModifier	M	1	D – Deceased L – Living V – Catastrophe Victim
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
TestIndicator	TestIndicator	O	1	Y, BLANK
Weight	Weight	M	7	Range of values Ex. 000-000
XraysAvailableIndicator	XraysAvailableIndicator	M	1	Blank, Y

Possible Combinations

1. (In/Out) MessageKeyModifier=**D** or **V**, BodyPartsStatusCode, SexCode, RaceCode, EstimatedDeathDate, BodyFoundDate, Height, Weight, EyeColorCode, HairColorCode, OriginatingAgencyCaseNumber, XraysAvailableIndicator, CauseOfDeath, OriginatingAgencyORI, [BloodTypeCode, CircumcisionCode, CorrectiveVisionPerscriptionCode, DNAIndicator, DNALocation, EstimatedBirthYear, EthnicityCode, FingerprintClassificationCode, FootprintAvailableIndicator, JewelryDescription, JewelryTypeCode, LinkageAgencyIdentifier, LinkageCaseNumber, MedicalExaminerAgencyAndCaseNumber, MedicalExaminerLocality, MedicalExaminerTelephoneNumber, MiscellaneousDescriptiveText, NotifyOriginatingAgencyIndicator, ScarsMarksTattoosCode, TestIndicator]
2. (In/Out) MessageKeyModifier=**L**, SexCode, RaceCode, BodyFoundDate, Height, Weight, EyeColorCode, HairColorCode, FingerprintClassificationCode, OriginatingAgencyCaseNumber, XraysAvailableIndicator, OriginatingAgencyORI, [BloodTypeCode, CircumcisionCode, CorrectiveVisionPerscriptionCode, DNAIndicator, DNALocation, EstimatedBirthYear, EthnicityCode, FootprintAvailableIndicator, JewelryDescription, JewelryTypeCode, LinkageAgencyIdentifier, LinkageCaseNumber, MedicalExaminerAgencyAndCaseNumber, MedicalExaminerLocality, MedicalExaminerTelephoneNumber, MiscellaneousDescriptiveText, NotifyOriginatingAgencyIndicator, ScarsMarksTattoosCode, TestIndicator]

WMPEUnidentifiedPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyFoundDate	BodyFoundDate	O	8	
BodyPartsStatusCode	BodyPartsStatusCode	O	15	See NCIC Code Manual
CauseOfDeath	CauseOfDeath	O	30	
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EstimatedBirthYear	EstimatedBirthYear	O	9	
EstimatedDeathDate	EstimatedDeathDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintAvailableIndicator	FootprintAvailableIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MedicalExaminerAgencyAndCaseNumber	MedicalExaminerAgencyAndCaseNumber	O	50	
MedicalExaminerLocality	MedicalExaminerLocality	O	30	
MedicalExaminerTelephoneNumber	MedicalExaminerTelephoneNumber	O	12	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
ModifiedMessageKey	ModifiedMessageKey	O	4	EUD - Deceased EUL - Living EUV - Catastrophe Victim
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
NCICNumber	NCICNumber	M	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
TestIndicator	TestIndicator	O	1	Y, BLANK
ValidatorName	ValidatorName	O	30	
Weight	Weight	O	3	
XraysAvailableIndicator	XraysAvailableIndicator	O	1	Blank, Y

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEUnidentifiedPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEUnidentifiedPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
CancellationDate	CancellationDate	M	8	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI, [MessageKeyModifier, OriginatingAgencyCaseNumber, PersonRecordRemovalReason, TestIndicator]
2. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [MessageKeyModifier, NCICNumber, PersonRecordRemovalReason, TestIndicator]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [MessageKeyModifier, Name, PersonRecordRemovalReason, TestIndicator]

WMPEWantedPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
HitResultsIndicator	HitResultsIndicator	O	2	See NCIC Code Manual
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	Blank, Y
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyORI	RecoveringAgencyORI	O	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, NCICNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonDetainerCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	M	20	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, NCICNumber, DetainerCaseNumber, OriginatingAgencyORI, [TestIndicator]
2. (In/Out) Name, OriginatingAgencyCaseNumber, DetainerCaseNumber, OriginatingAgencyORI, [TestIndicator]

3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, DetainerCaseNumber, OriginatingAgencyORI, [TestIndicator]

WMPEWantedPersonDetainerEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	M	20	
DetainerDate	DetainerDate	M	8	
IncarceratingAgencyORI	IncarceratingAgencyORI	M	9	
IncarcerationPlace	IncarcerationPlace	O	50	
IncarcerationStartDate	IncarcerationStartDate	O	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SentenceExpirationDate	SentenceExpirationDate	O	8	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out)
Name, NCICNumber, DetainerCaseNumber, DetainerDate, IncarceratingAgencyORI, OriginatingAgencyORI, [Any optional fields]
2. (In/Out)
Name, OriginatingAgencyCaseNumber, DetainerCaseNumber, DetainerDate, IncarceratingAgencyORI, OriginatingAgencyORI, [Any optional fields]
3. (In/Out)
NCICNumber, OriginatingAgencyCaseNumber, DetainerCaseNumber, DetainerDate, IncarceratingAgencyORI, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonDetainerModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	O	20	
DetainerDate	DetainerDate	O	8	
IncarceratingAgencyORI	IncarceratingAgencyORI	O	9	
IncarcerationPlace	IncarcerationPlace	O	50	
IncarcerationStartDate	IncarcerationStartDate	O	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SentenceExpirationDate	SentenceExpirationDate	O	8	
TestIndicator	TestIndicator	O	1	Y, BLANK
ValidatorName	ValidatorName	O	30	

Possible Combinations

1. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalOffenseIndicator	AdditionalOffenseIndicator	O	1	Blank, Y

AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	C	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
DocumentedAddressDate	DocumentedAddressDate	O	8	
EmancipationDate	EmancipationDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExtraditionLimitation	ExtraditionLimitation	M	2	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FraudulentBirthDate	FraudulentBirthDate	O	8	
FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	
FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	C	20	
FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	C	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	C	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
IncidentDate	IncidentDate	C	8	Warrant or violation date
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
NotifyOriginatingAgency	NotifyOriginatingAgency	O	1	Blank, Y
OffenseCode	OffenseCode	M	4	
OffenseCodeDescription	OffenseCodeDescription	O	20	
OperatorLicenseYear	OperatorLicenseYear	C	4	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OriginalOffenseCode	OriginalOffenseCode	C	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	

OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	3	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
TestIndicator	TestIndicator	O	1	Y, BLANK
WantedPersonType	WantedPersonType	O	1	Blank, J – Wanted Juvenile
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	M	3	

*Operator License fields must be entered as a set.

*License Plate fields must be entered as a set.

*VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, and VehicleStyleCode must be entered as a set.

Possible Combinations

1. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, BirthDate, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FBINumber [Any optional fields]
3. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, MiscellaneousNumber [Any optional fields]
4. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, SocialSecurityNumber [Any optional fields]
5. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseExpirationYear, [Any optional fields]
6. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, LicensePlateNumber, LicensePlateStateCode, LicensePlateExpirationYear, LicensePlateTypeCode, [Any optional fields]
7. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]
8. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentName, FraudulentBirthDate, [Any optional fields]

9. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentMiscellaneousNumber, [Any optional fields]
10. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentSocialSecurityNumber, [Any optional fields]
11. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentOperatorLicenseNumber, FraudulentOperatorLicenseStateCode, FraudulentOperatorLicenseExpirationYear, [Any optional fields]
12. (In/Out) OriginatingAgencyORI, WantedPersonType, Name, SexCode, RaceCode, BrithDate, EmancipationDate, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, [Any optional fields]

WMPEWantedPersonFraudulentDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonFraudulentDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
Extradition	Extradition	M	4	See NCIC Code Manual
HitResultsIndicator	HitResultsIndicator	O	2	See NCIC Code Manual
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	Blank, Y
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	
TestIndicator	TestIndicator	O	1	Y, BLANK

Possible Combinations

1. (In/Out) Name, NCICNumber, Extradition, RecoveryDate, OriginatingAgencyORI, [Any optional fields]

2. (In/Out) Name, OriginatingAgencyCaseNumber, Extradition, RecoveryDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, Extradition, RecoveryDate, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalOffenseIndicator	AdditionalOffenseIndicator	O	1	Blank, Y
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	
DNALocation	DNALocation	O	250	Blank, Y
DocumentedAddressDate	DocumentedAddressDate	O	8	
EmancipationDate	EmancipationDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExtraditionLimitation	ExtraditionLimitation	O	2	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IncidentDate	IncidentDate	C	8	Warrant or violation date
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	Blank EW – Wanted Person EWJ – Wanted Juvenile ET – Temporary Felony EW-C – Wanted Person with Caution EWJC – Wanted Juvenile with Caution ET-C – Temporary Felony with Caution
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	

Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgency	NotifyOriginatingAgency	O	1	Blank, Y
OffenseCode	OffenseCode	O	4	See NCIC Code Manual
OffenseCodeDescription	OffenseCodeDescription	O	20	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	
OperatorLicenseYear	OperatorLicenseYear	O	4	See NCIC Code Manual
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
TestIndicator	TestIndicator	O	1	Y, BLANK
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressCounty	AddressCounty	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetName	AddressStreetName	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetNumber	AddressStreetNumber	O	7	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

AddressTypeCode	AddressTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressZipCode	AddressZipCode	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	

ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressCounty	AddressCounty	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetName	AddressStreetName	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetNumber	AddressStreetNumber	O	7	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressTypeCode	AddressTypeCode	O	2	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressZipCode	AddressZipCode	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

*Operator License fields must be entered as a set.

*License Plate fields must be entered as a set.

*VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, and VehicleStyleCode must be entered as a set.

*Address fields must be entered as a set.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

Wanted Missing Person Inquiries (WMP-I)

WMPIMissingPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	M	2	Numeric; See NCIC manual
AreaCode	AreaCode	O	3	Alphanumeric; See NCIC code manual
EthnicityCode	EthnicityCode	M	1	Alphabetic: H, N. See NCIC code manual.
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Alphabetic: Y, N, or blank
EyeColorCode	EyeColorCode	M	3	Alphabetic; See NCIC code manual.
HairColorCode	HairColorCode	M	3	Alphabetic; See NCIC code manual.
Height	Height	M	3	Alphanumeric; See NCIC code manual

Name	Name	O	30	Alphanumeric; See NCIC manual
RaceCode	RaceCode	M	1	Alphabetic: I, A, B, W, U. See NCIC code manual
SexCode	SexCode	M	1	Alpha: M, F, U
TestIndicator	TestIndicator	O	1	Y, BLANK
Weight	Weight	M	3	Alphanumeric; See NCIC code manual

Possible Combinations

1. (In/Out) Age, EthnicityCode, EyeColorCode, HairColorCode, Height, RaceCode, SexCode Weight, [AreaCode, ExpandedNameSearchCode, Name, TestIndicator]

WMPProtectionOrderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	Numeric-Date. See NCIC manual
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Numeric: 0, 1, 2, 3 – See NCIC manual
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Alphabetic: Y, N, or blank
FBINumber	FBINumber	O	9	Alphanumeric. See NCIC manual
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y, N, or blank
LicensePlateNumber	LicensePlateNumber	C	10	Alphanumeric. See NCIC manual
LicensePlateStateCode	LicensePlateStateCode	C	2	Alphanumeric; See NCIC code manual
MiscellaneousNumber	MiscellaneousNumber	O	15	Alphanumeric, Special chars, See NCIC code manual
Name	Name	C	30	Alphanumeric; See NCIC manual
NCICNumber	NCICNumber	C	10	Alphanumeric. See NCIC manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	Alphanumeric. See NCIC manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	Alphanumeric, Special chars, See NCIC code manual
ProtectionOrderNumber	ProtectionOrderNumber	C	15	Alphanumeric, Special chars, See NCIC code manual
RaceCode	RaceCode	O	1	Alphabetic: I, A, B, W, U. See NCIC code manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Alphabetic: Y, N, or blank
SexCode	SexCode	O	1	Alpha: M, F, U
SocialSecurityNumber	SocialSecurityNumber	O	9	Numeric
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	Alphanumeric, See NCIC manual
VehicleMakeCode	VehicleMakeCode	C	24	Alphanumeric, See NCIC manual

Possible Combinations

1. (In/Out) Name, [BirthDate, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBINumber, ImageIndicator, MiscellaneousNumber, OperatorLicenseNumber, RaceCode, RelatedHitSearchIndicator, SexCode, SocialSecurityNumber, TestIndicator]
2. (In/Out) LicensePlateNumber, LicensePlateStateCode, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator, VehicleIdentificationNumber, VehicleMakeCode]
3. (In/Out) VehicleIdentificationNumber, VehicleMakeCode, [ImageIndicator, LicensePlateNumber, LicensePlateStateCode, RelatedHitSearchIndicator, TestIndicator]
4. (In/Out) Name, OriginatingAgencyCaseNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
5. (In/Out) Name, ProtectionOrderNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
6. (In/Out) NCICNumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]

WMPISexOffenderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressZipCode	AddressZipCode	C	10	Numeric, Special chars, See NCIC manual
BirthDate	BirthDate	O	8	Numeric-Date. See NCIC manual
BoatHullIdNumber	BoatHullIdNumber	O	20	Alphanumeric. See NCIC manual

ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Numeric: 0, 1, 2, 3 – See NCIC manual
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Alphabetic: Y, N, or blank
FBI Number	FBI Number	O	9	Alphanumeric. See NCIC manual
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y, N, or blank
LicensePlateNumber	LicensePlateNumber	O	10	Alphanumeric. See NCIC manual
LicensePlateStateCode	LicensePlateStateCode	O	2	Alphanumeric; See NCIC code manual
MiscellaneousNumber	MiscellaneousNumber	O	15	Alphanumeric, Special chars, See NCIC code manual
Name	Name	C	30	Alphanumeric; See NCIC manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	Alphanumeric. See NCIC manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	Alphanumeric, Special chars, See NCIC code manual
RaceCode	RaceCode	O	1	Alphabetic: I, A, B, W, U. See NCIC code manual
RegistrationNumber	RegistrationNumber	O	8	Alphanumeric. See NCIC manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Alphabetic: Y, N, or blank
SexCode	SexCode	O	1	Alpha: M, F, U
SexualOffenderStatusIndicator	SexualOffenderStatusIndicator	O	1	Alphabetic: Y, N, or blank. See NCIC manual.
SocialSecurityNumber	SocialSecurityNumber	O	9	Numeric
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	Alphanumeric, See NCIC manual
VehicleMakeCode	VehicleMakeCode	O	24	Alphanumeric, See NCIC manual

Possible Combinations

1. (In/Out) Name, [BirthDate, BoatHullIdNumber, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBI Number, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, MiscellaneousNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, RaceCode, RegistrationNumber, RelatedHitSearchIndicator, SexCode, SocialSecurityNumber, TestIndicator, VehicleIdentificationNumber, VehicleMakeCode]
2. (In/Out) AddressZipCode, [ImageIndicator, RelatedHitSearchIndicator, SexualOffenderStatusIndicator, TestIndicator]
3. (In/Out) Name, OriginatingAgencyCaseNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, TestIndicator]

WMPIUnidentifiedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	C	2	Numeric
AreaCode	AreaCode	O	3	Alphanumeric; See NCIC code manual
BodyPartsStatusCode	BodyPartsStatusCode	C	15	Alphabetic; See NCIC code manual
EthnicityCode	EthnicityCode	O	1	Alphabetic: H, N. See NCIC code manual.
EyeColorCode	EyeColorCode	C	3	Alphabetic; See NCIC code manual.
HairColorCode	HairColorCode	C	3	Alphabetic; See NCIC code manual.
Height	Height	C	3	Numeric; See NCIC code manual.
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y, N, or blank
NCICNumber	NCICNumber	C	10	Alphanumeric. See NCIC manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	Alphanumeric, Special chars, See NCIC code manual
RaceCode	RaceCode	C	1	Alphabetic: I, A, B, W, U. See NCIC code manual
SexCode	SexCode	C	1	Alpha: M, F, U
TestIndicator	TestIndicator	O	1	Y, BLANK

Weight	Weight	C	3	Alphanumeric; See NCIC code manual
--------	--------	---	---	------------------------------------

Possible Combinations

1. (In/Out) BodyPartsStatusCode, [AreaCode, EthnicityCode, ImageIndicator, RaceCode, SexCode, TestIndicator]
2. (In/Out) Age, EyeColorCode, HairColorCode, Height, Weight, RaceCode, SexCode [AreaCode, EthnicityCode, ImageIndicator, TestIndicator]
3. (In/Out) NCICNumber, [ImageIndicator, TestIndicator]
4. (In/Out) OriginatingAgencyCaseNumber, [ImageIndicator, TestIndicator]

WMPIWantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	Numeric-Date. See NCIC manual
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Numeric: 0, 1, 2, 3 – See NCIC manual
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Alphabetic: Y, N, or blank
FBINumber	FBINumber	O	9	Alphanumeric. See NCIC manual
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y, N, or blank
LicensePlateNumber	LicensePlateNumber	O	10	Alphanumeric. See NCIC manual
LicensePlateStateCode	LicensePlateStateCode	O	2	Alphanumeric; See NCIC code manual
MiscellaneousNumber	MiscellaneousNumber	O	15	Alphanumeric, Special chars, See NCIC code manual
Name	Name	O	30	Alphanumeric; See NCIC manual
NCICNumber	NCICNumber	O	10	Alphanumeric. See NCIC manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	Alphanumeric. See NCIC manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	Alphanumeric, Special chars, See NCIC code manual
RaceCode	RaceCode	O	1	Alphabetic: I, A, B, W, U. See NCIC code manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Alphabetic: Y, N, or blank
SexCode	SexCode	O	1	Alpha: M, F, U
SocialSecurityNumber	SocialSecurityNumber	O	9	Numeric
TestIndicator	TestIndicator	O	1	Y, BLANK
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	Alphanumeric, See NCIC manual
VehicleMakeCode	VehicleMakeCode	O	24	Alphanumeric, See NCIC manual

Possible Combinations

1. (In/Out) Name, [BirthDate, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, FBINumber, ImageIndicator, MiscellaneousNumber, OperatorLicenseNumber, RaceCode, RelatedHitSearchIndicator, SexCode, SocialSecurityNumber, TestIndicator]
2. (In/Out) LicensePlateNumber, LicensePlateStateCode, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator, VehicleIdentificationNumber, VehicleMakeCode]
3. (In/Out) VehicleIdentificationNumber, VehicleMakeCode, [ImageIndicator, LicensePlateNumber, LicensePlateStateCode, RelatedHitSearchIndicator, TestIndicator]
4. (In/Out) Name, OriginatingAgencyCaseNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, TestIndicator]
5. (In/Out) NCICNumber, [ImageIndicator, RelatedHitSearchIndicator, TestIndicator]

Expanded Transactions Supported:

NBLojackQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LoJackReplyCode	LoJackReplyCode	O	5	
MessageKeyModifier	MessageKeyModifier	M	1	

OperationCode	OperationCode	M	5	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	

Possible Combinations

1. (In/Out) MessageKeyModifier, OperationCode, OriginatingAgencyORI, [LoJackReplyCode]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- NSP OFML Interface Specification