

New Mexico (NM) NMLETS OFML

[Disclaimer Statement](#)

Transport:

TCPIP (Fox Talk)

Routing and Configuration Information:

Mnemonic Routing

- The NMLETS assigned ORI for a device (or for the site) should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.
- The NMLETS assigned mnemonic or terminal id for a device should be placed in the **<Authentication>/<Mnemonic>** field in the ConnectCIC header.
- The NMLETS assigned user id for a person should be placed in the **<Authentication>/<UserName>** field in the ConnectCIC header.

Security Requirements:

None known at this time.

Logon Requirements:

No login is required by NMLETS.

Certification Requirements:

Agency sponsor is required.

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	20	
RegistrationNumber	RegistrationNumber	C	8	
State	State	O	2	

Possible Combinations

1. (In/Out) BoatHullIdNumber, [State]
2. (In/Out) RegistrationNumber, [State]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
PurposeCode	PurposeCode	O	1	
SexCode	SexCode	C	1	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, [Attention, PurposeCode, State, State2, State3, State4, State5]
2. (In/Out) OperatorLicenseNumber, [Attention, PurposeCode, State, State2, State3, State4, State5]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	C	1	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, [State, State2, State3, State4, State5]
2. (In/Out) OperatorLicenseNumber, [State, State2, State3, State4, State5]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	O	10	
GunModel	GunModel	O	20	

GunSerialNumber	GunSerialNumber	M	20	
-----------------	-----------------	---	----	--

Possible Combinations

1. (In/Out) GunSerialNumber, [GunCaliber, GunMake, GunModel]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	20	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In/Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, [State, State2, State3, State4, State5]
2. (In/Out) VehicleIdentificationNumber, [State, State2, State3, State4, State5, VehicleMakeCode, VehicleYear]

Transactions Supported:

Basic Entry Package (BEP)

BEPStolenArticleCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	C	20	
ArticleSerialNumber2	ArticleSerialNumber2	C	20	
CancellationDate	CancellationDate	M	8	
NCICNumber	NCICNumber	M	10	
MessageKeyModifier	MessageKeyModifier	O	1	Blank – Stolen Article L – Lost Article
MessageKeyModifier2	MessageKeyModifier2	C	1	Blank – Single Article A – Multiple serialized articles
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OwnerAppliedNumber	OwnerAppliedNumber	C	20	
PropertyRecordRemovalReason	PropertyRecordRemovalReason	O	21	

Possible Combinations

1. **MessageKeyModifier2 = BLANK:** CancellationDate, NCICNumber, ArticleSerialNumber, OriginatingAgencyORI, [Optional fields]
2. **MessageKeyModifier2 = BLANK:** CancellationDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]
3. **MessageKeyModifier2 = BLANK:** CancellationDate, NCICNumber, OwnerAppliedNumber, OriginatingAgencyORI, [Optional fields]

4. **MessageKeyModifier2 = A:** CancellationDate, NCICNumber, ArticleSerialNumber, ArticleSerialNumber2, OriginatingAgencyORI, [Optional fields]
5. **MessageKeyModifier2 = A:** CancellationDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]

BEPStolenArticleClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	C	20	
ArticleSerialNumber2	ArticleSerialNumber2	C	20	
ClearDate	ClearDate	M	8	
MessageKeyModifier	MessageKeyModifier	O	1	Blank – Stolen Article L – Lost article
MessageKeyModifier2	MessageKeyModifier2	C	1	Blank – Single Article A – Multiple serialized articles
NCICNumber	NCICNumber	M	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OwnerAppliedNumber	OwnerAppliedNumber	C	20	
ReasonForPropertyRecordRemoval	PropertyRecordRemovalReason	O	21	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyIdentifier	RecoveringAgencyORI	O	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	

Possible Combinations

1. **MessageKeyModifier2 = BLANK:** ClearDate, NCICNumber, ArticleSerialNumber, OriginatingAgencyORI, [Optional fields]
2. **MessageKeyModifier2 = BLANK:** ClearDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]
3. **MessageKeyModifier2 = BLANK:** ClearDate, NCICNumber, OwnerAppliedNumber, OriginatingAgencyORI, [Optional fields]
4. **MessageKeyModifier2 = A:** ClearDate, NCICNumber, ArticleSerialNumber, ArticleSerialNumber2, OriginatingAgencyORI, [Optional fields]
5. **MessageKeyModifier2 = A:** ClearDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]

BEPStolenArticleEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleModel	ArticleModel	O	9	
ArticleSerialNumber	ArticleSerialNumber	C	20	
ArticleSerialNumber2	ArticleSerialNumber2	C	20	
ArticleTypeCode	ArticleTypeCode	M	7	
BrandName	BrandName	M	6	
HazardousMaterialsContainer	HazardousMaterialsContainer	O	25	
HoldForPrintsIndicator	HoldForPrintsIndicator	O	1	Blank Y – Hold for prints
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LotNumber	LotNumber	O	20	

MessageKeyModifier	MessageKeyModifier	O	1	Blank – Stolen Article L – Lost article
MessageKeyModifier2	MessageKeyModifier2	C	1	Blank – Single Article A – Multiple serialized articles
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	200	
NCICPublicDisseminationCode	NCICPublicDisseminationCode	M	8	Must be IN, OUT, or a date CCYYMMDD
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Y, BLANK
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OwnerAppliedNumber	OwnerAppliedNumber	C	20	
PartialLotIndicator	PartialLotIndicator	O	1	C - Complete P - Partial
TheftDate	TheftDate	M	8	
UnitedNationsNumber	UnitedNationsNumber	O	4	

Possible Combinations

1. **MessageKeyModifier2 = BLANK:**ArticleSerialNumber, ArticleTypeCode, BrandName, NCICPublicDisseminationCode, OriginatingAgencyCaseNumber, OriginatingAgencyORI, TheftDate, [Optional fields]
2. **MessageKeyModifier2 = BLANK:**OwnerAppliedNumber, ArticleTypeCode, BrandName, NCICPublicDisseminationCode, OriginatingAgencyCaseNumber, OriginatingAgencyORI, TheftDate, [Optional fields]
3. **MessageKeyModifier2 = BLANK:**ArticleSerialNumber, OwnerAppliedNumber, ArticleTypeCode, BrandName, NCICPublicDisseminationCode, OriginatingAgencyCaseNumber, OriginatingAgencyORI, TheftDate, [Optional fields]
4. **MessageKeyModifier2 = A:**ArticleSerialNumber, ArticleSerialNumber2, ArticleTypeCode, BrandName, NCICPublicDisseminationCode, OriginatingAgencyCaseNumber, OriginatingAgencyORI, TheftDate, [Optional fields]

BEPStolenArticleLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	C	20	
ArticleSerialNumber2	ArticleSerialNumber2	C	20	
MessageKeyModifier	MessageKeyModifier	O	1	Blank – Stolen Article L – Lost article
MessageKeyModifier2	MessageKeyModifier2	C	1	Blank – Single Article A – Multiple serialized articles
NCICNumber	NCICNumber	M	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OwnerAppliedNumber	OwnerAppliedNumber	C	20	
ReasonForPropertyRecordRemoval	PropertyRecordRemovalReason	O	21	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	

Possible Combinations

1. **MessageKeyModifier2 = BLANK:** NCICNumber, ArticleSerialNumber, OriginatingAgencyORI, RecoveryDate, [Optional fields]

2. **MessageKeyModifier2 = BLANK:** NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, RecoveryDate, [Optional fields]
3. **MessageKeyModifier2 = BLANK:** NCICNumber, OwnerAppliedNumber, OriginatingAgencyORI, RecoveryDate, [Optional fields]
4. **MessageKeyModifier2 = A:** NCICNumber, ArticleSerialNumber, ArticleSerialNumber2, OriginatingAgencyORI, RecoveryDate, [Optional fields]
5. **MessageKeyModifier2 = A:** NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, RecoveryDate, [Optional fields]

BEPStolenArticleModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleModel	ArticleModel	O	9	
ArticleSerialNumber	ArticleSerialNumber	C	20	
ArticleSerialNumber2*	ArticleSerialNumber2*	*	20	* -Used to MODIFY single article. (O) Used to IDENTIFY serialized articles. (C)
ArticleTypeCode	ArticleTypeCode	O	7	
BrandName	BrandName	O	6	
FormORI	FormORI	O	9	Modify the ORI on the record
HazardousMaterialsContainer	HazardousMaterialsContainer	O	25	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LotNumber	LotNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	Blank – Stolen Article L – Lost article
MessageKeyModifier2	MessageKeyModifier2	C	1	Blank – Single Article A – Multiple serialized articles
ModifyMessageKey	ModifyMessageKey	O	4	EA - Stolen Article ELA - Lost Article EAA- Stolen Article, Serialized ELAA - Lost Article, Serialized
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	200	
NCICNumber	NCICNumber	M	10	
NCICPublicDisseminationCode	NCICPublicDisseminationCode	O	8	Must be IN, OUT, or a date CCYYMMDD
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Y, BLANK
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OwnerAppliedNumber	OwnerAppliedNumber	C	20	
OwnerAppliedNumber2	OwnerAppliedNumber2	O	20	
PartialLotIndicator	PartialLotIndicator	O	1	C - Complete P - Partial
TheftDate	TheftDate	O	8	
UnitedNationsNumber	UnitedNationsNumber	O	4	

Possible Combinations

1. **MessageKeyModifier2 = BLANK:** NCICNumber, ArticleSerialNumber, OriginatingAgencyORI, [Optional fields]
2. **MessageKeyModifier2 = BLANK:** NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]
3. **MessageKeyModifier2 = BLANK:** NCICNumber, OwnerAppliedNumber, OriginatingAgencyORI, [Optional fields]
4. **MessageKeyModifier2 = A:** NCICNumber, ArticleSerialNumber, ArticleSerialNumber2, OriginatingAgencyORI, [Optional fields]

5. **MessageKeyModifier2 = A:** NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]

BEPStolenBoatCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullNumber	BoatHullNumber	C	20	
CancellationDate	CancellationDate	M	8	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PropertyRecordRemovalReason	PropertyRecordRemovalReason	O	21	
RegistrationNumber	RegistrationNumber	C	8	

Possible Combinations

1. (In/Out) CancellationDate, OriginatingAgencyCaseNumber, OriginatingAgencyORI, BoatHullNumber, [PropertyRecordRemovalReason]
2. (In/Out) CancellationDate, OriginatingAgencyCaseNumber, OriginatingAgencyORI, RegistrationNumber, [PropertyRecordRemovalReason]
3. (In/Out) CancellationDate, OriginatingAgencyCaseNumber, OriginatingAgencyORI, NCICNumber, [PropertyRecordRemovalReason]

BEPStolenBoatClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullNumber	BoatHullNumber	C	20	
ClearDate	ClearDate	M	8	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PropertyRecordRemovalReason	PropertyRecordRemovalReason	O	21	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyORI	RecoveringAgencyORI	O	9	
RegistrationNumber	RegistrationNumber	C	8	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	

Possible Combinations

1. (In/Out) ClearDate, OriginatingAgencyCaseNumber, OriginatingAgencyORI, BoatHullNumber, [Optional fields]
2. (In/Out) ClearDate, OriginatingAgencyCaseNumber, OriginatingAgencyORI, RegistrationNumber, [Optional fields]
3. (In/Out) ClearDate, OriginatingAgencyCaseNumber, OriginatingAgencyORI, NCICNumber, [Optional fields]

BEPStolenBoatEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatColorCode	BoatColorCode	O	7	
BoatFlagCode	BoatFlagCode	O	1	A - Occupants were armed at the time of theft

				P - Hold boat/trailer for latent fingerprints F - Both-occupants armed, plus hold for prints
BoatHullMaterialCode	BoatHullMaterialCode	O	2	
BoatHullNumber	BoatHullNumber	C	20	
BoatHullShapeCode	BoatHullShapeCode	O	2	
BoatLength	BoatLength	O	2	
BoatMakeCode	BoatMakeCode	M	24	
BoatModelName	BoatModelName	O	20	
BoatModelYear	BoatModelYear	M	4	
BoatName	BoatName	O	20	
BoatPropulsionCode	BoatPropulsionCode	O	2	
BoatTypeCode	BoatTypeCode	O	3	
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	
HomePort	HomePort	O	20	
ImageNCICNumber*	ImageNCICNumber*	O	10	
ImageTypeCode*	ImageTypeCode*	O	1	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	200	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Y, BLANK
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OwnerAppliedNumber	OwnerAppliedNumber	C	20	
RegistrationExpirationYear**	RegistrationExpirationYear**	C	4	
RegistrationNumber**	RegistrationNumber**	C	8	
RegistrationStateCode**	RegistrationStateCode**	C	2	
TheftDate	TheftDate	M	8	

* - If supplied, must be supplied as a set

** - If supplied, must be supplied as a set

Possible Combinations

1. (In/Out) BoatMakeCode, BoatModelYear, OriginatingAgencyCaseNumber, OriginatingAgencyORI, TheftDate, RegistrationNumber, RegistrationStateCode, RegistrationExpirationYear, [Optional fields]
2. (In/Out) BoatMakeCode, BoatModelYear, OriginatingAgencyCaseNumber, OriginatingAgencyORI, TheftDate, BoatHullNumber, [Optional fields]
3. (In/Out) BoatMakeCode, BoatModelYear, OriginatingAgencyCaseNumber, OriginatingAgencyORI, TheftDate, OwnerAppliedNumber, [Optional fields]

BEPStolenBoatLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullNumber	BoatHullNumber	C	20	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PropertyRecordRemovalReason	PropertyRecordRemovalReason	O	21	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	

RecoveryDate	RecoveryDate	M	8	
RegistrationNumber	RegistrationNumber	C	8	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	

Possible Combinations

1. (In/Out) RecoveryDate, OriginatingAgencyCaseNumber, OriginatingAgencyORI, BoatHullNumber, [Optional fields]
2. (In/Out) RecoveryDate, OriginatingAgencyCaseNumber, OriginatingAgencyORI, RegistrationNumber, [Optional fields]
3. (In/Out) RecoveryDate, OriginatingAgencyCaseNumber, OriginatingAgencyORI, NCICNumber, [Optional fields]

BEPStolenBoatModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatColorCode	BoatColorCode	O	7	
BoatHullNumber	BoatHullNumber	C	20	
BoatHullNumber2	BoatHullNumber2	O	20	
BoatHullShapeCode	BoatHullShapeCode	O	2	
BoatLength	BoatLength	O	2	
BoatMakeCode	BoatMakeCode	O	24	
BoatModelName	BoatModelName	O	20	
BoatModelYear	BoatModelYear	O	4	
BoatName	BoatName	O	20	
BoatHullMaterialCode	BoatHullMaterialCode	O	2	
BoatPropulsionCode	BoatPropulsionCode	O	2	
BoatTypeCode	BoatTypeCode	O	3	
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	
FormORI	FormORI	O	9	Modifies the ORI on the record
HomePort	HomePort	O	20	
ImageNCICNumber	ImageNCICNumber	O	10	
ImageTypeCode	ImageTypeCode	O	1	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	200	
ModifyMessageKey	ModifyMessageKey	O	4	EB, Stolen Boat EB-A, Stolen Boat, Occupants Armed EB-P, Stolen Boat, Hold for Prints EB-F, Stolen Boat, Occupants Armed and Hold for Prints
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Y, BLANK
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OwnerAppliedNumber	OwnerAppliedNumber	O	20	
RegistrationExpirationYear	RegistrationExpirationYear	O	4	
RegistrationNumber	RegistrationNumber	C	8	
RegistrationNumber2	RegistrationNumber2	O	8	
RegistrationStateCode	RegistrationStateCode	O	2	
TheftDate	TheftDate	O	8	

ValidatorName	ValidatorName	O	30	
---------------	---------------	---	----	--

Possible Combinations

1. (In/Out) OriginatingAgencyCaseNumber, OriginatingAgencyORI, NCICNumber, [Any optional fields]
2. (In/Out) OriginatingAgencyCaseNumber, OriginatingAgencyORI, BoatHullNumber, [Any optional fields]
3. (In/Out) OriginatingAgencyCaseNumber, OriginatingAgencyORI, RegistrationNumber, [Any optional fields]

BEPStolenGunCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
GunSerialNumber	GunSerialNumber	C	20	
MessageKeyModifier	MessageKeyModifier	O	1	BLANK - Stolen L - Lost F - Felony R – Recovered
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PropertyRecordRemovalReason	PropertyRecordRemovalReason	O	21	

Possible Combinations

1. **MessageKeyModifier = “,L, F, R:** CancellationDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, NCICNumber, [Optional fields]
2. **MessageKeyModifier = “,L, F, R:** CancellationDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, GunSerialNumber, [Optional fields]
3. **MessageKeyModifier = R:** CancellationDate, OriginatingAgencyORI, GunSerialNumber, NCICNumber, [Optional fields]

BEPStolenGunClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
IncidentDate	IncidentDate	*	8	Date of Clear for Stolen/Lost/Felony Gun (M*) Date of Theft for Recovered Gun (O*)
GunSerialNumber	GunSerialNumber	C	20	
MessageKeyModifier	MessageKeyModifier	O	1	BLANK - Stolen L - Lost F - Felony R – Recovered
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PropertyRecordRemovalReason	PropertyRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyORI	RecoveringAgencyORI	O	9	

Possible Combinations

1. **MessageKeyModifier** = ",L, F, R: OriginatingAgencyORI, OriginatingAgencyCaseNumber, NCICNumber, [IncidentDate*, Optional fields]
2. **MessageKeyModifier** = ",L, F, R: OriginatingAgencyORI, OriginatingAgencyCaseNumber, GunSerialNumber, [IncidentDate*, Optional fields]
3. **MessageKeyModifier** = R: OriginatingAgencyORI, GunSerialNumber, NCICNumber, [IncidentDate*, Optional fields]

BEPStolenGunEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	M	4	
GunMake	GunMake	M	24	
GunModel	GunModel	O	20	
GunSerialNumber	GunSerialNumber	M	20	
GunTypeCode	GunTypeCode	M	2	
HoldForPrintsIndicator	HoldForPrintsIndicator	O	1	Y, BLANK
IncidentDate	IncidentDate	M	8	Date of Clear for Stolen/Lost/Felony Gun Date of Theft for Recovered Gun
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	BLANK - Stolen L - Lost F - Felony R - Recovered
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	M	200	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Y, BLANK
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	

Possible Combinations

1. (In/Out) GunCaliber, GunMake, GunSerialNumber, GunTypeCode, IncidentDate, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]

BEPStolenGunLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
GunSerialNumber	GunSerialNumber	C	20	
MessageKeyModifier	MessageKeyModifier	O	1	BLANK - Stolen L - Lost F - Felony
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PropertyRecordRemovalReason	PropertyRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	

Possible Combinations

1. **MessageKeyModifier** = ",L, F: OriginatingAgencyORI, OriginatingAgencyCaseNumber, NCICNumber, RecoveryDate, [Optional fields]
2. **MessageKeyModifier** = ",L, F: OriginatingAgencyORI, OriginatingAgencyCaseNumber, GunSerialNumber, RecoveryDate, [Optional fields]

BEPStolenGunModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FormORI	FormORI	O	9	Modifies the ORI on the record
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	O	24	
GunModel	GunModel	O	20	
GunSerialNumber	GunSerialNumber	C	20	
GunSerialNumber2	GunSerialNumber2	O	20	
GunTypeCode	GunTypeCode	O	2	
IncidentDate	IncidentDate	O	8	Date of Clear for Stolen/Lost/Felony Gun Date of Theft for Recovered Gun
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	BLANK - Stolen L - Lost F - Felony R - Recovered
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	200	
ModifyMessageKey	ModifyMessageKey	O	5	EG - Enter Stolen Gun ELG - Enter Lost Gun ERG - Enter Recovered Gun EFG - Enter Felony Gun EG-P - Enter Stolen Gun, Hold for prints ELG-P - Enter Lost Gun, Hold for prints ERG-P - Enter Recovered Gun, Hold for prints EFG-P - Enter Felony Gun, Hold for prints
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Y, BLANK
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ValidatorName	ValidatorName	O	30	

Possible Combinations

1. **MessageKeyModifier** = ",L, F, R: OriginatingAgencyORI, OriginatingAgencyCaseNumber, NCICNumber, [Optional fields]
2. **MessageKeyModifier** = ",L, F, R: OriginatingAgencyORI, OriginatingAgencyCaseNumber, GunSerialNumber, [Optional fields]
3. **MessageKeyModifier** = R: OriginatingAgencyORI, GunSerialNumber, NCICNumber, [Optional fields]

BEPStolenPlateCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
LicensePlateNumber	LicensePlateNumber	C	10	

NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PropertyRecordRemovalReason	PropertyRecordRemovalReason	O	21	

Possible Combinations

1. (In/Out) CancellationDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, NCICNumber, [Optional fields]
2. (In/Out) CancellationDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, LicensePlateNumber, [Optional fields]

BEPStolenPlateClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
LicensePlateNumber	LicensePlateNumber	C	20	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PropertyRecordRemovalReason	PropertyRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyORI	RecoveringAgencyORI	O	9	

Possible Combinations

1. (In/Out) ClearDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, NCICNumber, [Optional fields]
2. (In/Out) ClearDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, LicensePlateNumber, [Optional fields]

BEPStolenPlateEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CautionIndicator	CautionIndicator	O	1	A - Occupants are armed P - Hold for latent prints F - Both A and P
LicensePlateNumber	LicensePlateNumber	M	10	
LicensePlateStateCode	LicensePlateStateCode	M	2	
LicensePlateTypeCode	LicensePlateTypeCode	M	2	
LicensePlateYear	LicensePlateYear	M	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	200	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Y, BLANK
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
TheftDate	TheftDate	M	8	

Possible Combinations

1. (In/Out) OriginatingAgencyCaseNumber, OriginatingAgencyORI, TheftDate, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, LicensePlateYear, [Optional fields]

BEPStolenPlateLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
LicensePlateNumber	LicensePlateNumber	C	20	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PropertyRecordRemovalReason	PropertyRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	

Possible Combinations

1. (In/Out) RecoveryDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, NCICNumber, [Optional fields]
2. (In/Out) RecoveryDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, LicensePlateNumber, [Optional fields]

BEPStolenPlateModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CautionIndicator	CautionIndicator	O	1	A - Occupants are armed P - Hold for latent prints F - Both A and P
FormORI	FormORI	O	9	Modifies the ORI on the record
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateNumber2	LicensePlateNumber2	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	O	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	200	
ModifyMessageKey	ModifyMessageKey	O	4	EL - Enter stolen plate EL-A - Enter stolen plate, occupants are armed EL-P - Enter stolen plate, hold for latent prints EL-F - Enter stolen plate, occupants are armed and hold for latent prints
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Y, BLANK
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
TheftDate	TheftDate	O	8	

ValidatorName	ValidatorName	O	30	
---------------	---------------	---	----	--

Possible Combinations

1. (In/Out) OriginatingAgencyORI, OriginatingAgencyCaseNumber, NCICNumber, [Optional fields]
2. (In/Out) OriginatingAgencyORI, OriginatingAgencyCaseNumber, LicensePlateNumber, [Optional fields]

BEPStolenVehicleCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
LicensePlateNumber	LicensePlateNumber	C	10	
NCICNumber	NCICNumber	C	10	
MessageKeyModifier	MessageKeyModifier	O	1	BLANK – Stolen Vehicle F – Felony Vehicle
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PropertyRecordRemovalReason	PropertyRecordRemovalReason	O	21	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In/Out) CancellationDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, NCICNumber, [Optional fields]
2. (In/Out) CancellationDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, LicensePlateNumber, [Optional fields]
3. (In/Out) CancellationDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, VehicleIdentificationNumber, [Optional fields]

BEPStolenVehicleClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
LicensePlateNumber	LicensePlateNumber	C	20	
MessageKeyModifier	MessageKeyModifier	O	1	BLANK – Stolen Vehicle F – Felony Vehicle
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PropertyRecordRemovalReason	PropertyRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyORI	RecoveringAgencyORI	O	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In/Out) ClearDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, NCICNumber, [Optional fields]
2. (In/Out) ClearDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, LicensePlateNumber, [Optional fields]
3. (In/Out) ClearDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, VehicleIdentificationNumber, [Optional fields]

BEPStolenVehicleEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CautionIndicator	CautionIndicator	O	1	A - Occupants are armed P - Hold for latent prints F - Both A and P
ImageNCICNumber	ImageNCICNumber	O	10	
ImageTypeCode	ImageTypeCode	O	1	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C*	2	
LicensePlateTypeCode	LicensePlateTypeCode	C*	2	
LicensePlateYear	LicensePlateYear	C*	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	BLANK – Stolen Vehicle F – Felony Vehicle
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	200	
NCICPublicDisseminationCode	NCICPublicDisseminationCode	M	8	Must be IN, OUT, or a date CCYYMMDD
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OwnerAppliedNumber	OwnerAppliedNumber	C	20	
TheftDate	TheftDate	M	8	
VehicleColorCode	VehicleColorCode	O	7	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	M	24	
VehicleModelCode	VehicleModelCode	O	3	
VehicleStyleCode	VehicleStyleCode	M	2	
VehicleYear	VehicleYear	M	4	

* - Must be supplied as a set with LicensePlateNumber when MessageKeyModifier = BLANK. Not required when MessageKeyModifier = F, but may be entered.

Possible Combinations

- MessageKeyModifier = BLANK:** OriginatingAgencyORI, VehicleYear, VehicleMakeCode, VehicleStyleCode, TheftDate, OriginatingAgencyCaseNumber, NCICPublicDisseminationCode, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, LicensePlateYear, [Optional fields]
- MessageKeyModifier = BLANK:** OriginatingAgencyORI, VehicleYear, VehicleMakeCode, VehicleStyleCode, TheftDate, OriginatingAgencyCaseNumber, NCICPublicDisseminationCode, VehicleIdentificationNumber, [Optional fields]
- MessageKeyModifier = BLANK:** OriginatingAgencyORI, VehicleYear, VehicleMakeCode, VehicleStyleCode, TheftDate, OriginatingAgencyCaseNumber, NCICPublicDisseminationCode, OwnerAppliedNumber, [Optional fields]
- MessageKeyModifier = F:** OriginatingAgencyORI, VehicleMakeCode, TheftDate, OriginatingAgencyCaseNumber, NCICPublicDisseminationCode, LicensePlateNumber, [Optional fields]
- MessageKeyModifier = F:** OriginatingAgencyORI, VehicleMakeCode, TheftDate, OriginatingAgencyCaseNumber, NCICPublicDisseminationCode, VehicleIdentificationNumber, [Optional fields]

BEPStolenVehicleLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	

LicensePlateNumber	LicensePlateNumber	C	20	
MessageKeyModifier	MessageKeyModifier	O	1	BLANK – Stolen Vehicle F – Felony Vehicle
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PropertyRecordRemovalReason	PropertyRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In/Out) RecoveryDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, NCICNumber, [Optional fields]
2. (In/Out) RecoveryDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, LicensePlateNumber, [Optional fields]
3. (In/Out) RecoveryDate, OriginatingAgencyORI, OriginatingAgencyCaseNumber, VehicleIdentificationNumber, [Optional fields]

BEPStolenVehicleModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FormORI	FormORI	O	9	Modifies the ORI on the record
ImageNCICNumber	ImageNCICNumber	O	10	
ImageTypeCode	ImageTypeCode	O	1	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateNumber2	LicensePlateNumber2	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	O	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	BLANK – Stolen Vehicle F – Felony Vehicle
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	200	
ModifyMessageKey	ModifyMessageKey	O	4	EV - Enter stolen vehicle EF – Enter felony vehicle EV-A - Enter stolen vehicle, occupants are armed EF-A – Enter felony vehicle, occupants are armed EV-P - Enter stolen vehicle, hold for latent prints EF-P – Enter felony vehicle, occupants are armed EV-F - Enter stolen vehicle, occupants are armed and hold for latent prints EF-F – Enter felony vehicle, occupants are armed and hold for latent prints
NCICNumber	NCICNumber	C	10	
NCICPublicDisseminationCode	NCICPublicDisseminationCode	O	8	Must be IN, OUT, or a date CCYYMMDD

NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OwnerAppliedNumber	OwnerAppliedNumber	O	20	
TheftDate	TheftDate	O	8	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleIdentificationNumber2	VehicleIdentificationNumber2	O		
VehicleMakeCode	VehicleMakeCode	O	24	
VehicleModelCode	VehicleModelCode	O	3	
VehicleStyleCode	VehicleStyleCode	O	2	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In/Out) OriginatingAgencyCaseNumber, OriginatingAgencyORI, LicensePlateNumber, [Any optional fields]
2. (In/Out) OriginatingAgencyCaseNumber, OriginatingAgencyORI, NCICNumber, [Any optional fields]
3. (In/Out) OriginatingAgencyCaseNumber, OriginatingAgencyORI, VehicleRegistrationNumber, [Any optional fields]

BEPWantedPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
CancellationDate	CancellationDate	M	8	

Possible Combinations

1. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI, [MessageKeyModifier, OriginatingAgencyCaseNumber, PersonRecordRemovalReason]
2. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [MessageKeyModifier, NCICNumber, PersonRecordRemovalReason]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [MessageKeyModifier, Name, PersonRecordRemovalReason]

BEPWantedPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
HitResultsIndicator	HitResultsIndicator	O	2	See NCIC Code Manual
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	

NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	Blank, Y
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyORI	RecoveringAgencyORI	O	9	

Possible Combinations

1. (In/Out) Name, NCICNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]

BEPWantedPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalOffenseIndicator	AdditionalOffenseIndicator	O	1	Blank, Y
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	C	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
DocumentedAddressDate	DocumentedAddressDate	O	8	
EmancipationDate	EmancipationDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExtraditionLimitation	ExtraditionLimitation	M	2	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FraudulentBirthDate	FraudulentBirthDate	O	8	
FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	
FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	C	20	
FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	C	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	C	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	

IncidentDate	IncidentDate	C	8	Warrant or violation date
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
NotifyOriginatingAgency	NotifyOriginatingAgency	O	1	Blank, Y
OffenseCode	OffenseCode	M	4	
OffenseCodeDescription	OffenseCodeDescription	O	20	
OperatorLicenseExpirationYear	OperatorLicenseExpirationYear	C	4	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OriginalOffenseCode	OriginalOffenseCode	C	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateIdNumber	StateIdNumber	O	10	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	3	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
WantedPersonType	WantedPersonType	O	1	Blank, J – Wanted Juvenile
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	M	3	

*Operator License fields must be entered as a set.

*License Plate fields must be entered as a set.

*VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, and VehicleStyleCode must be entered as a set.

Possible Combinations

1. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, BirthDate, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FBI Number [Any optional fields]

3. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, MiscellaneousNumber [Any optional fields]
4. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, SocialSecurityNumber [Any optional fields]
5. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseExpirationYear, [Any optional fields]
6. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, LicensePlateNumber, LicensePlateStateCode, LicensePlateExpirationYear, LicensePlateTypeCode, [Any optional fields]
7. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]
8. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentName, FraudulentBirthDate, [Any optional fields]
9. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentMiscellaneousNumber, [Any optional fields]
10. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentSocialSecurityNumber, [Any optional fields]
11. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentOperatorLicenseNumber, FraudulentOperatorLicenseStateCode, FraudulentOperatorLicenseExpirationYear, [Any optional fields]
12. (In/Out) OriginatingAgencyORI, WantedPersonType, Name, SexCode, RaceCode, BirthDate, EmancipationDate, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, [Any optional fields]

BEPWantedPersonLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
Extradition	Extradition	M	4	See NCIC Code Manual
HitResultsIndicator	HitResultsIndicator	O	2	See NCIC Code Manual
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	Blank, Y
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	

Possible Combinations

1. (In/Out) Name, NCICNumber, Extradition, RecoveryDate, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, Extradition, RecoveryDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, Extradition, RecoveryDate, OriginatingAgencyORI, [Any optional fields]

BEPWantedPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalOffenseIndicator	AdditionalOffenseIndicator	O	1	Blank, Y
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	
DNALocation	DNALocation	O	250	Blank, Y
DocumentedAddressDate	DocumentedAddressDate	O	8	
EmancipationDate	EmancipationDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExtraditionLimitation	ExtraditionLimitation	O	2	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IncidentDate	IncidentDate	C	8	Warrant or violation date
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	Blank EW – Wanted Person EWJ – Wanted Juvenile ET – Temporary Felony EW-C – Wanted Person with Caution EWJC – Wanted Juvenile with Caution

				ET-C – Temporary Felony with Caution
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgency	NotifyOriginatingAgency	O	1	Blank, Y
OffenseCode	OffenseCode	O	4	See NCIC Code Manual
OffenseCodeDescription	OffenseCodeDescription	O	20	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	
OperatorLicenseYear	OperatorLicenseYear	O	4	See NCIC Code Manual
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
StateldNumber	StateldNumber	O	10	
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
ValidatorNameName	ValidatorNameName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

Computerized Criminal History (CCH)

CCHCriminalHistoryAQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FreeText	FreeText	M	14400	
NletsDestination	NletsDestination	O	9	
NletsDestination2	NletsDestination2	O	9	
NletsDestination3	NletsDestination3	O	9	
NletsDestination4	NletsDestination4	O	9	
NletsDestination5	NletsDestination5	O	9	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PurposeCode	PurposeCode	O	1	

Possible Combinations

1. (In/Out) FreeText, [NletsDestination, NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, OriginatingAgencyORI, PurposeCode]

CCHCriminalHistoryFQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PurposeCode	PurposeCode	M	1	
State	State	O	2	
StateIdNumber	StateIdNumber	M	10	

Possible Combinations

1. (In/Out) Attention, PurposeCode, StateIdNumber, [OriginatingAgencyORI, State]

CCHCriminalHistoryIQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	10	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PurposeCode	PurposeCode	O	1	
RaceCode	RaceCode	O	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, [Attention, MiscellaneousNumber, OriginatingAgencyORI, PurposeCode, RaceCode, SocialSecurityNumber, State, State2, State3, State4, State5]
2. (In/Out) MiscellaneousNumber, Name, [Attention, OriginatingAgencyORI, PurposeCode, State, State2, State3, State4, State5]
3. (In/Out) Name, SocialSecurityNumber, [Attention, OriginatingAgencyORI, PurposeCode, State, State2, State3, State4, State5]

CCHCriminalHistoryQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	10	
FBINumber	FBINumber	C	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PurposeCode	PurposeCode	M	1	

RaceCode	RaceCode	O	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) BirthDate, Name, PurposeCode, SexCode, [Attention, MiscellaneousNumber, OriginatingAgencyORI, RaceCode, SocialSecurityNumber]
2. (In/Out) FBINumber, PurposeCode, [Attention, Name, OriginatingAgencyORI]
3. (In/Out) MiscellaneousNumber, Name, PurposeCode, [Attention, OriginatingAgencyORI]
4. (In/Out) Name, PurposeCode, SocialSecurityNumber, [Attention, OriginatingAgencyORI]
5. (In/Out) PurposeCode, StateIdNumber, [Attention, Name, OriginatingAgencyORI]

CCHCriminalHistoryQRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressBuilding	AddressBuilding	O	30	
AddressCityState	AddressCityState	O	30	
AddressStreet	AddressStreet	O	30	
AddressZipCode	AddressZipCode	O	9	
Attention	Attention	O	30	
DepartmentAgencyName	DepartmentAgencyName	O	30	
FBINumber	FBINumber	C	9	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PurposeCode	PurposeCode	O	1	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) FBINumber, [AddressBuilding, AddressCityState, AddressStreet, AddressZipCode, Attention, DepartmentAgencyName, OriginatingAgencyORI, PurposeCode]
2. (In/Out) StateIdNumber, [AddressBuilding, AddressCityState, AddressStreet, AddressZipCode, Attention, DepartmentAgencyName, OriginatingAgencyORI, PurposeCode]

CCHCriminalHistoryQWQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	10	
EnhancedNameSearchIndicator	EnhancedNameSearchIndicator	O	1	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	
ImageIndicator	ImageIndicator	O	1	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PurposeCode	PurposeCode	O	1	
RaceCode	RaceCode	C	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	

Possible Combinations

1. (In/Out) [Attention, BirthDate, EnhancedNameSearchIndicator, ExpandedBirthDateSearchCode, ImageIndicator, MiscellaneousNumber, Name,

OriginatingAgencyORI, PurposeCode, RaceCode, RelatedHitSearchIndicator, SexCode, SocialSecurityNumber]

CCHCriminalHistoryZRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FBINumber	FBINumber	C	9	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PurposeCode	PurposeCode	O	1	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) FBINumber, [OriginatingAgencyORI, PurposeCode]
2. (In/Out) StateIdNumber, [OriginatingAgencyORI, PurposeCode]

Wanted Missing Person Entry (WMPE)

WMPEDentalDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI

WMPEDentalDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DentalCharacteristics	DentalCharacteristics	M	319	See NCIC Code Manual
DentalModelsAvailableIndicator	DentalModelsAvailableIndicator	M	1	Y, N
DentalXraysAvailableIndicator	DentalXraysAvailableIndicator	M	1	Y, N
DentistRemarks	DentistRemarks	O	50	
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	

Possible Combinations

1. (In/Out) DentalCharacteristics, DentalModelsAvailableIndicator, DentalXraysAvailableIndicator, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [DentistRemarks]

WMPEDentalDataModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DentalCharacteristics	DentalCharacteristics	O	319	See NCIC Code Manual
DentalModelsAvailableIndicator	DentalModelsAvailableIndicator	O	1	Y, N
DentalXraysAvailableIndicator	DentalXraysAvailableIndicator	O	1	Y, N
DentistRemarks	DentistRemarks	O	50	
NCICNumber	NCICNumber	M	10	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	

Possible Combinations

1. (In/Out, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [DentistRemarks, DentalCharacteristics, DentalModelsAvailableIndicator, DentalXraysAvailableIndicator, ModifiedOriginatingAgencyORI]

WMPELocalWarrantClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Name	Name	M	30	
NmletsNumber	NmletsNumber	M	27	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
UserId	UserId	M	25	Defaults to Authentication/UserName value

Possible Combinations

1. (In/Out) Name, NmletsNumber, UserId, [OriginatingAgencyORI]

WMPELocalWarrantEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M	8	
BondAmount	BondAmount	O	7	
EyeColorCode	EyeColorCode	M	3	
FBINumber	FBINumber	O	10	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	
HairColorCode	HairColorCode	M	3	
Height	Height	M	3	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateYear	LicensePlateYear	O	4	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	M	30	
OffenseCode	OffenseCode	M	24	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
RaceCode	RaceCode	M	1	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	
SexCode	SexCode	M	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
UserId	UserId	O	25	Defaults to Authentication/UserName value
VehicleColorCode	VehicleColorCode	O	7	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	
VehicleStyleCode	VehicleStyleCode	O	2	
VehicleYear	VehicleYear	O	4	
WarrantDate	WarrantDate	M	8	
WarrantNumber	WarrantNumber	M	17	
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) Name, WarrantNumber, WarrantDate, SexCode, RaceCode, BirthDate, Height, Weight, EyeColorCode, HairColorCode, OffenseCode,[BondAmount, FBINumber, FingerprintClassificationCode, LicensePlateNumber, LicensePlateStateCode, LicensePlateYear, MiscellaneousDescriptiveText, MiscellaneousNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, OriginatingAgencyORI, ScarMarkTattooCode, SocialSecurityNumber, UserId, VehicleColorCode, VehicleIdentificationNumber, VehicleMakeCode, VehicleMakeCodeDescription, VehicleModelCode, VehicleStyleCode, VehicleYear]

WMPEMissingPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
CancellationDate	CancellationDate	M	8	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [PersonRecordRemovalReason]
2. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI, [PersonRecordRemovalReason]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [PersonRecordRemovalReason]

WMPEMissingPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
HitResultsIndicator	HitResultsIndicator	O	2	1-9, See NCIC Code Manual for description
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyORI	RecoveringAgencyORI	O	9	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [HitResultsIndicator, NumberMissingPersonsFound, NumberPersonsApprehended, OtherRecoveredPropertyValue, PersonArmedIndicator, PropertyRecoveredValue, RecoveringAgencyCaseNumber, RecoveringAgencyORI]
2. (In/Out) Name, NCICNumber, ClearDate, OriginatingAgencyORI, [HitResultsIndicator, NumberMissingPersonsFound, NumberPersonsApprehended, OtherRecoveredPropertyValue,

- PersonArmedIndicator, PropertyRecoveredValue, RecoveringAgencyCaseNumber, RecoveringAgencyORI]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [HitResultsIndicator, NumberMissingPersonsFound, NumberPersonsApprehended, OtherRecoveredPropertyValue, PersonArmedIndicator, PropertyRecoveredValue, RecoveringAgencyCaseNumber, RecoveringAgencyORI]

WMPEMissingPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyXRayCode	BodyXRayCode	O	1	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	See NCIC Code Manual
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EmancipationDate	EmancipationDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintIndicator	FootprintIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LastContactDate	LastContactDate	M	8	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
MissingPersonCircumstanceCode	MissingPersonCircumstanceCode	O	1	See NCIC Code Manual
MissingPersonCode	MissingPersonCode	M	2	See NCIC Code Manual
MissingPersonEntryType	MissingPersonEntryType	M	1	D – Disability E – Endangered I – Involuntary J – Emancipated Juvenile V – Catastrophe Victim O – Other
Name	Name	M	30	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	

OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarMarkTattooCode	ScarMarkTattooCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, BirthDate, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, FBINumber, [Any optional fields]
3. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, MiscellaneousNumber, [Any optional fields]
4. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, SocialSecurityNumber, [Any optional fields]
5. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
6. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, LicensePlateYear, [Any optional fields]
7. (In/Out) OriginatingAgencyORI, MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, VehicleIdentificationNumber, VehicleMakeCode, VehicleYear, VehicleStyleCode, [Any optional fields]
8. (In/Out) **MissingPersonEntryType = J**; OriginatingAgencyORI, Name, SexCode, RaceCode, BirthDate, EmancipationDate, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEMissingPersonLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
DispositionCode	DispositionCode	M	4	
HitResultsIndicator	HitResultsIndicator	O	2	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	

NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, RecoveryDate, DispositionCode, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, RecoveryDate, DispositionCode, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, RecoveryDate, DispositionCode, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	
BloodTypeCode	BloodTypeCode	O	5	
BodyXRayCode	BodyXRayCode	O	1	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	
CircumcisionCode	CircumcisionCode	O	1	
CitizenshipCode	CitizenshipCode	O	2	
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	
DNAIndicator	DNAIndicator	O	1	
DNALocation	DNALocation	O	250	
EmancipationDate	EmancipationDate	O	8	
EthnicityCode	EthnicityCode	O	1	
EyeColorCode	EyeColorCode	O	3	
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	
FootprintIndicator	FootprintIndicator	O	1	
HairColorCode	HairColorCode	O	3	
Height	Height	O	3	
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	
LastContactDate	LastContactDate	O	8	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	O	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
MissingPersonCircumstanceCode	MissingPersonCircumstanceCode	O	1	
MissingPersonCode	MissingPersonCode	O	2	

ModifiedMessageKey	ModifiedMessageKey	O	4	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	O	1	
ScarMarkTattooCode	ScarMarkTattooCode	O	10	
SexCode	SexCode	O	1	
SkinToneCode	SkinToneCode	O	3	
SocialSecurityNumber	SocialSecurityNumber	O	9	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	
VehicleStyleCode	VehicleStyleCode	O	2	
VehicleYear	VehicleYear	O	4	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonPersonWithInformationCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	M	30	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI
2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI

WMPEMissingPersonPersonWithInformationEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual

EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	M	500	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) Name, NCICNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]
4. (In/Out) Name, NCICNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]
5. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]
6. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonPersonWithInformationModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	M	30	
PersonWithInformationName2	PersonWithInformationName2	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	

Weight	Weight	O	3	
--------	--------	---	---	--

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonPWISupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	M	30	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonPWISupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonWithInformationName	PersonWithInformationName	M	30	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
----------------------	----------------------	---	---	--

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEMissingPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual.

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEProtectionOrderCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
MessageKeyModifier	MessageKeyModifier	O	1	Blank or P – Protection Order T – Temporary Protection Order
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, ProtectionOrderNumber, CancellationDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [Any optional fields]

WMPEProtectionOrderClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
MessageKeyModifier	MessageKeyModifier	O	1	Blank or P – Protection Order T – Temporary Protection Order
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, ProtectionOrderNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) Name, NCICNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]

WMPEProtectionOrderEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
BradyIndicator	BradyIndicator	O	1	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExpirationDate	ExpirationDate	M	8	
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IssueDate	IssueDate	M	8	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MessageKeyModifier	MessageKeyModifier	O	1	Blank or P – Protection Order T – Temporary Protection Order
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	O	30	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	C	8	
ProtectedPersonName	ProtectedPersonName	C	30	
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	C	9	
ProtectionOrderConditionsCode	ProtectionOrderConditionsCode	M	2	See NCIC Code Manual
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	
ServiceCode	ServiceCode	O	1	See NCIC Code Manual
ServiceDate	ServiceDate	O	8	
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	

StateIdNumber	StateIdNumber	O	10	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, BirthDate, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, FBINumber, [Any optional fields]
3. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, MiscellaneousNumber, [Any optional fields]
4. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, SocialSecurityNumber, [Any optional fields]
5. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
6. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, [Any optional fields]
7. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]
8. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, ProtectedPersonName, ProtectedPersonSocialSecurityNumber, [Any optional fields]
9. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, ProtectedPersonName, ProtectedPersonBirthDate, [Any optional fields]
10. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, BirthDate, [Any optional fields]
11. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, FBINumber, [Any optional fields]
12. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, MiscellaneousNumber, [Any optional fields]
13. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, SocialSecurityNumber, [Any optional fields]
14. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber,

- OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
15. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, [Any optional fields]
16. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]
17. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, ProtectedPersonName, ProtectedPersonSocialSecurityNumber, [Any optional fields]
18. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, ProtectedPersonName, ProtectedPersonBirthDate, [Any optional fields]

WMPEProtectionOrderModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
BradyIndicator	BradyIndicator	O	1	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExpirationDate	ExpirationDate	O	8	
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IssueDate	IssueDate	O	8	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MessageKeyModifier	MessageKeyModifier	O	1	Blank or P – Protection Order T – Temporary Protection Order
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	EPO ETO EPOC ETOC
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	

NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	
ProtectedPersonName	ProtectedPersonName	O	30	
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	
ProtectionOrderConditionsCode	ProtectionOrderConditionsCode	O	2	See NCIC Code Manual
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
ProtectionOrderNumber2	ProtectionOrderNumber2	O	15	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
ServiceCode	ServiceCode	O	1	
ServiceDate	ServiceDate	O	8	
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
StateIdNumber	StateIdNumber	O	10	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, ProtectionOrderNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEProtectionOrderSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should

				use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateExpirationYear	LicensePlateExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseExpirationYear	OperatorLicenseExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

ProtectedPersonName	ProtectedPersonName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderConditionCode	ProtectionOrderConditionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderNumber	ProtectionOrderNumber	C	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
-------------	-------------	---	---	---

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) Name, ProtectionOrderNumber, OriginatingAgencyORI, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEProtectionOrderSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateExpirationYear	LicensePlateExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should

				use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseExpirationYear	OperatorLicenseExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonName	ProtectedPersonName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderConditionCode	ProtectionOrderConditionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderNumber	ProtectionOrderNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) Name, ProtectionOrderNumber, OriginatingAgencyORI, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESexOffenderCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI
2. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI

WMPESexOffenderClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	

OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI
2. (In/Out) Name, NCICNumber, ClearDate, OriginatingAgencyORI
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI

WMPESexOffenderEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	M	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	M	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BoatColorCode	BoatColorCode	O	7	See NCIC Code Manual
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual
BoatHullNumber	BoatHullNumber	O	20	
BoatHullShapeCode	BoatHullShapeCode	O	2	
BoatLength	BoatLength	O	2	See NCIC Code Manual
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual
BoatModelName	BoatModelName	O	20	
BoatModelYear	BoatModelYear	O	4	
BoatName	BoatName	O	20	
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	
ConvictionDate	ConvictionDate	M	8	
ConvictionOffenseCode	ConvictionOffenseCode	M	4	See NCIC Code Manual
CrimeLocation	CrimeLocation	O	2	See NCIC Code Manual, State Code
DNALocation	DNALocation	O	250	
DNAIndicator	DNAIndicator	O	1	Blank, N, Y
EmailAddress	EmailAddress	O	80	
EmployerName	EmployerName	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
HomePort	HomePort	O	20	
InternetId	InternetId	O	80	
JuvenileOffenderIndicator	JuvenileOffenderIndicator	O	1	Blank, N, Y
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual

LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	C	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	M	30	
NCICNumber	NCICNumber	O	10	
Occupation	Occupation	O	80	
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	
RaceCode	RaceCode	M	1	See NCIC Code Manual
RegistrationEndDate	RegistrationEndDate	M	8	
RegistrationNumber	RegistrationNumber	O	8	
RegistrationStartDate	RegistrationStartDate	M	8	
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual
ResidenceBeginDate	ResidenceBeginDate	O	8	
ResidenceEndDate	ResidenceEndDate	O	8	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SchoolName	SchoolName	O	80	
SexCode	SexCode	M	1	See NCIC Code Manual
SexOffenderTier	SexOffenderTier	O	1	See NCIC Code Manual
SexualPredatorIndicator	SexualPredatorIndicator	O	1	Blank, N, Y
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
StateIdNumber	StateIdNumber	O	10	
TelephoneNumber	TelephoneNumber	O	12	
TelephoneType	TelephoneType	C	1	See NCIC Code Manual
RegistrationExpirationYear	RegistrationExpirationYear	O	2	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleOwnershipCode	VehicleOwnershipCode	O	2	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
VictimAge	VictimAge	O	2	
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) Name, SexCode, RaceCode, BirthDate, RegistrationStartDate, RegistrationEndDate, Height, Weight, HairColorCode, EyeColorCode, ConvictionOffenseCode, ConvictionDate,

OriginatingAgencyCaseNumber, AddressStateCode, OriginatingAgencyORI, [Any optional fields]

WMPESexOffenderModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BoatColorCode	BoatColorCode	O	7	See NCIC Code Manual
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual
BoatHullNumber	BoatHullNumber	O	20	
BoatHullShapeCode	BoatHullShapeCode	O	2	
BoatLength	BoatLength	O	2	See NCIC Code Manual
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual
BoatModelName	BoatModelName	O	20	
BoatModelYear	BoatModelYear	O	4	
BoatName	BoatName	O	20	
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	
ConvictionDate	ConvictionDate	O	8	
ConvictionOffenseCode	ConvictionOffenseCode	O	4	See NCIC Code Manual
CrimeLocation	CrimeLocation	O	2	See NCIC Code Manual, State Code
DNALocation	DNALocation	O	250	
DNAIndicator	DNAIndicator	O	1	Blank, N, Y
EmailAddress	EmailAddress	O	80	
EmployerName	EmployerName	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
HomePort	HomePort	O	20	
InternetId	InternetId	O	80	
JuvenileOffenderIndicator	JuvenileOffenderIndicator	O	1	Blank, N, Y
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	

LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	O	10	
Occupation	Occupation	O	80	
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
RegistrationEndDate	RegistrationEndDate	O	8	
RegistrationNumber	RegistrationNumber	O	8	
RegistrationStartDate	RegistrationStartDate	O	8	
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual
ResidenceBeginDate	ResidenceBeginDate	O	8	
ResidenceEndDate	ResidenceEndDate	O	8	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SchoolName	SchoolName	O	80	
SexCode	SexCode	O	1	See NCIC Code Manual
SexOffenderTier	SexOffenderTier	O	1	See NCIC Code Manual
SexualPredatorIndicator	SexualPredatorIndicator	O	1	Blank, N, Y
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
StateIdNumber	StateIdNumber	O	10	
TelephoneNumber	TelephoneNumber	O	12	
TelephoneType	TelephoneType	O	1	See NCIC Code Manual
RegistrationExpirationYear	RegistrationExpirationYear	O	2	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleOwnershipCode	VehicleOwnershipCode	O	2	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
VictimAge	VictimAge	O	2	
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]

3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESexOffenderSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullNumber	BoatHullNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullShapeCode	BoatHullShapeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatLength	BoatLength	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelName	BoatModelName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelYear	BoatModelYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatName	BoatName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
EmailAddress	EmailAddress	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Employer	Employer	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
InternetId	InternetId	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
Occupation	Occupation	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProfessionalLicenseNumberType	ProfessionalLicenseNumberType	O	80	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationExpirationYear	RegistrationExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationNumber	RegistrationNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SchoolName	SchoolName	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
StateIdNumber	StateIdNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumber	TelephoneNumber	O	12	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumberType	TelephoneNumberType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleOwnershipCode	VehicleOwnershipCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimAge	VictimAge	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESexOffenderSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullNumber	BoatHullNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullShapeCode	BoatHullShapeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatLength	BoatLength	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelName	BoatModelName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelYear	BoatModelYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatName	BoatName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
EmailAddress	EmailAddress	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Employer	Employer	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
InternetId	InternetId	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
Occupation	Occupation	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProfessionalLicenseNumberType	ProfessionalLicenseNumberType	O	80	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationExpirationYear	RegistrationExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationNumber	RegistrationNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SchoolName	SchoolName	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
StateIdNumber	StateIdNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumber	TelephoneNumber	O	12	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumberType	TelephoneNumberType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleOwnershipCode	VehicleOwnershipCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimAge	VictimAge	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESupervisedReleaseCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [Any optional fields]

WMPESupervisedReleaseClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]

WMPESupervisedReleaseEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArrestDate	ArrestDate	O	8	
ArrestingAgencyORI	ArrestingAgencyORI	O	9	
BirthDate	BirthDate	C	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EmailAddress	EmailAddress	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	
FraudulentBirthDate	FraudulentBirthDate	O	8	
FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	

FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	O	20	
FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	O	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	O	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
IncarcerationPlace	IncarcerationPlace	O	50	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ReleaseDate	ReleaseDate	O	8	
ReleaseLocation	ReleaseLocation	O	50	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SentencingCourtORI	SentencingCourtORI	O	9	
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
SupervisingOfficerName	SupervisingOfficerName	M	30	
SupervisingOfficerTelephone	SupervisingOfficerTelephone	M	12	
SupervisionStartDate	SupervisionStartDate	M	8	
SupervisionExpirationDate	SupervisionExpirationDate	M	8	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
WarrantCourtORI	WarrantCourtORI	O	9	
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, BirthDate, [Any optional fields]

2. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, FBINumber, [Any optional fields]
3. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, MiscellaneousNumber, [Any optional fields]
4. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, SocialSecurityNumber, [Any optional fields]
5. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
6. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, [Any optional fields]
7. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]

WMPESupervisedReleaseFraudulentDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]

3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESupervisedReleaseFraudulentDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESupervisedReleaseModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArrestDate	ArrestDate	O	8	
ArrestingAgencyORI	ArrestingAgencyORI	O	9	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EmailAddress	EmailAddress	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual

FraudulentBirthDate	FraudulentBirthDate	O	8	
FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	
FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	O	20	
FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	O	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	O	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IncarcerationPlace	IncarcerationPlace	O	50	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	EC EC-C
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ProbationExpirationDate	ProbationExpirationDate	O	8	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ReleaseLocation	ReleaseLocation	O	50	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SentencingCourtORI	SentencingCourtORI	O	9	
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
SupervisingOfficerName	SupervisingOfficerName	O	30	
SupervisingOfficerTelephone	SupervisingOfficerTelephone	O	12	
SupervisionStartDate	SupervisionStartDate	O	8	
SupervisionReleaseDate	SupervisionReleaseDate	O	5	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	

WarrantCourtORI	WarrantCourtORI	O	9	
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESupervisedReleaseSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPESupervisedReleaseSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEUnidentifiedPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RecordRemovalReason	RecordRemovalReason	O	21	

Possible Combinations

1. (In/Out) CancellationDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [RecordRemovalReason]

WMPEUnidentifiedPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RecordRemovalReason	RecordRemovalReason	O	21	

Possible Combinations

1. (In/Out) ClearDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [RecordRemovalReason]

WMPEUnidentifiedPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyFoundDate	BodyFoundDate	M	8	
BodyPartsStatusCode	BodyPartsStatusCode	C	15	See NCIC Code Manual
CauseOfDeath	CauseOfDeath	O	30	
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EstimatedBirthYear	EstimatedBirthYear	C	9	
EstimatedDeathDate	EstimatedDeathDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual

EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintAvailableIndicator	FootprintAvailableIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	7	Range of values Ex. 000-000
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MedicalExaminerAgencyAndCaseNumber	MedicalExaminerAgencyAndCaseNumber	O	50	
MedicalExaminerLocality	MedicalExaminerLocality	O	30	
MedicalExaminerTelephoneNumber	MedicalExaminerTelephoneNumber	O	12	
MessageKeyModifier	MessageKeyModifier	M	1	D – Deceased L – Living V – Catastrophe Victim
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
Weight	Weight	M	7	Range of values Ex. 000-000
XraysAvailableIndicator	XraysAvailableIndicator	M	1	Blank, Y

Possible Combinations

1. (In/Out) MessageKeyModifier=**D** or **V**, BodyPartsStatusCode, SexCode, RaceCode, EstimatedDeathDate, BodyFoundDate, Height, Weight, EyeColorCode, HairColorCode, OriginatingAgencyCaseNumber, XraysAvailableIndicator, CauseOfDeath, OriginatingAgencyORI, [BloodTypeCode, CircumcisionCode, CorrectiveVisionPerscriptionCode, DNAIndicator, DNALocation, EstimatedBirthYear, EthnicityCode, FingerprintClassificationCode, FootprintAvailableIndicator, JewelryDescription, JewelryTypeCode, LinkageAgencyIdentifier, LinkageCaseNumber, MedicalExaminerAgencyAndCaseNumber, MedicalExaminerLocality, MedicalExaminerTelephoneNumber, MiscellaneousDescriptiveText, NotifyOriginatingAgencyIndicator, ScarsMarksTattoosCode]
2. (In/Out) MessageKeyModifier=**L**, SexCode, RaceCode, BodyFoundDate, Height, Weight, EyeColorCode, HairColorCode, FingerprintClassificationCode, OriginatingAgencyCaseNumber, XraysAvailableIndicator, OriginatingAgencyORI, [BloodTypeCode, CircumcisionCode, CorrectiveVisionPerscriptionCode, DNAIndicator, DNALocation, EstimatedBirthYear, EthnicityCode, FootprintAvailableIndicator, JewelryDescription, JewelryTypeCode, LinkageAgencyIdentifier, LinkageCaseNumber, MedicalExaminerAgencyAndCaseNumber, MedicalExaminerLocality, MedicalExaminerTelephoneNumber, MiscellaneousDescriptiveText, NotifyOriginatingAgencyIndicator, ScarsMarksTattoosCode]

WMPEUnidentifiedPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyFoundDate	BodyFoundDate	O	8	
BodyPartsStatusCode	BodyPartsStatusCode	O	15	See NCIC Code Manual

CauseOfDeath	CauseOfDeath	O	30	
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EstimatedBirthYear	EstimatedBirthYear	O	9	
EstimatedDeathDate	EstimatedDeathDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintAvailableIndicator	FootprintAvailableIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MedicalExaminerAgencyAndCaseNumber	MedicalExaminerAgencyAndCaseNumber	O	50	
MedicalExaminerLocality	MedicalExaminerLocality	O	30	
MedicalExaminerTelephoneNumber	MedicalExaminerTelephoneNumber	O	12	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
ModifiedMessageKey	ModifiedMessageKey	O	4	EUD - Deceased EUL - Living EUV – Catastrophe Victim
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
NCICNumber	NCICNumber	M	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
ValidatorName	ValidatorName	O	30	
Weight	Weight	O	3	
XraysAvailableIndicator	XraysAvailableIndicator	O	1	Blank, Y

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEUnidentifiedPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	

OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEUnidentifiedPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
CancellationDate	CancellationDate	M	8	

Possible Combinations

1. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI, [MessageKeyModifier, OriginatingAgencyCaseNumber, PersonRecordRemovalReason]
2. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [MessageKeyModifier, NCICNumber, PersonRecordRemovalReason]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [MessageKeyModifier, Name, PersonRecordRemovalReason]

WMPEWantedPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
HitResultsIndicator	HitResultsIndicator	O	2	See NCIC Code Manual

MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	Blank, Y
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyORI	RecoveringAgencyORI	O	9	

Possible Combinations

1. (In/Out) Name, NCICNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonDetainerCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	M	20	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	

Possible Combinations

1. (In/Out) Name, NCICNumber, DetainerCaseNumber, OriginatingAgencyORI
2. (In/Out) Name, OriginatingAgencyCaseNumber, DetainerCaseNumber, OriginatingAgencyORI
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, DetainerCaseNumber, OriginatingAgencyORI

WMPEWantedPersonDetainerEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	M	20	
DetainerDate	DetainerDate	M	8	
IncarceratingAgencyORI	IncarceratingAgencyORI	M	9	
IncarcerationPlace	IncarcerationPlace	O	50	
IncarcerationStartDate	IncarcerationStartDate	O	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SentenceExpirationDate	SentenceExpirationDate	O	8	

Possible Combinations

1. (In/Out)
Name, NCICNumber, DetainerCaseNumber, DetainerDate, IncarceratingAgencyORI, OriginatingAgencyORI, [Any optional fields]

2. (In/Out)
Name, OriginatingAgencyCaseNumber, DetainerCaseNumber, DetainerDate, IncarceratingAgencyORI, OriginatingAgencyORI, [Any optional fields]
3. (In/Out)
NCICNumber, OriginatingAgencyCaseNumber, DetainerCaseNumber, DetainerDate, IncarceratingAgencyORI, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonDetainerModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	O	20	
DetainerDate	DetainerDate	O	8	
IncarceratingAgencyORI	IncarceratingAgencyORI	O	9	
IncarcerationPlace	IncarcerationPlace	O	50	
IncarcerationStartDate	IncarcerationStartDate	O	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SentenceExpirationDate	SentenceExpirationDate	O	8	
ValidatorName	ValidatorName	O	30	

Possible Combinations

1. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalOffenseIndicator	AdditionalOffenseIndicator	O	1	Blank, Y
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	C	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
DocumentedAddressDate	DocumentedAddressDate	O	8	
EmancipationDate	EmancipationDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExtraditionLimitation	ExtraditionLimitation	M	2	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual

FraudulentBirthDate	FraudulentBirthDate	O	8	
FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	
FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	C	20	
FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	C	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	C	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
IncidentDate	IncidentDate	C	8	Warrant or violation date
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
NotifyOriginatingAgency	NotifyOriginatingAgency	O	1	Blank, Y
OffenseCode	OffenseCode	M	4	
OffenseCodeDescription	OffenseCodeDescription	O	20	
OperatorLicenseExpirationYear	OperatorLicenseExpirationYear	C	4	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OriginalOffenseCode	OriginalOffenseCode	C	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateldNumber	StateldNumber	O	10	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	3	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
WantedPersonType	WantedPersonType	O	1	Blank, J – Wanted Juvenile
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	M	3	

*Operator License fields must be entered as a set.

*License Plate fields must be entered as a set.

*VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, and VehicleStyleCode must be entered as a set.

Possible Combinations

1. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, BirthDate, [Any optional fields]
2. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FBINumber [Any optional fields]
3. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, MiscellaneousNumber [Any optional fields]
4. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, SocialSecurityNumber [Any optional fields]
5. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseExpirationYear, [Any optional fields]
6. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, LicensePlateNumber, LicensePlateStateCode, LicensePlateExpirationYear, LicensePlateTypeCode, [Any optional fields]
7. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]
8. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentName, FraudulentBirthDate, [Any optional fields]
9. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentMiscellaneousNumber, [Any optional fields]
10. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentSocialSecurityNumber, [Any optional fields]
11. (In/Out) OriginatingAgencyORI, Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentOperatorLicenseNumber, FraudulentOperatorLicenseStateCode, FraudulentOperatorLicenseExpirationYear, [Any optional fields]
12. (In/Out) OriginatingAgencyORI, WantedPersonType, Name, SexCode, RaceCode, BirthDate, EmancipationDate, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, [Any optional fields]

WMPEWantedPersonFraudulentDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonFraudulentDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]

3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
Extradition	Extradition	M	4	See NCIC Code Manual
HitResultsIndicator	HitResultsIndicator	O	2	See NCIC Code Manual
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	Blank, Y
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	

Possible Combinations

1. (In/Out) Name, NCICNumber, Extradition, RecoveryDate, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, Extradition, RecoveryDate, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, Extradition, RecoveryDate, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalOffenseIndicator	AdditionalOffenseIndicator	O	1	Blank, Y
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	
DNALocation	DNALocation	O	250	Blank, Y
DocumentedAddressDate	DocumentedAddressDate	O	8	
EmancipationDate	EmancipationDate	O	8	

EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExtraditionLimitation	ExtraditionLimitation	O	2	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IncidentDate	IncidentDate	C	8	Warrant or violation date
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	Blank EW – Wanted Person EWJ – Wanted Juvenile ET – Temporary Felony EW-C – Wanted Person with Caution EWJC – Wanted Juvenile with Caution ET-C – Temporary Felony with Caution
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgency	NotifyOriginatingAgency	O	1	Blank, Y
OffenseCode	OffenseCode	O	4	See NCIC Code Manual
OffenseCodeDescription	OffenseCodeDescription	O	20	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	
OperatorLicenseYear	OperatorLicenseYear	O	4	See NCIC Code Manual
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
StateIdNumber	StateIdNumber	O	10	
ValidatorNameName	ValidatorNameName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	

WarrantNumber	WarrantNumber	O	15	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressCounty	AddressCounty	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetName	AddressStreetName	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetNumber	AddressStreetNumber	O	7	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressTypeCode	AddressTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressZipCode	AddressZipCode	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

WMPEWantedPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressCounty	AddressCounty	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetName	AddressStreetName	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetNumber	AddressStreetNumber	O	7	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressTypeCode	AddressTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressZipCode	AddressZipCode	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

*Operator License fields must be entered as a set.

*License Plate fields must be entered as a set.

*VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, and VehicleStyleCode must be entered as a set.

*Address fields must be entered as a set.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

Wanted Missing Person Inquiries (WMP-I)

WMPIMissingPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	M	2	
AreaCode	AreaCode	O	3	See NCIC Code Manual
EthnicityCode	EthnicityCode	M	1	See NCIC Code Manual
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Blank, Y
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
Name	Name	O	30	
RaceCode	RaceCode	M	1	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) Age, EthnicityCode, EyeColorCode, HairColorCode, Height, RaceCode, SexCode, Weight, [AreaCode, ExpandedNameSearchCode, Name]

WMPINletsSexOffenderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Blank, Y
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
PurposeCode	PurposeCode	O	1	
SexCode	SexCode	C	1	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	M	2	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, State, [Attention, ImageIndicator, PurposeCode]
2. (In/Out) FBINumber, State, [Attention, ImageIndicator, PurposeCode]
3. (In/Out) MiscellaneousNumber, State, [Attention, ImageIndicator, PurposeCode]
4. (In/Out) SocialSecurityNumber, State, [Attention, ImageIndicator, PurposeCode]
5. (In/Out) StateIdNumber, State, [Attention, ImageIndicator, PurposeCode]

WMPINletsStateWarrantQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
RaceCode	RaceCode	O	1	
SexCode	SexCode	O	1	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	M	2	

Possible Combinations

1. (In/Out) BirthDate, Name, State, [RaceCode, SexCode]
2. (In/Out) FBINumber, Name, State
3. (In/Out) MiscellaneousNumber, Name, State
4. (In/Out) Name, SocialSecurityNumber, State
5. (In/Out) Name, OperatorLicenseNumber, State

WMPProtectionOrderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Blank, Y
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Blank, Y
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Blank, Y
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
RaceCode	RaceCode	O	1	See NCIC Code Manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Blank, Y
SexCode	SexCode	O	1	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	

Possible Combinations

1. (In/Out) Name, BirthDate, [ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, RaceCode, RelatedHitSearchIndicator, SexCode]
2. (In/Out) Name, OriginatingAgencyCaseNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator]
3. (In/Out) Name, ProtectionOrderNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator]
4. (In/Out) NCICNumber, [ImageIndicator, RelatedHitSearchIndicator]
5. (In/Out) Name, FBINumber, [ImageIndicator, RelatedHitSearchIndicator]
6. (In/Out) Name, MiscellaneousNumber, [ImageIndicator, RelatedHitSearchIndicator]

7. (In/Out) Name, OperatorLicenseNumber, [ImageIndicator, RelatedHitSearchIndicator]
8. (In/Out) Name, SocialSecurityNumber, [ImageIndicator, RelatedHitSearchIndicator]
9. (In/Out) LicensePlateNumber, LicensePlateStateCode, [ImageIndicator, RelatedHitSearchIndicator, VehicleIdentificationNumber, VehicleMakeCode, VehicleMakeCodeDescription]
10. (In/Out) VehicleIdentificationNumber, VehicleMakeCode, [ImageIndicator, RelatedHitSearchIndicator, LicensePlateNumber, LicensePlateStateCode, VehicleMakeCodeDescription]

WMPISexOffenderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
BoatHullNumber	BoatHullNumber	C	20	
BoatRegistrationNumber	BoatRegistrationNumber	C	10	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Blank, Y
ExpandedNameSearchIndicator	ExpandedNameSearchIndicator	O	1	Blank, Y
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Blank, Y
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	O	1	See NCIC Code Manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SexCode	SexCode	O	1	See NCIC Code Manual
SexualOffenderStatusIndicator	SexualOffenderStatusIndicator	O	1	Y,N
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
ZipCode	ZipCode	C	10	

Possible Combinations

1. (In/Out) Name, **and at least one** BirthDate, BoatHullNumber, BoatRegistrationNumber, FBINumber, LicensePlateNumber, MiscellaneousNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, SocialSecurityNumber, VehicleIdentificationNumber, [ExpandedBirthDateSearchCode, ExpandedNameSearchIndicator, ImageIndicator, LicensePlateStateCode, RaceCode, RelatedHitSearchIndicator, SexCode, VehicleMakeCode, VehicleMakeCodeDescription]
2. (In/Out) ZipCode, [SexualOffenderStatusIndicator, ImageIndicator]

WMPIUnidentifiedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	C	2	
AreaCode	AreaCode	O	3	See NCIC Code Manual
BodyPartsStatusCode	BodyPartsStatusCode	C	15	See NCIC Code Manual
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	C	3	See NCIC Code Manual
HairColorCode	HairColorCode	C	3	See NCIC Code Manual
Height	Height	C	3	

ImageIndicator	ImageIndicator	O	1	Blank, Y
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	C	1	See NCIC Code Manual
SexCode	SexCode	C	1	See NCIC Code Manual
Weight	Weight	C	3	

Possible Combinations

1. (In/Out) Age, EyeColorCode, HairColorCode, Height, RaceCode, SexCode, Weight, [AreaCode, EthnicityCode, ImageIndicator]
2. (In/Out) BodyPartsStatusCode, [AreaCode, EthnicityCode, ImageIndicator, RaceCode, SexCode]
3. (In/Out) NCICNumber, [ImageIndicator]
4. (In/Out) OriginatingAgencyCaseNumber, [ImageIndicator]

WMPIWantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Blank, Y
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Blank, Y
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Blank, Y
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	O	1	See NCIC Code Manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Blank, Y
SexCode	SexCode	O	1	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	

Possible Combinations

1. (In/Out) Name, BirthDate, [ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, RaceCode, RelatedHitSearchIndicator, SexCode]
2. (In/Out) Name, OriginatingAgencyCaseNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator]
3. (In/Out) NCICNumber, [ImageIndicator, RelatedHitSearchIndicator]
4. (In/Out) Name, FBINumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator]
5. (In/Out) Name, MiscellaneousNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator]
6. (In/Out) Name, OperatorLicenseNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator]
7. (In/Out) Name, SocialSecurityNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator]
8. (In/Out) LicensePlateNumber, LicensePlateStateCode, [ImageIndicator, RelatedHitSearchIndicator, VehicleIdentificationNumber, VehicleMakeCode, VehicleMakeCodeDescription]

9. (In/Out) VehicleIdentificationNumber, VehicleMakeCode, [ImageIndicator, RelatedHitSearchIndicator, LicensePlateNumber, LicensePlateStateCode, VehicleMakeCodeDescription]

Expanded Transactions Supported:

IdentityTheftCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
CancellationDate	CancellationDate	M	8	

Possible Combinations

1. (In/Out) Name, NCICNumber, CancellationDate, OriginatingAgencyORI, [PersonRecordRemovalReason]
2. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [PersonRecordRemovalReason]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, OriginatingAgencyORI, [PersonRecordRemovalReason]

IdentityTheftEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M	8	
BirthPlaceCode	BirthPlaceCode	M	2	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
IdentityTheftTypeCode	IdentityTheftTypeCode	M	4	ACCT-Checking or Saving Account CFRD-Credit Card GOVT-Government Documents or Benefits INVT-Securities or Other Investments LOAN-Loans NETT-Internet or E-mail OTHR-Other UTIL-Phone or Utilities
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	M	30	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	O	20	

OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Password	Password	M	20	
PurgeDate	PurgeDate	O	8	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
TheftDate	TheftDate	O	8	
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) OriginatingAgencyORI, Name, SexCode, BirthDate, BirthPlaceCode, RaceCode, Height, Weight, HairColorCode, EyeColorCode, OriginatingAgencyCaseNumber, Password, IdentityTheftTypeCode, [Any optional fields]

IdentityTheftModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FormORI	FormORI	O	9	Modifies the ORI on the record
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IdentityTheftTypeCode	IdentityTheftTypeCode	O	4	ACCT-Checking or Saving Account CFRD-Credit Card GOVT-Government Documents or Benefits INVT-Securities or Other Investments LOAN-Loans NETT-Internet or E-mail OTHR-Other UTIL-Phone or Utilities
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifyMessageKey	ModifyMessageKey	O	4	EID, Identity Theft Entry EIDC, Identity Theft Entry, with Caution
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y

OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
Password	Password	O	20	
PurgeDate	PurgeDate	O	8	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
TheftDate	TheftDate	O	8	
ValidatorName	ValidatorName	O	30	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]
2. (In/Out) Name, NCICNumber, OriginatingAgencyORI, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Any optional fields]

StolenSecuritiesCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
NCICNumber	NCICNumber	M	10	
MessageKeyModifier	MessageKeyModifier	C	1	Blank – Single Security S – Multiple serialized securities
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PropertyRecordRemovalReason	PropertyRecordRemovalReason	O	21	
SerialNumber	SerialNumber	C	20	
SerialNumber2	SerialNumber2	C	20	

Possible Combinations

1. **MessageKeyModifier = BLANK**: CancellationDate, NCICNumber, SerialNumber, OriginatingAgencyORI, [PropertyRecordRemovalReason]
2. **MessageKeyModifier = BLANK**: CancellationDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [PropertyRecordRemovalReason]
3. **MessageKeyModifier = S**: CancellationDate, NCICNumber, SerialNumber, SerialNumber2, OriginatingAgencyORI
4. **MessageKeyModifier = S**: CancellationDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI

StolenSecuritiesClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
MessageKeyModifier	MessageKeyModifier	C	1	Blank – Single Security S – Multiple serialized securities
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	

NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ReasonForPropertyRecordRemoval	PropertyRecordRemovalReason	O	21	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyIdentifier	RecoveringAgencyORI	O	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
SerialNumber	SerialNumber	C	20	
SerialNumber2	SerialNumber2	C	20	

Possible Combinations

1. **MessageKeyModifier = BLANK:** ClearDate, OriginatingAgencyCaseNumber, SerialNumber, OriginatingAgencyORI, [Optional fields]
2. **MessageKeyModifier = BLANK:** ClearDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]
3. **MessageKeyModifier = S:** ClearDate, OriginatingAgencyCaseNumber, SerialNumber, SerialNumber2, OriginatingAgencyORI, [RecoveringAgencyORI, RecoveringAgencyCaseNumber]
4. **MessageKeyModifier = S:** ClearDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [RecoveringAgencyORI, RecoveringAgencyCaseNumber]

StolenSecuritiesEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Denomination	Denomination	M	9	
Issuer	Issuer	M	15	
Owner	Owner	M	40	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	C	1	Blank – Single Security S – Multiple serialized securities
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	200	
NCICPublicDisseminationCode	NCICPublicDisseminationCode	C	8	Must be IN, OUT, or a date CCYYMMDD
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Y, BLANK
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RansomMoneyIndicator	RansomMoneyIndicator	O	1	B-Bait Money C-Counterfeit R-Ransom
SecurityDate	SecurityDate	O	8	
SecurityTypeCode	SecurityTypeCode	M	2	
SerialNumber	SerialNumber	M	20	
SerialNumber2	SerialNumber2	C	20	
SocialSecurityNumber	SocialSecurityNumber	O	9	
TheftDate	TheftDate	M	8	

Possible Combinations

1. **MessageKeyModifier = BLANK:** Denomination, Issuer, NCICPublicDisseminationCode, Owner, OriginatingAgencyCaseNumber, OriginatingAgencyORI, SecurityTypeCode, SerialNumber, TheftDate, [Optional fields]

2. **MessageKeyModifier = S:** Denomination, Issuer, Owner, OriginatingAgencyCaseNumber, OriginatingAgencyORI, SecurityTypeCode, SerialNumber, SerialNumber2, TheftDate, [Optional fields]

StolenSecuritiesLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
MessageKeyModifier	MessageKeyModifier	C	1	Blank – Single Security S – Multiple serialized securities
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
ReasonForPropertyRecordRemoval	PropertyRecordRemovalReason	O	21	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveryDate	RecoveryDate	M	8	
SerialNumber	SerialNumber	C	20	
SerialNumber2	SerialNumber2	C	20	

Possible Combinations

1. **MessageKeyModifier = BLANK:** RecoveryDate, OriginatingAgencyCaseNumber, SerialNumber, OriginatingAgencyORI, [Optional fields]
2. **MessageKeyModifier = BLANK:** RecoveryDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]
3. **MessageKeyModifier = S:** RecoveryDate, NCICNumber, SerialNumber, SerialNumber2, OriginatingAgencyORI, [RecoveringAgencyCaseNumber]
4. **MessageKeyModifier = S:** RecoveryDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [RecoveringAgencyCaseNumber]

StolenSecuritiesModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Denomination	Denomination	O	9	
FormORI	FormORI	O	9	Modifies the ORI on the record
Issuer	Issuer	O	15	
Owner	Owner	O	40	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	Blank – Single Security S – Multiple serialized securities
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	200	
ModifyMessageKey	ModifyMessageKey	O	4	ES, Single Security Entry ESS, Multiple Serialized Securities Entry
NCICNumber	NCICNumber	C	10	
NCICPublicDisseminationCode	NCICPublicDisseminationCode	O	8	Must be IN, OUT, or a date CCYYMMDD
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Y, BLANK
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
RansomMoneyIndicator	RansomMoneyIndicator	O	1	B-Bait Money

				C-Counterfeit R-Ransom
SecurityDate	SecurityDate	O	8	
SecurityTypeCode	SecurityTypeCode	O	2	
SerialNumber	SerialNumber	C	20	Identifies a single security, or the beginning of a range of several securities
SerialNumber2	SerialNumber2	C	20	Modifies the serial number on a single security, or identifies the end of a range of several securities
SerialNumber3	SerialNumber3	O	20	Modifies the beginning of a range of several securities
SerialNumber4	SerialNumber4	O	20	Modifies the end of a range of several securities
SocialSecurityNumber	SocialSecurityNumber	O	9	
TheftDate	TheftDate	M	8	
ValidatorName	ValidatorName	O	30	

Possible Combinations

1. **MessageKeyModifier = BLANK**: OriginatingAgencyCaseNumber, SerialNumber, OriginatingAgencyORI, [Optional fields]
2. **MessageKeyModifier = BLANK**: NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]
3. **MessageKeyModifier = S**: NCICNumber, SerialNumber, SerialNumber2, OriginatingAgencyORI, [Optional fields]
4. **MessageKeyModifier = S**: NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]

StolenPartCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PartSerialNumber	PartSerialNumber	C	20	
PropertyRecordRemovalReason	PropertyRecordRemovalReason	O	21	

Possible Combinations

1. (In/Out): CancellationDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]
2. (In/Out): CancellationDate, PartSerialNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]

StolenPartClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PartSerialNumber	PartSerialNumber	C	20	
ReasonForPropertyRecordRemoval	PropertyRecordRemovalReason	O	21	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	

RecoveringAgencyIdentifier	RecoveringAgencyORI	O	9	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	

Possible Combinations

1. (In/Out): ClearDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]
2. (In/Out): ClearDate, PartSerialNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]

StolenPartEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BrandName	BrandName	M	6	
Category	Category	M	2	
EnginePowerCode	EnginePowerCode	O	5	
HoldForPrintsIndicator	HoldForPrintsIndicator	O	1	Blank Y – Hold for prints
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	M	200	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Y, BLANK
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OwnerAppliedNumber	OwnerAppliedNumber	C	20	
PartSerialNumber	PartSerialNumber	C	20	
TheftDate	TheftDate	M	8	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In/Out): BrandName, Category, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, OriginatingAgencyORI, TheftDate, PartSerialNumber, [Optional fields]
2. (In/Out): BrandName, Category, MiscellaneousDescriptiveText, OriginatingAgencyCaseNumber, OriginatingAgencyORI, TheftDate, OwnerAppliedNumber, [Optional fields]

StolenPartLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
PartSerialNumber	PartSerialNumber	C	20	
ReasonForPropertyRecordRemoval	PropertyRecordRemovalReason	O	21	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	

Possible Combinations

1. (In/Out): RecoveryDate, NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]
2. (In/Out): RecoveryDate, PartSerialNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]

StolenPartModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BrandName	BrandName	O	6	
Category	Category	O	2	
EnginePowerCode	EnginePowerCode	O	5	
FormORI	FormORI	O	9	Modifies the originating agency identifier on the record
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	200	
ModifyMessageKey	ModifyMessageKey	O	4	EP - Stolen Part Entry EP-P – Stolen Part Entry, Hold for Prints
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Y, BLANK
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
OwnerAppliedNumber	OwnerAppliedNumber	O	20	
PartSerialNumber	PartSerialNumber	C	20	
PartSerialNumber2	PartSerialNumber2	O	20	
TheftDate	TheftDate	O	8	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In/Out): PartSerialNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]
2. (In/Out): NCICNumber, OriginatingAgencyCaseNumber, OriginatingAgencyORI, [Optional fields]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- OpenFox NMLETS Interface Specification v1.0

