

Nevada (NV) JLINK

[Disclaimer Statement](#)

Transport:

TCPIP Justice Link

Routing and Configuration Information:

Save Byte Routing (Primary)

Mnemonic Routing (Secondary)

- The JLINK assigned ORI for a device (or for the site) should be placed in the <Authentication>/<ORI> field in the ConnectCIC header.
- The JLINK assigned Mnemonic for a device should be placed in the <Authentication>/<Mnemonic> field in the ConnectCIC header.
- The JLINK assigned User ID should be placed in the <Authentication>/<UserName> field in the ConnectCIC header.

Security Requirements:

None known at this time.

Logon Requirements:

Server level logon to connect to JLINK

User logon form application layer.

Certification Requirements:

Agency sponsor is required.

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	20	
RegistrationNumber	RegistrationNumber	C	8	
State	State	O	2	

Possible Combinations

1. (In/Out) BoatHullIdNumber, [State]
2. (In/Out) RegistrationNumber, [State]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	C	30	
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
PurposeCode	PurposeCode	C	1	
SexCode	SexCode	C	1	
State	State	O	2	

Possible Combinations

1. (In/Out) Attention, BirthDate, Name, PurposeCode, SexCode, [State]
2. (In/Out) Attention, OperatorLicenseNumber, PurposeCode, [State]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	C	1	
State	State	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, [State]
2. (In/Out) OperatorLicenseNumber, [State]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	O	4	
GunMakeCode	GunMakeCode	O	3	
GunSerialNumber	GunSerialNumber	M	11	

Possible Combinations

1. (In/Out) GunSerialNumber, [GunCaliber, GunMakeCode]

LogoffRequest

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Password	Password	M	8	
UserName	UserName	O	20	

Possible Combinations

1. (In/Out) Password, [UserName]

LogonRequest

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Password	Password	M	8	
UserName	UserName	O	20	

Possible Combinations

1. (In/Out) Password, [UserName]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	8	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
State	State	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	
VehicleYear	VehicleYear	C	4	

Possible Combinations

1. (In/Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, [State]
2. (In/Out) VehicleIdentificationNumber, [State]
3. (In/Out) VehicleIdentificationNumber, VehicleMakeCode, VehicleYear, [State]

Transactions Supported:

Computerized Criminal History (CCH)

CCHCriminalHistoryAQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
Destination	Destination	M	9	The value may be an ORI or a State code
Destination2	Destination2	O	9	The value may be an ORI or a State code
Destination3	Destination3	O	9	The value may be an ORI or a State code
Destination4	Destination4	O	9	The value may be an ORI or a State code
Destination5	Destination5	O	9	The value may be an ORI or a State code
FreeText	FreeText	M		
PurposeCode	PurposeCode	M	1	

Possible Combinations

1. (In/Out) Attention, Destination, PurposeCode, FreeText, [Destination2, Destination3, Destination4, Destination5]

CCHCriminalHistoryFQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressZipCode	AddressZipCode	O	9	
Attention	Attention	M	30	
Building	Building	O	30	
CityState	CityState	O	30	
DepartmentName	DepartmentName	O	30	
PurposeCode	PurposeCode	M	1	

State	State	O	2	
StateIdNumber	StateIdNumber	M	10	

Possible Combinations

1. (In/Out) Attention, PurposeCode, StateIdNumber, [AddressZipCode, Building, CityState, DepartmentName, State]

CCHCriminalHistoryIPQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressZipCode	AddressZipCode	O	9	
Attention	Attention	C	30	
Building	Building	O	30	
CityState	CityState	O	30	
DepartmentName	DepartmentName	O	30	
InterpolIdNumber	InterpolIdNumber	O	60	
PurposeCode	PurposeCode	C	1	
State	State	O	2	
StateIdNumber	StateIdNumber	C	10	
BirthDate	BirthDate	O	8	
Name	Name	O	100	

Possible Combinations

1. (In/Out) InterpolIdNumber, BirthDate, Name

CCHCriminalHistoryIQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	C	30	
BirthDate	BirthDate	C	8	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	C	30	
PurposeCode	PurposeCode	C	1	
RaceCode	RaceCode	O	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
State	State	O		
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	

Possible Combinations

1. (In/Out) Attention, BirthDate, Name, PurposeCode, SexCode, [MiscellaneousNumber, RaceCode, SocialSecurityNumber, State, State2, State3, State4, State5]

CCHCriminalHistoryQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
PurposeCode	PurposeCode	C	1	

RaceCode	RaceCode	C	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) BirthDate, Name, PurposeCode, RaceCode, SexCode, [Attention, MiscellaneousNumber, SocialSecurityNumber]
2. (In/Out) FBINumber, PurposeCode, [Attention]
3. (In/Out) MiscellaneousNumber, Name, PurposeCode, [Attention]
4. (In/Out) Name, PurposeCode, SocialSecurityNumber, [Attention]
5. (In/Out) PurposeCode, StateIdNumber, [Attention]

CCHCriminalHistoryQRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	C	30	
FBINumber	FBINumber	C	9	
Name	Name	O	30	
PurposeCode	PurposeCode	C	1	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) Attention, FBINumber, PurposeCode
2. (In/Out) Attention, PurposeCode, StateIdNumber

CCHCriminalHistoryZRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FBINumber	FBINumber	C	9	
PurposeCode	PurposeCode	O	1	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) FBINumber, [PurposeCode]
2. (In/Out) StateIdNumber, [PurposeCode]

Expanded Transactions Supported:

DispatchQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	
RaceCode	RaceCode	O	1	
SexCode	SexCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
VehicleColorCode	VehicleColorCode	O	7	

VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	24	
VehicleModelCode	VehicleModelCode	C	3	
VehicleStyleCode	VehicleStyleCode	C	2	
VehicleYear	VehicleYear	C	4	

Possible Combinations

1. (In/Out) BirthDate, Name, [LicensePlateNumber, OperatorLicenseNumber, OperatorLicenseStateCode, RaceCode, SexCode, SocialSecurityNumber, VehicleIdentificationNumber]
2. (In/Out) LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, LicensePlateYear
3. (In/Out) OperatorLicenseNumber, OperatorLicenseStateCode, [SocialSecurityNumber]
4. (In/Out) VehicleIdentificationNumber, VehicleMakeCode, VehicleModelCode, VehicleStyleCode, VehicleYear, [LicensePlateStateCode, VehicleColorCode]

NLETSGeneralPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	C	20	
AddressState	AddressState	C	20	
AddressStreet	AddressStreet	C	20	
AddressStreetName2	AddressStreetName2	O	20	
AddressZipCode	AddressZipCode	C	10	
AdmissionNumber	AdmissionNumber	C	30	
AlienNumber	AlienNumber	C	9	
BirthDate	BirthDate	O	8	
Country	Country	O	30	
FBINumber	FBINumber	C	9	
FingerPrintID	FingerPrintID	C	30	
Height	Height	O	3	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
PassportNumber	PassportNumber	C	20	
PetitionNumber	PetitionNumber	C	30	
SEVISID	SEVISID	C	30	
SexCode	SexCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateIDNumber	StateIDNumber	C	9	
TECSCaseID	TECSCaseID	C	30	
TECSSubjectID	TECSSubjectID	C	30	
TelephoneNumber	TelephoneNumber	C	20	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) AddressCity, AddressState, AddressStreet, [AddressStreetName2, Country]
2. (In/Out) AddressStreet, AddressZipCode, [AddressStreetName2, Country]
3. (In/Out) AdmissionNumber
4. (In/Out) AlienNumber
5. (In/Out) FBINumber
6. (In/Out) FingerPrintID
7. (In/Out) Name, [Height, SexCode, Weight]
8. (In/Out) OperatorLicenseNumber

9. (In/Out) PassportNumber
10. (In/Out) PetitionNumber
11. (In/Out) SEVISID
12. (In/Out) SocialSecurityNumber
13. (In/Out) StateIdNumber
14. (In/Out) TECSCaseID
15. (In/Out) TECSSubjectID
16. (In/Out) TelephoneNumber

NLETSInterpolQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
InterpolIdNumber	InterpolIdNumber	C	60	
BirthDate	BirthDate	C	8	
Name	Name	C	100	

Possible Combinations

1. (In/Out) BirthDate, Name
2. (In/Out) InterpolIdNumber

QueryPassThrough

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FreeText	FreeText	M		

Possible Combinations

1. (In/Out) FreeText

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- JLINK Documentation