

Nevada (NV) JLINK XML

[Disclaimer Statement](#)

Transport:

Web Services - XML

Routing and Configuration Information:

Save Byte Routing (Primary)

Mnemonic Routing (Secondary)

- The JLINK assigned ORI for a device (or for the site) should be placed in the <Authentication>/<ORI> field in the ConnectCIC header.
- The JLINK assigned Mnemonic for a device should be placed in the <Authentication>/<Mnemonic> field in the ConnectCIC header.
- The JLINK assigned User ID should be placed in the <Authentication>/<UserName> field in the ConnectCIC header.

Security Requirements:

None known at this time.

Logon Requirements:

Server level logon to connect to JLINK

User logon form application layer.

Certification Requirements:

Agency sponsor is required.

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y or blank

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode, [ImageIndicator]

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	20	
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y or blank
RegistrationNumber	RegistrationNumber	C	8	

State	State	O	2	
-------	-------	---	---	--

Possible Combinations

1. (In/Out) BoatHullIdNumber, [ImageIndicator, State]
2. (In/Out) RegistrationNumber, [ImageIndicator, State]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y or blank
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	30	
PurposeCode	PurposeCode	O	1	C,J,E,F,D,S
SexCode	SexCode	O	1	
State	State	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, [Attention, ImageIndicator, PurposeCode, SexCode, State]
2. (In/Out) OperatorLicenseNumber, [Attention, ImageIndicator, PurposeCode, State]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
ImageIndicator	ImageIndicator	O	1	0: No image (Default) 1: NCIC/Nlets image 2: NCIC/NV DMV image (In-state only)
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	C	1	
State	State	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, [ImageIndicator, State]
2. (In/Out) OperatorLicenseNumber, [ImageIndicator, State]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	O	4	
GunMakeCode	GunMakeCode	O	3	
GunSerialNumber	GunSerialNumber	M	11	
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y or blank

Possible Combinations

1. (In/Out) GunSerialNumber, [ImageIndicator, GunCaliber, GunMakeCode]

LogonRequest

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Password	Password	M		
NewPassword	NewPassword	O		
UserName	UserName	M		

Possible Combinations

1. (In/Out) Password, UserName

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageIndicator	ImageIndicator	O	1	0: No image (Default) 1: NCIC/Nlets image
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
State	State	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleModelCode	VehicleModelCode	O	3	
VehicleStyleCode	VehicleStyleCode	O	2	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In/Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, [State]
2. (In/Out) VehicleIdentificationNumber, [State, VehicleMakeCode, VehicleModelCode, VehicleStyleCode, VehicleYear]

Transactions Supported:

Agency Operations and Support (AOS)

AOSHazardousMaterialQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
UnitedNationsNumber	UnitedNationsNumber	M	4	

Possible Combinations

1. (In/Out) UnitedNationsNumber

AOSLojackCheckQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LoJackReplyCode	LoJackReplyCode	M	5	
NletsDestination	NletsDestination	O	9	
NletsDestination2	NletsDestination2	O	9	
NletsDestination3	NletsDestination3	O	9	
NletsDestination4	NletsDestination4	O	9	
NletsDestination5	NletsDestination5	O	9	

Possible Combinations

1. LoJackReplyCode, [NletsDestination (up to 5)]

AOSLojackQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LoJackReplyCode	LoJackReplyCode	M	5	
NletsDestination	NletsDestination	O	9	
NletsDestination2	NletsDestination2	O	9	

NletsDestination3	NletsDestination3	O	9	
NletsDestination4	NletsDestination4	O	9	
NletsDestination5	NletsDestination5	O	9	

Possible Combinations

1. LoJackReplyCode, [NletsDestination (up to 5)]

Canadian Basic Inquiries (CBI)

CbiArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	23	
ArticleTypeCode	ArticleTypeCode	M	2	See Nlets Wiki
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	Y, N
ReasonCode	ReasonCode	M	1	See Nlets Wiki

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode, PersonPropertyInSightIndicator, ReasonCode

CbiBoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	12	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	Y, N
ReasonCode	ReasonCode	M	1	See Nlets Wiki
RegistrationNumber	RegistrationNumber	C	7	
State	State	C	2	See Nlets Wiki

Possible Combinations

1. (In/Out) BoatHullIdNumber, PersonPropertyInSightIndicator, ReasonCode
2. (In/Out) RegistrationNumber, PersonPropertyInSightIndicator, ReasonCode, State

CbiDriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M	8	
Name	Name	M	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	Optional for Alberta, British Columbia, Quebec, and Ontario.
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	Y, N
ReasonCode	ReasonCode	M	1	See Nlets Wiki
SexCode	SexCode	M	1	
State	State	M	2	See Nlets Wiki

Possible Combinations

1. (In/Out) Name, BirthDate, SexCode, PersonPropertyInSightIndicator, ReasonCode, State, [OperatorLicenseNumber]

CbiGunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunSerialNumber	GunSerialNumber	M	23	
GunTypeCode	GunTypeCode	M	2	See Nlets Wiki

PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	Y, N
ReasonCode	ReasonCode	M	1	See Nlets Wiki

Possible Combinations

1. (In/Out) GunSerialNumber, GunTypeCode, PersonPropertyInSightIndicator, ReasonCode

CbiVehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	10	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	Y, N
ReasonCode	ReasonCode	M	1	See Nlets Wiki
State	State	M	2	See Nlets Wiki
VehicleIdentificationNumber	VehicleIdentificationNumber	C	17	

Possible Combinations

1. (In/Out) VehicleIdentificationNumber, PersonPropertyInSightIndicator, ReasonCode, State
2. (In/Out) LicensePlateNumber, PersonPropertyInSightIndicator, ReasonCode, State

Computerized Criminal History (CCH)

CCHCriminalHistoryQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Alphanumeric,Special chars,See NCIC code manual
BirthDate	BirthDate	C	8	Numeric-Date. See NCIC manual
FBINumber	FBINumber	C	9	Alphanumeric. See NCIC manual
MiscellaneousNumber	MiscellaneousNumber	C	15	Alphanumeric,Special chars,See NCIC code manual
Name	Name	C	30	Alphanumeric,Special chars,See NCIC code manual
NvJlinkApplication	NvJlinkApplication	O	4	CJIS – Composite query NCIC – NCIC-only query BLANK – Defaults to CJIS
PurposeCode	PurposeCode	M	1	Alphabetic: C,D,E,F,J,S. See NCIC code manual
RaceCode	RaceCode	C	1	Alphabetic: I, A, B, W, U. See NCIC code manual
ReasonCode	ReasonCode	O	30	Alphabetic: C,D,F,J,H. See JLINK documentation
SexCode	SexCode	C	1	Alphabetic: M, F, U. See NCIC code manual
SocialSecurityNumber	SocialSecurityNumber	C	9	Numeric
StateIdNumber	StateIdNumber	C	10	Alphanumeric. See NCIC manual

Possible Combinations

1. (In/Out) BirthDate , Name, PurposeCode, RaceCode, SexCode, [Attention, NvJlinkApplication, ReasonCode]
2. (In/Out) BirthDate , Name, PurposeCode, RaceCode, SexCode, SocialSecurityNumber, [Attention, NvJlinkApplication, ReasonCode]
3. (In/Out) BirthDate , Name, PurposeCode, RaceCode, SexCode, MiscellaneousNumber, [Attention, NvJlinkApplication, ReasonCode]
4. (In/Out) Name, PurposeCode, SocialSecurityNumber, [Attention, NvJlinkApplication, ReasonCode]
5. (In/Out) Name, MiscellaneousNumber, PurposeCode, [Attention, NvJlinkApplication, ReasonCode]
6. (In/Out) PurposeCode, StateIdNumber, [Attention, Name, NvJlinkApplication, ReasonCode]
7. (In/Out) FBINumber, PurposeCode, [Attention, Name, NvJlinkApplication, ReasonCode]

CCHCriminalHistoryQRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	30	Alphanumeric,Special chars,See NCIC manual
AddressStreet	AddressStreet	O	30	Alphanumeric,Special chars,See NCIC manual
AddressZipCode	AddressZipCode	O	9	Numeric
Attention	Attention	M	30	Alphanumeric,Special chars,See NCIC code manual
BuildingName	BuildingName	O	30	Alphanumeric,Special chars,See NCIC code manual
DepartmentName	DepartmentName	O	30	Alphanumeric,Special chars,See NCIC code manual
FBINumber	FBINumber	C	9	Alphanumeric. See NCIC manual
Name	Name	O	30	Alphanumeric,Special chars,See NCIC code manual
NvJlinkApplication	NvJlinkApplication	O	4	CJIS – Composite query NCIC – NCIC-only query BLANK – Defaults to CJIS
PurposeCode	PurposeCode	M	1	Alpahbetic: C,D,E,F,J,S. See NCIC code manual
ReasonCode	ReasonCode	O	30	Alphabetic. C,D,F,J,H. See JLINK documentation
StateldNumber	StateldNumber	C	10	Alphanumeric,Special chars,See NCIC code manual

Possible Combinations

1. (In/Out) Attention, FBINumber, PurposeCode, [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName, Name, NvJlinkApplication, ReasonCode]
2. (In/Out) Attention, PurposeCode, StateldNumber [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName, Name, NvJlinkApplication, ReasonCode]

CCHCriminalHistoryQWQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Alphanumeric,Special chars,See NCIC code manual
BirthDate	BirthDate	C	8	Numeric-Date. See NCIC manual
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Numeric: 1, 2, 3 – See NCIC manual
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Alphabetic: Y, N, or blank
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y or blank
MiscellaneousNumber	MiscellaneousNumber	C	15	Alphanumeric,Special chars,See NCIC code manual
Name	Name	M	30	Alphanumeric,Special chars,See NCIC code manual
NvJlinkApplication	NvJlinkApplication	O	1	CJIS – Composite query NCIC – NCIC-only query BLANK – Defaults to CJIS
PurposeCode	PurposeCode	M	1	Alpahbetic: C,D,E,F,J,S. See NCIC code manual
RaceCode	RaceCode	C	1	Alphabetic: I, A, B, W, U. See NCIC code manual
ReasonCode	ReasonCode	O	30	Alphabetic. C,D,F,J,H. See JLINK documentation
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Alphabetic: Y, N, or blank
SexCode	SexCode	C	1	Alpha: M, F, U
SocialSecurityNumber	SocialSecurityNumber	C	9	Numeric

Possible Combinations

1. (In/Out) BirthDate , Name, PurposeCode, RaceCode, SexCode, [Attention, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, NvJlinkApplication, ReasonCode, RelatedHitSearchIndicator]
2. (In/Out) BirthDate , Name, PurposeCode, RaceCode, SexCode, SocialSecurityNumber, [Attention, ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, NvJlinkApplication, RelatedHitSearchIndicator]
3. (In/Out) BirthDate , Name, PurposeCode, RaceCode, ReasonCode, SexCode, MiscellaneousNumber, [Attention, ExpandedBirthDateSearchCode,

- ExpandedNameSearchCode, ImageIndicator, NvJlinkApplication, ReasonCode, RelatedHitSearchIndicator]
4. (In/Out) Name, PurposeCode, SocialSecurityNumber, [Attention, ExpandedNameSearchCode, ImageIndicator, NvJlinkApplication, ReasonCode, RelatedHitSearchIndicator]
5. (In/Out) Name, MiscellaneousNumber, PurposeCode, [Attention, ExpandedNameSearchCode, ImageIndicator, NvJlinkApplication, ReasonCode, RelatedHitSearchIndicator]

CCHCriminalHistoryAQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	Alphanumeric; See NLETS manual
FreeText	FreeText	M	14400	Alphanumeric, special chars; See NLETS manual
NletsDestination	NletsDestination	M	9	2- or 9-character destination ORI
NletsDestination2	NletsDestination2	O	9	2- or 9-character destination ORI
NletsDestination3	NletsDestination3	O	9	2- or 9-character destination ORI
NletsDestination4	NletsDestination4	O	9	2- or 9-character destination ORI
NletsDestination5	NletsDestination5	O	9	2- or 9-character destination ORI
PurposeCode	PurposeCode	M	1	Alphabetic: C,D,E,F,J,I,S. See NLETS manual

Possible Combinations

1. (In/Out) Attention, FreeText, NletsDestination, PurposeCode, [NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5]

CCHCriminalHistoryARQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	Alphanumeric; See NLETS manual
FreeText	FreeText	O	14400	Alphanumeric, special chars; See NLETS manual
NletsDestination	NletsDestination	O	9	9-character destination ORI
PurposeCode	PurposeCode	O	1	Alphabetic: C,D,E,F,J,I,S. See NLETS manual

Possible Combinations

1. (In/Out) Attention, FreeText, NletsDestination, PurposeCode

CCHCriminalHistoryFQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	30	Alphanumeric, Special chars, See NCIC manual
AddressStreet	AddressStreet	O	30	Alphanumeric, Special chars, See NCIC manual
AddressZipCode	AddressZipCode	O	9	Numeric
Attention	Attention	M	30	Alphanumeric, Special chars, See NCIC manual
BuildingName	BuildingName	O	30	Alphanumeric, Special chars, See NCIC manual
DepartmentName	DepartmentName	O	30	Alphanumeric, Special chars, See NCIC manual
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y or blank
NvJlinkApplication	NvJlinkApplication	O	5	CJIS – Composite query NLETS – NLETS-only query BLANK – Defaults to CJIS
PurposeCode	PurposeCode	M	1	Alphabetic: C,D,E,F,J,I,S. See NLETS manual
State	State	O	2	2 alphanumeric character NLETS state/province code
StateIdNumber	StateIdNumber	M	10	Alphanumeric, Special chars, See NCIC code manual

Possible Combinations

1. (In/Out) Attention, PurposeCode, StateIdNumber, [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName, ImageIndicator, NvJlinkApplication, State]

CCHCriminalHistoryIQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	Alphanumeric,Special chars,See NCIC manual
BirthDate	BirthDate	M	8	Numeric-Date. See NCIC/NLETS manual
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y or blank
MiscellaneousNumber	MiscellaneousNumber	O	15	Alphanumeric,Special chars,See NCIC code manual
Name	Name	M	30	Alphanumeric,Special chars,See NCIC/NLETS manual
NvJlinkApplication	NvJlinkApplication	O	5	CJIS – Composite query NLETS – NLETS-only query BLANK – Defaults to CJIS
PurposeCode	PurposeCode	M	1	Alpahbetic: C,D,E,F,J,I,S. See NLETS manual
RaceCode	RaceCode	O	1	Alphabetic: I, A, B, W, U. See NCIC code manual
SexCode	SexCode	M	1	Alpha: M, F, U
SocialSecurityNumber	SocialSecurityNumber	O	9	Numeric
State	State	O	2	2 alphanumeric character NLETS state/province code

Possible Combinations

1. (In/Out) Attention, BirthDate, Name, PurposeCode, SexCode, [ImageIndicator, MiscellaneousNumber, NvJlinkApplication, RaceCode, SocialSecurityNumber, State]

Wanted Missing Person Entry (WMPE)

WMPEProtectionOrderServiceEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BINIdNumber	BINIdNumber	C	18	See JLINK operating manual
CourtCaseNumber	CourtCaseNumber	C	15	AN, special chars. See JLINK operating manual. 5 fields are supported. Additional identifiers should use the XML tag name with the number 2-5 appended.
CourtORI	CourtORI	C	9	Alphanumeric, See JLINK operating manual
ProtectionOrderNumber	ProtectionOrderNumber	C	18	Alphanumeric, See JLINK operating manual. 5 fields are supported. Additional identifiers should use the XML tag name with the number 2-5 appended.
ProtectionOrderTypeCode	ProtectionOrderTypeCode	C	3	See JLINK operating manual. EXT - Extended Protective Order FRO - Foreign Order MEX - Modified Extended Protection Order MTO - Modified Temporary Protection Order TPO - Temporary Protective Order NOH - Notice of Hearing OOH - Order of Hearing

				10 fields are supported. Additional identifiers should use the XML tag name with the number 2-10 appended.
ServiceAgencyORI	ServiceAgencyORI	M	9	Alphanumeric, See JLINK operating manual
ServiceOfficerIdNumber	ServiceOfficerIdNumber	M	7	Alphanumeric, See JLINK operating manual
ServiceOfficerName	ServiceOfficerName	M	30	Alphanumeric, See JLINK operating manual
ServiceDate	ServiceDate	M	8	Numeric, Date. See JLINK operating manual
ServiceTime	ServiceTime	M	10	See JLINK operating manual. Military or standard time format. Examples: Military: 2210, 0815 Standard: 10:10P, 8:15A
ServiceTypeCode	ServiceTypeCode	C	3	See JLINK operating manual. CAP - Court Appearance HCY - Hard Copy MAI - Mail VER - Verbal 10 fields are supported. Additional identifiers should use the XML tag name with the number 2-10 appended.

Possible Combinations - #1 is required for all entries; #2 and #3 can have none, one, or both entered on a given entry as well, but are not required.

1. ServiceAgencyORI, ServiceDate, ServiceOfficerIdNumber, ServiceOfficerName, ServiceTime
2. BINIdNumber, ProtectionOrderNumber, ProtectionOrderTypeCode, ServiceTypeCode, [ProtectionOrderNumber2...5, ProtectionOrderTypeCode2...5, ServiceTypeCode2...5]
3. CourtCaseNumber, CourtORI, ProtectionOrderTypeCode6, ServiceTypeCode6, [CourtCaseNumber2...5, ProtectionOrderTypeCode6...10, ServiceTypeCode6...10]

Wanted Missing Person Inquiries (WMP-I)

WMPProtectionOrderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AgencyIdCode	AgencyIdCode	O	3	See JLINK manual 5 fields are supported. Additional identifiers should use the XML tag name with the number 2-5 appended.
AgencyIdNumber	AgencyIdNumber	O	5	See JLINK manual 5 fields are supported. Additional identifiers should use the XML tag name with the number 2-5 appended.
AgencyTypeCode	AgencyTypeCode	O	1	See JLINK manual 5 fields are supported. Additional identifiers should use the XML tag name with the number 2-5 appended.
AlsoKnownAs	AlsoKnownAs	O	50	Alphanumeric, Special chars, See NCIC code manual
BINIdNumber	BINIdNumber	O	5	See JLINK manual
BirthDate	BirthDate	O	8	Numeric-Date. See NCIC manual
CourtCaseNumber	CourtCaseNumber	O	10	Alphanumeric. See JLINK manual
DisplayIndicator	DisplayIndicator	O	1	Y, BLANK. See JLINK manual
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Y, BLANK. See NCIC manual

ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Y, BLANK. See NCIC manual
FBINumber	FBINumber	O	9	Alphanumeric. See NCIC manual
FingerprintBasedIndicator	FingerprintBasedIndicator	O	1	Y, BLANK. See JLINK manual
FullResponseIndicator	FullResponseIndicator	O	1	Y, BLANK. See JLINK manual
Height	Height	O	3	Numeric. See NCIC manual
ImageIndicator	ImageIndicator	O	1	Y, BLANK. See NCIC manual
InquiryTypeIndicator	InquiryTypeIndicator	O	1	1 - Both NCIC and NV (Default) 2 - NCIC Only 3 - NV Only
JuvenileIndicator	JuvenileIndicator	O	1	Y, BLANK. See JLINK manual
LicensePlateNumber	LicensePlateNumber	C	10	Alphanumeric. See NCIC manual
LicensePlateStateCode	LicensePlateStateCode	C	2	Alphanumeric. See NCIC manual
MDTIndicator	MDTIndicator	O	1	Y, BLANK. See JLINK manual
MiscellaneousNumber	MiscellaneousNumber	C	15	Alphanumeric, Special chars, See NCIC manual
Name	Name	O	30	Alphanumeric, Special chars, See NCIC code manual
NCICNumber	NCICNumber	C	10	Alphanumeric. See NCIC manual
NdiConfidentialCode	NdiConfidentialCode	O	1	See JLINK manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	Alphanumeric, Special chars, See NCIC code manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	Alphanumeric, Special chars, See NCIC code manual
PMTCode	PMTCode	O	13	See JLINK manual
PCNIdNumber	PCNIdNumber	O	7	See JLINK manual
ProtectionOrderNumber	ProtectionOrderNumber	O	1	See JLINK manual
RaceCode	RaceCode	O	1	Alphabetic: I, A, B, W, U. See NCIC code manual
RecordStatusCode	RecordStatusCode	O	1	See JLINK manual
RecordTypeCode	RecordTypeCode	O	1	See JLINK manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Y, BLANK. See JLINK manual
RNGCode	RNGCode	O	2	Range; See JLINK manual
SexCode	SexCode	O	1	Alphabetic: M, F, U. See NCIC code manual
SocialSecurityNumber	SocialSecurityNumber	O	9	Numeric. See NCIC manual
StateIdNumber	StateIdNumber	O	10	Alphanumeric. See NCIC manual
SuppressedIndicator	SuppressedIndicator	O	1	Y, BLANK. See JLINK manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	Alphanumeric, See NCIC Code Manual
VehicleMakeCode	VehicleMakeCode	C	24	Alphanumeric, See NCIC Code Manual
Weight	Weight	O	3	Numeric. See NCIC manual
WRNCode	WRNCode	O	1	See JLINK manual

Possible Combinations

1. **(NV)** [AgencyIdCode, AgencyIdNumber, AgencyTypeCode, AlsoKnownAs, BINIdNumber, BirthDate, CourtCaseNumber, DisplayIndicator, FBINumber, FingerprintBasedIndicator, FullResponseIndicator, Height, JuvenileIndicator, MDTIndicator, Name, NdiConfidentialCode, OperatorLicenseNumber, OriginatingAgencyCaseNumber, PMTCode, PCNIdNumber, ProtectionOrderNumber, RaceCode, RecordStatusCode, RecordTypeCode, RNGCode, SexCode, SocialSecurityNumber, StateIdNumber, SuppressedIndicator, LicensePlateNumber, LicensePlateStateCode, VehicleIdentificationNumber, Weight, WRNCode]
2. **(NCIC)** Name, BirthDate, [ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, RaceCode, RelatedHitSearchIndicator, SexCode]
3. **(NCIC)** Name, OriginatingAgencyCaseNumber, [ExpandedNameSearchCode, ImageIndicator, RaceCode, RelatedHitSearchIndicator, SexCode]

4. **(NCIC)** Name, ProtectionOrderNumber, [ExpandedNameSearchCode, ImageIndicator, RaceCode, RelatedHitSearchIndicator, SexCode]
5. **(NCIC)** NCICNumber, [ImageIndicator, RelatedHitSearchIndicator]
6. **(NCIC)** Name, FBINumber, [ImageIndicator, RelatedHitSearchIndicator]
7. **(NCIC)** Name, MiscellaneousNumber, [ImageIndicator, RelatedHitSearchIndicator]
8. **(NCIC)** Name, OperatorLicenseNumber, [ImageIndicator, RelatedHitSearchIndicator]
9. **(NCIC)** Name, SocialSecurityNumber, [ImageIndicator, RelatedHitSearchIndicator]
10. **(NCIC)** LicensePlateNumber, LicensePlateStateCode, [ImageIndicator, RelatedHitSearchIndicator, VehicleIdentificationNumber, VehicleMakeCode]
11. **(NCIC)** VehicleIdentificationNumber, VehicleMakeCode, [ImageIndicator, RelatedHitSearchIndicator, LicensePlateNumber, LicensePlateStateCode]

WMPIWantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values	
AllRecordsIndicator	AllRecordsIndicator	O	1	Y, BLANK, See JLINK operating manual	
BirthDate	BirthDate	C	8	Numeric, Date. See NCIC code manual	
CcwIndicator	CcwIndicator	O	1	Y, BLANK, See JLINK operating manual	
CletsInformationCode	CletsInformationCode	O	2	Alphanumeric, See JLINK operating manual	
CriminalHistoryIndicator	CriminalHistoryIndicator	O	1	Y, BLANK, See JLINK operating manual	
DonsIndicator	DonsIndicator	O	1	Y, BLANK, See JLINK operating manual	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Numeric: 1, 2, 3 – See NCIC manual	
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Blank, Y	
FBINumber	FBINumber	C	9	FBINumber	FBINumber
FingerprintBasedFprAndNfrIndicator	FingerprintBasedFprAndNfrIndicator	O	1	Y, BLANK, See JLINK operating manual	
ImageIndicator	ImageIndicator	O	1	Blank, Y	
LicensePlateNumber	LicensePlateNumber	C	10	Alphanumeric, See NCIC Code Manual	
LicensePlateStateCode	LicensePlateStateCode	C	2	Alphabetic, See NCIC Code Manual	
MaxRowsCode	MaxRowsCode	O	2	Numeric, see JLINK operating manual	
MessageKeyModifier	MessageKeyModifier	O	1	Blank, A, E, F, S See NCIC Wanted Person File for additional information on different message keys available.	
MDTIndicator	MDTIndicator	O	1	Y, BLANK, See JLINK manual	
MSTIndicator	MSTIndicator	O	1	Y, BLANK, See JLINK manual	
MiscellaneousNumber	MiscellaneousNumber	C	15	MiscellaneousNumber	MiscellaneousNumber
Name	Name	C	30	Alphanumeric, Special chars, See NCIC code manual	
NCICNumber	NCICNumber	C	10	Alphanumeric, See NCIC Code Manual	
NvJlinkApplication	NvJlinkApplication	O	4	CJIS – Composite query NCIC – NCIC-only query BLANK – Defaults to CJIS	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	Alphanumeric, Special chars, See NCIC code manual	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	Alphanumeric, Special chars, See NCIC code manual	
ProtectionOrdersIndicator	ProtectionOrdersIndicator	O	1	Y, BLANK, See JLINK operating manual	
RaceCode	RaceCode	O	1	See NCIC Code Manual	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Blank, Y	
ResponseTypeCode	ResponseTypeCode	O	1	Defaults to 0 if not specified	
SexCode	SexCode	O	1	See NCIC Code Manual	
SexOffendersIndicator	SexOffendersIndicator	O	1	Y, BLANK, See JLINK operating manual	
SocialSecurityNumber	SocialSecurityNumber	C	9	Numeric, See NCIC code manual	

SoundexIndicator	SoundexIndicator	O	1	Y, BLANK, See JLINK operating manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	Alphanumeric, See NCIC Code Manual
VehicleMakeCode	VehicleMakeCode	C	24	See NCIC Code Manual

Possible Combinations

1. (In/Out) Name, BirthDate, [Optional Fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, [Optional Fields]
3. (In/Out) NCICNumber, [Optional Fields]
4. (In/Out) Name, FBINumber, [Optional Fields]
5. (In/Out) Name, MiscellaneousNumber, [Optional Fields]
6. (In/Out) Name, OperatorLicenseNumber, [Optional Fields]
7. (In/Out) Name, SocialSecurityNumber, [Optional Fields]
8. (In/Out) LicensePlateNumber, LicensePlateStateCode, [Optional Fields, VehicleIdentificationNumber, VehicleMakeCode]
9. (In/Out) VehicleIdentificationNumber, VehicleMakeCode, [Optional Fields, LicensePlateNumber, LicensePlateStateCode]

Expanded Transactions Supported:

CanadianDriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M	8	
Name	Name	M	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	
ReasonCode	ReasonCode	O	1	
SexCode	SexCode	O	1	
State	State	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, PersonPropertyInSightIndicator, [OperatorLicenseNumber, ReasonCode, SexCode, State]

DispatchQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
ImageIndicator	ImageIndicator	O	1	0: No image (Default) 1: NCIC/Nlets image 2: NCIC/NV DMV image (In-state only)
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
RaceCode	RaceCode	O	1	
SexCode	SexCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
State	State	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleModelCode	VehicleModelCode	O	3	
VehicleStyleCode	VehicleStyleCode	O	2	

VehicleYear	VehicleYear	O	4	
-------------	-------------	---	---	--

Possible Combinations

1. (In/Out) Name, [BirthDate, ImageIndicator, RaceCode, SexCode, State]
2. (In/Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, [ImageIndicator, State]
3. (In/Out) OperatorLicenseNumber, [ImageIndicator, SocialSecurityNumber, State]
4. (In/Out) VehicleIdentificationNumber, [ImageIndicator, State, VehicleMakeCode, VehicleModelCode, VehicleStyleCode, VehicleYear]

NvJlinkDspt

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	10	
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y or blank
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	O	4	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
RaceCode	RaceCode	O	1	
SexCode	SexCode	O	1	
State	State	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleModelCode	VehicleModelCode	O	3	
VehicleStyleCode	VehicleStyleCode	O	2	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In/Out) OperatorLicenseNumber, [ImageIndicator, State]
2. (In/Out) BirthDate, Name, OperatorLicenseNumber, [ImageIndicator, RaceCode, SexCode, State]
3. (In/Out) BirthDate, Name, [ImageIndicator, RaceCode, SexCode, State]
4. (In/Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, [ImageIndicator, State, VehicleIdentificationNumber, VehicleMakeCode, VehicleModelCode, VehicleStyleCode, VehicleYear]
5. (In/Out) VehicleIdentificationNumber, [ImageIndicator, State, VehicleMakeCode, VehicleModelCode, VehicleStyleCode, VehicleYear]

NvJlinkDQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y or blank
Name	Name	C	30	
NvJlinkApplication	NvJlinkApplication	O	5	CJIS – Composite query NLETS – NLETS-only query BLANK – Defaults to NLETS
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	M	2	
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, [ImageIndicator, NvJlinkApplication, State]

2. (In/Out) OperatorLicenseNumber, [ImageIndicator, NvJlinkApplication, State]
3. (In) SocialSecurityNumber, [ImageIndicator] *****In-state CJIS DMV lookup ONLY**

NvJlinkDNQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
City	City	O	20	Alphanumeric, See Nlets Wiki
CletsInformationCode	CletsInformationCode	O	2	Alphanumeric, See JLINK operating manual
County	County	O	20	Alphanumeric, See Nlets Wiki
MDTIndicator	MDTIndicator	O	1	Y, BLANK, See JLINK manual
Name	Name	M	30	Alphanumeric, Special characters, See NCIC Code Manual
NextPage	NextPage	O	20	See Nlets Wiki
NvJlinkApplication	NvJlinkApplication	O	5	CJIS – Composite query NLETS – NLETS-only query BLANK – Defaults to CJIS
Age	Age	O	2	See Nlets Wiki
SexCode	SexCode	O	1	Alpha, M, F, U. See Nlets Wiki
State	State	O	2	See Nlets Wiki
State2	State2	O	2	See Nlets Wiki
State3	State3	O	2	See Nlets Wiki
State4	State4	O	2	See Nlets Wiki
State5	State5	O	2	See Nlets Wiki

Possible Combinations

1. (In/Out) Name, [Optional Fields]

NvJlinkNletsFPQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
InterpolIdNumber	InterpolIdNumber	M	60	

Possible Combinations

2. (In/Out) InterpolIdNumber

NvJlinkNletsGPQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	2	
AddressStateCode	AddressStateCode	O	2	
AddressStreet	AddressStreet	O	20	
AddressZipCode	AddressZipCode	O	5	
Age	Age	O	2	
AlienAdmissionNumber	AlienAdmissionNumber	O	30	
AlienRegistrationNumber	AlienRegistrationNumber	O	9	
AlsoKnownAs	AlsoKnownAs	O	30	
BirthDate	BirthDate	C	8	
DocumentIdNumber	DocumentIdNumber	O	21	
EyeColorCode	EyeColorCode	O	3	
FBINumber	FBINumber	O	15	
FingerprintIdNumber	FingerprintIdNumber	O	30	
HairColorCode	HairColorCode	O	3	
Height	Height	O	3	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	

LocationStateCode	LocationStateCode	C	2	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
PetitionNumber	PetitionNumber	O	30	
RaceCode	RaceCode	O	1	
SexCode	SexCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
StateIdNumber	StateIdNumber	O	10	
StudentExchangeIdNumber	StudentExchangeIdNumber	O	30	
TecsCaseNumber	TecsCaseNumber	O	30	
TecsIdNumber	TecsIdNumber	O	30	
TelephoneNumber	TelephoneNumber	C	10	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, BirthDate, PersonPropertyInSightIndicator, [AddressCity, AddressCounty, AddressStateCode, AddressStreet, AddressZipCode, Age, AlienAdmissionNumber, AlienRegistrationNumber, AlsoKnownAs, , DocumentIdNumber, EyeColorCode, FBINumber, FingerprintIdNumber, HairColorCode, Height, PersonPropertyInSightIndicator, LocationStateCode, MiscellaneousNumber, OperatorLicenseNumber, PetitionNumber, RaceCode, SexCode, SocialSecurityNumber, StateIdNumber, StudentExchangeIdNumber, TecsCaseNumber, TecsIdNumber, TelephoneNumber, Weight]
2. (In/Out) TelephoneNumber, PersonPropertyInSightIndicator, [AddressCity, AddressCounty, AddressStateCode, AddressStreet, AddressZipCode, Age, AlienAdmissionNumber, AlienRegistrationNumber, AlsoKnownAs, BirthDate, DocumentIdNumber, EyeColorCode, FBINumber, FingerprintIdNumber, HairColorCode, Height, PersonPropertyInSightIndicator, LocationStateCode, MiscellaneousNumber, Name, OperatorLicenseNumber, OriginatingAgencyORI, PetitionNumber, RaceCode, SexCode, SocialSecurityNumber, StateIdNumber, StudentExchangeIdNumber, TecsCaseNumber, TecsIdNumber, Weight]
3. (In/Out) LocationStateCode, PersonPropertyInSightIndicator, [AddressCity, AddressCounty, AddressStateCode, AddressStreet, AddressZipCode, Age, AlienAdmissionNumber, AlienRegistrationNumber, AlsoKnownAs, BirthDate, DocumentIdNumber, EyeColorCode, FBINumber, FingerprintIdNumber, HairColorCode, Height, PersonPropertyInSightIndicator, MiscellaneousNumber, Name, OperatorLicenseNumber, OriginatingAgencyORI, PetitionNumber, RaceCode, SexCode, SocialSecurityNumber, StateIdNumber, StudentExchangeIdNumber, TecsCaseNumber, TecsIdNumber, TelephoneNumber, Weight]

NvJlinkNletsIPQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M	8	
Name	Name	M	100	

Possible Combinations

1. (In/Out) BirthDate, Name

NvJlinkNletsWQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M	8	
Name	Name	M	30	
PersonPropertyInSightIndicator	PersonPropertyInSightIndicator	M	1	Y, N
ReasonCode	ReasonCode	M	1	See Nlets Wiki
SexCode	SexCode	M	1	

Possible Combinations

1. (In/Out) Name, BirthDate, SexCode, PersonPropertyInSightIndicator, ReasonCode

NvJlinkQVQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AllRecordsIndicator	AllRecordsIndicator	O	1	Y, BLANK, See JLINK operating manual
CcwIndicator	CcwIndicator	O	1	Y, BLANK, See JLINK operating manual
CletsInformationCode	CletsInformationCode	O	2	Alphanumeric, See JLINK operating manual
CriminalHistoryIndicator	CriminalHistoryIndicator	O	1	Y, BLANK, See JLINK operating manual
DonsIndicator	DonsIndicator	O	1	Y, BLANK, See JLINK operating manual
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Numeric: 1, 2, 3 – See NCIC manual
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Alphabetic: Y, N, or blank
FingerprintBasedFprAndNfrIndicator	FingerprintBasedFprAndNfrIndicator	O	1	Y, BLANK, See JLINK operating manual
ImageIndicator	ImageIndicator	O	1	Blank, Y
LicensePlateNumber	LicensePlateNumber	C	10	Alphanumeric, See NCIC Code Manual
LicensePlateStateCode	LicensePlateStateCode	C	2	Alphabetic, See NCIC Code Manual
MaxRowsCode	MaxRowsCode	O	2	Numeric, see JLINK operating manual
NCICNumber	NCICNumber	C	10	Alphanumeric, See NCIC Code Manual
MDTIndicator	MDTIndicator	O	1	Y, BLANK, See JLINK operating manual
MSTIndicator	MSTIndicator	O	1	Y, BLANK, See JLINK operating manual
NvJlinkApplication	NvJlinkApplication	O	4	CJIS – Composite query NCIC – NCIC-only query BLANK – Defaults to CJIS
ProtectionOrdersIndicator	ProtectionOrdersIndicator	O	1	Y, BLANK, See JLINK operating manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Blank, Y
ResponseTypeCode	ResponseTypeCode	O	1	Defaults to 0 if not specified
SexOffendersIndicator	SexOffendersIndicator	O	1	Y, BLANK, See JLINK operating manual
SoundexIndicator	SoundexIndicator	O	1	Y, BLANK, See JLINK operating manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	Alphanumeric, See NCIC Code Manual
VehicleMakeCode	VehicleMakeCode	C	24	Alphanumeric See NCIC Code Manual

Possible Combinations

1. (In/Out) NCICNumber, [Optional Fields]
2. (In/Out) LicensePlateNumber, LicensePlateStateCode, [Optional Fields, VehicleIdentificationNumber, VehicleMakeCode]
3. (In/Out) VehicleIdentificationNumber, VehicleMakeCode, [Optional Fields, LicensePlateNumber, LicensePlateStateCode]

NvJlinkRQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AllRecordsIndicator	AllRecordsIndicator	O	1	Y, BLANK, See JLINK operating manual
CcwIndicator	CcwIndicator	O	1	Y, BLANK, See JLINK operating manual
CletsInformationCode	CletsInformationCode	O	2	Alphanumeric, See JLINK operating manual
CriminalHistoryIndicator	CriminalHistoryIndicator	O	1	Y, BLANK, See JLINK operating manual
DonsIndicator	DonsIndicator	O	1	Y, BLANK, See JLINK operating manual
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Numeric: 1, 2, 3 – See NCIC manual
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Alphabetic: Y, N, or blank
FingerprintBasedFprAndNfrIndicator	FingerprintBasedFprAndNfrIndicator	O	1	Y, BLANK, See JLINK operating manual
ImageIndicator	ImageIndicator	O	1	Blank, Y
LicensePlateNumber	LicensePlateNumber	C	10	Alphanumeric, See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	Alphabetic, See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	Numeric, Year, See NCIC Code Manual
MaxRowsCode	MaxRowsCode	O	2	Numeric, see JLINK operating manual
MDTIndicator	MDTIndicator	O	1	Y, BLANK, See JLINK operating manual
MSTIndicator	MSTIndicator	O	1	Y, BLANK, See JLINK operating manual
NvJlinkApplication	NvJlinkApplication	O	4	CJIS – Composite query NCIC – NCIC-only query BLANK – Defaults to CJIS
ProtectionOrdersIndicator	ProtectionOrdersIndicator	O	1	Y, BLANK, See JLINK operating manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Blank, Y
ResponseTypeCode	ResponseTypeCode	O	1	Defaults to 0 if not specified
SexOffendersIndicator	SexOffendersIndicator	O	1	Y, BLANK, See JLINK operating manual
SoundexIndicator	SoundexIndicator	O	1	Y, BLANK, See JLINK operating manual
State	State	O	2	Alphabetic, See NCIC Code Manual
State2	State2	O	2	Alphabetic, See NCIC Code Manual
State3	State3	O	2	Alphabetic, See NCIC Code Manual
State4	State4	O	2	Alphabetic, See NCIC Code Manual
State5	State5	O	2	Alphabetic, See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	Alphanumeric, See NCIC Code Manual
VehicleMakeCode	VehicleMakeCode	O	4	Alphanumeric, See NCIC Code Manual
VehicleYear	VehicleYear	O	4	Numeric, Year, See NCIC Code Manual

Possible Combinations

1. (In/Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, [Optional Fields]
2. (In/Out) VehicleIdentificationNumber, [Optional Fields]

NvJlinkScopeQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	C	50	Alphanumeric, Special characters
BirthDate	BirthDate	O	8	Date
DisplayIndicator	DisplayIndicator	O	1	0 – abbreviated metro 1- detailed metro (default)
EventIdNumber	EventIdNumber	C	20	Alphanumeric
IdentificationNumber	IdentificationNumber	C	20	Alphanumeric, Special characters
IdTypeCode	IdTypeCode	O	1	Alpha only
ImageIndicator	ImageIndicator	O	1	TRUE, 1, T, or Y ; FALSE, 0, F, N
Name	Name	C	90	Alphanumeric, Special characters
PersonnelIdNumber	PersonnelIdNumber	C	20	Alphanumeric, See JLINK operating manual
RaceCode	RaceCode	O	1	Alpha only
ScopeOperatorId	ScopeOperatorId	O	3	Alphanumeric
SexCode	SexCode	O	1	Alpha only; M, F, U
SoundexCode	SoundexCode	O	5	TRUE, 1, T, or Y ; FALSE, 0, F, N

Possible Combinations

1. (In) IdentificationNumber, [DisplayIndicator, IdTypeCode, ScopeOperatorId]
2. (In) Name, [AlsoKnownAs, BirthDate, DisplayIndicator, RaceCode, ScopeOperatorId, SexCode, SoundexCode, ImageIndicator]
3. (In) AlsoKnownAs, [BirthDate, DisplayIndicator, Name, RaceCode, ScopeOperatorId, SexCode, SoundexCode, ImageIndicator]
4. (In) PersonnelIdNumber, [ScopeOperatorId]
5. (In) EventIdNumber, [ScopeOperatorId]

NvJlinkScopeWVSCQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
EngineIdNumber	EngineIdNumber	C	30	Alphanumeric, See JLINK operating manual
EventIdNumber	EventIdNumber	C	20	Alphanumeric, See JLINK operating manual
LicensePlateNumber	LicensePlateNumber	C	10	Alphanumeric, See NCIC Code Manual
LicensePlateStateCode	LicensePlateStateCode	O	2	Alphabetic, See NCIC Code Manual
Name	Name	C	90	Alphanumeric, Special characters, See NCIC Code Manual
PersonnelIdNumber	PersonnelIdNumber	C	20	Alphanumeric, See JLINK operating manual
ScopeOperatorId	ScopeOperatorId	O	3	Alphanumeric, See JLINK operating manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	Alphanumeric, See NCIC Code Manual

Possible Combinations

1. (In) EngineIdNumber, [ScopeOperatorId]
2. (In) EventIdNumber, [ScopeOperatorId]
3. (In) Name, [ScopeOperatorId]
4. (In) PersonnelIdNumber, [ScopeOperatorId]
5. (In) LicensePlateNumber, [LicensePlateStateCode, ScopeOperatorId]
6. (In) VehicleIdentificationNumber, [ScopeOperatorId]

NvJlinkSTASQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AgencyIdNumber	AgencyIdNumber	O	5	See JLINK manual

AgencyTypeCode	AgencyTypeCode	O	1	See JLINK manual
AgencyIdCode	AgencyIdCode	O	3	See JLINK manual
AgencyIdNumber2	AgencyIdNumber2	O	5	See JLINK manual
AgencyTypeCode2	AgencyTypeCode2	O	1	See JLINK manual
AgencyIdCode2	AgencyIdCode2	O	3	See JLINK manual
AllRecordsIndicator	AllRecordsIndicator	O	1	Y, BLANK. See JLINK manual
Attention	Attention	O	30	Alphanumeric,Special chars,See NCIC code manual
AlsoKnownAs	AlsoKnownAs	O	50	Alphanumeric,Special chars,See NCIC code manual
BINIdNumber	BINIdNumber	O	5	See JLINK manual
BirthDate	BirthDate	O	8	Numeric-Date. See NCIC manual
CCNIdNumber	CCNIdNumber	O	10	Alphanumeric. See JLINK manual
CcwIndicator	CcwIndicator	O	1	Y, BLANK. See JLINK manual
CivilApplicationsIndicator	CivilApplicationsIndicator	O	1	Y, BLANK. See JLINK manual
ContactOrdersIndicator	ContactOrdersIndicator	O	1	Y, BLANK. See JLINK manual
CriminalHistoryIndicator	CriminalHistoryIndicator	O	1	Y, BLANK. See JLINK manual
CustodyRecordsIndicator	CustodyRecordsIndicator	O	1	Y, BLANK. See JLINK manual
DisplayIndicator	DisplayIndicator	O	1	Y, BLANK. See JLINK manual
DonsIndicator	DonsIndicator	O	1	Y, BLANK. See JLINK manual
FBINumber	FBINumber	O	9	Alphanumeric. See NCIC manual
FingerprintBasedFprAndNfrIndicator	FingerprintBasedFprAndNfrIndicator	O	1	Y, BLANK. See JLINK manual
FingerprintBasedFprIndicator	FingerprintBasedFprIndicator	O	1	Y, BLANK. See JLINK manual
FingerprintBasedIndicator	FingerprintBasedIndicator	O	1	Y, BLANK. See JLINK manual
FingerprintBasedNfrIndicator	FingerprintBasedNfrIndicator	O	1	Y, BLANK. See JLINK manual
Height	Height	O	3	Numeric. See NCIC manual
JuvenileIndicator	JuvenileIndicator	O	1	Y, BLANK. See JLINK manual
Name	Name	O	30	Alphanumeric,Special chars,See NCIC code manual
NdiConfidentialCode	NdiConfidentialCode	O	1	See JLINK manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	Alphanumeric,Special chars,See NCIC code manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	Alphanumeric,Special chars,See NCIC code manual
PONCode	PONCode	O	1	See JLINK manual
PMTCode	PMTCode	O	13	See JLINK manual
PCNIdNumber	PCNIdNumber	O	7	See JLINK manual
PurposeCode	PurposeCode	O	1	Alphabetic: C,D,E,F,J,S. See NCIC code manual
ProtectionOrdersIndicator	ProtectionOrdersIndicator	O	1	Y, BLANK. See JLINK manual
RaceCode	RaceCode	O	1	Alphabetic: I, A, B, W, U. See NCIC code manual
RecordStatusCode	RecordStatusCode	O	1	See JLINK manual
RecordTypeCode	RecordTypeCode	O	1	See JLINK manual
SuppressedIndicator	SuppressedIndicator	O	1	Y, BLANK. See JLINK manual
RNGCode	RNGCode	O	2	Range; See JLINK manual
SexCode	SexCode	O	1	Alphabetic: M, F, U. See NCIC code manual
SexOffendersIndicator	SexOffendersIndicator	O	1	Y, BLANK. See JLINK manual
SocialSecurityNumber	SocialSecurityNumber	O	9	Numeric. See NCIC manual
SortDescendingIndicator	SortDescendingIndicator	O	1	Y, BLANK. See JLINK manual
StateldNumber	StateldNumber	O	10	Alphanumeric. See NCIC manual

LicensePlateNumber	LicensePlateNumber	O	10	Alphanumeric, See NCIC Code Manual
LicensePlateStateCode	LicensePlateStateCode	O	2	Alphabetic, See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	Alphanumeric, See NCIC Code Manual
Weight	Weight	O	3	Numeric. See NCIC manual
WantsWarrantsIndicator	WantsWarrantsIndicator	O	1	Y, BLANK. See JLINK manual
WHModeCode	WHModeCode	O	1	See JLINK manual
WorkCardsIndicator	WorkCardsIndicator	O	1	Y, BLANK. See JLINK manual
WRNCode	WRNCode	O	1	See JLINK manual

Possible Combinations

(In) [AgencyIdNumber, AgencyTypeCode, AgencyIdCode, AgencyIdNumber2, AgencyTypeCode2, AgencyIdCode2, AllRecordsIndicator, Attention, AlsoKnownAs, BINIdNumber, BirthDate, CCNIdNumber, CcwIndicator, CivilApplicationsIndicator, ContactOrdersIndicator, CriminalHistoryIndicator, CustodyRecordsIndicator, DisplayIndicator, DonsIndicator, FBI Number, FingerprintBasedFprAndNfrIndicator, FingerprintBasedFprIndicator, FingerprintBasedIndicator, FingerprintBasedNfrIndicator, Height, JuvenileIndicator, Name, NdiConfidentialCode, OperatorLicenseNumber, OriginatingAgencyCaseNumber, PONCode, PMTCode, PCNIdNumber, PurposeCode, ProtectionOrdersIndicator, RaceCode, RecordStatusCode, RecordTypeCode, SuppressedIndicator, RNGCode, SexCode, SexOffendersIndicator, SocialSecurityNumber, SortDescendingIndicator, StateIdNumber, LicensePlateNumber, LicensePlateStateCode, VehicleIdentificationNumber, Weight, WantsWarrantsIndicator, WHModeCode, WorkCardsIndicator, WRNCode]

NvJlinkXmlDLICQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	O	1	

Possible Combinations

1. (In) BirthDate, Name, [SexCode]
2. (In) OperatorLicenseNumber

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- JLINK Documentation

