

Nevada (NV) LEMS XML

[Disclaimer Statement](#)

Transport:

Web Services - XML

Routing and Configuration Information:

Save Byte Routing (Primary)

Mnemonic Routing (Secondary)

- The NCJIS assigned ORI for a device (or for the site) should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.
- The NCJIS assigned deviceId for a device should be placed in the **<Authentication>/<Mnemonic>** field in the ConnectCIC header.
- The NCJIS assigned User ID should be placed in the **<Authentication>/<UserName>** field in the ConnectCIC header.

Security Requirements:

None known at this time.

Logon Requirements:

None. Security provided by Client Certificate implementation/configuration.

Certification Requirements:

Agency sponsor is required.

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	
ImageIndicator	ImageIndicator	O	1	Y or blank

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode, [ImageIndicator]

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	20	
ImageIndicator	ImageIndicator	O	1	Y or blank
RegistrationNumber	RegistrationNumber	C	8	
State	State	O	2	

State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	

Possible Combinations

1. (In/Out) BoatHullIdNumber, [Any optional fields]
2. (In/Out) RegistrationNumber, [Any optional fields]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	30	
PurposeCode	PurposeCode	M	1	C,J,E,F,D,S
SexCode	SexCode	O	1	
State	State	O	2	

Possible Combinations

1. (In/Out) Attentionpn, PurposeCode, BirthDate, Name, [Any optional fields]
2. (In/Out) Attentionpn, PurposeCode, OperatorLicenseNumber, [Any optional fields]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	See NCIC Manual
ImageIndicator	ImageIndicator	O	1	Y or Blank
Name	Name	C	30	See NCIC manual
NCICSearchIndicator	NCICSearchIndicator	O	1	N or Blank
NletsInterpolSearchIndicator	NletsInterpolSearchIndicator	O	1	Y or Blank
NletsWarrantSearchIndicator	NletsWarrantSearchIndicator	O	1	N or Blank
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	C	1	
SoundexIndicator	SoundexIndicator	O	1	N or Blank
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	
StateRecordSearchIndicator	StateRecordSearchIndicator	O	1	N or Blank
StateWarrantSearchIndicator	StateWarrantSearchIndicator	O	1	N or Blank

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, [Any optional fields]
2. (In/Out) OperatorLicenseNumber, [Any optional fields]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	O	4	
GunMakeCode	GunMakeCode	O	3	
GunSerialNumber	GunSerialNumber	M	11	
ImageIndicator	ImageIndicator	O	1	Alphabetic: Y or blank

Possible Combinations

1. (In/Out) GunSerialNumber, [Any optional fields]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageIndicator	ImageIndicator	O	1	Y or Blank
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
NCICSearchIndicator	NCICSearchIndicator	O	1	N or Blank
NletsInterpolSearchIndicator	NletsInterpolSearchIndicator	O	1	Y or Blank
State	State	O	2	
StateWarrantSearchIndicator	StateWarrantSearchIndicator	O	1	N or Blank
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleModelCode	VehicleModelCode	O	3	
VehicleStyleCode	VehicleStyleCode	O	2	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In/Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, [Any optional fields]
2. (In/Out) VehicleIdentificationNumber, [Any optional fields]

Transactions Supported:

Agency Operations and Support (AOS)

AOSHazardousMaterialQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
ChemicalName	ChemicalName	C	50	
UnitedNationsNumber	UnitedNationsNumber	C	4	

Possible Combinations

1. (In/Out) ChemicalName, [OriginatingAgencyORI]
2. (In/Out) UnitedNationsNumber, [OriginatingAgencyORI]

AOSLojackCheckQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LoJackReplyCode	LoJackReplyCode	M	5	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	

Possible Combinations

1. (In/Out) LoJackReplyCode, [OriginatingAgencyORI]

AOSLojackQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LoJackReplyCode	LoJackReplyCode	M	5	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	

Possible Combinations

1. (In/Out) LoJackReplyCode, [OriginatingAgencyORI]

AOSLojackQuietQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LoJackReplyCode	LoJackReplyCode	M	5	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	

Possible Combinations

1. (In/Out) LoJackReplyCode, [OriginatingAgencyORI]

Canadian Basic Inquiries (CBI)

CBIArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	23	
ArticleTypeCode	ArticleTypeCode	M	2	AA,BI,BU,HH,JE,MI,MT,OM,PA,PE,PH,RA,SC,SP,OT
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PersonPropertyInSiteIndicator	PersonPropertyInSiteIndicator	O	1	Y, N
ReasonCode	ReasonCode	O	1	N,F,V,T,S,H

Possible Combinations

1. (Out) ArticleSerialNumber, ArticleTypeCode, [OriginatingAgencyORI, PersonPropertyInSiteIndicator, ReasonCode]

CBIBoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	12	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PersonPropertyInSiteIndicator	PersonPropertyInSiteIndicator	O	1	Y, N
ReasonCode	ReasonCode	O	1	N,F,V,T,S,H
RegistrationNumber	RegistrationNumber	C	10	
State	State	C	2	See Nlets Wiki

Possible Combinations

1. (Out) [BoatHullIdNumber, [OriginatingAgencyORI, PersonPropertyInSiteIndicator, ReasonCode]
2. (Out) RegistrationNumber, [OriginatingAgencyORI, PersonPropertyInSiteIndicator, ReasonCode, State]

CBIDriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M	10	
Name	Name	M	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PersonPropertyInSiteIndicator	PersonPropertyInSiteIndicator	O	1	Y, N
ReasonCode	ReasonCode	O	1	N,F,V,T,S,H
SexCode	SexCode	M	1	F,M,U See Nlets Wiki
State	State	M	2	

Possible Combinations

1. (Out) BirthDate, Name, SexCode, State, [OperatorLicenseNumber, OriginatingAgencyORI, PersonPropertyInSiteIndicator, ReasonCode]

CBIGunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunSerialNumber	GunSerialNumber	M	23	
GunTypeCode	GunTypeCode	M	2	SG,RI,RW,OT
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PersonPropertyInSiteIndicator	PersonPropertyInSiteIndicator	O	1	Y or Blank
ReasonCode	ReasonCode	O	1	N,F,V,T,S,H

Possible Combinations

1. (Out) GunSerialNumber, GunTypeCode, [OriginatingAgencyORI, PersonPropertyInSiteIndicator, ReasonCode]

CBIVehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	10	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PersonPropertyInSiteIndicator	PersonPropertyInSiteIndicator	O	1	Y, N
ReasonCode	ReasonCode	O	1	N,F,V,T,S,H
State	State	M	2	See Nlets Wiki
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (Out) LicensePlateNumber, State, [OriginatingAgencyORI, PersonPropertyInSiteIndicator, ReasonCode]
2. (Out) State, VehicleIdentificationNumber, [OriginatingAgencyORI, PersonPropertyInSiteIndicator, ReasonCode]

Computerized Criminal History (CCH)

CCHCriminalHistoryAQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	O	10	
FreeText	FreeText	M	14400	
GeneralAppearanceDescription	GeneralAppearanceDescription	O	14400	
Name	Name	O	30	
NletsDestination	NletsDestination	M	9	
NletsDestination2	NletsDestination2	O	9	
NletsDestination3	NletsDestination3	O	9	
NletsDestination4	NletsDestination4	O	9	
NletsDestination5	NletsDestination5	O	9	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PurposeCode	PurposeCode	M	1	A,C,D,E,F,H,I,J,R,S,V,X

Possible Combinations

1. (In/Out) Attention, FreeText, NletsDestination, PurposeCode, [BirthDate, GeneralAppearanceDescription, Name, NletsDestination2, NletsDestination3, NletsDestination4, NletsDestination5, OriginatingAgencyORI]

CCHCriminalHistoryARQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
FreeText	FreeText	M	14400	
NletsDestination	NletsDestination	M	9	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PurposeCode	PurposeCode	M	1	A,C,D,E,F,H,I,J,R,S,V,X

Possible Combinations

1. (In/Out) Attention, FreeText, NletsDestination, PurposeCode, [OriginatingAgencyORI]

CCHCriminalHistoryFQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	25	
AddressStateCode	AddressStateCode	O	2	
AddressStreet	AddressStreet	O	30	
AddressZipCode	AddressZipCode	O	10	
Attention	Attention	M	30	
Building	Building	O	30	
DepartmentName	DepartmentName	O	30	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PurposeCode	PurposeCode	M	1	A,C,D,E,F,H,I,J,R,S,V,X
State	State	O	2	
StateIdNumber	StateIdNumber	M	10	

Possible Combinations

1. (In/Out) Attention, PurposeCode, StateIdNumber, [AddressCity, AddressStateCode, AddressStreet, AddressZipCode, Building, DepartmentName, OriginatingAgencyORI, State]

CCHCriminalHistoryIQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	10	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PurposeCode	PurposeCode	M	1	A,C,D,E,F,H,I,J,R,S,V,X
RaceCode	RaceCode	O	1	I, A, B, W, U. See NCIC code manual
SexCode	SexCode	C	1	F,M,U See Nlets Wiki
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	M	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	

Possible Combinations

1. (In/Out) Attention, PurposeCode, Name, BirthDate, SexCode, [OriginatingAgencyORI, RaceCode, State, State2, State3, State4, State5]
2. (In/Out) Attention, PurposeCode, Name, BirthDate, SexCode, SocialSecurityNumber, State, [OriginatingAgencyORI, RaceCode, State2, State3, State4, State5]

3. (In/Out) Attention, PurposeCode, Name, BirthDate, SexCode, MiscellaneousNumber, State, [OriginatingAgencyORI, RaceCode, State2, State3, State4, State5]
4. (In/Out) Attention, PurposeCode, Name, SocialSecurityNumber, State, [OriginatingAgencyORI, State2, State3, State4, State5]
5. (In/Out) Attention, PurposeCode, Name, MiscellaneousNumber, State, [OriginatingAgencyORI, State2, State3, State4, State5]

CCHCriminalHistoryQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AgencyNumber	AgencyNumber	O	20	Agency identifier, ie.OCA
Attention	Attention	M	30	
BINIdNumber	BINIdNumber	C	18	State definition - Base Identification Number
BirthDate	BirthDate	C	10	
BirthDateRange	BirthDateRange	O	2	
FBINumber	FBINumber	C	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
Nickname	Nickname	O	30	State definition - Moniker
PCNIdNumber	PCNIdNumber	C		State definition - Process Control Number
PurposeCode	PurposeCode	M	1	A,C,D,E,F,H,I,J,R,S,V,X See JLINK manual
RaceCode	RaceCode	C	1	I, A, B, W, U. See NCIC code manual
ReasonCode	ReasonCode	M	1	C,D,F,H,J See JLINK manual
ResponseTypeCode	ResponseTypeCode	O	1	S,I,M See JLINK manual
SexCode	SexCode	C	1	M,F,X See NCIC code manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) Attention, PurposeCode, Name, BirthDate, RaceCode, ReasonCode, SexCode, [OriginatingAgencyORI, ResponseTypeCode]
2. (In/Out) Name, BirthDate, SexCode, SocialSecurityNumber, [Attention, OriginatingAgencyORI, PurposeCode, RaceCode, ResponseTypeCode]
3. (In/Out) Name, BirthDate, SexCode, MiscellaneousNumber, [Attention, OriginatingAgencyORI, PurposeCode, RaceCode, ResponseTypeCode]
4. (In/Out) Attention, Name, PurposeCode, SocialSecurityNumber, [OriginatingAgencyORI, ResponseTypeCode]
5. (In/Out) Attention, Name, MiscellaneousNumber, PurposeCode, [OriginatingAgencyORI, ResponseTypeCode]
6. (In/Out) Attention, StateIdNumber, PurposeCode, [Name, OriginatingAgencyORI, ResponseTypeCode]
7. (In/Out) Attention, FBINumber, PurposeCode, [Name, OriginatingAgencyORI, ResponseTypeCode]
8. (In/Out) Attention, PurposeCode, SocialSecurityNumber, [OriginatingAgencyORI, ResponseTypeCode]
9. (In) Attention, PurposeCode, AgencyNumber, [OriginatingAgencyORI, ResponseTypeCode]
10. (In) Attention, PurposeCode, BINIdNumber, [OriginatingAgencyORI, ResponseTypeCode]
11. (In) Attention, PurposeCode, PCNIdNumber, [OriginatingAgencyORI, ResponseTypeCode]
12. (In) Attention, PurposeCode, Nickname, [OriginatingAgencyORI, ResponseTypeCode]

CCHCriminalHistoryQRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	25	
AddressStateCode	AddressStateCode	O	2	

AddressStreet	AddressStreet	O	30	
AddressZipCode	AddressZipCode	O	10	
Attention	Attention	M	30	
Building	Building	O	30	
DepartmentName	DepartmentName	O	30	
FBINumber	FBINumber	C	9	
OriginatingAgencyORI	OriginatingAgencyORI	O		
PurposeCode	PurposeCode	M	1	A,C,D,E,F,H,I,J,R,S,V,X See JLINK manual
ReasonCode	ReasonCode	O	1	C,D,F,H,J See JLINK manual
StateldNumber	StateldNumber	C	10	

Possible Combinations

1. (In/Out) Attention, PurposeCode, StateldNumber, [AddressCity, AddressStateCode, AddressStreet, AddressZipCode, Building, DepartmentName, OriginatingAgencyORI]
2. Attention, PurposeCode, FBINumber, [AddressCity, AddressStateCode, AddressStreet, AddressZipCode, Building, DepartmentName, OriginatingAgencyORI]

CCHCriminalHistoryQWQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	10	
FBINumber	FBINumber	C	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
OriginatingAgencyORI	OriginatingAgencyORI	O		
PurposeCode	PurposeCode	M	1	A,C,D,E,F,H,I,J,R,S,V,X See JLINK manual
RaceCode	RaceCode	O	1	I, A, B, W, U. See NCIC code manual
SexCode	SexCode	C	1	F,M,U See NCIC code manual
SocialSecurityNumber	SocialSecurityNumber	C	9	

Possible Combinations

1. (In/Out) Attention, Name, PurposeCode, Choice(BirthDate, FBINumber, MiscellaneousNumber, SocialSecurityNumber), [OriginatingAgencyORI, RaceCode, SexCode]

Wanted Missing Person Entries (WMPE)

WMPEProtectionOrderServiceEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BINIdNumber	BINIdNumber	C	18	
CourtCaseNumber	CourtCaseNumber	C	15	5 fields are supported. Additional identifiers should use tag name with the number 2-5 appended.
CourtORI	CourtORI	C	9	
JuvenileIndicator	JuvenileIndicator	O	1	Y, N, Blank 10 fields are supported. Additional identifiers should use the tag name with the number 2-10 appended. Tag names 6 – 10 are used with the CourtCaseNumber's 1- 5. See below
ParentOrGuardianIndicator	ParentOrGuardianIndicator	O	1	Y, N, Blank 10 fields are supported. Additional identifiers should use the tag name with the number 2-10 appended. Tag names 6 – 10 are used with the CourtCaseNumber's 1- 5. See below

ProtectionOrderNumber	ProtectionOrderNumber	C	18	5 fields are supported. Additional identifiers should use tag name with the number 2-5 appended.
ProtectionOrderTypeCode	ProtectionOrderTypeCode	C	3	EXT - Extended Protective Order FRO - Foreign Order MEX - Modified Extended Protection Order MTO - Modified Temporary Protection Order TPO - Temporary Protective Order NOH - Notice of Hearing OOH - Order of Hearing 10 fields are supported. Additional identifiers should use the tag name with the number 2-10 appended. Tag names 6 – 10 are used with the CourtCaseNumber's 1- 5. See below
ServiceAgencyORI	ServiceAgencyORI	M	9	
ServiceDate	ServiceDate	M	10	
ServicedIndicator	ServicedIndicator	O	1	Y, N, Blank 10 fields are supported. Additional identifiers should use the tag name with the number 2-10 appended. Tag names 6 – 10 are used with the CourtCaseNumber's 1- 5. See below
ServiceOfficerIdNumber	ServiceOfficerIdNumber	M	7	
ServiceOfficerName	ServiceOfficerName	M	30	
ServiceTime	ServiceTime	M	10	
ServiceTypeCode	ServiceTypeCode	C	3	CAP - Court Appearance HCY - Hard Copy MAI - Mail VER – Verbal 10 fields are supported. Additional identifiers should use the tag name with the number 2-10 appended. Tag names 6 – 10 are used with the CourtCaseNumber's 1- 5. See below

Possible Combinations - #1 is required for all entries; #2 and #3 can have none, one, or both entered on a given entry as well, but are not required.

1. ServiceAgencyORI, ServiceDate, ServiceOfficerIdNumber, ServiceOfficerName, ServiceTime
2. BINIdNumber, ProtectionOrderNumber, ProtectionOrderTypeCode, ServiceTypeCode, [JuvenileIndicator...5, ParentOrGuardianIndicator...5, ProtectionOrderNumber2...5, ProtectionOrderTypeCode2...5, ServiceTypeCode2...5, ServicedIndicator2...5]
3. CourtORI, CourtCaseNumber, ProtectionOrderTypeCode6, ServiceTypeCode6, [CourtCaseNumber2...5, JuvenileIndicator6...10, ParentOrGuardianIndicator6...10, ProtectionOrderTypeCode7...10, ServiceTypeCode7...10, ServicedIndicator6...10]

Wanted Missing Person Inquiries (WMP-I)

WMPIProtectionOrderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AgencyIdNumber	AgencyIdNumber	C	9	
BINIdNumber	BINIdNumber	C	10	
BirthDate	BirthDate	C	10	
CourtCaseNumber	CourtCaseNumber	C	15	

ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	DEFAULT:3 1,2,3
EnhancedNameSearchIndicator	EnhancedNameSearchIndicator	O	1	DEFAULT:Y Y, N, Blank
FBINumber	FBINumber	C	9	
HistoryRecordsIndicator	HistoryRecordsIndicator	O	1	DEFAULT: Y Y, N or blank. Not currently implemented by state
ImageIndicator	ImageIndicator	O	1	DEFAULT::N Y, N or blank
LicensePlateNumber	LicensePlateNumber	C	10	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
Nickname	Nickname	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	15	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
RaceCode	RaceCode	O	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	DEFAULT:Y Y, N or blank
SexCode	SexCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	O	2	
StateIdNumber	StateIdNumber	C	10	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	4	

Possible Combinations

1. (In) [AgencyIdNumber, BINIdNumber, CourtCaseNumber, FBINumber, LicensePlateNumber, MiscellaneousNumber, Name, Nickname, OperatorLicenseNumber, OriginatingAgencyCaseNumber, ProtectionOrderNumber, RaceCode, SexCode, SocialSecurityNumber, StateIdNumber, vehicleIdentificationNumber, VehicleMakeCode, HistoryRecordsIndicator, ImageIndicator, RelatedHitSearchIndicator]
2. (Out) Name, BirthDate, [EnhancedNameSearchIndicator, ExpandedBirthDateSearchCode, RaceCode, SexCode, HistoryRecordsIndicator, ImageIndicator, RelatedHitSearchIndicator]
3. (Out) Name, FBINumber, [EnhancedNameSearchIndicator, HistoryRecordsIndicator, ImageIndicator, RelatedHitSearchIndicator]
4. (Out) Name, MiscellaneousNumber, [EnhancedNameSearchIndicator, HistoryRecordsIndicator, ImageIndicator, RelatedHitSearchIndicator]
5. (Out) Name, SocialSecurityNumber, [EnhancedNameSearchIndicator, HistoryRecordsIndicator, ImageIndicator, RelatedHitSearchIndicator]
6. (Out) Name, OperatorLicenseNumber, [EnhancedNameSearchIndicator, HistoryRecordsIndicator, ImageIndicator, RelatedHitSearchIndicator]
7. (Out) Name, OriginatingAgencyCaseNumber, [EnhancedNameSearchIndicator, HistoryRecordsIndicator, ImageIndicator, RelatedHitSearchIndicator]
8. (Out) Name, LicensePlateNumber, State, [EnhancedNameSearchIndicator, HistoryRecordsIndicator, ImageIndicator, RelatedHitSearchIndicator]
9. (Out) Name, VehicleIdentificationNumber, VehicleMakeCode, [EnhancedNameSearchIndicator, HistoryRecordsIndicator, ImageIndicator, RelatedHitSearchIndicator]
10. (Out) Name, ProtectionOrderNumber, [HistoryRecordsIndicator, ImageIndicator, RelatedHitSearchIndicator]
11. (Out) NCICNumber, [HistoryRecordsIndicator, ImageIndicator, RelatedHitSearchIndicator]

WMPIWantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BINIdNumber	BINIdNumber	C	10	
BirthDate	BirthDate	C	10	
EnhancedNameSearchIndicator	EnhancedNameSearchIndicator	O	1	Y, N or Blank Default:N
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	1,2, 3 or Blank Default:Blank
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Y, N or Blank Default:N
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NCICSearchIndicator	NCICSearchIndicator	O	1	Y, N or Blank Default:Y
NletsWarrantSearchIndicator	NletsWarrantSearchIndicator	O	1	Y, N or Blank Default:Y
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	O	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Y, N or Blank Default:Y
SexCode	SexCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateRecordSearchIndicator	StateRecordSearchIndicator	O	1	Y, N or Blank Default:Y
StateWarrantSearchIndicator	StateWarrantSearchIndicator	O	1	Y, N or Blank Default:Y
StateWarrantNumber	StateWarrantNumber	C	20	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	
WarrantNumber	WarrantNumber	C	20	

Possible Combinations

1. (In/Out) BINIdNumber, [ImageIndicator, Any optional indicator field]
2. (In/Out) Name, BirthDate, [ExpandedBirthDateSearchCode, RaceCode, SexCode, Any optional indicator field]
3. (In/Out) Name, FBINumber, [Any optional indicator field]
4. (In/Out) Name, MiscellaneousNumber, [Any optional indicator field]
5. (In/Out) Name, SocialSecurityNumber, [Any optional indicator field]
6. (In/Out) Name, OperatorLicenseNumber, [Any optional indicator field]
7. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional indicator field]
8. (In/Out) LicensePlateNumber, LicensePlateStateCode, [Any optional indicator field]
9. (In/Out) VehicleIdentificationNumber, VehicleMakeCode, [Any optional indicator field]
10. (In/Out) NCICNumber, [Name, Any optional indicator field]
11. (In/Out) StateWarrantNumber, [Any optional indicator field]
12. (In/Out) WarrantNumber, [Any optional indicator field]

Expanded Transactions Supported:

AlarmExchangeResponse

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlarmResponse	AlarmResponse	M	14400	
DestinationORI	DestinationORI	M	9	

FormORI	FormORI	O	9	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	

Possible Combinations

1. (In/Out) AlarmResponse, DestinationORI, [FormORI, OriginatingAgencyORI]

DispatchQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
ImageIndicator	ImageIndicator	O	1	Y or Blank
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
RaceCode	RaceCode	C	1	I, A, B, W, U. See NCIC code manual
SexCode	SexCode	O	1	M, F, U. See NCIC code manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
State	State	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleStyleCode	VehicleStyleCode	O	2	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In/Out) [BirthDate, LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, Name, OperatorLicenseNumber, RaceCode, SexCode, SocialSecurityNumber, State, VehicleIdentificationNumber, VehicleMakeCode, VehicleYear]

NvLemsDLICQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	10	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	O	1	

Possible Combinations

1. (In) BirthDate, Name, [SexCode]
2. (In) OperatorLicenseNumber

NvLemsDNQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	25	See Nlets Wiki
AddressStateCode	AddressStateCode	O	2	See Nlets Wiki
Age	Age	O	3	See Nlets Wiki
ImageIndicator	ImageIndicator	O	1	Y, N or Blank
Name	Name	M	30	See NCIC Code Manual
OriginatingAgencyORI	OriginatingAgencyORI	O	9	

SexCode	SexCode	O	1	M, F, U. See Nlets Wiki
State	State	O	2	See Nlets Wiki
State2	State2	O	2	See Nlets Wiki
State3	State3	O	2	See Nlets Wiki
State4	State4	O	2	See Nlets Wiki
State5	State5	O	2	See Nlets Wiki

Possible Combinations

1. (In/Out) Name, [AddressCity, AddressStateCode, Age, OriginatingAgencyORI, SexCode, State]

NvLemsDQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	10	
ImageIndicator	ImageIndicator	O	1	Y, N or Blank Default:N
Name	Name	C	30	
NCICSearchIndicator	NCICSearchIndicator	O	1	Y, N or Blank Default:N
NletsInterpolPersonSearchIndicator	NletsInterpolPersonSearchIndicator	O	1	Y, N or Blank Default:N
NletsWarrantSearchIndicator	NletsWarrantSearchIndicator	O	1	Y, N or Blank Default:N
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	O	1	M, F, U. See Nlets Wiki
SocialSecurityNumber	SocialSecurityNumber	C	20	
SoundexIndicator	SoundexIndicator	O	1	Y, N or Blank Default:Y
State	State	O	2	See Nlets Wiki
State2	State2	O	2	See Nlets Wiki
State3	State3	O	2	See Nlets Wiki
State4	State4	O	2	See Nlets Wiki
State5	State5	O	2	See Nlets Wiki
StateRecordSearchIndicator	StateRecordSearchIndicator	O	1	Y, N or Blank Default:N
StateWarrantSearchIndicator	StateWarrantSearchIndicator	O	1	Y, N or Blank Default:N

Possible Combinations

1. (In/Out) Name, [BirthDate, SexCode, State, State2, State3, State4, State5, any optional indicator field]
2. (In/Out) OperatorLicenseNumber, [State, State2, State3, State4, State5, any optional indicator field]
3. (In/Out) SocialSecurityNumber, [State, , any optional indicator field]

NvLemsFPQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
InterpolIdNumber	InterpolIdNumber	M	60	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
QueryReason	QueryReason	O	20	

Possible Combinations

1. (In/Out) InterpolIdNumber, [OriginatingAgencyORI, QueryReason]

NvLemsGPQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	C	20	
AddressStateCode	AddressStateCode	C	2	

AddressStreetName	AddressStreetName	C	25	
AddressStreetNameSecond	AddressStreetNameSecond	O	20	
AddressStreetNumber	AddressStreetNumber	C	6	
AddressZipCode	AddressZipCode	C	10	
AlienRegistrationNumber	AlienRegistrationNumber	C	15	
BirthDate	BirthDate	O	10	
DocumentIdNumber	DocumentIdNumber	C	64	
Name	Name	C	30	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PassportNumber	PassportNumber	C	20	
SocialSecurityNumber	SocialSecurityNumber	C	9	

Possible Combinations

1. (In/Out) Name, [BirthDate, OriginatingAgencyORI, PassportNumber]
2. (In/Out) SocialSecurityNumber, [OriginatingAgencyORI]
3. (In/Out) AlienRegistrationNumber, [OriginatingAgencyORI]
4. (In/Out) AddressStreetName, AddressStreetNumber, [AddressCity, AddressStateCode, AddressStreetNameSecond, AddressZipCode, OriginatingAgencyORI]
5. (In/Out) AddressCity, [OriginatingAgencyORI]
6. (In/Out) AddressStateCode, [OriginatingAgencyORI]
7. (In/Out) AddressZipCode, [OriginatingAgencyORI]
8. (In/Out) DocumentIdNumber, [OriginatingAgencyORI]

NvLemsIPQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	10	
Name	Name	O	30	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
QueryReason	QueryReason	O	20	

Possible Combinations

1. (In/Out) [BirthDate, Name, OriginatingAgencyORI, QueryReason]

NvLemsQVQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageIndicator	ImageIndicator	O	1	Y or Blank
LicensePlateNumber	LicensePlateNumber	C	10	
NCICNumber	NCICNumber	C	10	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Y or Blank
State	State	O	2	
StateWarrantSearchIndicator	StateWarrantSearchIndicator	O	1	Y or Blank
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	

Possible Combinations

1. (In/Out) LicensePlateNumber, State, [ImageIndicator, RelatedHitSearchIndicator, StateWarrantSearchIndicator]
2. (In/Out) NCICNumber, [ImageIndicator, RelatedHitSearchIndicator, StateWarrantSearchIndicator]
3. (In/Out) VehicleIdentificationNumber, VehicleMakeCode, [ImageIndicator, RelatedHitSearchIndicator, StateWarrantSearchIndicator]

NvLemsRQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageIndicator	ImageIndicator	O	1	Y or Blank
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
NCICSearchIndicator	NCICSearchIndicator	O	1	Y or Blank
NletsInterpolSearchIndicator	NletsInterpolSearchIndicator	O	1	Y or Blank
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	
StateWarrantSearchIndicator	StateWarrantSearchIndicator	O	1	Y or Blank
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In/Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, [ImageIndicator, NCICSearchIndicator, NletsInterpolSearchIndicator, State, State2, State3, State4, State5, StateWarrantSearchIndicator]
2. (In/Out) VehicleIdentificationNumber, [ImageIndicator, NCICSearchIndicator, NletsInterpolSearchIndicator, State, State2, State3, State4, State5, StateWarrantSearchIndicator, VehicleMakeCode, VehicleYear]

NvLemsScopeQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	C	50	Alphanumeric, Special characters
BirthDate	BirthDate	O	8	Date
DisplayIndicator	DisplayIndicator	O	1	0 – abbreviated metro 1- detailed metro (default)
EventIdNumber	EventIdNumber	C	20	Alphanumeric
IdentificationNumber	IdentificationNumber	C	20	Alphanumeric, Special characters
IdTypeCode	IdTypeCode	O	1	Alpha only
ImageIndicator	ImageIndicator	O	1	TRUE, 1, T, or Y ; FALSE, 0, F, N
Name	Name	C	90	Alphanumeric, Special characters
PersonnelIdNumber	PersonnelIdNumber	C	20	Alphanumeric, See JLINK operating manual
RaceCode	RaceCode	O	1	Alpha only
ScopeOperatorId	ScopeOperatorId	O	3	Alphanumeric
SexCode	SexCode	O	1	Alpha only; M, F, U
SoundexCode	SoundexCode	O	5	TRUE, 1, T, or Y ; FALSE, 0, F, N

Possible Combinations

1. (In) IdentificationNumber, [DisplayIndicator, IdTypeCode, ScopeOperatorId]
2. (In) Name, [AlsoKnownAs, BirthDate, DisplayIndicator, RaceCode, ScopeOperatorId, SexCode, SoundexCode, ImageIndicator]
3. (In) AlsoKnownAs, [BirthDate, DisplayIndicator, Name, RaceCode, ScopeOperatorId, SexCode, SoundexCode, ImageIndicator]
4. (In) PersonnelIdNumber, [ScopeOperatorId]
5. (In) EventIdNumber, [ScopeOperatorId]

NvLemsScopeWVSCQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
EngineIdNumber	EngineIdNumber	C	30	Alphanumeric, See JLINK operating manual
EventIdNumber	EventIdNumber	C	20	Alphanumeric, See JLINK operating manual
LicensePlateNumber	LicensePlateNumber	C	10	Alphanumeric, See NCIC Code Manual
LicensePlateStateCode	LicensePlateStateCode	O	2	Alphabetic, See NCIC Code Manual
Name	Name	C	90	Alphanumeric, Special characters, See NCIC Code Manual
PersonnelIdNumber	PersonnelIdNumber	C	20	Alphanumeric, See JLINK operating manual
ScopeOperatorId	ScopeOperatorId	O	3	Alphanumeric, See JLINK operating manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	Alphanumeric, See NCIC Code Manual

Possible Combinations

1. (In) EngineIdNumber, [ScopeOperatorId]
2. (In) EventIdNumber, [ScopeOperatorId]
3. (In) Name, [ScopeOperatorId]
4. (In) PersonnelIdNumber, [ScopeOperatorId]
5. (In) LicensePlateNumber, [LicensePlateStateCode, ScopeOperatorId]
6. (In) VehicleIdentificationNumber, [ScopeOperatorId]

NvLemsSTASQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AllRecordsIndicator	AllRecordsIndicator	O	1	Y or Blank - Search all records
Attention	Attention	M	30	Alphanumeric, Special chars, See NCIC code manual
BINIdNumber	BINIdNumber	C	10	Base Identification Number – See JLINK manual
BirthDate	BirthDate	O	10	Numeric-Date. See NCIC manual
BirthDateRange	BirthDateRange	O	1	1, 2 or Blank
CcwIndicator	CcwIndicator	O	1	Y or Blank - Concealed Carry Weapons
CriminalHistoryIndicator	CriminalHistoryIndicator	O	1	Y or Blank - Criminal History Search
DonsIndicator	DonsIndicator	O	1	Y or Blank - Dangerous Offender Search
FBINumber	FBINumber	C	9	FBI Number – See NCIC manual
FingerprintFprIndicator	FingerprintFprIndicator	O	1	Y or Blank - Fingerprint Search
FingerprintNfrIndicator	FingerprintNfrIndicator	O	1	Y or Blank - Non Fingerprint Search
Name	Name	C	30	Alphanumeric, Special characters, See NCIC Code Manual
Nickname	Nickname	C	30	Moniker – See NCIC manual
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
PCNIdNumber	PCNIdNumber	C	10	Process Control Number – See JLINK manual
ProtectionOrdersIndicator	ProtectionOrdersIndicator	O	1	Y or Blank - Protection Orders Search
PurposeCode	PurposeCode	M	1	A,C,D,E,F,H,I,J,R,S,V,X See JLINK manual
RaceCode	RaceCode	O	1	I, A, B, W, U. See NCIC code manual
ReasonCode	ReasonCode	O	1	C,D,F,H,J - See JLINK manual
SexCode	SexCode	O	1	
SexOffendersIndicator	SexOffendersIndicator	O	1	Y or Blank - Sex Offenders Search
SocialSecurityNumber	SocialSecurityNumber	C	9	
SortDescendingIndicator	SortDescendingIndicator	O	1	Y or Blank - Sort descending returns
StateIdNumber	StateIdNumber	C	10	
WantsWarrantsIndicator	WantsWarrantsIndicator	O	1	Y or Blank - Wants Warrants Search

The following indicators can be either **AllRecordsIndicator** or any one or more of the following: **CcwIndicator, CriminalHistoryIndicator, DonsIndicator, FingerprintFprIndicator, FingerprintNfrIndicator, ProtectionOrdersIndicator, SexOffendersIndicator, SortDescendingIndicator, WantsWarrantsIndicator**. These can be used with any combination below.

Possible Combinations

1. (In/Out) Attention, PurposeCode, BINIdNumber, [OriginatingAgencyORI, ReasonCode]
2. (In/Out) Attention, PurposeCode, Name, [BirthDate, BirthDateRange, OriginatingAgencyORI, RaceCode, ReasonCode, SexCode]
3. (In/Out) Attention, PurposeCode, Nickname, [BirthDate, BirthDateRange, OriginatingAgencyORI, RaceCode, ReasonCode, SexCode]
4. (In/Out) Attention, PurposeCode, FBINumber, [OriginatingAgencyORI, ReasonCode]
5. (In/Out) Attention, PurposeCode, PCNIdNumber, [OriginatingAgencyORI, ReasonCode]
6. (In/Out) Attention, PurposeCode, SocialSecurityNumber, [OriginatingAgencyORI, ReasonCode]
7. (In/Out) Attention, PurposeCode, StateIdNumber, [OriginatingAgencyORI, ReasonCode]

NvLemsWQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M	10	
Name	Name	M	30	
OriginatingAgencyORI	OriginatingAgencyORI	O	9	
ReasonCode	ReasonCode	O	1	N,F,V,T,S,H
SexCode	SexCode	M	1	M, F

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, [OriginatingAgencyORI, ReasonCode]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- JLINK Documentation