

New York (NY) NYSPIN

[Disclaimer Statement](#)

Transport:

TCP/IP – ccpi

Routing and Configuration Information:

Save byte routing

- The NYSPIN assigned agency ORI should be placed in the **Authentication>/<ORI>** field in the ConnectCIC header.
- The agency-assigned Mnemonic for a device should be placed in the **<Authentication>/<Mnemonic>** field in the ConnectCIC header (see “Mnemonics” below).

Mnemonics -- These are provided by the agency. Individual mnemonics are required for each of your end stations (workstations, mobile devices, etc.). These are agency-define; not assigned by the state. The value must be between 1 and 999. Any numbers between 1 and 999 are acceptable and do not have to be in order, but the mnemonics should be tied to a specific destination. (**Note: This field should be exchanged between vendor and ConnectCIC without leading zeros.** For example, if the device mnemonic is 1, pass ConnectCIC just a 1 (not 0001); if the device mnemonic is 23, pass 23 (not 0023), etc. This number is sent from vendor to ConnectCIC as the Mnemonic field in the Authentication block.

Logon Requirements:

None

Certification Requirements:

Need Site Sponsor; prior to being granted access to the Product NYSPIN application, each site must test every transaction the site wants to utilize in a “live” environment with the NYSPIN test server.

For every interface, besides actual testing of the message transactions, the following is required by NYSPIN:

1. Unsolicited Messages – For every interface, even inquiry only interfaces, the vendor must be able to accept and display unsolicited messages on a designated terminal. ConnectCIC can be configured to route all unsolicited messages to an identified device. Once configured, the vendor will receive all unsolicited messages complete with the device routing information. It is highly recommended that vendors pass this information to the end-user device. Without such, the agency may not be able to pass their certification to gain access to the production system.

To configure ConnectCIC for such, refer to the “NYSPIN ConnectCIC Install & Config Checklist” document section “ConnectCIC Software Configuration Requirements.”

2. Connection Lost – NYSPIN will require the vendor/agency during the test to identify when the connection to NYSPIN is lost. ConnectCIC does detect this and passes a message via the API to the vendor, however, we do not know if the vendor displays this information for end users or not. However, we highly recommend that vendors do otherwise the agency may not pass their certification test which is required in order to gain access to the product system. CommSys does have another way to identify if a connection is lost, but it requires access to the ConnectCIC Config Tool. In the ConnectCIC Config Tool there is a “ConnectCIC Server Status” section, under this section there is a “State Connection Established” checkbox, if this is unchecked, no connection to NYSPIN is currently active.

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Article Type	ArticleTypeCode	M	7	
Serial Number	ArticleSerialNumber	M	20	

Possible Combinations (fields within the square brackets are optional)

1. ArticleTypeCode, ArticleSerialNumber

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Boat Hull Number	BoatHullIdNumber	C	20	
Registration Number	RegistrationNumber	C	8	

Possible Combinations (fields within the square brackets are optional)

1. RegistrationNumber
2. BoatHullIdNumber

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Birth date	BirthDate	C	8	
Driver License Number	OperatorLicenseNumber	C	20	
Message Data	FreeText	O	76	
Operator	Operator	C	31	
Name	Name	C	30	
Return All Pages	ReturnAllPages	O*	1	Y (default) & N

Sex	SexCode	C	1	
State	State	C	2	

*This is defaulted to “Y” unless a “N” is specified by Vendor.

Possible Combinations (fields within the square brackets are optional)

1. (InState) DriverLicenseNumber, [ReturnAllPages, FreeText]
2. (OutofState) DriverLicenseNumber, State, [FreeText]
3. (InState) Name, BirthDate, SexCode, [ReturnAllPages, FreeText]
4. (OutofState) Name, BirthDate, SexCode, State, [FreeText]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Gun Caliber	GunCaliber	C	4	
Gun Make	GunMake	C	3	
Serial Number	GunSerialNumber	M	11	

Possible Combinations (fields within the square brackets are optional)

1. GunSerialNumber [GunCaliber, GunMake]

NextPageQuery*

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Page Type	PageType	M	4	DCON, RCON, DMOR, RMOR

*This query allows you to support manual requests for additional information for the in-state driver license queries and the in-state vehicle registration query by license plate number only. Note: You must have entered a “N” in the <ReturnAllPages> tag on the initial query which states you only want the first page of data instead of all data at once. The following options are available:

- For the next page of data on in-state driver license query, enter DMOR,
- For the next page of data for in-state vehicle registration by license plate number, enter RMOR,
- For the next group list (i.e. list of names) for in-state driver license query, enter DCON.
- For the next group list (i.e. list of names) for in-state vehicle registration by license plate number query, enter RCON.

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
License Plate Number	LicensePlateNumber	C	8	
License Plate Type	LicensePlateTypeCode	C	2	
License Plate Year	LicensePlateYear	C	4	
Message Data	FreeText	O	76	
Return All Pages	ReturnAllPages	O*	1	Y (default) & N
State	State	C	2	
Vehicle Identification Number	VehicleIdentificationNumber	C	20	
Vehicle Year	VehicleYear	C	4	
Vehicle Make	VehicleMakeCode	C	3	

*This is defaulted to “Y” unless a “N” is specified by Vendor.

Possible Combinations (fields within the square brackets are optional)

1. (InState) LicensePlateNumber, [ReturnAllPages, LicensePlateType, FreeText]

2. (OutOfState) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, State, [FreeText]
3. (InState) VehicleIdentificationNumber, [VehicleYear, VehicleMakeCode]
4. (OutOfState) VehicleIdentificationNumber, State, [VehicleYear, VehicleMakeCode]

Transactions Supported:

None

Expanded Transactions Supported:

HazardousMaterialQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Message Data	FreeText	O	76	
United Nations Number	UnitedNationsNumber	M	4	

Possible Combinations (fields within the square brackets are optional)

1. UnitedNationsNumber [FreeText]

MissingPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Message Data	FreeText	C	76	
Birth Date	BirthDate	C	8	
Name	Name	C	30	
Race	RaceCode	C	1	
Sex	SexCode	C	1	
NCIC Number	NCICNumber	C	10	

Possible Combinations (fields within the square brackets are optional)

1. Name, BirthDate, SexCode, [RaceCode, FreeText]
2. NCICNumber

QueryPassThrough**

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Message Data	FreeText	M	100	

****This is a message key pass through and does not require the header of the message, only the body. Example: (Header)QA.ORI/123456789.TYP/YTHING.SER/123456**
Bolded text would be sent to ConnectCIC server in the FreeText tag.

WantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Message Data	FreeText	O	76	
Name	Name	M	30	
Birth Date	BirthDate	M	8	
Race	RaceCode	C	1	

Sex	SexCode	M	1	
-----	---------	---	---	--

Possible Combinations *(fields within the square brackets are optional)*

1. Name, BirthDate, SexCode, [RaceCode, FreeText]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

NYSPIN stipulates that for certain transactions, if an empty data value is present for a given optional field, then an asterisk (*) character should be sent instead. This rule is not consistent, however, since optional fields for other transactions do not require an asterisk (*). To shield vendors from this requirement, ConnectCIC will manage this behavior and send the asterisks (*) when needed. No additional defaulting or other text handling is required of the vendor. However, when implementing and certifying your interface with NYSPIN you may be asked if you are performing this function, in which you can let them know the interface is compliant.

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- NYSPIN Interface Specifications
- NYSPIN TCP/IP Protocol Specifications
- NYSPIN TCP/IP Interface Agency Message Specification