

Oklahoma (OK) OLETS [Statement](#)

[Disclaimer](#)

Transport:

DMPP2020 Extended

Routing and Configuration Information:

Save byte routing (For most queries)

Mnemonic routing

- The OLETS assigned ORI for a device (or for the site) should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.
- The OLETS assigned Mnemonic for a device should be placed in the **<Authentication>/<Mnemonic>** field in the ConnectCIC header.

Security Requirements:

OLETS currently does not require vendor's employees who will be exposed to CJIS data to be fingerprinted for background checks.

Logon Requirements:

<LogonRequest>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
User Name	UserName	M	15	
Password	Password	M	15	
New Password	NewPassword	O	15	
ReType New Password	ReTypeNewPassword	O	15	

Possible Combinations *(fields within the square brackets are optional)*

1. [UserName,Password [NewPassword,ReTypeNewPassword]]

<LogoffRequest>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
User Name	UserName	O	15	

If send ConnectCIC a blank form (just the header information), we will log off the mnemonic (device).

Possible Combinations *(fields within the square brackets are optional)*

1. [UserName]

Certification Requirements:

None

Need Site Sponsor

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

<ArticleSingleQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Article Type Code	ArticleTypeCode	M	7	
Image Indicator	ImageIndicator	O	1	
Owner Applied Number	OwnerAppliedNumber	O	20	
Related Search Hit	RelatedSearchHitIndicator	O	1	
Article Serial Number	ArticleSerialNumber	M	20	

Possible Combinations *(fields within the square brackets are optional)*

1. ArticleSerialNumber, ArticleTypeCode [ImageIndicator, OwnerAppliedNumber, RelatedSearchHitIndicator]

<BoatQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Boat Hull Number	BoatHullIdNumber*	C	20	Boat Hull Number, Owner Applied Number, Serial Number, Vehicle Identification Number
Image Indicator	ImageIndicator	O	1	
NCIC Number	NCICNumber	C	10	
Reference	Reference	O	15	
Related Search Hit	RelatedSearchHitIndicator	O	1	
Registration Number	RegistrationNumber	C	8	
State	State	O	2	Default = OK

*This query field can also have the VIN, SER, and OAN entered in this field to run a NCIC (QB) query. You may want to design your inquiry form with these as separate fields but they must be passed to ConnectCIC in the BoatHullIdNumber field.

Possible Combinations *(fields within the square brackets are optional)*

1. (InState) BoatHullIdNumber [Reference]
2. (InState) RegistrationNumber [Reference]
3. BoatHullIdNumber [State, ImageIndicator, RelatedSearchHitIndicator]
4. NCICNumber [ImageIndicator, RelatedSearchHitIndicator]
5. RegistrationNumber [State, BoatHullIdNumber, ImageIndicator, RelatedSearchHitIndicator]
6. RegistrationNumber, BoatHullIdNumber [State, ImageIndicator, RelatedSearchHitIndicator]

<DriverHistoryQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	50	
Birth Date	BirthDate	C	8	
Destination State Code	DestinationCode	M	2	

Name	Name	C	30	
Operator License Number	OperatorLicenseNumber	C	20	
Purpose	PurposeCode	O	1	
Sex	SexCode	C	1	

Possible Combinations (*fields within the square brackets are optional*)

1. Name, BirthDate, SexCode, DestinationCode [Attention, PurposeCode]
2. OperatorLicenseNumber, DestinationCode [Attention, PurposeCode]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
InquiryType	InquiryType	C	1	S (Standard), C (Complete)
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	C	1	
State	State	O	2	

Possible Combinations

1. (In) InquiryType, OperatorLicenseNumber
2. (In/Out) BirthDate, Name, SexCode, [State]
3. (In/Out) OperatorLicenseNumber, [State]

<GunQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Gun Caliber	GunCaliber	O	4	
Gun Make	GunMake	O	23	
Gun Model	GunModel	O	4	
Image Indicator	ImageIndicator	O	1	Y, N or blank
Related Search Hit	RelatedSearchHitIndicator	O	1	Y, N or blank
Gun Serial Number	GunSerialNumber	M	11	

Possible Combinations (*fields within the square brackets are optional*)

1. GunSerialNumber [GunCaliber, GunMake, GunModel, ImageIndicator, RelatedSearchHitIndicator]

<VehicleRegistrationQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Decal Number	DecalNumber	C	20	
License Plate Type	LicensePlateTypeCode	C	2	Default=PC
License Plate Number	LicensePlateNumber	C	10	
License Plate Year	LicensePlateYear	C	4	Default=Current Year
NCIC Number	NCICNumber	C	10	
State	State	C	2	Default = OK
Title Lien Information	TitleLienInformation	C	20	
Vehicle Year	VehicleYear	C	4	
Vehicle Identification Number	VehicleIdentificationNumber	C	20	
Vehicle Make	VehicleMakeCode	C	4	

Possible Combinations (*fields within the square brackets are optional*)

1. (InState) DecalNumber
2. (InState) TitleLienInformation
3. LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear
4. LicensePlateNumber, State
5. NCICNumber

6. VehicleIdentificationNumber, VehicleMakeCode, VehicleYear

Expanded Queries:

<AdministrativeMessage>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Destination Code/Identifier	DestinationCode	M	2-9	2-Character State Code or destination ORI
Destination Code/Identifier 2	DestinationCode2	O	2-9	2-Character State Code or destination ORI
Destination Code/Identifier 3	DestinationCode3	O	2-9	2-Character State Code or destination ORI
Destination Code/Identifier 4	DestinationCode4	O	2-9	2-Character State Code or destination ORI
Destination Code/Identifier 5	DestinationCode5	O	2-9	2-Character State Code or destination ORI
Message Text	FreeText	M	501	

Possible Combinations (fields within the square brackets are optional)

1. FreeText, DestinationCode [DestinationCode2, DestinationCode3, DestinationCode4, DestinationCode5]

<CriminalHistoryIndexQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	50	
Birth Date	BirthDate	C	8	
FBI Number	FBINumber	C	9	
Miscellaneous Number	MiscellaneousNumber	C	15	
Name	Name	C	30	
Purpose	PurposeCode	M	1	
Race	RaceCode	C	1	
Sex	SexCode	C	1	
Social Security Number	SocialSecurityNumber	C	9	
State Identification Number	StateIdNumber	C	10	

Possible Combinations (fields within the square brackets are optional)

1. FBINumber, Attention, PurposeCode
2. (In State) MiscellaneousNumber, Attention, PurposeCode
3. (In State) SocialSecurityNumber, Attention, PurposeCode
4. Name, BirthDate, SexCode, RaceCode, Attention, PurposeCode [MiscellaneousNumber, SocialSecurityNumber]
5. StateIdNumber, Attention, PurposeCode

<CriminalHistoryRecordQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address Building	AddressBuilding	O	20	
Address City State	AddressCityState	O	50	
Address Department	AddressDepartment	O	20	
Address Street Name	AddressStreetName	O	50	
Address Zip Code	AddressZipCode	O	10	
Attention	Attention	M	50	
FBI Number	FBINumber	C	9	
Purpose	PurposeCode	M	1	
State Identification Number	StateIdNumber	C	10	

Possible Combinations (fields within the square brackets are optional)

1. FBINumber, Attention, PurposeCode, [AddressDepartment, AddressBuilding, AddressStreetName, AddressCityState, AddressZipCode]
2. StateIdNumber, Attention, PurposeCode, [AddressDepartment, AddressBuilding, AddressStreetName, AddressCityState, AddressZipCode]

<CriminalHistorySupplementalQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address Building	AddressBuilding	O	20	
Address City State	AddressCityState	O	50	
Address Department	AddressDepartment	O	20	
Address Street Name	AddressStreetName	O	50	
Address Zip Code	AddressZipCode	O	10	
Attention	Attention	M	50	
Destination	DestinationCode	M	9	
Destination 2	DestinationCode2	O	9	
Destination 3	DestinationCode3	O	9	
Destination 4	DestinationCode4	O	9	
Destination 5	DestinationCode5	O	9	
Purpose	PurposeCode	M	1	
Text	FreeText	M	300	

Possible Combinations (fields within the square brackets are optional)

1. Attention, PurposeCode, DestinationCode, FreeText, [AddressDepartment, AddressBuilding, AddressStreetName, AddressCityState, AddressZipCode, DestinationCode2, DestinationCode3, DestinationCode4, DestinationCode5]

<CriminalHistorySupplementalResponse>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	50	
Data	FreeText	M	14400	
Destination	DestinationCode	M	9	
Purpose	PurposeCode	M	1	

Possible Combinations (fields within the square brackets are optional)

1. Attention, PurposeCode, DestinationCode, FreeText

<FullCriminalHistoryQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address Building	AddressBuilding	O	20	
Address City State	AddressCityState	O	50	
Address Department	AddressDepartment	O	20	
Address Street Name	AddressStreetName	O	50	
Address Zip Code	AddressZipCode	O	10	
Attention	Attention	M	50	
Destination State Code	DestinationCode	M	2	
Purpose	PurposeCode	M	1	
State Identification Number	StateIdNumber	M	10	

Possible Combinations (fields within the square brackets are optional)

1. StateIdNumber, Attention, PurposeCode, DestinationCode [AddressDepartment, AddressBuilding, AddressStreetName, AddressCityState, AddressZipCode]

<IIICriminalHistoryQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	50	
Destination State Code	DestinationCode	M	2	
Destination State Code 2	DestinationCode2	O	2	
Destination State Code 3	DestinationCode3	O	2	
Destination State Code 4	DestinationCode4	O	2	
Destination State Code 5	DestinationCode5	O	2	
Date of Birth	BirthDate	C	8	
Miscellaneous Number	MiscellaneousNumber	C	15	
Name	Name	M	30	

Purpose	PurposeCode	M	1	
Race	RaceCode	C	1	
Sex	SexCode	C	1	
Social Security Number	SocialSecurityNumber	C	9	

Possible Combinations (fields within the square brackets are optional)

1. Name, BirthDate, SexCode, RaceCode, Attention, PurposeCode, DestinationCode [DestinationCode2, DestinationCode3, DestinationCode4, DestinationCode5]
2. Name, BirthDate, SexCode, RaceCode, MiscellaneousNumber, Attention, PurposeCode, DestinationCode [DestinationCode2, DestinationCode3, DestinationCode4, DestinationCode5]
3. Name, BirthDate, SexCode, RaceCode, SocialSecurityNumber, Attention, PurposeCode, DestinationCode [DestinationCode2, DestinationCode3, DestinationCode4, DestinationCode5]
4. Name, MiscellaneousNumber, Attention, PurposeCode, DestinationCode [DestinationCode2, DestinationCode3, DestinationCode4, DestinationCode5]
5. Name, SocialSecurityNumber, Attention, PurposeCode, DestinationCode [DestinationCode2, DestinationCode3, DestinationCode4, DestinationCode5]

<ImpoundVehicleReport>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Agency Address City	AgencyAddressCity	O	15	
Agency Address Street Name	AgencyAddressStreetName	O	50	
Agency Address State	AgencyAddressStateCode	O	2	Default = OK
Agency Address Zip Code	AgencyAddressZipCode	O	10	
Agency Name	AgencyName	O	50	
Authorization	Authorization	O	50	
Badge Number	BadgeNumber	O	10	
Date Of Impound	ImpoundDate	O	8	
From	From	O	36	
License Plate Number	LicensePlateNumber	O	10	
License Plate State	State	O	2	
License Plate Year	LicensePlateYear	O	4	
Officer Name	OfficerName	O	15	
Time	Time	O	5	
Operator	UserName	O	15	
Vehicle Identification Number	VehicleIdentificationNumber	O	20	
Vehicle Make Code	VehicleMakeCode	O	4	
Vehicle Model Code	VehicleModelCode	O	4	
Vehicle Year	VehicleYear	O	4	
Wrecker Address City	WreckerAddressCity	O	15	
Wrecker Address Street Name	WreckerAddressStreetName	O	50	
Wrecker Address State	WreckerAddressStateCode	O	2	
Wrecker Address Zip Code	WreckerAddressZipCode	O	10	
Wrecker Name	WreckerName	O	50	

Possible Combinations (fields within the square brackets are optional)

1. Enter all known information

<JuvenileFileQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Birth Date	BirthDate	C	8	
File Number	FileNumber	C	10	
Name	Name	C	30	
Race	RaceCode	C	1	
Sex	SexCode	C	1	

Possible Combinations (fields within the square brackets are optional)

1. FileNumber
2. Name, SexCode, BirthDate, RaceCode, [FileNumber]

<JuvenileNameQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Birth Date	BirthDate	O	8	
Name	Name	C	30	
Race	RaceCode	O	1	
Sex	SexCode	C	1	

Possible Combinations (fields within the square brackets are optional)

1. Name, SexCode, [BirthDate, RaceCode]

<MissingPersonQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	M	8	
Eye Color	EyeColorCode	M	3	
Hair Color	HairColorCode	M	3	
Height	Height	M	3	
Name	Name	O	30	
Race	RaceCode	M	1	
Sex	SexCode	M	1	
Weight	Weight	M	3	

Possible Combinations (fields within the square brackets are optional)

1. Age, EyeColorCode, HairColorCode, Height, RaceCode, SexCode, Weight [Name]

<OASISPersonofInterestQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	50	
Birth Date	BirthDate	O	8	
Driver License Number	OperatorLicenseNumber	C	20	
Name	Name	C	30	
Reference Number	ReferenceNumber	C	15	
Social Security Number	SocialSecurityNumber	C	9	

Possible Combinations (fields within the square brackets are optional)

1. Name, Attention [BirthDate]
2. OperatorLicenseNumber, Attention
3. SocialSecurityNumber, Attention
4. ReferenceNumber, Attention

<OASISItemofInterestQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Article Serial Number	ArticleSerialNumber	C	15	
Attention	Attention	M	50	
License Plate Number	LicensePlateNumber	C	10	
ReferenceNumber	ReferenceNumber	C	15	

Possible Combinations (fields within the square brackets are optional)

1. ArticleSerialNumber, Attention
2. LicensePlateNumber, Attention
3. ReferenceNumber, Attention

<ORIQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ORI	FormORI	M	9	
Destination Identifier	DestinationCode	C	2	2-Character State Code

This transaction combines the NLETS ORION Directory (TQ) and the NCIC ORI Query (ZO). The DestinationCode field controls if the inquiry is routed to NLETS or NCIC. Default is to NCIC if not supplied.

Possible Combinations (fields within the square brackets are optional)

1. FormORI (Searches NCIC)
2. FormORI, DestinationCode (Searches Nlets)

<QueryPassThrough>*

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Message Data	FreeText	M		

Possible Combinations

FreeText

*This is a message key pass through and does not require the header of the message, only the body.

Example: (Header)**QA.ORI/123456789.TYP/YTHING.SER/123456**

Bolded text would be sent to ConnectCIC server in the FreeText tag.

<SecuritiesRegistrationQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Denomination	Denomination	C	9	
Issuer	Issuer	O	15	
Originating Agency Case Number	OriginatingAgencyCaseNumber	C	20	
Owner	Owner	C	40	
Security Serial Number	SecuritySerialNumber	C	18	
Security Type Code	SecurityTypeCode	C	2	
Social Security Number	SocialSecurityNumber	C	9-9	

Possible Combinations (fields within the square brackets are optional)

1. Owner
2. Owner, OriginatingAgencyCaseNumber
3. Owner, SecurityTypeCode
4. Owner, SocialSecurityNumber
5. SecurityTypeCode, SecuritySerialNumber, Denomination [Issuer (if non-U.S. Treasury issues and currency)]
6. SocialSecurityNumber

<SnowmobileRegistrationQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Birth Date	BirthDate	C	8	
Name	Name	C	30	
Registration Number	RegistrationNumber	C	8	
State	State	O	2-2	Default = OK
Vehicle Identification Number	VehicleIdentificationNumber	C	17	

Possible Combinations (fields within the square brackets are optional)

1. Name, BirthDate [State]
2. RegistrationNumber [State]
3. VehicleIdentificationNumber [State]

<UnidentifiedPersonQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	C	8	
Area Code	AreaCode	C	3	
Body Part Status Code	BodyPartStatusCode	C	15	
Eye Color	EyeColorCode	C	3	
Hair Color	HairColorCode	C	3	

Height	Height	C	3	
NCIC Number	NCICNumber	C	9	
Originating Agency Case Number	OriginatingAgencyCaseNumber	C	20	
Race	RaceCode	C	1	
Sex	SexCode	C	1	
Weight	Weight	C	3	

Possible Combinations *(fields within the square brackets are optional)*

1. Age, SexCode, RaceCode, HairColorCode, EyeColorCode, Weight, Height
2. BodyPartStatusCode, AreaCode, SexCode, RaceCode
3. NCICNumber
4. OriginatingAgencyCaseNumber

<WantedPersonQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Birth Date	BirthDate	C	8	
FBI Number	FBINumber	C	9	
License Plate Number	LicensePlateNumber	C	10	
Miscellaneous Number	MiscellaneousNumber	C	15	
Name	Name	C	30	
Operator License Number	OperatorLicenseNumber	C	20	
Originating Agency Case Number	OriginatingAgencyCaseNumber	C	9	
Race Code	RaceCode	O	1-1	
Sex Code	SexCode	O	1-1	
Social Security Number	SocialSecurityNumber	C	9-9	
State	State	O	2	Default = OK
Vehicle Identification Number	VehicleIdentificationNumber	C	20	
Vehicle Make	VehicleMakeCode	C	4	

Possible Combinations *(fields within the square brackets are optional)*

1. LicensePlateNumber [State]
2. Name, BirthDate [RaceCode, SexCode, FBINumber, MiscellaneousNumber, SocialSecurityNumber, OperatorLicenseNumber]
3. Name, FBINumber [MiscellaneousNumber, SocialSecurityNumber, OperatorLicenseNumber]
4. Name, MiscellaneousNumber [SocialSecurityNumber, OperatorLicenseNumber]
5. Name, SocialSecurityNumber [OperatorLicenseNumber]
6. Name, OperatorLicenseNumber
7. Name, OriginatingAgencyCaseNumber
8. VehicleIdentificationNumber, VehicleMakeCode

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- Oklahoma Interface Specifications

