

Rhode Island (RI) RILETS

[Statement](#)

[Disclaimer](#)

Transport:

TCPIP

Frame is <STX> <ETX>

Routing and Configuration Information:

Mnemonic Routing

- The RILETS assigned ORI for a device (or for the site) should be placed in the <Authentication>/<ORI> field in the ConnectCIC header.
- The RILETS assigned Mnemonic for a device should be placed in the <Authentication>/<Mnemonic> field in the ConnectCIC header.

Security Requirements:

None known at this time.

Logon Requirements:

None known at this time.

Certification Requirements:

Agency sponsor is required.

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

<ArticleSingleQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Article Type Code	ArticleTypeCode	O	4-7	
Serial Number	ArticleSerialNumber	M	1-20	

Possible Combinations *(fields within the square brackets are optional)*

1. ArticleSerialNumber, [ArticleTypeCode]

<BoatQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

Boat Hull Number	BoatHullIdNumber	C	1-20	
Registration Number	RegistrationNumber	C	1-10	

Possible Combinations (fields within the square brackets are optional)

1. BoatHullIdNumber, [RegistrationNumber]
2. RegistrationNumber, [BoatHullIdNumber]

<GunQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Gun Caliber	GunCaliber	O	4-7	
Gun Make	GunMake	O	2-23	
Serial Number	GunSerialNumber	M	1-11	

Possible Combinations (fields within the square brackets are optional)

1. GunSerialNumber, [GunMake, GunCaliber]

<DriverLicenseQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Birth Date	BirthDate	C	8-8	
Name	Name	C	3-30	
Operator License Number	OperatorLicenseNumber	C	1-20	
Sex Code	SexCode	O	1-1	
State	State	C	2-2	

Possible Combinations (fields within the square brackets are optional)

1. Name, BirthDate, State, [SexCode]
2. OperatorLicenseNumber, State

<VehicleRegistrationQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
License Plate Number	LicensePlateNumber	C	1-8	
License Plate State Code	LicensePlateStateCode	M	2-2	
License Plate Type Code	LicensePlateTypeCode	O	2-2	
License Plate Year	LicensePlateYear	O	4-4	
Vehicle Identification Number	VehicleIdentificationNumber	C	2-20	

Possible Combinations (fields within the square brackets are optional)

1. LicensePlateNumber, LicensePlateStateCode, [LicensePlateTypeCode, LicensePlateYear]
2. VehicleIdentificationNumber, LicensePlateStateCode

Expanded Queries:

<CriminalHistoryQuery>

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	C	1-15	
Birth Date	BirthDate	C	8-8	
Name	Name	C	3-30	
Operator License Number	OperatorLicenseNumber	C	1-20	
Purpose Code	PurposeCode	C	1-1	
Sex Code	SexCode	C	1-1	
State	State	O	2-2	

Possible Combinations *(fields within the square brackets are optional)*

1. PurposeCode, Name, BirthDate, SexCode, Attention, [State]
2. PurposeCode, OperatorLicenseNumber, Attention, [State]

<QueryPassThrough>*

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Message Data	FreeText	M		

Possible Combinations *(fields within the square brackets are optional)*

1. FreeText

*This is a message key pass through and does not require the header of the message, only the body.

Example: (Header)**QA.ORI/123456789.TYP/YTHING.SER/123456**

Bolded text would be sent to ConnectCIC server in the FreeText tag.

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- RILETS Documentation (Transport & Message Keys)