

South Dakota (SD) SDLETS

[Disclaimer Statement](#)

Transport:

TCP/IP DMPP2020 with AES Encryption extensions

Routing and Configuration Information:

Save Byte Routing

- The SDLETS assigned ORI for a device (or for the site) should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.
 - **<Authentication>/<OriginatingAgencyORI>** may be used to record the agency ORI that a transaction is being run “on-behalf-of”, if different from **<Authentication>/<ORI>**.
 - The transaction field OriginatingAgencyORI was originally used for this purpose; this use is now deprecated.
 - See Item 2 of the “Building a Request” section of the “XML Specification” developer document for more information.
- The SDLETS assigned Mnemonic (also called Device ID, Term ID) for a device should be placed in the **<Authentication>/<Mnemonic>** field in the ConnectCIC header.
- The SDLETS assigned User ID should be placed in the **Authentication>/<UserName>** field in the ConnectCIC header.

Logon Requirements:

None

Certification Requirements:

None

Need Site Sponsor

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	20	
BoatMakeCode	BoatMakeCode	O	24	
RegistrationNumber	RegistrationNumber	C	8	
ImageIndicator	ImageIndicator	O	1	
State	State	C	2	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	

Possible Combinations

1. (In/Out) BoatHullIdNumber, [BoatMakeCode, ImageIndicator, RelatedHitSearchIndicator, State]
2. (In/Out) RegistrationNumber, [ImageIndicator, RelatedHitSearchIndicator, State]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
ImageIndicator	ImageIndicator	O	1	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
PurposeCode	PurposeCode	O	1	
SexCode	SexCode	C	1	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, [Attention, PurposeCode, State, State2, State3, State4, State5]
2. (In/Out) OperatorLicenseNumber, [Attention, ImageIndicator, PurposeCode, State, State2, State3, State4, State5]

DriverLicenseQuery

*** Images from SD DLs will only come back on OLN ***

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
ImageIndicator	ImageIndicator	O	1	'Y' or blank
Name	Name	C	30	

OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	
SexCode	SexCode	O	1	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, [ImageIndicator, SexCode, State, State2, State3, State4, State5]
2. (In/Out) OperatorLicenseNumber, [ImageIndicator, OperatorLicenseStateCode, State, State2, State3, State4, State5]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	O	10	
GunModel	GunModel	O	20	
GunSerialNumber	GunSerialNumber	M	20	

Possible Combinations

1. (In/Out) GunSerialNumber, [GunCaliber, GunMake, GunModel]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	20	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In/Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, [State, State2, State3, State4, State5]
2. (In/Out) VehicleIdentificationNumber, [State, State2, State3, State4, State5, VehicleMakeCode, VehicleYear]

Expanded Queries Supported:

Computerized Criminal History (CCH) Package

CCHCriminalHistoryQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
PurposeCode	PurposeCode	M	1	
RaceCode	RaceCode	C	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) Attention, PurposeCode, Name, RaceCode, SexCode, BirthDate, [MiscellaneousNumber, SocialSecurityNumber]
2. (In/Out) Attention, PurposeCode, Name, MiscellaneousNumber
3. (In/Out) Attention, PurposeCode, Name, SocialSecurityNumber
4. (In/Out) Attention, PurposeCode, StateIdNumber, [Name]
5. (In/Out) Attention, PurposeCode, FBINumber, [Name]

CCHCriminalHistoryQRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
FBINumber	FBINumber	C	9	
PurposeCode	PurposeCode	M	1	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) Attention, FBINumber, PurposeCode
2. (In/Out) Attention, PurposeCode, StateIdNumber

CCHCriminalHistoryQWIQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PurposeCode	PurposeCode	M	1	
RaceCode	RaceCode	C	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	

StateIdNumber	StateIdNumber	C	10	
---------------	---------------	---	----	--

Possible Combinations

1. (In/Out) Attention, PurposeCode, Name, RaceCode, SexCode, BirthDate, [MiscellaneousNumber, SocialSecurityNumber, RelatedHitSearchIndicator, ExpandedNameSearchCode, ImageIndicator]
2. (In/Out) Attention, PurposeCode, Name, MiscellaneousNumber, [RelatedHitSearchIndicator, ExpandedNameSearchCode, ImageIndicator]
3. (In/Out) Attention, PurposeCode, Name, SocialSecurityNumber, [RelatedHitSearchIndicator, ExpandedNameSearchCode, ImageIndicator]
4. (In/Out) Attention, PurposeCode, Name, StateIdNumber, [RelatedHitSearchIndicator, ExpandedNameSearchCode, ImageIndicator]
5. (In/Out) Attention, PurposeCode, Name, FBINumber, [RelatedHitSearchIndicator, ExpandedNameSearchCode, ImageIndicator]
6. (In/Out) Attention, PurposeCode, Name, OriginatingAgencyCaseNumber, [RelatedHitSearchIndicator, ExpandedNameSearchCode, ImageIndicator]

CCHCriminalHistoryZRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FBINumber	FBINumber	C	9	
PurposeCode	PurposeCode	O	1	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) FBINumber, [PurposeCode]
2. (In/Out) StateIdNumber, [PurposeCode]

CCHCriminalHistoryFQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address	Address	O	30	
Attention	Attention	M	30	
Building	Building	O	30	
CityAndState	CityAndState	O	30	
DepartmentName	DepartmentName	O	30	
PurposeCode	PurposeCode	M	1	C, F, E, D, J, I or S.
State	State	M	2	
StateIdNumber	StateIdNumber	M	10	
ZipCode	ZipCode	O	9	

Possible Combinations

1. (In/Out) Attention, PurposeCode, State, StateIdNumber, [Address, Building, CityAndState, DepartmentName, ZipCode]

CCHCriminalHistoryIQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	8	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
PurposeCode	PurposeCode	M	1	C, F, E, D, J, I or S
RaceCode	RaceCode	O	1	
SexCode	SexCode	C	1	

SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	M	2	

Possible Combinations

1. (In/Out) Attention, PurposeCode, State, Name, BirthDate, SexCode, [RaceCode]
2. (In/Out) Attention, PurposeCode, State, Name, BirthDate, SexCode, [RaceCode, SocialSecurityNumber]
3. (In/Out) Attention, PurposeCode, State, Name, BirthDate, SexCode, [RaceCode, MiscellaneousNumber]
4. (In/Out) Attention, PurposeCode, State, SocialSecurityNumber
5. (In/Out) Attention, PurposeCode, State, MiscellaneousNumber

Other queries

DriverQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
Name	Name	M	30	
SexCode	SexCode	O	1	

Possible Combinations

1. (In/Out) Name, [BirthDate, SexCode]

NicsAgencySearchQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	M	8	
BirthPlaceCode	BirthPlaceCode	O	2	
CitizenshipCode	CitizenshipCode	O	2	
CitizenshipCountryCode	CitizenshipCountryCode	O	2	
CitizenshipCountryCode2	CitizenshipCountryCode2	O	2	
CitizenshipCountryCode3	CitizenshipCountryCode3	O	2	
FederalFirearmsLicenseNumber	FederalFirearmsLicenseNumber	C	15	
Height	Height	O	3	
MessageKeyModifier	MessageKeyModifier	O	1	P
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	M	30	
NonImmigrantVisaIndicator	NonImmigrantVisaIndicator	O	1	Y, N, X
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	
PurposeCode	PurposeCode	M	2*	Multiple codes can be submitted and are optional, separated by a comma and space, and in ascending order. Ex: PUR/09, 10
RaceCode	RaceCode	M	1	
RegistrationStateCode	RegistrationStateCode	M	2	
SexCode	SexCode	M	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
StateFirearmsLicenseNumber	StateFirearmsLicenseNumber	C	15	
StateTransactionNumber	StateTransactionNumber	O	12	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, SexCode, RaceCode, PurposeCode, RegistrationStateCode, FederalFirearmsLicenseNumber, Attention, [Optional fields]

- (In/Out) Name, SexCode, RaceCode, PurposeCode, RegistrationStateCode, StateFirearmsLicenseNumber, Attention, [Optional fields]

RegisteredVehicleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Name	Name	M	30	

Possible Combinations

- (In/Out) Name

Wanted and Missing Person Entry (WMPE) Package

WMPEDentalDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	

Possible Combinations

- (In/Out) NCICNumber, OriginatingAgencyCaseNumber,

WMPEDentalDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DentalCharacteristics	DentalCharacteristics	M	319	See NCIC Code Manual
DentalModelsAvailableIndicator	DentalModelsAvailableIndicator	M	1	Y, N
DentalXraysAvailableIndicator	DentalXraysAvailableIndicator	M	1	Y, N
DentistRemarks	DentistRemarks	O	50	
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	

Possible Combinations

- (In/Out) DentalCharacteristics, DentalModelsAvailableIndicator, DentalXraysAvailableIndicator, NCICNumber, OriginatingAgencyCaseNumber, [DentistRemarks]

WMPEDentalDataModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DentalCharacteristics	DentalCharacteristics	O	319	See NCIC Code Manual
DentalModelsAvailableIndicator	DentalModelsAvailableIndicator	O	1	Y, N
DentalXraysAvailableIndicator	DentalXraysAvailableIndicator	O	1	Y, N
DentistRemarks	DentistRemarks	O	50	
NCICNumber	NCICNumber	M	10	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	

Possible Combinations

- (In/Out, NCICNumber, OriginatingAgencyCaseNumber, [DentistRemarks, DentalCharacteristics, DentalModelsAvailableIndicator, DentalXraysAvailableIndicator, ModifiedOriginatingAgencyORI]

WMPEMissingPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Name	Name	C	30	

NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
CancellationDate	CancellationDate	M	8	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, [PersonRecordRemovalReason]
2. (In/Out) Name, NCICNumber, CancellationDate, [PersonRecordRemovalReason]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, [PersonRecordRemovalReason]

WMPEMissingPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
HitResultsIndicator	HitResultsIndicator	O	2	1-9, See NCIC Code Manual for description
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyORI	RecoveringAgencyORI	O	9	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, [HitResultsIndicator, NumberMissingPersonsFound, NumberPersonsApprehended, OtherRecoveredPropertyValue, PersonArmedIndicator, PropertyRecoveredValue, RecoveringAgencyCaseNumber, RecoveringAgencyORI]
2. (In/Out) Name, NCICNumber, ClearDate, [HitResultsIndicator, NumberMissingPersonsFound, NumberPersonsApprehended, OtherRecoveredPropertyValue, PersonArmedIndicator, PropertyRecoveredValue, RecoveringAgencyCaseNumber, RecoveringAgencyORI]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, [HitResultsIndicator, NumberMissingPersonsFound, NumberPersonsApprehended, OtherRecoveredPropertyValue, PersonArmedIndicator, PropertyRecoveredValue, RecoveringAgencyCaseNumber, RecoveringAgencyORI]

WMPEMissingPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyXRayCode	BodyXRayCode	O	1	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual

CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	See NCIC Code Manual
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EmancipationDate	EmancipationDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintIndicator	FootprintIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LastContactDate	LastContactDate	M	8	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
MissingPersonCircumstanceCode	MissingPersonCircumstanceCode	O	1	See NCIC Code Manual
MissingPersonCode	MissingPersonCode	M	2	See NCIC Code Manual
MissingPersonEntryType	MissingPersonEntryType	M	1	D – Disability E – Endangered I – Involuntary J – Emancipated Juvenile V – Catastrophe Victim O – Other
Name	Name	M	30	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	O	20	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarMarkTattooCode	ScarMarkTattooCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
Weight	Weight	M	3	

Possible Combinations

1. (In/Out)MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, BirthDate, [Any optional fields]
2. (In/Out)MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, FBINumber, [Any optional fields]
3. (In/Out)MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, MiscellaneousNumber, [Any optional fields]
4. (In/Out)MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, SocialSecurityNumber, [Any optional fields]
5. (In/Out)MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
6. (In/Out)MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, LicensePlateYear, [Any optional fields]
7. (In/Out)MissingPersonEntryType, Name, SexCode, RaceCode, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, VehicleIdentificationNumber, VehicleMakeCode, VehicleYear, VehicleStyleCode, [Any optional fields]
8. (In/Out) **MissingPersonEntryType = J**;Name, SexCode, RaceCode, BirthDate, EmancipationDate, Height, Weight, EyeColorCode, HairColorCode, MissingPersonCode, LastContactDate, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEMissingPersonLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
DispositionCode	DispositionCode	M	4	
HitResultsIndicator	HitResultsIndicator	O	2	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, RecoveryDate, DispositionCode, [Any optional fields]
2. (In/Out) Name, NCICNumber, RecoveryDate, DispositionCode, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, RecoveryDate, DispositionCode, [Any optional fields]

WMPEMissingPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	
BloodTypeCode	BloodTypeCode	O	5	
BodyXRayCode	BodyXRayCode	O	1	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	
CircumcisionCode	CircumcisionCode	O	1	
CitizenshipCode	CitizenshipCode	O	2	
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	
DNAIndicator	DNAIndicator	O	1	
DNALocation	DNALocation	O	250	
EmancipationDate	EmancipationDate	O	8	
EthnicityCode	EthnicityCode	O	1	
EyeColorCode	EyeColorCode	O	3	
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	
FootprintIndicator	FootprintIndicator	O	1	
HairColorCode	HairColorCode	O	3	
Height	Height	O	3	
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	
LastContactDate	LastContactDate	O	8	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	
LicensePlateYear	LicensePlateYear	O	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
MissingPersonCircumstanceCode	MissingPersonCircumstanceCode	O	1	
MissingPersonCode	MissingPersonCode	O	2	
ModifiedMessageKey	ModifiedMessageKey	O	4	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
RaceCode	RaceCode	O	1	
ScarMarkTattooCode	ScarMarkTattooCode	O	10	
SexCode	SexCode	O	1	
SkinToneCode	SkinToneCode	O	3	
SocialSecurityNumber	SocialSecurityNumber	O	9	

ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	
VehicleStyleCode	VehicleStyleCode	O	2	
VehicleYear	VehicleYear	O	4	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEMissingPersonPersonWithInformationCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PersonWithInformationName	PersonWithInformationName	M	30	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName
2. (In/Out) Name, NCICNumber, PersonWithInformationName
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName

WMPEMissingPersonPersonWithInformationEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	M	500	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PersonWithInformationName	PersonWithInformationName	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, [Any optional fields]
3. (In/Out) Name, NCICNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, [Any optional fields]

4. (In/Out) Name, NCICNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, [Any optional fields]
5. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, BirthDate, MiscellaneousDescriptiveText, [Any optional fields]
6. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, SocialSecurityNumber, MiscellaneousDescriptiveText, [Any optional fields]

WMPEMissingPersonPersonWithInformationModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PersonWithInformationName	PersonWithInformationName	M	30	
PersonWithInformationName2	PersonWithInformationName2	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, [Any optional fields]

WMPEMissingPersonPWISupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PersonWithInformationName	PersonWithInformationName	M	30	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, [Any optional fields]

WMPEMissingPersonPWISupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PersonWithInformationName	PersonWithInformationName	M	30	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, PersonWithInformationName, [Any optional fields]
2. (In/Out) Name, NCICNumber, PersonWithInformationName, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, PersonWithInformationName, [Any optional fields]

WMPEMissingPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
-------------	-------------	---	---	--

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEMissingPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEProtectionOrderCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
MessageKeyModifier	MessageKeyModifier	O	1	Blank or P – Protection Order T – Temporary Protection Order
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, [Any optional fields]
2. (In/Out) Name, ProtectionOrderNumber, CancellationDate, [Any optional fields]
3. (In/Out) Name, NCICNumber, CancellationDate, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, [Any optional fields]

WMPEProtectionOrderClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

ClearDate	ClearDate	M	8	
MessageKeyModifier	MessageKeyModifier	O	1	Blank or P – Protection Order T – Temporary Protection Order
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, [Any optional fields]
2. (In/Out) Name, ProtectionOrderNumber, ClearDate, [Any optional fields]
3. (In/Out) Name, NCICNumber, ClearDate, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, [Any optional fields]

WMPEProtectionOrderEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
BradyIndicator	BradyIndicator	O	1	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExpirationDate	ExpirationDate	M	8	
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IssueDate	IssueDate	M	8	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MessageKeyModifier	MessageKeyModifier	O	1	Blank or P – Protection Order T – Temporary Protection Order
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	O	30	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	C	8	

ProtectedPersonName	ProtectedPersonName	C	30	
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	C	9	
ProtectionOrderConditionsCode	ProtectionOrderConditionsCode	M	2	See NCIC Code Manual
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	
ServiceCode	ServiceCode	O	1	See NCIC Code Manual
ServiceDate	ServiceDate	O	8	
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, BirthDate, [Any optional fields]
2. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, FBINumber, [Any optional fields]
3. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, MiscellaneousNumber, [Any optional fields]
4. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, SocialSecurityNumber, [Any optional fields]
5. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
6. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, [Any optional fields]
7. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]
8. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, ProtectedPersonName, ProtectedPersonSocialSecurityNumber, [Any optional fields]
9. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, OriginatingAgencyCaseNumber, ProtectedPersonName, ProtectedPersonBirthDate, [Any optional fields]
10. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, BirthDate, [Any optional fields]
11. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, FBINumber, [Any optional fields]
12. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, MiscellaneousNumber, [Any optional fields]
13. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, SocialSecurityNumber, [Any optional fields]

14. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
15. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, [Any optional fields]
16. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]
17. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, ProtectedPersonName, ProtectedPersonSocialSecurityNumber, [Any optional fields]
18. (In/Out) Name, SexCode, RaceCode, ExpirationDate, ProtectionOrderConditionsCode, IssueDate, ProtectionOrderNumber, ProtectedPersonName, ProtectedPersonBirthDate, [Any optional fields]

WMPEProtectionOrderModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
BradyIndicator	BradyIndicator	O	1	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExpirationDate	ExpirationDate	O	8	
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IssueDate	IssueDate	O	8	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MessageKeyModifier	MessageKeyModifier	O	1	Blank or P – Protection Order T – Temporary Protection Order
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	EPO ETO EPOC ETOC
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	

Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	
ProtectedPersonName	ProtectedPersonName	O	30	
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	
ProtectionOrderConditionsCode	ProtectionOrderConditionsCode	O	2	See NCIC Code Manual
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
ProtectionOrderNumber2	ProtectionOrderNumber2	O	15	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
ServiceCode	ServiceCode	O	1	
ServiceDate	ServiceDate	O	8	
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, ProtectionOrderNumber, [Any optional fields]
3. (In/Out) Name, NCICNumber, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEProtectionOrderSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateExpirationYear	LicensePlateExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonName	ProtectedPersonName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderConditionCode	ProtectionOrderConditionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderNumber	ProtectionOrderNumber	C	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) Name, ProtectionOrderNumber, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEProtectionOrderSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateExpirationYear	LicensePlateExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProtectedPersonBirthDate	ProtectedPersonBirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonName	ProtectedPersonName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonRaceCode	ProtectedPersonRaceCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSexCode	ProtectedPersonSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectedPersonSocialSecurityNumber	ProtectedPersonSocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderConditionCode	ProtectionOrderConditionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProtectionOrderNumber	ProtectionOrderNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual.

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) Name, ProtectionOrderNumber, [Any optional fields]
4. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESexOffenderCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate
2. (In/Out) Name, NCICNumber, CancellationDate
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate

WMPESexOffenderClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate
2. (In/Out) Name, NCICNumber, ClearDate
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate

WMPESexOffenderEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	

AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	M	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	M	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BoatColorCode	BoatColorCode	O	7	See NCIC Code Manual
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual
BoatHullNumber	BoatHullNumber	O	20	
BoatHullShapeCode	BoatHullShapeCode	O	2	
BoatLength	BoatLength	O	2	See NCIC Code Manual
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual
BoatModelName	BoatModelName	O	20	
BoatModelYear	BoatModelYear	O	4	
BoatName	BoatName	O	20	
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	
ConvictionDate	ConvictionDate	M	8	
ConvictionOffenseCode	ConvictionOffenseCode	M	4	See NCIC Code Manual
CrimeLocation	CrimeLocation	O	2	See NCIC Code Manual, State Code
DNALocation	DNALocation	O	250	
DNAIndicator	DNAIndicator	O	1	Blank, N, Y
EmailAddress	EmailAddress	O	80	
EmployerName	EmployerName	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
HomePort	HomePort	O	20	
InternetId	InternetId	O	80	
JuvenileOffenderIndicator	JuvenileOffenderIndicator	O	1	Blank, N, Y
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	C	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	M	30	
NCICNumber	NCICNumber	O	10	
Occupation	Occupation	O	80	
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	

OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	
RaceCode	RaceCode	M	1	See NCIC Code Manual
RegistrationEndDate	RegistrationEndDate	M	8	
RegistrationNumber	RegistrationNumber	O	8	
RegistrationStartDate	RegistrationStartDate	M	8	
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual
ResidenceBeginDate	ResidenceBeginDate	O	8	
ResidenceEndDate	ResidenceEndDate	O	8	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SchoolName	SchoolName	O	80	
SexCode	SexCode	M	1	See NCIC Code Manual
SexOffenderTier	SexOffenderTier	O	1	See NCIC Code Manual
SexualPredatorIndicator	SexualPredatorIndicator	O	1	Blank, N, Y
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
StateIdNumber	StateIdNumber	O	10	
TelephoneNumber	TelephoneNumber	O	12	
TelephoneType	TelephoneType	C	1	See NCIC Code Manual
RegistrationExpirationYear	RegistrationExpirationYear	O	2	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleOwnershipCode	VehicleOwnershipCode	O	2	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
VictimAge	VictimAge	O	2	
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) Name, SexCode, RaceCode, BirthDate, RegistrationStartDate, RegistrationEndDate, Height, Weight, HairColorCode, EyeColorCode, ConvictionOffenseCode, ConvictionDate, OriginatingAgencyCaseNumber, AddressStateCode, [Any optional fields]

WMPESexOffenderModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	

BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
BoatColorCode	BoatColorCode	O	7	See NCIC Code Manual
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual
BoatHullNumber	BoatHullNumber	O	20	
BoatHullShapeCode	BoatHullShapeCode	O	2	
BoatLength	BoatLength	O	2	See NCIC Code Manual
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual
BoatModelName	BoatModelName	O	20	
BoatModelYear	BoatModelYear	O	4	
BoatName	BoatName	O	20	
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	
ConvictionDate	ConvictionDate	O	8	
ConvictionOffenseCode	ConvictionOffenseCode	O	4	See NCIC Code Manual
CrimeLocation	CrimeLocation	O	2	See NCIC Code Manual, State Code
DNALocation	DNALocation	O	250	
DNAIndicator	DNAIndicator	O	1	Blank, N, Y
EmailAddress	EmailAddress	O	80	
EmployerName	EmployerName	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
HomePort	HomePort	O	20	
InternetId	InternetId	O	80	
JuvenileOffenderIndicator	JuvenileOffenderIndicator	O	1	Blank, N, Y
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	O	10	
Occupation	Occupation	O	80	
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	

OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	
RaceCode	RaceCode	O	1	See NCIC Code Manual
RegistrationEndDate	RegistrationEndDate	O	8	
RegistrationNumber	RegistrationNumber	O	8	
RegistrationStartDate	RegistrationStartDate	O	8	
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual
ResidenceBeginDate	ResidenceBeginDate	O	8	
ResidenceEndDate	ResidenceEndDate	O	8	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SchoolName	SchoolName	O	80	
SexCode	SexCode	O	1	See NCIC Code Manual
SexOffenderTier	SexOffenderTier	O	1	See NCIC Code Manual
SexualPredatorIndicator	SexualPredatorIndicator	O	1	Blank, N, Y
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
StateldNumber	StateldNumber	O	10	
TelephoneNumber	TelephoneNumber	O	12	
TelephoneType	TelephoneType	O	1	See NCIC Code Manual
RegistrationExpirationYear	RegistrationExpirationYear	O	2	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleOwnershipCode	VehicleOwnershipCode	O	2	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
VictimAge	VictimAge	O	2	
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESexOffenderSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

BoatHullNumber	BoatHullNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullShapeCode	BoatHullShapeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatLength	BoatLength	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelName	BoatModelName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelYear	BoatModelYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatName	BoatName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
EmailAddress	EmailAddress	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Employer	Employer	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
InternetId	InternetId	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
Occupation	Occupation	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProfessionalLicenseNumberType	ProfessionalLicenseNumberType	O	80	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationExpirationYear	RegistrationExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationNumber	RegistrationNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SchoolName	SchoolName	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
StateIdNumber	StateIdNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

TelephoneNumber	TelephoneNumber	O	12	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumberType	TelephoneNumberType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleOwnershipCode	VehicleOwnershipCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimAge	VictimAge	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESexOffenderSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullMaterialCode	BoatHullMaterialCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

BoatHullNumber	BoatHullNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatHullShapeCode	BoatHullShapeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatLength	BoatLength	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatMakeCode	BoatMakeCode	O	24	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelName	BoatModelName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatModelYear	BoatModelYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatName	BoatName	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatPropulsionCode	BoatPropulsionCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BoatTypeCode	BoatTypeCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CoastGuardDocumentNumber	CoastGuardDocumentNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
EmailAddress	EmailAddress	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Employer	Employer	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
InternetId	InternetId	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
Occupation	Occupation	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OffenderStatusCode	OffenderStatusCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProfessionalLicenseNumber	ProfessionalLicenseNumber	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ProfessionalLicenseNumberType	ProfessionalLicenseNumberType	O	80	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationExpirationYear	RegistrationExpirationYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationNumber	RegistrationNumber	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RegistrationStateCode	RegistrationStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
RelationshipToVictimCode	RelationshipToVictimCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SchoolName	SchoolName	O	80	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
StateldNumber	StateldNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

TelephoneNumber	TelephoneNumber	O	12	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
TelephoneNumberType	TelephoneNumberType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleOwnershipCode	VehicleOwnershipCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimAge	VictimAge	O	2	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VictimSexCode	VictimSexCode	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESouthDakotaProtectionOrderModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address	Address	O	30	
BirthDate	BirthDate	O	8	
CautionIndicator	CautionIndicator	O	1	
CIRCode	CIRCode	O	2	
CountyCode	CountyCode	O	2	
DefendantCustodyCode	DefendantCustodyCode	O	6	
EmployerAddress	EmployerAddress	O	30	
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual

HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IncarcerationStartDate	IncarcerationStartDate	O	8	
IncarcerationServedDate	IncarcerationServedDate	O	8	
JudgeName	JudgeName	O	20	
SentenceExpirationDate	SentenceExpirationDate	O	8	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
Name	Name	M	30	
NoAbuseIndicator	NoAbuseIndicator	O	1	
NoContactCode	NoContactCode	O	4	
NoPhysicalContactIndicator	NoPhysicalContactIndicator	O	1	
NoStalkingIndicator	NoStalkingIndicator	O	1	
NoVerbalContactIndicator	NoVerbalContactIndicator	O	1	
NoWeaponIndicator	NoWeaponIndicator	O	1	
PlaintiffName	PlaintiffName	O	30	
PlaintiffCustodyCode	PlaintiffCustodyCode	O	3	
RaceCode	RaceCode	O	1	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
SRNNumber	SRNNumber	M	11	
StayOutAddress	StayOutAddress	O	30	
SurrenderWeaponIndicator	SurrenderWeaponIndicator	O	1	
VacateIndicator	VacateIndicator	O	1	
VacateAddress	VacateAddress	O	30	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
WeaponOwnerIndicator	WeaponOwnerIndicator	O	1	
Weight	Weight	O	3	

Possible Combinations

1. (In) Name, SRNNumber, [Any optional fields]

WMPESouthDakotaWantedPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
SRNNumber	SRNNumber	M	11	

Possible Combinations

1. (In) OriginatingAgencyCaseNumber, SRNNumber

WMPESouthDakotaWantedPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FelonyIndicator	FelonyIndicator	O	1	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
GEOIndicator	GEOIndicator	M	1	S - state wide service R - restricted. Must specify in MiscellaneousDescriptiveText.
Height	Height	O	3	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	M	30	
NGTIndicator	NGTIndicator	M	1	Y - day and night service N - day service only
OffenseCode	OffenseCode	M	4	
OffenseCodeDescription	OffenseCodeDescription	O	20	
OperatorLicenseYear	OperatorLicenseYear	O	4	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
WarrantDate	WarrantDate	O	8	
Weight	Weight	O	3	

*Operator License fields must be entered as a set.

*License Plate fields must be entered as a set.

*VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, and VehicleStyleCode must be entered as a set.

Possible Combinations

1. (In) GEOIndicator, Name, NGTIndicator, OffenseCode, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESouthDakotaWantedPersonModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FelonyIndicator	FelonyIndicator	O	1	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
GEOIndicator	GEOIndicator	O	1	S - state wide service R - restricted. Must specify in MiscellaneousDescriptiveText.
Height	Height	O	3	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	O	30	
NGTIndicator	NGTIndicator	O	1	Y - day and night service N - day service only
OffenseCode	OffenseCode	O	4	
OffenseCodeDescription	OffenseCodeDescription	O	20	
OperatorLicenseYear	OperatorLicenseYear	O	4	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
SRNNumber	SRNNumber	M	11	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
WarrantDate	WarrantDate	O	8	
Weight	Weight	O	3	

*Operator License fields must be entered as a set.

*License Plate fields must be entered as a set.

*VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, and VehicleStyleCode must be entered as a set.

Possible Combinations

1. (In) SRNNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESouthDakotaWantedPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressCounty	AddressCounty	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetName	AddressStreetName	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetNumber	AddressStreetNumber	O	7	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressTypeCode	AddressTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressZipCode	AddressZipCode	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SRNNumber	SRNNumber	M	11	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In) Name, OriginatingAgencyCaseNumber, SRNNumber, [Any optional fields]
2. (In) Name, NCICNumber, SRNNumber, [Any optional fields]
3. (In) NCICNumber, OriginatingAgencyCaseNumber, SRNNumber, [Any optional fields]

WMPESouthDakotaWantedPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressCounty	AddressCounty	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetName	AddressStreetName	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetNumber	AddressStreetNumber	O	7	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressTypeCode	AddressTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressZipCode	AddressZipCode	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SRNNumber	SRNNumber	M	11	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In) Name, OriginatingAgencyCaseNumber, SRNNumber, [Any optional fields]
2. (In) Name, NCICNumber, SRNNumber, [Any optional fields]
3. (In) NCICNumber, OriginatingAgencyCaseNumber, SRNNumber, [Any optional fields]

WMPESupervisedReleaseCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, [Any optional fields]
2. (In/Out) Name, NCICNumber, CancellationDate, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, [Any optional fields]

WMPESupervisedReleaseClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, [Any optional fields]
2. (In/Out) Name, NCICNumber, ClearDate, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, [Any optional fields]

WMPESupervisedReleaseEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArrestDate	ArrestDate	O	8	
ArrestingAgencyORI	ArrestingAgencyORI	O	9	
BirthDate	BirthDate	C	8	
BirthPlace	BirthPlace	O	2	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EmailAddress	EmailAddress	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	
FraudulentBirthDate	FraudulentBirthDate	O	8	
FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	
FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	O	20	
FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	O	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	O	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
IncarcerationPlace	IncarcerationPlace	O	50	

LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageCaseNumber	LinkageCaseNumber	O	20	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	C	4	
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ReleaseDate	ReleaseDate	O	8	
ReleaseLocation	ReleaseLocation	O	50	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SentencingCourtORI	SentencingCourtORI	O	9	
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
SupervisingOfficerName	SupervisingOfficerName	M	30	
SupervisingOfficerTelephone	SupervisingOfficerTelephone	M	12	
SupervisionStartDate	SupervisionStartDate	M	8	
SupervisionExpirationDate	SupervisionExpirationDate	M	8	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	2	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
WarrantCourtORI	WarrantCourtORI	O	9	
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, BirthDate, [Any optional fields]
2. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, FBI Number, [Any optional fields]
3. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, MiscellaneousNumber, [Any optional fields]
4. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, SocialSecurityNumber, [Any optional fields]

5. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseYear, [Any optional fields]
6. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, LicensePlateNumber, LicensePlateStateCode, LicensePlateTypeCode, [Any optional fields]
7. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OriginatingAgencyCaseNumber, SupervisionExpirationDate, SupervisionStartDate, SupervisingOfficerName, SupervisingOfficerTelephone, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]

WMPESupervisedReleaseFraudulentDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESupervisedReleaseFraudulentDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	

NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESupervisedReleaseModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArrestDate	ArrestDate	O	8	
ArrestingAgencyORI	ArrestingAgencyORI	O	9	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EmailAddress	EmailAddress	O	80	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FraudulentBirthDate	FraudulentBirthDate	O	8	
FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	
FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	O	20	
FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	O	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	O	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IncarcerationPlace	IncarcerationPlace	O	50	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	

MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	EC EC-C
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual
OperatorLicenseYear	OperatorLicenseYear	O	4	
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
ProbationExpirationDate	ProbationExpirationDate	O	8	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ReleaseLocation	ReleaseLocation	O	50	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SentencingCourtORI	SentencingCourtORI	O	9	
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
SupervisingOfficerName	SupervisingOfficerName	O	30	
SupervisingOfficerTelephone	SupervisingOfficerTelephone	O	12	
SupervisionStartDate	SupervisionStartDate	O	8	
SupervisionReleaseDate	SupervisionReleaseDate	O	5	
ValidatorName	ValidatorName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
WarrantCourtORI	WarrantCourtORI	O	9	
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESupervisedReleaseSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPESupervisedReleaseSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	

NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEUnidentifiedPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
CancellationDate	CancellationDate	M	8	
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
RecordRemovalReason	RecordRemovalReason	O	21	

Possible Combinations

1. (In/Out) CancellationDate, NCICNumber, OriginatingAgencyCaseNumber, [RecordRemovalReason]

WMPEUnidentifiedPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
RecordRemovalReason	RecordRemovalReason	O	21	

Possible Combinations

1. (In/Out) ClearDate, NCICNumber, OriginatingAgencyCaseNumber, [RecordRemovalReason]

WMPEUnidentifiedPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyFoundDate	BodyFoundDate	M	8	
BodyPartsStatusCode	BodyPartsStatusCode	C	15	See NCIC Code Manual
CauseOfDeath	CauseOfDeath	O	30	
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EstimatedBirthYear	EstimatedBirthYear	C	9	
EstimatedDeathDate	EstimatedDeathDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintAvailableIndicator	FootprintAvailableIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	7	Range of values Ex. 000-000
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MedicalExaminerAgencyAndCaseNumber	MedicalExaminerAgencyAndCaseNumber	O	50	
MedicalExaminerLocality	MedicalExaminerLocality	O	30	
MedicalExaminerTelephoneNumber	MedicalExaminerTelephoneNumber	O	12	
MessageKeyModifier	MessageKeyModifier	M	1	D – Deceased L – Living V – Catastrophe Victim
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
Weight	Weight	M	7	Range of values Ex. 000-000
XraysAvailableIndicator	XraysAvailableIndicator	M	1	Blank, Y

Possible Combinations

1. (In/Out) MessageKeyModifier=**D** or **V**, BodyPartsStatusCode, SexCode, RaceCode, EstimatedDeathDate, BodyFoundDate, Height, Weight, EyeColorCode, HairColorCode, OriginatingAgencyCaseNumber, XraysAvailableIndicator, CauseOfDeath, [BloodTypeCode, CircumcisionCode, CorrectiveVisionPerscriptionCode, DNAIndicator, DNALocation, EstimatedBirthYear, EthnicityCode, FingerprintClassificationCode, FootprintAvailableIndicator, JewelryDescription, JewelryTypeCode, LinkageAgencyIdentifier, LinkageCaseNumber, MedicalExaminerAgencyAndCaseNumber, MedicalExaminerLocality, MedicalExaminerTelephoneNumber, MiscellaneousDescriptiveText, NotifyOriginatingAgencyIndicator, ScarsMarksTattoosCode]
2. (In/Out) MessageKeyModifier=**L**, SexCode, RaceCode, BodyFoundDate, Height, Weight, EyeColorCode, HairColorCode, FingerprintClassificationCode, OriginatingAgencyCaseNumber, XraysAvailableIndicator, [BloodTypeCode, CircumcisionCode, CorrectiveVisionPerscriptionCode, DNAIndicator, DNALocation, EstimatedBirthYear, EthnicityCode, FootprintAvailableIndicator, JewelryDescription, JewelryTypeCode, LinkageAgencyIdentifier, LinkageCaseNumber, MedicalExaminerAgencyAndCaseNumber, MedicalExaminerLocality, MedicalExaminerTelephoneNumber, MiscellaneousDescriptiveText, NotifyOriginatingAgencyIndicator, ScarsMarksTattoosCode]

WMPEUnidentifiedPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BloodTypeCode	BloodTypeCode	O	5	See NCIC Code Manual
BodyFoundDate	BodyFoundDate	O	8	
BodyPartsStatusCode	BodyPartsStatusCode	O	15	See NCIC Code Manual
CauseOfDeath	CauseOfDeath	O	30	
CorrectiveVisionPerscriptionCode	CorrectiveVisionPerscriptionCode	O	40	
CircumcisionCode	CircumcisionCode	O	1	See NCIC Code Manual
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	
EstimatedBirthYear	EstimatedBirthYear	O	9	
EstimatedDeathDate	EstimatedDeathDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FootprintAvailableIndicator	FootprintAvailableIndicator	O	1	Blank, Y
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
JewelryDescription	JewelryDescription	O	100	
JewelryTypeCode	JewelryTypeCode	O	50	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MedicalExaminerAgencyAndCaseNumber	MedicalExaminerAgencyAndCaseNumber	O	50	
MedicalExaminerLocality	MedicalExaminerLocality	O	30	
MedicalExaminerTelephoneNumber	MedicalExaminerTelephoneNumber	O	12	
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
ModifiedMessageKey	ModifiedMessageKey	O	4	EUD - Deceased EUL - Living EUV - Catastrophe Victim
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
NCICNumber	NCICNumber	M	10	
NotifyOriginatingAgencyIndicator	NotifyOriginatingAgencyIndicator	O	1	Blank, Y

OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
ValidatorName	ValidatorName	O	30	
Weight	Weight	O	3	
XraysAvailableIndicator	XraysAvailableIndicator	O	1	Blank, Y

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEUnidentifiedPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEUnidentifiedPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageType	ImageType	O	1	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
NCICNumber	NCICNumber	M	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEWantedPersonCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	

OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
CancellationDate	CancellationDate	M	8	

Possible Combinations

1. (In/Out) Name, NCICNumber, CancellationDate, [MessageKeyModifier, OriginatingAgencyCaseNumber, PersonRecordRemovalReason]
2. (In/Out) Name, OriginatingAgencyCaseNumber, CancellationDate, [MessageKeyModifier, NCICNumber, PersonRecordRemovalReason]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, CancellationDate, MessageKeyModifier, Name, PersonRecordRemovalReason]

WMPEWantedPersonClear

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ClearDate	ClearDate	M	8	
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
HitResultsIndicator	HitResultsIndicator	O	2	See NCIC Code Manual
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	Blank, Y
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveringAgencyORI	RecoveringAgencyORI	O	9	

Possible Combinations

1. (In/Out) Name, NCICNumber, ClearDate, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, ClearDate, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, ClearDate, [Any optional fields]

WMPEWantedPersonDetainerCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	M	20	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	

Possible Combinations

1. (In/Out) Name, NCICNumber, DetainerCaseNumber
2. (In/Out) Name, OriginatingAgencyCaseNumber, DetainerCaseNumber
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, DetainerCaseNumber

WMPEWantedPersonDetainerEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	M	20	
DetainerDate	DetainerDate	M	8	
IncarceratingAgencyORI	IncarceratingAgencyORI	M	9	

IncarcerationPlace	IncarcerationPlace	O	50	
IncarcerationStartDate	IncarcerationStartDate	O	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
SentenceExpirationDate	SentenceExpirationDate	O	8	

Possible Combinations

1. (In/Out) Name, NCICNumber, DetainerCaseNumber, DetainerDate, IncarceratingAgencyORI, Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, DetainerCaseNumber, DetainerDate, IncarceratingAgencyORI, Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, DetainerCaseNumber, DetainerDate, IncarceratingAgencyORI, [Any optional fields]

WMPEWantedPersonDetainerModify

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DetainerCaseNumber	DetainerCaseNumber	O	20	
DetainerDate	DetainerDate	O	8	
IncarceratingAgencyORI	IncarceratingAgencyORI	O	9	
IncarcerationPlace	IncarcerationPlace	O	50	
IncarcerationStartDate	IncarcerationStartDate	O	8	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
SentenceExpirationDate	SentenceExpirationDate	O	8	
ValidatorName	ValidatorName	O	30	

Possible Combinations

1. (In/Out) Name, NCICNumber, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEWantedPersonEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalOffenseIndicator	AdditionalOffenseIndicator	O	1	Blank, Y
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	C	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionIndicator	CautionIndicator	O	1	Blank, C
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	Blank, Y
DNALocation	DNALocation	O	250	

DocumentedAddressDate	DocumentedAddressDate	O	8	
EmancipationDate	EmancipationDate	C	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExtraditionLimitation	ExtraditionLimitation	M	2	See NCIC Code Manual
EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	C	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
FraudulentBirthDate	FraudulentBirthDate	O	8	
FraudulentMiscellaneousNumber	FraudulentMiscellaneousNumber	O	15	
FraudulentName	FraudulentName	O	30	
FraudulentOperatorLicenseNumber	FraudulentOperatorLicenseNumber	C	20	
FraudulentOperatorLicenseStateCode	FraudulentOperatorLicenseStateCode	C	2	See NCIC Code Manual
FraudulentOperatorLicenseYear	FraudulentOperatorLicenseYear	C	4	
FraudulentSocialSecurityNumber	FraudulentSocialSecurityNumber	O	9	
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
IncidentDate	IncidentDate	C	8	Warrant or violation date
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	C	4	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	
NotifyOriginatingAgency	NotifyOriginatingAgency	O	1	Blank, Y
OffenseCode	OffenseCode	M	4	
OffenseCodeDescription	OffenseCodeDescription	O	20	
OperatorLicenseYear	OperatorLicenseYear	C	4	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	C	2	See NCIC Code Manual
OriginalOffenseCode	OriginalOffenseCode	C	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	M	20	
RaceCode	RaceCode	M	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateldNumber	StateldNumber	O	10	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	C	3	See NCIC Code Manual
VehicleYear	VehicleYear	C	4	
WantedPersonType	WantedPersonType	O	1	Blank, J – Wanted Juvenile

WarrantNumber	WarrantNumber	O	15	
Weight	Weight	M	3	

*Operator License fields must be entered as a set.

*License Plate fields must be entered as a set.

*VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, and VehicleStyleCode must be entered as a set.

Possible Combinations

1. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, BirthDate, [Any optional fields]
2. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FBI Number [Any optional fields]
3. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, MiscellaneousNumber [Any optional fields]
4. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, SocialSecurityNumber [Any optional fields]
5. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, OperatorLicenseNumber, OperatorLicenseStateCode, OperatorLicenseExpirationYear, [Any optional fields]
6. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, LicensePlateNumber, LicensePlateStateCode, LicensePlateExpirationYear, LicensePlateTypeCode, [Any optional fields]
7. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, VehicleStyleCode, [Any optional fields]
8. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentName, FraudulentBirthDate, [Any optional fields]
9. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentMiscellaneousNumber, [Any optional fields]
10. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentSocialSecurityNumber, [Any optional fields]
11. (In/Out) Name, SexCode, RaceCode, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, FraudulentOperatorLicenseYear, FraudulentOperatorLicenseStateCode, FraudulentOperatorLicenseExpirationYear, [Any optional fields]
12. (In/Out) WantedPersonType, Name, SexCode, RaceCode, BirthDate, EmancipationDate, Height, Weight, HairColorCode, OffenseCode, IncidentDate, OriginatingAgencyCaseNumber, ExtraditionLimitation, [Any optional fields]

WMPEWantedPersonFraudulentDataCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyORI	OriginatingAgencyORI	M	9	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEWantedPersonFraudulentDataEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
FraudulentName	FraudulentName	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]

3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEWantedPersonLocate

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ContrabandRecoveredValue	ContrabandRecoveredValue	O	8	
Extradition	Extradition	M	4	See NCIC Code Manual
HitResultsIndicator	HitResultsIndicator	O	2	See NCIC Code Manual
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
NumberMissingPersonsFound	NumberMissingPersonsFound	O	20	
NumberPersonsApprehended	NumberPersonsApprehended	O	3	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OtherRecoveredPropertyValue	OtherRecoveredPropertyValue	O	8	
PersonArmedIndicator	PersonArmedIndicator	O	1	Blank, Y
PersonRecordRemovalReason	PersonRecordRemovalReason	O	21	
PropertyRecoveredValue	PropertyRecoveredValue	O	8	
RecoveringAgencyCaseNumber	RecoveringAgencyCaseNumber	O	20	
RecoveryDate	RecoveryDate	M	8	

Possible Combinations

1. (In/Out) Name, NCICNumber, Extradition, RecoveryDate, [Any optional fields]
2. (In/Out) Name, OriginatingAgencyCaseNumber, Extradition, RecoveryDate, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, Extradition, RecoveryDate, [Any optional fields]

WMPEWantedPersonModify

*Field deletion supported in this transaction. See Clear Attribute document for more information.

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AdditionalOffenseIndicator	AdditionalOffenseIndicator	O	1	Blank, Y
AddressCity	AddressCity	O	20	
AddressCounty	AddressCounty	O	20	
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual
AddressStreetName	AddressStreetName	O	25	
AddressStreetNumber	AddressStreetNumber	O	7	
AddressType	AddressType	O	2	See NCIC Code Manual
AddressZipCode	AddressZipCode	O	10	
BirthDate	BirthDate	O	8	
BirthPlaceCode	BirthPlaceCode	O	2	See NCIC Code Manual
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual
ClearVehicleDataIndicator	ClearVehicleDataIndicator	O	1	Blank, Y
CourtORI	CourtORI	O	9	
DNAIndicator	DNAIndicator	O	1	
DNALocation	DNALocation	O	250	Blank, Y
DocumentedAddressDate	DocumentedAddressDate	O	8	
EmancipationDate	EmancipationDate	O	8	
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
ExtraditionLimitation	ExtraditionLimitation	O	2	See NCIC Code Manual

EyeColorCode	EyeColorCode	O	3	See NCIC Code Manual
FBINumber	FBINumber	O	9	
FingerprintClassificationCode	FingerprintClassificationCode	O	20	See NCIC Code Manual
HairColorCode	HairColorCode	O	3	See NCIC Code Manual
Height	Height	O	3	
IncidentDate	IncidentDate	C	8	Warrant or violation date
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual
LicensePlateYear	LicensePlateYear	O	4	See NCIC Code Manual
LinkageAgencyIdentifier	LinkageAgencyIdentifier	O	9	
LinkageCaseNumber	LinkageCaseNumber	O	20	
MessageKeyModifier	MessageKeyModifier	O	1	Blank T – Temporary Felon
MiscellaneousDescriptiveText	MiscellaneousDescriptiveText	O	500	
MiscellaneousNumber	MiscellaneousNumber	O	15	
ModifiedMessageKey	ModifiedMessageKey	O	4	Blank EW – Wanted Person EWJ – Wanted Juvenile ET – Temporary Felony EW-C – Wanted Person with Caution EWJC – Wanted Juvenile with Caution ET-C – Temporary Felony with Caution
ModifiedOriginatingAgencyORI	ModifiedOriginatingAgencyORI	O	9	
Name	Name	C	30	
Name2	Name2	O	30	
NCICNumber	NCICNumber	C	10	
NotifyOriginatingAgency	NotifyOriginatingAgency	O	1	Blank, Y
OffenseCode	OffenseCode	O	4	See NCIC Code Manual
OffenseCodeDescription	OffenseCodeDescription	O	20	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	
OperatorLicenseYear	OperatorLicenseYear	O	4	See NCIC Code Manual
OriginalOffenseCode	OriginalOffenseCode	O	4	See NCIC Code Manual
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
OriginatingAgencyCaseNumber2	OriginatingAgencyCaseNumber2	O	20	
RaceCode	RaceCode	O	1	See NCIC Code Manual
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual
SexCode	SexCode	O	1	See NCIC Code Manual
SkinToneCode	SkinToneCode	O	3	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	O	9	
StateldNumber	StateldNumber	O	10	
ValidatorNameName	ValidatorNameName	O	30	
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual
VehicleStyleCode	VehicleStyleCode	O	3	See NCIC Code Manual
VehicleYear	VehicleYear	O	4	
WarrantNumber	WarrantNumber	O	15	
Weight	Weight	O	3	

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEWantedPersonSupplementalCancel

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressCounty	AddressCounty	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetName	AddressStreetName	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetNumber	AddressStreetNumber	O	7	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressTypeCode	AddressTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressZipCode	AddressZipCode	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
StateldNumber	StateldNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]

2. (In/Out) Name, NCICNumber, [Any optional fields]

3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

WMPEWantedPersonSupplementalEntry

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressCounty	AddressCounty	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStateCode	AddressStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetName	AddressStreetName	O	25	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressStreetNumber	AddressStreetNumber	O	7	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressTypeCode	AddressTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AddressZipCode	AddressZipCode	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
AlsoKnownAs	AlsoKnownAs	O	30	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
BirthDate	BirthDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CautionMedicalConditionsCode	CautionMedicalConditionsCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
CitizenshipCode	CitizenshipCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
DocumentedAddressDate	DocumentedAddressDate	O	8	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageNCICNumber	ImageNCICNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
ImageTypeCode	ImageTypeCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateNumber	LicensePlateNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateStateCode	LicensePlateStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateTypeCode	LicensePlateTypeCode	O	2	See NCIC Code Manual

				9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
LicensePlateYear	LicensePlateYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
MiscellaneousNumber	MiscellaneousNumber	O	15	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseStateCode	OperatorLicenseStateCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OperatorLicenseYear	OperatorLicenseYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ScarsMarksTattoosCode	ScarsMarksTattoosCode	O	10	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
SocialSecurityNumber	SocialSecurityNumber	O	9	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
StateldNumber	StateldNumber	O	10	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleColorCode	VehicleColorCode	O	7	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	See NCIC Code Manual. 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleModelCode	VehicleModelCode	O	3	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleStyleCode	VehicleStyleCode	O	2	See NCIC Code Manual 9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.
VehicleYear	VehicleYear	O	4	9 fields are supported. Additional identifiers should use the XML tag name with the number 2-9 appended.

*Operator License fields must be entered as a set.

*License Plate fields must be entered as a set.

*VehicleIdentificationNumber, VehicleYear, VehicleMakeCode, and VehicleStyleCode must be entered as a set.

*Address fields must be entered as a set.

Possible Combinations

1. (In/Out) Name, OriginatingAgencyCaseNumber, [Any optional fields]
2. (In/Out) Name, NCICNumber, [Any optional fields]
3. (In/Out) NCICNumber, OriginatingAgencyCaseNumber, [Any optional fields]

Wanted and Missing Person Inquiry (WMPI) Package

WMPIMissingPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	M	2	
AreaCode	AreaCode	O	3	See NCIC Code Manual
EthnicityCode	EthnicityCode	M	1	See NCIC Code Manual
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Blank, Y
EyeColorCode	EyeColorCode	M	3	See NCIC Code Manual
HairColorCode	HairColorCode	M	3	See NCIC Code Manual
Height	Height	M	3	
Name	Name	O	30	
RaceCode	RaceCode	M	1	See NCIC Code Manual
SexCode	SexCode	M	1	See NCIC Code Manual
Weight	Weight	M	3	

Possible Combinations

1. (In/Out) Age, EthnicityCode, EyeColorCode, HairColorCode, Height, RaceCode, SexCode, Weight, [AreaCode, ExpandedNameSearchCode, Name]

WMPINletsSexOffenderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Blank, Y
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
PurposeCode	PurposeCode	O	1	
SexCode	SexCode	C	1	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	M	2	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, State, [Attention, ImageIndicator, PurposeCode]
2. (In/Out) FBINumber, State, [Attention, ImageIndicator, PurposeCode]
3. (In/Out) MiscellaneousNumber, State, [Attention, ImageIndicator, PurposeCode]
4. (In/Out) SocialSecurityNumber, State, [Attention, ImageIndicator, PurposeCode]
5. (In/Out) StateIdNumber, State, [Attention, ImageIndicator, PurposeCode]

WMPINletsStateWarrantQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
RaceCode	RaceCode	O	1	
SexCode	SexCode	O	1	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	M	2	

Possible Combinations

1. (In/Out) BirthDate, Name, State, [RaceCode, SexCode]
2. (In/Out) FBINumber, Name, State
3. (In/Out) MiscellaneousNumber, Name, State
4. (In/Out) Name, SocialSecurityNumber, State
5. (In/Out) Name, OperatorLicenseNumber, State

WMPProtectionOrderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Blank, Y
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Blank, Y
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Blank, Y
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	See NCIC Code Manual
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
RaceCode	RaceCode	O	1	See NCIC Code Manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Blank, Y
SexCode	SexCode	O	1	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	

Possible Combinations

1. (In/Out) Name, BirthDate, [ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, RaceCode, RelatedHitSearchIndicator, SexCode]
2. (In/Out) Name, OriginatingAgencyCaseNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator]
3. (In/Out) Name, ProtectionOrderNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator]
4. (In/Out) NCICNumber, [ImageIndicator, RelatedHitSearchIndicator]
5. (In/Out) Name, FBINumber, [ImageIndicator, RelatedHitSearchIndicator]
6. (In/Out) Name, MiscellaneousNumber, [ImageIndicator, RelatedHitSearchIndicator]

7. (In/Out) Name, OperatorLicenseNumber, [ImageIndicator, RelatedHitSearchIndicator]
8. (In/Out) Name, SocialSecurityNumber, [ImageIndicator, RelatedHitSearchIndicator]
9. (In/Out) LicensePlateNumber, LicensePlateStateCode, [ImageIndicator, RelatedHitSearchIndicator, VehicleIdentificationNumber, VehicleMakeCode, VehicleMakeCodeDescription]
10. (In/Out) VehicleIdentificationNumber, VehicleMakeCode, [ImageIndicator, RelatedHitSearchIndicator, LicensePlateNumber, LicensePlateStateCode, VehicleMakeCodeDescription]

WMPISexOffenderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
BoatHullNumber	BoatHullNumber	C	20	
BoatRegistrationNumber	BoatRegistrationNumber	C	10	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Blank, Y
ExpandedNameSearchIndicator	ExpandedNameSearchIndicator	O	1	Blank, Y
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Blank, Y
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	O	1	See NCIC Code Manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SexCode	SexCode	O	1	See NCIC Code Manual
SexualOffenderStatusIndicator	SexualOffenderStatusIndicator	O	1	Y,N
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	
ZipCode	ZipCode	C	10	

Possible Combinations

1. (In/Out) Name, **and at least one** BirthDate, BoatHullNumber, BoatRegistrationNumber, FBINumber, LicensePlateNumber, MiscellaneousNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, SocialSecurityNumber, VehicleIdentificationNumber, [ExpandedBirthDateSearchCode, ExpandedNameSearchIndicator, ImageIndicator, LicensePlateStateCode, RaceCode, RelatedHitSearchIndicator, SexCode, VehicleMakeCode, VehicleMakeCodeDescription]
2. (In/Out) ZipCode, [SexualOffenderStatusIndicator, ImageIndicator]

WMPISouthDakotaProtectionOrderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
LicensePlateNumber	LicensePlateNumber	C	10	
Name	Name	M	30	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
PLAText	PLAText	C	30	
SequenceNumber	SequenceNumber	C	3	
SocialSecurityNumber	SocialSecurityNumber	C	9	

SRNNumber	SRNNumber	C	11	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	

Possible Combinations

1. (In) Name, BirthDate,
2. (In) Name, OriginatingAgencyCaseNumber
3. (In) Name, PLAText
4. (In) Name, SRNNumber
5. (In) Name, SequenceNumber
6. (In) Name, SocialSecurityNumber
7. (In) Name, LicensePlateNumber
8. (In) Name, VehicleIdentificationNumber

WMPISouthDakotaSexOffenderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	10	
Name	Name	M	30	
SequenceNumber	SequenceNumber	C	3	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateIdNumber	StateIdNumber	C	10	
SRNNumber	SRNNumber	C	11	

Possible Combinations

1. (In) Name, BirthDate
2. (In) Name, FBINumber
3. (In) Name, StateIdNumber
4. (In) Name, SRNNumber
5. (In) Name, SequenceNumber
6. (In) Name, SocialSecurityNumber

WMPIUnidentifiedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	C	2	
AreaCode	AreaCode	O	3	See NCIC Code Manual
BodyPartsStatusCode	BodyPartsStatusCode	C	15	See NCIC Code Manual
EthnicityCode	EthnicityCode	O	1	See NCIC Code Manual
EyeColorCode	EyeColorCode	C	3	See NCIC Code Manual
HairColorCode	HairColorCode	C	3	See NCIC Code Manual
Height	Height	C	3	
ImageIndicator	ImageIndicator	O	1	Blank, Y
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	C	1	See NCIC Code Manual
SexCode	SexCode	C	1	See NCIC Code Manual
Weight	Weight	C	3	

Possible Combinations

1. (In/Out) Age, EyeColorCode, HairColorCode, Height, RaceCode, SexCode, Weight, [AreaCode, EthnicityCode, ImageIndicator]
2. (In/Out) BodyPartsStatusCode, [AreaCode, EthnicityCode, ImageIndicator, RaceCode, SexCode]
3. (In/Out) NCICNumber, [ImageIndicator]

4. (In/Out) OriginatingAgencyCaseNumber, [ImageIndicator]

WMPIWantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Blank, Y
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Blank, Y
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	Blank, Y
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	O	1	See NCIC Code Manual
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	Blank, Y
SexCode	SexCode	O	1	See NCIC Code Manual
SocialSecurityNumber	SocialSecurityNumber	C	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	4	See NCIC Code Manual
VehicleMakeCodeDescription	VehicleMakeCodeDescription	O	20	

Possible Combinations

1. (In/Out) Name, BirthDate, [ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, RaceCode, RelatedHitSearchIndicator, SexCode]
2. (In/Out) Name, OriginatingAgencyCaseNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator]
3. (In/Out) NCICNumber, [ImageIndicator, RelatedHitSearchIndicator]
4. (In/Out) Name, FBINumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator]
5. (In/Out) Name, MiscellaneousNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator]
6. (In/Out) Name, OperatorLicenseNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator]
7. (In/Out) Name, SocialSecurityNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator]
8. (In/Out) LicensePlateNumber, LicensePlateStateCode, [ImageIndicator, RelatedHitSearchIndicator, VehicleIdentificationNumber, VehicleMakeCode, VehicleMakeCodeDescription]
9. (In/Out) VehicleIdentificationNumber, VehicleMakeCode, [ImageIndicator, RelatedHitSearchIndicator, LicensePlateNumber, LicensePlateStateCode, VehicleMakeCodeDescription]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- DMPP-2020 Interface Specifications