

Tennessee (TN) METRO

Transport:

HTTP Web Service

Routing and Configuration Information:

Primary: Save Bytes

Secondary: Mnemonic

Tertiary: ORI

- The TIES assigned ORI for a device (or for the site) should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.
- The ARMS assigned User Sequence Number should be placed in the **<Authentication>/<UserName>** field in the ConnectCIC header.
- The Agency assigned Computer Name for the device should be placed in the **<Authentication>/<Mnemonic>** field in the ConnectCIC header.

Security Requirements:

Background Checks – Tennessee requires each vendor to have any personnel who will be working with secure data (transactions) to be fingerprinted for background checks and they require a NCIC card and Tennessee card charging \$24 for each card (\$48/person). You will also need to complete the security paperwork (CJIS Security Addendum and TBI Vendor Eligibility Form) before your first Tennessee agency is installed. These can be done directly with TBI. Information can be obtained through an agency or through the Tennessee Bureau of Investigation (615-744-4001).

Logon Requirements:

None

Certification Requirements:

None

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	20	
RegistrationNumber	RegistrationNumber	C	8	
State	State	O	2	

Possible Combinations

1. (In/Out) BoatHullIdNumber, [RegistrationNumber, State]
2. (In/Out) RegistrationNumber, [BoatHullIdNumber, State]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
PurposeCode	PurposeCode	M	1	
SexCode	SexCode	C	1	
State	State	O	2	

Possible Combinations

1. (In/Out) Attention, BirthDate, Name, PurposeCode, SexCode, [State]
2. (In/Out) Attention, OperatorLicenseNumber, PurposeCode, [State]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
RaceCode	RaceCode	O	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	C	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	24	

Possible Combinations

1. (In) BirthDate, Name
2. (In) OperatorLicenseNumber
3. (In) SocialSecurityNumber
4. (In/Out) BirthDate, Name, [ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, MiscellaneousNumber,

- OperatorLicenseNumber, RaceCode, RelatedHitSearchIndicator, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
- (In/Out) MiscellaneousNumber, Name, [BirthDate, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, OperatorLicenseNumber, RaceCode, RelatedHitSearchIndicator, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
 - (Out) BirthDate, Name, SexCode, State
 - (Out) OperatorLicenseNumber, State

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	O	23	
GunSerialNumber	GunSerialNumber	M	11	

Possible Combinations

- (In/Out) GunSerialNumber, [GunCaliber, GunMake]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	O	30	
AddressStreetName	AddressStreetName	O	30	
AddressStreetNumber	AddressStreetNumber	O	30	
DealerLicensePlateNumber	DealerLicensePlateNumber	C	20	
HandicapPlacardNumber	HandicapPlacardNumber	C	20	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
Name	Name	C	30	
State	State	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleYear	VehicleYear	C	4	

Possible Combinations

- (In) DealerLicensePlateNumber
- (In) HandicapPlacardNumber
- (In) LicensePlateNumber
- (In) Name, [AddressCity, AddressStreetName, AddressStreetNumber]
- (In) VehicleIdentificationNumber
- (Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, State
- (Out) State, VehicleIdentificationNumber, [VehicleMakeCode]

Expanded Queries Supported:

AlarmExchangeResponse

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlarmResponse	AlarmResponse	M	14400	
DestinationORI	DestinationORI	M	9	
FormORI	FormORI	O	9	

Possible Combinations

- (In/Out) AlarmResponse, DestinationORI, [FormORI]

P1AlarmExchangeResponse

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlarmResponse	AlarmResponse	M	14400	
DestinationORI	DestinationORI	M	9	
FormORI	FormORI	O	9	

Possible Combinations

1. (In/Out) AlarmResponse, DestinationORI, [FormORI]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- TIES Operating Manual
- ARMS Interface Document