

Tennessee (TN) TIES

Transport:

TCP/IP

Routing and Configuration Information:

Route by ORI – Save Information is by token

- The TIES assigned ORI for a device (or for the site) should be placed in the <Authentication>/<ORI> field in the ConnectCIC header.

Security Requirements:

Background Checks – Tennessee requires each vendor to have any personnel who will be working with secure data (transactions) to be fingerprinted for background checks and they require a NCIC card and Tennessee card charging \$24 for each card (\$48/person). You will also need to complete the security paperwork (CJIS Security Addendum and TBI Vendor Eligibility Form) before your first Tennessee agency is installed. These can be done directly with TBI. Information can be obtained through an agency or through the Tennessee Bureau of Investigation (615-744-4001).

Logon Requirements:

None

Certification Requirements:

None

TBI does encourage Vendors to test against their TIES Test Server. CommSys has tested.

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	20	
RegistrationNumber	RegistrationNumber	C	8	
State	State	O	2	
InquiryTypeIndicator	InquiryTypeIndicator	O	1	1-Registration Check Only 2-Hot files Check Only 3-Registration and hotfiles check (default)

Possible Combinations

1. (In/Out) BoatHullIdNumber, [State, InquiryTypeIndicator]
2. (In/Out) RegistrationNumber, [State, InquiryTypeIndicator]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
PurposeCode	PurposeCode	M	1	
SexCode	SexCode	C	1	
State	State	O	2	

Possible Combinations

1. (In/Out) Attention, BirthDate, Name, PurposeCode, SexCode, [State]
2. (In/Out) Attention, OperatorLicenseNumber, PurposeCode, [State]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	
ImageIndicator	ImageIndicator	O	1	Y, N
InquiryTypeIndicator	InquiryTypeIndicator	O	1	1-Registration Check Only 2-Hot files Check Only 3-Registration and hotfiles check (default)
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
RaceCode	RaceCode	O	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	C	2	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, [ExpandedNameSearchCode, ImageIndicator, RaceCode, State, InquiryTypeIndicator, RelatedHitSearchIndicator]
2. (In) OperatorLicenseNumber
3. (Out) OperatorLicenseNumber, State ***No hotfiles check conducted**
4. (In) SocialSecurityNumber

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	O	4	
GunMake	GunMake	O	23	
GunSerialNumber	GunSerialNumber	M	20	

Possible Combinations

1. (In/Out) GunSerialNumber, [GunCaliber, GunMake]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
DealerLicensePlateNumber	DealerLicensePlateNumber	C	20	
HandicapPlacardNumber	HandicapPlacardNumber	C	20	
InquiryTypeIndicator	InquiryTypeIndicator	O	1	1-Registration Check Only 2-Hot files Check Only 3-Registration and hotfiles check (default)
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
State	State	C	2	
TemporaryLicensePlateNumber	TemporaryLicensePlateNumber	C	10	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	4	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In) LicensePlateNumber, [InquiryTypeIndicator]
2. (Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, State, [InquiryTypeIndicator]
3. (In/Out) VehicleIdentificationNumber, [InquiryTypeIndicator, State, VehicleMakeCode, VehicleYear]
4. (In) DealerLicensePlateNumber, [InquiryTypeIndicator]
5. (In) HandicapPlacardNumber *(No hot files check conducted)
6. (In) TemporaryLicensePlateNumber *(No hot files check conducted)

Transactions Supported:

Agency Operations and Support (AOS)

AOSHazardousMaterialsQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
UnitedNationsNumber	UnitedNationsNumber	M	4	

Possible Combinations

1. (In/Out) UnitedNationsNumber

Expanded Transactions Supported:

AlarmExchangeResponse

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlarmResponse	AlarmResponse	M	14400	
DestinationORI	DestinationORI	M	9	

FormORI	FormORI	O	9	
---------	---------	---	---	--

Possible Combinations

1. (In/Out) AlarmResponse, DestinationORI, [FormORI]

P1AlarmExchangeResponse

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AlarmResponse	AlarmResponse	M	14400	
DestinationORI	DestinationORI	M	9	
FormORI	FormORI	O	9	

Possible Combinations

1. (In/Out) AlarmResponse, DestinationORI, [FormORI]

ProtectionOrderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	
FBINumber	FBINumber	O	9	
ImageIndicator	ImageIndicator	O	1	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	C	30	
NCICNumber	NCICNumber	C	10	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
ProtectionOrderNumber	ProtectionOrderNumber	C	15	
RaceCode	RaceCode	O	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SexCode	SexCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	24	

** An inquiry of the Protection Order File may be made by name and one, more than one, or all of the following alphanumeric identifiers: DOB, FBI, MNU, SOC, and OLN. Additionally, inquiries may be made using vehicle data, NAM and OCA only, NAM and PNO only, or NIC only.

Possible Combinations

1. (In/Out) Name and an additional identifier, [BirthDate, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, MiscellaneousNumber, OperatorLicenseNumber, RaceCode, RelatedHitSearchIndicator, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
2. (In/Out) LicensePlateNumber, LicensePlateStateCode
3. (In/Out) VehicleIdentificationNumber, VehicleMakeCode
4. (In/Out) Name, OriginatingAgencyCaseNumber
5. (In/Out) Name, ProtectionOrderNumber
6. (In/Out) NCICNumber

QueryPassThrough

Field Name	XML Tag Name	M/C/O	Size	Possible Values
------------	--------------	-------	------	-----------------

Message Data	FreeText	M	100	
--------------	----------	---	-----	--

Possible Combinations

1. FreeText

*This is a message key pass through and does not require the header of the message, only the body.

Example: (Header)**QA.ORI/123456789.TYP/YTHING.SER/123456**

Bolded text would be sent to ConnectCIC server in the FreeText tag.

SexOffenderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	O	8	
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	
FBINumber	FBINumber	O	9	
ImageIndicator	ImageIndicator	O	1	
LicensePlateNumber	LicensePlateNumber	O	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	O	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	O	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SexCode	SexCode	O	1	
SexOffenderStatusCode	SexOffenderStatusCode	O	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
VehicleIdentificationNumber	VehicleIdentificationNumber	O	20	
VehicleMakeCode	VehicleMakeCode	O	24	

** An inquiry of the Convicted Sexual Offender Registry File may be made by name and one, more than one, or all of the following alphanumeric identifiers: DOB, FBI, MNU, SOC, OLN, LIC, and/or VIN.

Possible Combinations

- (In/Out) Name and an additional identifier, [BirthDate, ExpandedNameSearchCode, FBINumber, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, MiscellaneousNumber, OperatorLicenseNumber, RaceCode, RelatedHitSearchIndicator, SexCode, SexOffenderStatusCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
- (In/Out) Name, OriginatingAgencyCaseNumber

TnTiesBoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCity	AddressCity	C	20	
BirthDate	BirthDate	C	8	
BoatHullIdNumber	BoatHullIdNumber	C	20	
Name	Name	C	30	
RegistrationNumber	RegistrationNumber	C	8	
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	C	2	

Possible Combinations (Double asterisk “**” denotes registration **ONLY** queried; no hotfiles)

1. (In/Out) BoatHullIdNumber, [State]
2. (In/Out) RegistrationNumber, [State]
3. (In/Out) Name, BirthDate, [State]
4. (In)** Name, AddressCity
5. (In)** SocialSecurityNumber

TnTiesDriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressStreetNumber	AddressStreetNumber	O	30	
AddressStreetName	AddressStreetName	O	30	
AddressCity	AddressCity	O	30	
AddressCounty	AddressCounty	O	20	
Age	Age	O	2	
BirthDate	BirthDate	C	8	
ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	
ImageIndicator	ImageIndicator	O	1	Y, N
Name	Name	C	30	
NextPage	NextPage	O	20	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	C	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	C	2	

Possible Combinations (Double asterisk “**” denotes registration **ONLY** queried; no hotfiles)

1. (In)** Name, [AddressStreetName, AddressStreetNumber, AddressCity]
2. (In) Name, BirthDate, [SexCode, ImageIndicator, RelatedHitSearchIndicator, ExpandedNameSearchCode]
3. (In) SocialSecurityNumber, [ExpandedNameSearchCode, ImageIndicator, InquiryTypeIndicator, State, RelatedHitSearchIndicator]
4. (Out)** Name, [Age, SexCode, AddressCity, AddressCounty, NextPage]
5. (Out) Name, BirthDate, SexCode, [ImageIndicator, RelatedHitSearchIndicator, ExpandedNameSearchCode]
6. (In) OperatorLicenseNumber, [ExpandedNameSearchCode, ImageIndicator, InquiryTypeIndicator, RelatedHitSearchIndicator]
7. (Out)** OperatorLicenseNumber, State
8. (In/Out) Name, OperatorLicenseNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, SexCode, State]
9. (In/Out) Name, SocialSecurityNumber, [ExpandedNameSearchCode, ImageIndicator, RelatedHitSearchIndicator, SexCode, State]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- TIES Operating Manual