

Wyoming (WY) WCJIN

[Disclaimer Statement](#)

Transport:

TCPIP

IP pair Wyoming Specific Transport

Routing and Configuration Information:

ORI Routing

- The WCJIN assigned ORI for a device (or for the site) should be placed in the <Authentication>/<ORI> field in the ConnectCIC header.
- The WCJIN assigned Mnemonic (also known as TDAC) for a device should be placed in the <Authentication>/<Mnemonic> field in the ConnectCIC header.
- The WCJIN assigned User Id should be placed in the <Authentication>/<UserName> field in the ConnectCIC header.

Security Requirements:

None known at this time.

Logon Requirements:

None known at this time.

Certification Requirements:

Agency sponsor is required.

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	20	
RegistrationNumber	RegistrationNumber	C	8	
State	State	O	2	

Possible Combinations

1. (In/Out) BoatHullIdNumber, [State]
2. (In/Out) RegistrationNumber, [State]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
ImageIndicator	ImageIndicator	O	1	Y
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	C	1	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, [ImageIndicator, State, State2, State3, State4, State5]
2. (In/Out) OperatorLicenseNumber, [ImageIndicator, State, State2, State3, State4, State5]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	O	4	
GunMakeCode	GunMakeCode	O	3	
GunSerialNumber	GunSerialNumber	M	11	

Possible Combinations

1. (In/Out) GunSerialNumber, [GunCaliber, GunMakeCode]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	8	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
State	State	O	2	
State2	State2	O	2	
State3	State3	O	2	
State4	State4	O	2	
State5	State5	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	24	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In/Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, [State, State2, State3, State4, State5]
2. (In/Out) VehicleIdentificationNumber, [State, State2, State3, State4, State5, VehicleMakeCode, VehicleYear]

Expanded Queries:

QueryPassThrough

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FreeText	FreeText	M	100	

Possible Combinations

1. (In/Out) FreeText

*This is a message key pass through and does not require the header of the message, only the body.

Example: (Header)**QA.ORI/123456789.TYP/YTHING.SER/123456**

Bolded text would be sent to ConnectCIC server in the FreeText tag.

Computerized Criminal History (CCH) Package:

CCHCriminalHistoryAQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
FreeText	FreeText	M	14400	
NletsDestination	NletsDestination	M	9	
NletsDestination2	NletsDestination2	O	9	
NletsDestination3	NletsDestination3	O	9	
NletsDestination4	NletsDestination4	O	9	
PurposeCode	PurposeCode	M	1	

Possible Combinations

1. (In/Out) Attention, FreeText, NletsDestination, PurposeCode, [NletsDestination2, NletsDestination3, NletsDestination4]

CCHCriminalHistoryARQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
FreeText	FreeText	M	14400	
NletsDestination	NletsDestination	M	9	
PurposeCode	PurposeCode	M	1	

Possible Combinations

1. (In/Out) Attention, FreeText, NletsDestination, PurposeCode

CCHCriminalHistoryFQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	30	

AddressStreet	AddressStreet	O	30	
AddressZipCode	AddressZipCode	O	9	
Attention	Attention	M	30	
BuildingName	BuildingName	O	30	
DepartmentName	DepartmentName	O	30	
ImageIndicator	ImageIndicator	O	1	
PurposeCode	PurposeCode	M	1	
State	State	C	2	
StateIdNumber	StateIdNumber	M	10	

Possible Combinations

1. (In) Attention, PurposeCode, StateIdNumber, [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName, ImageIndicator]
2. (Out) Attention, PurposeCode, StateIdNumber, State [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName, ImageIndicator]

CCHCriminalHistoryIQQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	C	30	
BirthDate	BirthDate	C	8	
ImageIndicator	ImageIndicator	O	1	
MiscellaneousNumber	MiscellaneousNumber	O	15	
Name	Name	C	30	
PurposeCode	PurposeCode	C	1	
RaceCode	RaceCode	O	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	O	9	
State	State	O	2	

Possible Combinations

1. (In) Attention, BirthDate, Name, PurposeCode, SexCode, [ImageIndicator, MiscellaneousNumber, RaceCode, SocialSecurityNumber]
2. (Out) Attention, BirthDate, Name, PurposeCode, SexCode, State, [ImageIndicator, MiscellaneousNumber, RaceCode, SocialSecurityNumber]

CCHCriminalHistoryQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
PurposeCode	PurposeCode	C	1	
RaceCode	RaceCode	C	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) BirthDate, Name, PurposeCode, RaceCode, SexCode, [Attention]
2. (In/Out) BirthDate, MiscellaneousNumber, Name, PurposeCode, RaceCode, SexCode, [Attention]

3. (In/Out) BirthDate, Name, PurposeCode, RaceCode, SexCode, SocialSecurityNumber, [Attention]
4. (In/Out) Name, PurposeCode, SocialSecurityNumber, [Attention]
5. (In/Out) MiscellaneousNumber, Name, PurposeCode, [Attention]
6. (In/Out) PurposeCode, StateIdNumber, [Attention, Name]
7. (In/Out) FBINumber, PurposeCode, [Attention, Name]

CCHCriminalHistoryQRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	30	
AddressStreet	AddressStreet	O	30	
AddressZipCode	AddressZipCode	O	9	
Attention	Attention	M	30	
BuildingName	BuildingName	O	30	
DepartmentName	DepartmentName	O	30	
FBINumber	FBINumber	C	10	
PurposeCode	PurposeCode	M	1	
StateIdNumber	StateIdNumber	C	10	
Name	Name	O	30	

Possible Combinations

1. (In/Out) Attention, FBINumber, PurposeCode, [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName, Name]
2. (In/Out) Attention, PurposeCode, StateIdNumber, [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName, Name]

CCHCriminalHistoryQWQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	O	30	
BirthDate	BirthDate	C	8	
EnhancedNameSearchIndicator	EnhancedNameSearchIndicator	O	1	
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	
ImageIndicator	ImageIndicator	O	1	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
PurposeCode	PurposeCode	C	1	
RaceCode	RaceCode	C	1	
RelatedHitSearchIndicator	RelatedHitSearchIndicator	O	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	

Possible Combinations

1. (In/Out) BirthDate, MiscellaneousNumber, Name, PurposeCode, RaceCode, SexCode, [Attention, EnhancedNameSearchIndicator, ExpandedBirthDateSearchCode, ImageIndicator, RelatedHitSearchIndicator]
2. (In/Out) BirthDate, Name, PurposeCode, RaceCode, SexCode, [Attention, EnhancedNameSearchIndicator, ExpandedBirthDateSearchCode, ImageIndicator, RelatedHitSearchIndicator]
3. (In/Out) BirthDate, Name, PurposeCode, RaceCode, SexCode, SocialSecurityNumber, [Attention, EnhancedNameSearchIndicator, ExpandedBirthDateSearchCode, ImageIndicator, RelatedHitSearchIndicator]

4. (In/Out) MiscellaneousNumber, Name, PurposeCode, [Attention, EnhancedNameSearchIndicator, ImageIndicator, RelatedHitSearchIndicator]
5. (In/Out) Name, PurposeCode, SocialSecurityNumber, [Attention, EnhancedNameSearchIndicator, ImageIndicator, RelatedHitSearchIndicator]

CCHCriminalHistoryZRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
AddressCityState	AddressCityState	O	30	
AddressStreet	AddressStreet	O	30	
AddressZipCode	AddressZipCode	O	9	
Attention	Attention	M	30	
BuildingName	BuildingName	O	30	
DepartmentName	DepartmentName	O	30	
FBINumber	FBINumber	C	10	
PurposeCode	PurposeCode	M	1	
StateIdNumber	StateIdNumber	C	10	

Possible Combinations

1. (In/Out) Attention, FBINumber, PurposeCode, [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName]
2. (In/Out) Attention, PurposeCode, StateIdNumber, [AddressCityState, AddressStreet, AddressZipCode, BuildingName, DepartmentName]

Wanted & Missing Person Inquiry (WMPI) Package:

WMPISexOffenderQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
BoatHullSerialNumber	BoatHullSerialNumber	C	20	
BoatRegistrationNumber	BoatRegistrationNumber	C	8	
ExpandedBirthDateSearchIndicator	ExpandedBirthDateSearchIndicator	O	1	(Blank) Normal birth date search '1' Include +/- 1 year '2' Include transposed month/day '3' Both
ExpandedNameSearchIndicator	ExpandedNameSearchIndicator	O	1	'Y' Expanded name search 'N' (default) Normal name search
FBINumber	FBINumber	C	9	
ImageIndicator	ImageIndicator	O	1	'Y' Include images 'N' (default) Do not include images.
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	C	2	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
RaceCode	RaceCode	O	1	
RelatedSearchHitIndicator	RelatedSearchHitIndicator	O	1	'Y' Search related hits 'N' (default) Do not search related hits
SexCode	SexCode	O	1	
SexOffenderStatusCode	SexOffenderStatusCode	O	1	'Y' (default) for only active NSOR records 'N' for active, cleared, and expired records.
SocialSecurityNumber	SocialSecurityNumber	C	9	

VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	C	24	
ZipCode	ZipCode	C	10	

Possible Combinations

1. (In/Out) Name, [BoatHullSerialNumber, BoatRegistrationNumber, ExpandedBirthDateSearchIndicator, ExpandedNameSearchIndicator, FBINumber, ImageIndicator, LicensePlateNumber, LicensePlateStateCode, MiscellaneousNumber, OperatorLicenseNumber, OriginatingAgencyCaseNumber, RaceCode, RelatedSearchHitIndicator, SexCode, SocialSecurityNumber, VehicleIdentificationNumber, VehicleMakeCode]
2. (In/Out) ZipCode, [ImageIndicator, SexOffenderStatusCode]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide
- Wyoming CJIS Documentation