

Transport:

Routing and Configuration Information:

Mnemonic Routing

- The HCJDC assigned ORI for a device (or for the site) should be placed in the <Authentication>/<ORI> field in the ConnectCIC header.
- The HCJDC assigned Mnemonic for a device should be placed in the <Authentication>/<Mnemonic> field in the ConnectCIC header.

Security Requirements:

None known at this time.

Logon Requirements:

None known at this time.

Certification Requirements:

Agency sponsor is required.

Data-Mined Transactions:

NCIC (QA, QB, QG, QV, QW) and DMV (Person and Vehicle)

[Tags returned from Data mining](#)

Basic Queries Supported:

ArticleSingleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ArticleSerialNumber	ArticleSerialNumber	M	20	
ArticleTypeCode	ArticleTypeCode	M	7	

Possible Combinations

1. (In/Out) ArticleSerialNumber, ArticleTypeCode

BoatQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BoatHullIdNumber	BoatHullIdNumber	C	20	Alphanumeric
ImageIndicator	ImageIndicator	O	1	Alpha, 'Y' or 'N'
RegistrationNumber	RegistrationNumber	C	8	Alphanumeric
RelatedSearchHitIndicator	RelatedSearchHitIndicator	O	1	Alpha, 'Y' or 'N'

State	State	O	2	Alpha
-------	-------	---	---	-------

Possible Combinations

1. (In) BoatHullIdNumber, [ImageIndicator, RelatedSearchHitIndicator]
2. (Out) BoatHullIdNumber, State [ImageIndicator, RelatedSearchHitIndicator]
3. (In) RegistrationNumber, [ImageIndicator, RelatedSearchHitIndicator]
4. (Out) RegistrationNumber, State [ImageIndicator, RelatedSearchHitIndicator]

DriverHistoryQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	C	1	
State	State	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, SexCode, [State]
2. (In/Out) OperatorLicenseNumber, [State]

DriverLicenseQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
RaceCode	RaceCode	O	1	
SexCode	SexCode	C	1	
State	State	O	2	

Possible Combinations

1. (In/Out) BirthDate, Name, [RaceCode, SexCode]
2. (In/Out) BirthDate, Name, SexCode, [State]
3. (In/Out) OperatorLicenseNumber, [State]

GunQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
GunCaliber	GunCaliber	O	4	
GunMakeCode	GunMakeCode	O	23	
GunSerialNumber	GunSerialNumber	M	20	

Possible Combinations

1. (In/Out) GunSerialNumber, [GunCaliber, GunMakeCode]

VehicleRegistrationQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
ImageIndicator	ImageIndicator	O	1	
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
LicensePlateTypeCode	LicensePlateTypeCode	C	2	
LicensePlateYear	LicensePlateYear	C	4	
RelatedSearchHitIndicator	RelatedSearchHitIndicator	O	1	
State	State	O	2	

VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	24	
VehicleYear	VehicleYear	O	4	

Possible Combinations

1. (In/Out) LicensePlateNumber, [LicensePlateStateCode]
2. (In/Out) LicensePlateNumber, LicensePlateTypeCode, LicensePlateYear, [State]
3. (In/Out) VehicleIdentificationNumber, [ImageIndicator, RelatedSearchHitIndicator, VehicleMakeCode]
4. (In/Out) VehicleIdentificationNumber, [State, VehicleMakeCode, VehicleYear]

Transactions Supported:

Computerized Criminal History (CCH)

CCHCriminalHistoryAQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
DestinationORI	DestinationORI	M	9	
FreeText	FreeText	O	14400	
PurposeCode	PurposeCode	M	1	

Possible Combinations

1. (In/Out) Attention, DestinationORI, PurposeCode, [FreeText]

CCHCriminalHistoryFQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address	Address	O	30	
Attention	Attention	M	30	
Building	Building	O	30	
CityAndState	CityAndState	O	30	
DepartmentName	DepartmentName	O	30	
ImageIndicator	ImageIndicator	O	1	
PurposeCode	PurposeCode	M	1	
State	State	M	2	
StateIDNumber	StateIDNumber	M	10	
ZipCode	ZipCode	O	9	

Possible Combinations

1. (In/Out) Attention, PurposeCode, State, StateIDNumber, [Address, Building, CityAndState, DepartmentName, ImageIndicator, ZipCode]

CCHCriminalHistoryIQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	8	
ImageIndicator	ImageIndicator	O	1	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	M	30	

PurposeCode	PurposeCode	M	1	
RaceCode	RaceCode	O	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
State	State	M	2	

Possible Combinations

1. (In/Out) Attention, BirthDate, Name, PurposeCode, SexCode, State, [ImageIndicator, MiscellaneousNumber, RaceCode, SocialSecurityNumber]
2. (In/Out) Attention, MiscellaneousNumber, Name, PurposeCode, State, [ImageIndicator]
3. (In/Out) Attention, Name, PurposeCode, SocialSecurityNumber, State, [ImageIndicator]

CCHCriminalHistoryQHQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Attention	Attention	M	30	
BirthDate	BirthDate	C	8	
FBINumber	FBINumber	C	9	
MiscellaneousNumber	MiscellaneousNumber	C	15	
Name	Name	C	30	
PurposeCode	PurposeCode	M	1	
RaceCode	RaceCode	C	1	
SexCode	SexCode	C	1	
SocialSecurityNumber	SocialSecurityNumber	C	9	
StateIDNumber	StateIDNumber	C	10	

Possible Combinations

1. (In/Out) Attention, BirthDate, MiscellaneousNumber, Name, PurposeCode, RaceCode, SexCode
2. (In/Out) Attention, BirthDate, Name, PurposeCode, RaceCode, SexCode
3. (In/Out) Attention, BirthDate, Name, PurposeCode, RaceCode, SexCode, SocialSecurityNumber
4. (In/Out) Attention, FBINumber, Name, PurposeCode
5. (In/Out) Attention, FBINumber, PurposeCode
6. (In/Out) Attention, MiscellaneousNumber, Name, PurposeCode
7. (In/Out) Attention, Name, PurposeCode, SocialSecurityNumber
8. (In/Out) Attention, Name, PurposeCode, StateIDNumber
9. (In/Out) Attention, PurposeCode, StateIDNumber

CCHCriminalHistoryQRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address	Address	O	30	
Attention	Attention	O	30	
Building	Building	O	30	
CityAndState	CityAndState	O	30	
DepartmentName	DepartmentName	O	30	
FBINumber	FBINumber	C	9	
PurposeCode	PurposeCode	M	1	
StateIDNumber	StateIDNumber	C	10	
ZipCode	ZipCode	O	9	

Possible Combinations

1. (In/Out) Attention, FBINumber, PurposeCode, [Address, Building, CityAndState, DepartmentName, ZipCode]

2. (In/Out) Address, PurposeCode, StateIDNumber, [Attention, Building, CityAndState, DepartmentName, ZipCode]

CCHCriminalHistoryZRQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
FBINumber	FBINumber	C	9	
PurposeCode	PurposeCode	O	1	
StateIDNumber	StateIDNumber	C	10	

Possible Combinations

1. (In/Out) FBINumber, [PurposeCode]
2. (In/Out) StateIDNumber, [PurposeCode]

Expanded Transactions Supported:

SecuritiesStolenQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Denomination	Denomination	C	9	
Issuer	Issuer	O	15	
NCICNumber	NCICNumber	C	10	
OriginatingAgencyCaseNumber	OriginatingAgencyCaseNumber	C	20	
Owner	Owner	C	40	
RelatedSearchHitIndicator	RelatedSearchHitIndicator	O	1	
SecurityDate	SecurityDate	O	8	
SecuritySerialNumber	SecuritySerialNumber	C	9	
SecurityTypeCode	SecurityTypeCode	C	2	
SocialSecurityNumber	SocialSecurityNumber	C	9	

Possible Combinations

1. (In/Out) NCICNumber, [RelatedSearchHitIndicator ,SecurityDate]
2. (In/Out) Denomination, SecuritySerialNumber, SecurityTypeCode, [Issuer, RelatedSearchHitIndicator ,SecurityDate]
3. (In/Out) OriginatingAgencyCaseNumber, Owner, [RelatedSearchHitIndicator,SecurityDate]
4. (In/Out) Owner, [RelatedSearchHitIndicator,SecurityDate ,SecurityTypeCode]
5. (In/Out) SocialSecurityNumber, [Owner, RelatedSearchHitIndicator,SecurityDate]

StolenVehicleQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
LicensePlateNumber	LicensePlateNumber	C	10	
LicensePlateStateCode	LicensePlateStateCode	O	2	
VehicleIdentificationNumber	VehicleIdentificationNumber	C	20	
VehicleMakeCode	VehicleMakeCode	O	24	

Possible Combinations

1. (In/Out) LicensePlateNumber, [LicensePlateStateCode]
2. (In/Out) VehicleIdentificationNumber, [VehicleMakeCode]

WantedPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	C	8	YYYYMMDD
ExpandedBirthDateSearchCode	ExpandedBirthDateSearchCode	O	1	Numeric, '1' or '0'

ExpandedNameSearchCode	ExpandedNameSearchCode	O	1	Alpha, 'Y' or 'N'
ImageIndicator	ImageIndicator	O	1	Alpha, 'Y' or 'N'
Name	Name	C	30	Alphanumeric, special characters
RelatedSearchHitIndicator	RelatedSearchHitIndicator	O	1	Alpha, 'Y' or 'N'
SexCode	SexCode	O	1	Alpha, 'M F or U'

Possible Combinations

1. (In/Out) BirthDate, Name, [ExpandedBirthDateSearchCode, ExpandedNameSearchCode, ImageIndicator, RaceCode, RelatedSearchHitIndicator, SexCode]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)

Notes:

None

References:

- NCIC 2000 Operations Manual
- NLETS User Guide