

Contra Costa County, CA (CA_CONTRA_COSTA)

[Disclaimer Statement](#)

Transport:

TCP/IP (Level II)

Routing and Configuration Information:

Save Bytes (Primary)

Mnemonic (Secondary)

- The Contra Costa County assigned ORI for a device (or for the site) should be placed in the **<Authentication>/<ORI>** field in the ConnectCIC header.
- The Contra Costa County assigned Mnemonic for a device should be placed in the **<Authentication>/<Mnemonic>** field in the ConnectCIC header.
- The agency assigned User ID should be placed in the **<Authentication>/<UserName>** field in the ConnectCIC header.
- The agency assigned Terminal Identifier should be placed in the **<Authentication>/<DeviceId>** field in the ConnectCIC header.

Security Requirements:

Agency must adhere to all requirements set forth by Contra Costa County for operation of a direct connection.

Logon Requirements:

None

Certification Requirements:

None

Transaction Requirements:

Beginning July 21, 2021 CLETS requires a “Purpose Code” field to be supplied with every CLETS transaction. The information regarding this purpose code was published by CLETS in Information Bulletin 20-03-CJIS and covers the “Purpose Code” field added to satisfy Assembly Bill (AB) 1747.

Any transaction which does not supply a valid Purpose Code value will be rejected by CLETS. ConnectCIC does not default the value of field; it must be provided by the partner implementation as a user selectable field.

The CLETS “Purpose Code” value must be supplied to ConnectCIC via the **<CaRequestPurposeCode>** element as a sibling to the transaction-specific elements covered in this document. The **<CaRequestPurposeCode>** element is mandatory for all transactions.

The element is a single character value which may be one of the following:

- **C** – Criminal Justice
- **I** – Immigration Enforcement
- **U** – Investigate Violations of Title 8, section 1325 of the United States Code

Basic Queries Supported:

None

Transactions Supported:

None

Expanded Queries Supported:

CaContraCostaJawsWarrantQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
BirthDate	BirthDate	M	8	
Name	Name	M	30	
RequestingAgencyId	RequestingAgencyId	M	2	See JAWS Inquiry and Update Documentation

Possible Combinations

1. (In/Out) BirthDate, Name, RequestingAgencyId

CaContraCostaJawsPersonQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Address	Address	O	3	
AddressCity	AddressCity	O	13	
Age	Age	C	2	
BirthDate	BirthDate	C	8	
Name	Name	M	30	
RaceCode	RaceCode	O	1	
RequestingAgencyId	RequestingAgencyId	M	2	See JAWS Inquiry and Update Documentation
SexCode	SexCode	C	1	
State	State	C	2	

Possible Combinations

1. (In) BirthDate, Name, RequestingAgencyId, [Address, AddressCity]
2. (In) Age, Name, RequestingAgencyId, [Address, AddressCity]
3. (In/Out) Name, RequestingAgencyId, [Age, BirthDate, RaceCode, SexCode]
4. (Out) BirthDate, Name, SexCode, State, RequestingAgencyId
5. (Out) Age, Name, State, RequestingAgencyId, [AddressCity, SexCode]

CLETSPersonSuperQuery

Field Name	XML Tag Name	M/C/O	Size	Possible Values
Age	Age	C	2	
BirthDate	BirthDate	C	10	
Name	Name	C	30	
OperatorLicenseNumber	OperatorLicenseNumber	C	20	
SexCode	SexCode	C	1	
State	State	O		

Possible Combinations

1. (In/Out) OperatorLicenseNumber

2. (In/Out) Name, SexCode, Age
3. (In/Out) Name, SexCode, BirthDate, [State]

Hardware/Software Requirements:

[ConnectCIC Third-Party Hardware and Software Minimum Requirements](#)