Tabelle 1: 1.Versuchsteil: Rauschfrei

ϕ in Rad	U in Volt
0.000	0.474
0.262	0.255
0.524	0.010
0.785	-0.274
1.047	-0.611
1.309	-0.865
1.571	-0.971
1.833	-1.062
3.142	-0.357
4.712	0.968

Tabelle 2: 2.Versuchsteil: Verrauscht

ϕ in Rad	U in Volt
0.000	0.357
0.262	0.230
0.524	0.025
0.785	-0.229
1.047	-0.484
1.309	-0.682
1.571	-0.738
1.833	-0.814
3.142	-0.307
4.712	0.772

Tabelle 3: 3. Versuchsteil: Photodiode

r in Metern	Intensität in Volt
5.20×10^{-2}	2.80×10^{-3}
1.02×10^{-1}	2.82×10^{-3}
1.52×10^{-1}	1.66×10^{-3}
2.02×10^{-1}	9.50×10^{-4}
2.52×10^{-1}	6.05×10^{-4}
3.02×10^{-1}	4.42×10^{-4}
3.52×10^{-1}	3.13×10^{-4}
4.02×10^{-1}	2.50×10^{-4}
4.52×10^{-1}	2.00×10^{-4}
5.02×10^{-1}	1.50×10^{-4}
6.02×10^{-1}	9.25×10^{-5}
7.02×10^{-1}	5.75×10^{-5}
8.02×10^{-1}	5.00×10^{-5}
9.02×10^{-1}	3.00×10^{-5}
1.00	2.50×10^{-5}
1.00	3.00×10^{-5}
1.20	2.00×10^{-5}
1.40	1.50×10^{-5}
1.60	1.50×10^{-5}
1.80	5.00×10^{-6}