

I. INTRODUCTION

In the beginning of the 20th century, the study of the structure of atoms began to intensify. In particular, J.J. Thomson, after the discover of the electrons, hypothesized the “plum pudding” model: the structure of the atom consists of electrons occupying a region of space uniformly and positively charged. Ernest Rutherford tested if this behaviour of nature was plausible and set up his famous experiment, proving that Thomson’s prediction was not explained by experimental data. His idea was to study the atomic structure through scattering experiments, namely bombarding a thin gold target with α particles projectiles. This was the start of a revolution, since with the experimental data he obtained he was finally able to solve a long standing riddle by introducing a new hypothesis. It was the birth of the Rutherford model, where the positive charge is densely-packed in the center, forming the nucleus.

Returning to the present time, a general scattering process is typically described in terms of the differential cross section. This is nothing more than a function describind the probability of a scattering event to occur. In the particular case of a charged particle as projectile going against a nucleus target, the differential cross section according to Rutherford description reads:

$$\frac{d\sigma}{d\Omega} = \left(\frac{ZZ'e^2}{16\pi\epsilon_0 E} \right)^2 \frac{1}{\sin^4 \frac{\theta}{2}} \quad (1)$$

where:

- Z and Z' are the atomic numbers of the incoming particle and of the scattering material, respectively;
- e is the unit charge, namely the charge of a proton;
- E is the energy of the incoming particle;
- θ is the polar angle at which the incoming particle scatters with respect to the center of the scattering, namely the atom nucleus.

However, the expression given in Eq. 1 is only an approximation given by a simplified model and naive geometrical hypotheses. In fact, for small angles it diverges and this is in contrast with the experimental observations. In a real experiment we do not deal with beams with a point-like section or monochromatic. They have a more complex shape that should be modeled and the energy of its particles can more or less dispersed. Every of these details could apport a small correction to the already known result, but if we sum up all of them together, we can find significantly different results from the theoretical expectations.

Given these premises, on which the following discussion will hold on, this work represents the final report of the experimental activity done for the Advanced Physics Laboratory course. The core aim is to reproduce Rutherford’s result, but, more in particular, we want to:

- elaborate and describe an appropriate experimental setup for performing measurments of charged particles scattering;
- characterize the instruments employed for the measurments;
- model through numerical simulations the experimental apparatus components and conditions and the physics of the phenomenon under study, basing its behaviour on theoretical considerations from which Rutherford model was elaborated;
- measure the differential cross section of the scattering analyzed and compare it with the expected result from simulation.

Due to the shorter time at our disposal for the exceptional situation of 2020, the activity would have come to completely different results without the heredity of previous years students, who worked on the same topic. Several technical realizations have been taken from them, in particular:

- the α source support;
- the collimators of the beam;
- the support of the detector;
- the mechanics and electronics for the motor control;
- the software for the acquisition from the silicon detector and of the control of the digitizer.

Several improvements and new systems have been introduced by us during the experimental activity, including:

- a new ALPIDE pixel detector for the acquisition, with a finer geometrical resolution, along with its support and the software needed to control it from an FPGA;
- an improved configuration for the mechanical system of the motor, in order to perform acquisitions with both the detectors contemporaneously in the vacuum chamber;
- a new simulation of the apparatus and of the physics of the scattering process;
- several small improvements to the entire setup, including the possibility to perform all the operations for data acquisition in remote.

The report is organized as follow:

- in Section ??, we introduce every piece of the experimental apparatus. Particular attention will be reserved to the acquisition system for both the detector employed and to their geometrical configuration with respect to the source support and the collimators;
- in Section ??, we treat the preliminary technical operations applied for the characterization of the detectors, such as efficiency calculations and working point;
- in Section ??, we discuss about the modeling of the physics of the process and the geometry of the apparatus through a complete simulation, written in Python3;
- in Section ??, we come to the acquisition of data and to their analysis, needed to extract the differential cross section distribution.