Getting Started with uCXpresso.BLE



2014/3/14

v1.0.1

History:

2014/3/14 Add Overview

2014/3/12 Add “Create A New Project”, “Serial Terminal & Debug”

2014/3/11 First Edition

Overview

First of all, an espresso is necessary,

and the uCXpresso.BLE framework have to work on the LPCXpresso IDE, you need to install the LPCXpresso IDE in your system first. The LPCXpresso IDE are available for Windows, Linux and Mac OS/X, also you can download the LPCXpresso IDE from www.lpcware.com with a free license after register. About LPCXpresso IDE, please refer to http://www.lpcware.com/lpcxpresso/download

The uCXpresso.BLE framework is a RTOS C++ framework that port for the ARM Cortex-M0 MCU and BLE (Bluetooth Low Energy), and provides many features such as Peripherals (ADC, PWM, I2C, SPI, PIO, Interrupt, Timer….), BLE Services (Serial, Proximity, Heart Rate Meter…) and Multi-Thread (RTOS Thread, Semaphore, Mutex, MailBox…).

Easy to use with C++ framework:

Ex. A LED on the pin 19 of nano11U37

```
CPin led(P19);      // connect led object to P19 pin
led.output();       // set P19 as an output pin
led = HIGH;         // set P19 to HIGH (turn on LED)
```

Multiple Pin Definition:



Ex. Set P20 as an input pin

```
CPin key(P20);          // connect key object to P20
key.input();            // set key as an input pin with internal Pull-Up.
if ( key==LOW ) {       // check key PIN LEVEL
     ...
}
```

Ex. Set P20 as a PWM output

```
CPwm::period(0.02);     // set globel PWM period time to 20ms
CPwm servo(PWM1);       // connect servo object to PWM1 (P20)
servo.enable();         // enable the servo PWM to output
servo.dutyCycle(0.8);   // set servo duty-cycle to 80%
servo = 0.005;          // set servo PWM period to 5ms
```

Multi-Thread

uCXpresso.BLE framework also base on an advanced Real-Time operating system (RTOS) that called the FreeRTOS. The multi thread will simplify your design, coding and maintenance.

Final,

let uCXpresso.BLE C++ Framework to shorten the developer's time , improves the qualities and enjoys the development.

1. Upgrade Your LPCXpresso IDE

1.1. Increase VM memory for Windows System

a. Close LPCXpesso if executing.

b. Open c:/nxp/LPCXpresso_x.x/lpcxpresso/lpcxpresso.ini

c. Modify MaxPermSize to 512

1.2 Install new software (Eclipse Plug-in)

LPCXpresso Main Menu > Help > Install New Software…

Click [Add]



1.3 Install Eclipse Plug-In

Name: Eclipse Juno

Location: http://download.eclipse.org/releases/juno



In General Purpose Tools section, select “Marketplace Client”



In Mobile and Device Development section, select “Target Management Terminal”



Click [Next] to start the installation. In progress, you need to [Confirm >] the Selected Features, and [accept] the licenses of software, and click [OK] to confirm any security-warning message, click [Yes] to restart and finish the installation if need.



1.4. Install RXTX Plug-in

Name: RXTX

Location: http://archive.eclipse.org/tm/updates/rxtx/



Select latest version “RXTX End-User Runtime”



Click [Next] to start the installation.

Remark:

For Mac OS/X user, you have to follow below steps to enable the USB CDC virtual COM. Port:

1. Open Terminal App of OS/X
2. Type :

   sudo mkdir /var/lock

   sudo chmod a+rw /var/lock

In Windows System, The USB CDC driver can be download from below link:

for NANO11Uxx : http://www.embeda.com.tw/tw/wp-content/uploads/2014/01/nano11Uxx_usb_driver.zip (unzip and copy INF file to desktop, and USBCOM port driver direct to the INF file.)

1.5. Install new software from Eclipse Marketplace

Click LPCXpresso Main Menu > Help > Marketplace…



1.6 Install Subversion – SVN Team Provider (Plug-in)

In Find, input “SVN” and click [Go]



Click [Install] to start the installation. In progress, you need to [Confirm >] the Selected Features, and [accept] the licenses of software, and click [OK] to confirm any security-warning message. Click [Yes] to restart and finish the installation if need.



After restart, you may need to install the SVN connector kit:



Select the latest version “SVN Kit x.x.x”, and click [Finish] to start the installation. Confirm and click [Next], and [accept] the licenses of software, and click [OK] to confirm any security-warning message. Click [Yes] to restart and finish the installation if need.

1-7. Show the SVN and Terminal Views

Click LPCXpresso Main Menu > Window > Show View > Other…



Select the “SVN Repositories” and “Terminal”, click [OK]

Move the “SVN Repositories” Tab to “Project Explorer” right side (optional)



2. Install uCXpresso.BLE Framework

2.1 Using GitHub Repositories

In “SVN Repositories” Tab, Click “New Repository Location”,



and URL Input: https://github.com/ucxpresso/nano11uxx

2.2 Check Out uCXpresso.BLE framework

Expand the uCXpresso.BLE SVN repository



trunk: uCXpresso.BLE RC version

branches: All released version

Select “uCXpresso.BLE” folder, and click right button of mouse, and click “Check Out” in drop down menu.

The uCXpresso.BLE framework show in your workspace after check out.



2.3 Check Out example “blinkLED”

In SVN Repositories Tab, select the “blinkLED” folder in “/examples”, then Check Out it.



2.4 Build the "blinkLED" example project

1. Click "blinkLED" Project on Project Explorer View.
2. Click "Console" View
3. Click "Build 'blinkLED' [Debug] on Quick Start View.



In Console View, the compiler will create a "blinkLED.bin" image file.



Note:

code size = text + data = 25292 bytes

ram size = data + bss = 7288 bytes

3. Download Image File

3.1 Erase Flash Code Memory

First, you need to erase the flash memory for new binary image. Click the "ISP" button on the nano11U37-BLE. In Finder (or File Manager) will creates an USB Disk and called "nanoFLASH"



Remove the "firmware.bin" and move to trash.

Note:

In ISP (bootloader) mode: The LED1, LED2, LED3 and LED4 are blink together.

3.2 Program Flash Code Memory

Copy the “blinkLED.bin” from “blinkLED\Debug” folder to nanoFLASH



Eject the “nanoFLASH” disk and click the “ISP” button of NANO11U37-BLE again to execute your binary code. (In App Mode)

Note:



The “ISP” button.

4. Serial Terminal & Debug

4.1 Serial Terminal (Use USB CDC Virtual COM. Port)

In main.cpp of blinkLED, the usbCDC will be enabled.



In Terminal View, click “New Terminal Connection” to add a new connection.



In Terminal Settings:

1. View Title: NANO11U37-BLE

2. Connection Type: Serial

3. Port : /dev/tty.usbmodemABC1 (for Mac OS/X)



The blinkLED serial shell will run in the Terminal View





Command:

ver, to show the kernel & module version.

heap, to check the available size of heap memory.

task, to check all of tasks in the system.

debug, to enter to debug mode to view the DBG(…) message from user's program.

4.2 Debug

Add 'key' object in main.cpp of blinkLED project.



And add the key check in while loop.

Build Debug and download blinkLED.bin to nanoFLASH, then execute it.

In Terminal View, input 'debug' command to enter the debug mode:



Try to push the key (pin 18) to LOW, and you can see the debug message to show in the terminal view.

4.3 Made an invalidly debug message code.

Made an invalidly debug message code in [Release Build]



Using the #ifdef DEBUG to block and define the DBG to dbg_printf, and #else to block and define the DBG(...) to nothing.

Rename dbg.printf(...) to DBG(...) in your program



Now, The DBG(...) message code will be create in the [Debug Build] only, not in the [Release Build].

5. Create A New Project

5.1 Check Out the “new_project” template

In SVN Repositories View, Expand the three and “Check Out” the “new_project” to workspace.



The “new_project” will show in workspace after Check Out.



Rename the “new_project” to new project name what you want.



For example to rename to “blink” as below,



An empty project “blink” is in the workspace.



Expand the ‘src’ folder of ‘blink’ project, and start to program your main.cpp.

6. Example ble_multiple Project

The ble_multiple project included:

1. Tickless Power Save Feature
2. BLE Arduino Firmata Test
3. BLE Battery Level Service
4. BLE Heath Thermometer Service
5. BLE Proximity Service



iOS App : BLE Arduino

https://itunes.apple.com/tw/app/ble-arduino/id547628998

Youtube Firmata Demo: http://youtu.be/7v7_mqfynRA

7. Class Manual

6.1 Online Class Manual

https://rawgithub.com/ucxpresso/nano11uxx/master/uCXpresso.BLE/doc/doxygen/html/index.html