



FLUXX

Geographic Focus Breadcrumbs via API

Table of Contents

Overview 3

Fetch a Geo Place Relationship Record..... 4

Fetch a Geo Place Record 6

Fetch a Geo Place (breadcrumb) Record 7

Overview

This article will cover how to retrieve the Geographic Focus' Breadcrumbs from the via the API.

To retrieve the breadcrumb data, you will have to first call the `geo_place_relationship` table, this will allow you the select which breadcrumb you would like to use (if you have multiple). Once the breadcrumb is selected you will need to call the `geo_place` table for each object in the ancestry (aka breadcrumb).

Fetch a Geo Place Relationship Record

Parameters

- Filter
 - Parses data based on query.
- Relation
 - Specifies related fields that should be returned.
- Cols
 - Specifies a list of fields that should be returned.

Required Fields

- geo_place_relationship
- geoplaceable_id

These required fields are for the filter parameter.

Example API Call

```
curl --globoff 'https://<--client site-->/api/rest/v2/geo_place_relationship?filter[geo_place_relationship][geoplaceable_id]=<--request id-->&cols=["geo_place_id","geoplaceable_id","geoplaceable_type"]' --header 'Authorization: Bearer <--token-->'
```

Returned Payload

```
{
  "records": {
    "geo_place_relationship": [
      {
        "id": 282378,
        "geo_place_id": 2009999,
        "geoplaceable_id": 21490683,
        "geoplaceable_type": "GrantRequest"
      },
      {
        "id": 282379,
        "geo_place_id": 1088127,
        "geoplaceable_id": 21490683,
        "geoplaceable_type": "GrantRequest"
      }
    ]
  },
  "total_pages": 1,
  "total_entries": 2,
  "current_page": 1,
}
```

```
"per_page": 25  
}
```

Fetch a Geo Place Record

Parameters

- Cols
 - Specifies a list of fields that should be returned.

Example API Call

```
curl --globoff 'https://<--client site-->/api/rest/v2/geo_place/<--geo place id-->?cols=["name","ancestry"]' --header 'Authorization: Bearer <--token-->'
```

Returned Payload

```
{
  "geo_place": {
    "id": 1088127,
    "name": "Bubanza",
    "ancestry": "1000000/7001242/7100025/7001630"
  }
}
```

Fetch a Geo Place (breadcrumb) Record

Parameters

- Cols
 - Specifies a list of fields that should be returned.

Example API Call

```
curl --globoff 'https://<--client site-->/api/rest/v2/geo_place/<--ancestry id-->?cols=["name","ancestry"]' --header 'Authorization: Bearer <--token-->'
```

Returned Payload

```
{
  "geo_place": {
    "id": 7001630,
    "name": "Burundi",
    "ancestry": "1000000/7001242/7100025"
  }
}
```
