



FLUXX

Select Field Values via API

Table of Contents

Overview 3

Create Value..... 4

Create Sub Value 5

Update Value 6



Overview

This article will cover how to create, and update values in a select field via the API.

This article assumes you already have a select field created in Fluxx.

Create Value

Parameters

- Data
 - Passes in data into the value.
- Cols
 - Specifies a list of fields that should be returned.

Required Fields

- model_attribute_id
 - This ID of the select field.
- value
 - Name of the value.
- description
 - Description of the value.

This is typically the same as value.

Example API Call

```
curl --globoff -X POST "<your Fluxx site>/api/rest/v2/model_attribute_value" -F  
'data={"model_attribute_id":59242,"value":"Fluxx Test","description":"Fluxx Test Description"}' -F  
'cols=["value","description"]' --header 'Authorization: Bearer <--token-->'
```

Returned Payload

```
{  
  "model_attribute_value": {  
    "id": 9962642,  
    "description": "Fluxx Test Description",  
    "value": "Fluxx Test"  
  }  
}
```

Create Sub Value

Parameters

- Data
 - Passes in data into the value.
- Cols
 - Specifies a list of fields that should be returned.

Required Fields

- model_attribute_id
 - This ID of the select field.
- dependent_model_attribute_value_id
 - This is the id of the parent value.
- value
 - Name of the value.
- description
 - Description of the value.

This is typically the same as value.

Example API Call

```
curl --globoff -X POST "<your Fluxx site>/api/rest/v2/model_attribute_value" -F
'data={"model_attribute_id":59242,"value":"Sub Fluxx Test","description":"Sub Fluxx Test
Description","dependent_model_attribute_value_id":9962642}' -F
'cols=["value","description","dependent_model_attribute_value_id"]' --header 'Authorization: Bearer <-
-token-->'
```

Returned Payload

```
{
  "model_attribute_value": {
    "id": 9962644,
    "description": "Sub Fluxx Test Description",
    "value": "Sub Fluxx Test",
    "dependent_model_attribute_value_id": 9962642
  }
}
```

Update Value

Parameters

- Data
 - Updates the data in the value.
- Cols
 - Specifies a list of fields that should be returned.

The same call can be made for sub-values. This is because all values are stored in the `model_attribute_values` table.

Example API Call

```
curl --globoff -X PUT "<your Fluxx site>/api/rest/v2/model_attribute_value/9962642" -F 'data={"value":"Fluxx Updated Value"}' -F 'cols=["value","description"]' --header 'Authorization: Bearer <--token-->'
```

Returned Payload

```
{
  "model_attribute_value": {
    "id": 9962642,
    "description": "Fluxx Test Description",
    "value": "Fluxx Updated Value"
  }
}
```
