

Open API

Merchant integration specification — users, assets, purchases, redemptions, wallet

Version	1.0
Date	September 3, 2026
Auth	x-api-key on every request
Operations	29 HTTP operations

Base URL

```
https://open-api.rocket-loyalty.com/functions/v1
```

Strictly private & confidential. For the merchant named on the covering email or agreement. Do not redistribute. Examples use placeholder identifiers — substitute your own user, reward, SKU, and API key values.

How to call the API

Mint a key in Rocket Loyalty admin: **Settings** → **API Keys**. Send JSON on POST/PATCH.

```
curl 'https://open-api.rocket-loyalty.com/functions/v1/api-users/by-tel/%2B66812345678' \
--header 'x-api-key: YOUR_API_KEY'
```

Success bodies are `{ "success": true, "data": { ... }, "meta": { "request_id", "response_time_ms" } }`.

Failures use `success: false` plus `code` / `error` (see Error Codes).

Not in v1: absolute points or ticket balance SET; store-credit / Shopify credit ticket types; ticket-type catalog create/list; public purchase-cancel.

Endpoint index

Lookup aliases (email, phone, LINE, serial, ...) are listed as separate paths.

Method	Path	Summary
POST	/api-users	Create or update user
GET	/api-users/{identifier}	Get user by user_id
PATCH	/api-users/{identifier}	Update user by user_id
GET	/api-users/by-external-id/{value}	Get user by external_user_id
PATCH	/api-users/by-external-id/{value}	Update user by external_user_id
GET	/api-users/by-email/{value}	Get user by email
PATCH	/api-users/by-email/{value}	Update user by email
GET	/api-users/by-tel/{value}	Get user by tel
PATCH	/api-users/by-tel/{value}	Update user by tel
GET	/api-users/by-line-id/{value}	Get user by line id
PATCH	/api-users/by-line-id/{value}	Update user by line id
POST	/api-assets	Create or update asset
GET	/api-assets/{identifier}	Get asset
PATCH	/api-assets/{identifier}	Update asset

Method	Path	Summary
GET	/api-assets/by-external-id/{value}	Get asset by external id
PATCH	/api-assets/by-external-id/{value}	Update asset by external id
GET	/api-assets/by-asset-code/{value}	Get asset by asset code
PATCH	/api-assets/by-asset-code/{value}	Update asset by asset code
GET	/api-assets/by-serial-number/{value}	Get asset by serial number
PATCH	/api-assets/by-serial-number/{value}	Update asset by serial number
POST	/api-purchases	Create purchase
GET	/api-purchases/{transaction_number}	Get purchase
PATCH	/api-purchases/{transaction_number}	Update purchase
POST	/api-redemptions	Redeem reward with points
GET	/api-redemptions/{redemption_code}	Get redemption
POST	/api-redemptions/{redemption_code}/cancel	Cancel redemption
POST	/api-redemptions/{redemption_code}/mark-used	Mark redemption used
POST	/api-wallet/transactions	Post points or ticket earn or burn ledger delta
GET	/api-wallet/transactions	List wallet ledger history

1. Authentication with API Key

All API requests require authentication using the `x-api-key` header.

Item	Value
Base URL	<code>https://open-api.rocket-loyalty.com/functions/v1</code>
Auth Method	Custom API Key Header

Item	Value
Header	x-api-key: {your-api-key}
Expiration	None — API keys remain valid until revoked

Generate API keys in the Rocket Loyalty admin dashboard under **Settings** → **API Keys**.

2. Create or Update User

Create new users or update existing users in the Rocket Loyalty system.

Item	Value
Method	POST
URI	/api-users
Content-Type	application/json

Request Data Model

Basic Information

Field	Required	Type	Remark
tel	Mandatory	String	Phone number. Accepts both 0812345678 and +66812345678 format; system auto-normalizes to +66 E.164.
fullname	Mandatory	String	Full name
firstname	Optional	String	First name
lastname	Optional	String	Last name
email	Optional	String	Email address
line_id	Optional	String	LINE messenger ID
id_card	Optional	String	National ID card number
birth_date	Optional	Date	Format: YYYY-MM-DD (e.g. 1990-01-15)

External Integration

Field	Required	Type	Remark
external_user_id	Optional	String	Partner external user ID

User Classification

Field	Required	Type	Remark
user_type	Optional	String	Default: buyer . Options: buyer , seller
user_stage	Optional	String	Customer lifecycle stage. Options: lead , account , prospect , customer , churned

Communication Preferences

Field	Required	Type	Remark
channel_email	Optional	Boolean	Default: true
channel_sms	Optional	Boolean	Default: false
channel_line	Optional	Boolean	Default: true
channel_push	Optional	Boolean	Default: true

Address & Custom Fields

Field	Required	Type	Remark
addresses	Optional	Array	User addresses (see structure below)
address_mode	Optional	String	Default: replace . Options: replace , add
form_submissions	Optional	Array	Custom profile fields like brand_interest (see structure below)
upsert	Optional	Boolean	Default: false . If true , updates existing user; if false , errors if user exists

addresses Array Structure

Field	Type
address_line_1	String
address_line_2	String
state	String
city	String
district	String
subdistrict	String
postcode	String

form_submissions Array Structure

Field	Required	Type	Remark
form_template_code	Mandatory	String	Must be USER_PROFILE for brand interest
submission_mode	Optional	String	Default: create . Options: create , update
form_data	Mandatory	Object	Field key-value pairs (see below)

Available form_data Fields:

Field Key	Type	Options	Remark
brand_interest	Array	luxury , sports , electronics , fashion , home	Multi-select brand preferences

Example Request — Create Lead with Brand Interest

```
{
  "tel": "+66863210111",
  "fullname": "John Smith",
  "email": "john.smith@example.com",
  "external_user_id": "001BW00000B3Ait",
  "user_stage": "lead",
  "form_submissions": [
    {
      "form_template_code": "USER_PROFILE",
      "submission_mode": "create",
      "form_data": {
        "brand_interest": ["luxury", "fashion"]
      }
    }
  ]
}
```

Example Request — Create Account Customer

```
{
  "tel": "+66812345678",
  "fullname": "Jane Doe",
  "firstname": "Jane",
  "lastname": "Doe",
  "email": "jane.doe@example.com",
  "external_user_id": "EXT_USER_002",
  "birth_date": "1985-03-15",
  "user_stage": "account",
  "channel_email": true,
  "channel_sms": true,
  "addresses": [
    {
      "address_line_1": "123 Sukhumvit Road",
      "city": "Bangkok",
      "district": "Khlong Toei",
      "postcode": "10110"
    }
  ],
  "form_submissions": [
    {
      "form_template_code": "USER_PROFILE",
      "submission_mode": "create",
      "form_data": {
        "brand_interest": ["electronics", "sports", "home"]
      }
    }
  ],
  "upsert": true
}
```

Example Response — 201 Created (or 200 if upsert updated)

```
{
  "success": true,
  "data": {
    "success": true,
    "user_id": "0815c8fc-10f7-4181-8bf9-4db14e48598f",
    "external_user_id": "EXT_USER_002",
    "created": true,
    "updated": false,
    "addresses_added": 1,
    "addresses_deleted": 0,
    "form_submissions_created": 1,
    "form_submissions_updated": 0
  },
  "meta": {
    "request_id": "req_user001",
    "response_time_ms": 189
  }
}
```

Example Response — 409 User Already Exists (when `upsert=false`)

```
{
  "success": false,
  "error": "User already exists",
  "code": "USER_EXISTS",
  "details": "User with tel '+66812345678' already exists. Use upsert=true to update.",
  "request_id": "req_user002"
}
```

Example curl

```
curl --location 'https://open-api.rocket-loyalty.com/functions/v1/api-users' \
--header 'Content-Type: application/json' \
--header 'x-api-key: YOUR_API_KEY_HERE' \
--data '{
  "tel": "+66812345678",
  "fullname": "Jane Doe",
  "firstname": "Jane",
  "lastname": "Doe",
  "email": "jane.doe@example.com",
  "external_user_id": "EXT_USER_002",
  "birth_date": "1985-03-15",
  "user_stage": "account",
  "addresses": [
    {
      "address_line_1": "123 Sukhumvit Road",
      "city": "Bangkok",
      "postcode": "10110"
    }
  ],
  "form_submissions": [
    {
      "form_template_code": "USER_PROFILE",
      "submission_mode": "create",
      "form_data": {
        "brand_interest": ["electronics", "sports", "home"]
      }
    }
  ],
  "upsert": true
}'
```

3. Update User Details

Update existing user information. All fields are **OPTIONAL** — only provide fields you want to update.

Item	Value
Method	PATCH
Content-Type	application/json

URI Options:

URI	Lookup by
/api-users/by-external-id/{external_user_id}	External user ID
/api-users/by-email/{email}	Email address
/api-users/by-tel/{phone}	Phone number
/api-users/by-line-id/{line_id}	LINE ID
/api-users/{user_id}	UUID

Request Data Model

Field	Type	Remark
fullname	String	Full name
firstname	String	First name
lastname	String	Last name
email	String	Email address
tel	String	Phone number
line_id	String	LINE messenger ID
id_card	String	National ID card
birth_date	Date	Format: YYYY-MM-DD
user_stage	String	Customer lifecycle stage
channel_email	Boolean	Email preference
channel_sms	Boolean	SMS preference
channel_line	Boolean	LINE preference
channel_push	Boolean	Push notification preference
addresses	Array	User addresses
address_mode	String	replace or add
form_submissions	Array	Update custom fields like brand_interest

Example — Update User Stage (Lead → Account)

```
{
  "user_stage": "account"
}
```

Example — Update Brand Interest

```
{
  "form_submissions": [
    {
      "form_template_code": "USER_PROFILE",
      "submission_mode": "update",
      "form_data": {
        "brand_interest": ["luxury", "electronics"]
      }
    }
  ]
}
```

Example — Update Multiple Fields

```
{
  "email": "newemail@example.com",
  "user_stage": "account",
  "form_submissions": [
    {
      "form_template_code": "USER_PROFILE",
      "submission_mode": "update",
      "form_data": {
        "brand_interest": ["sports", "fashion"]
      }
    }
  ]
}
```

Example Response — 200 Success

```
{
  "success": true,
  "data": {
    "success": true,
    "user_id": "0815c8fc-10f7-4181-8bf9-4db14e48598f",
    "updated_fields": ["user_stage", "form_submissions"],
    "addresses_added": 0,
    "addresses_deleted": 0,
    "form_submissions_created": 0,
    "form_submissions_updated": 1
  },
  "meta": {
    "request_id": "req_update_user001",
    "response_time_ms": 145
  }
}
```

Example Response — 404 User Not Found

```
{
  "success": false,
  "error": "User not found",
  "code": "USER_NOT_FOUND",
  "details": "No user found with external_user_id 'EXT_USER_999'",
  "request_id": "req_update_user002"
}
```

Example curl — Update by External ID

```
curl --location --request PATCH \
  'https://open-api.rocket-loyalty.com/functions/v1/api-users/by-external-id/EXT_USER_002' \
--header 'Content-Type: application/json' \
--header 'x-api-key: YOUR_API_KEY_HERE' \
--data '{
  "user_stage": "account",
  "form_submissions": [
    {
      "form_template_code": "USER_PROFILE",
      "submission_mode": "update",
      "form_data": {
        "brand_interest": ["luxury", "electronics"]
      }
    }
  ]
}'
```

Example curl — Update by Phone

```
curl --location --request PATCH \
  'https://open-api.rocket-loyalty.com/functions/v1/api-users/by-tel/%2B66812345678' \
--header 'Content-Type: application/json' \
--header 'x-api-key: YOUR_API_KEY_HERE' \
--data '{
  "user_stage": "account"
}'
```

4. Retrieve User Information

Retrieve user profile details including custom fields, member status, and cache-backed tier progress.

Item	Value
Method	GET

URI Options: (same as Update User)

URI	Lookup by
/api-users/by-external-id/{external_user_id}	External user ID
/api-users/by-email/{email}	Email address
/api-users/by-tel/{phone}	Phone number
/api-users/by-line-id/{line_id}	LINE ID
/api-users/{user_id}	UUID

Query parameters

Parameter	Default	Description
<code>include_tier</code>	<code>true</code>	When <code>false</code> , omits <code>member_status</code> and <code>tier</code> (legacy slim payload).
<code>include</code>	—	Comma-separated includes; must contain <code>tier</code> to return tier fields when using this param instead of <code>include_tier</code> .

Tier **progress** (`tier.progress`) is read from the `tier_progress` cache only — no live recompute on request.

Member status mapping

<code>member_status</code>	Meaning
<code>active</code>	Not frozen; <code>is_active</code> is true or null
<code>suspended</code>	<code>is_freeze</code> is true
<code>inactive</code>	<code>is_active</code> is false and not frozen

Soft-deleted members return `404 USER_NOT_FOUND`.

Response fields (tier block)

Field	Type	Description
<code>member_status</code>	string	<code>active</code> , <code>inactive</code> , or <code>suspended</code>
<code>tier</code>	object null	Null when user has no tier assignment
<code>tier.tier_id</code>	uuid	Current tier ID
<code>tier.tier_code</code>	uuid	Canonical tier code (same as <code>tier_id</code>)
<code>tier.tier_name</code>	string	Display name
<code>tier.effective_at</code>	timestampz	When current tier was achieved (ISO 8601 UTC)
<code>tier.current_tier_thres hold.metric</code>	string	<code>points</code> , <code>sales</code> , <code>orders</code> , or <code>ticket</code>
<code>tier.current_tier_thres hold.amount</code>	number	Threshold for current tier
<code>tier.progress</code>	object omitted	Omitted when no cache row or user is at top tier
<code>tier.progress.current_a mount</code>	number	Cached progress toward next tier
<code>tier.progress.percent</code>	number	Progress percent toward next tier
<code>tier.progress.next_tier _id</code>	uuid	Next tier ID
<code>tier.progress.next_tier _name</code>	string	Next tier display name

Field	Type	Description
tier.progress.next_tier_threshold_amount	number	Points/spend required for next tier

Example Request

GET https://open-api.rocket-loyalty.com/functions/v1/api-users/by-tel/+66812345678

Example Response

```
{
  "success": true,
  "data": {
    "user": {
      "user_id": "0815c8fc-10f7-4181-8bf9-4db14e48598f",
      "external_user_id": "EXT_USER_002",
      "fullname": "Jane Doe",
      "firstname": "Jane",
      "lastname": "Doe",
      "email": "jane.doe@example.com",
      "tel": "+66812345678",
      "line_id": null,
      "birth_date": "1985-03-15",
      "user_type": "buyer",
      "user_stage": "account",
      "member_status": "active",
      "tier_id": "uuid",
      "persona_id": null,
      "points_balance": 1250,
      "tier": {
        "tier_id": "uuid",
        "tier_code": "uuid",
        "tier_name": "Gold",
        "effective_at": "2025-06-01T00:00:00+00:00",
        "current_tier_threshold": {
          "metric": "points",
          "amount": 5000
        },
        "progress": {
          "metric": "points",
          "current_amount": 1250,
          "percent": 25.0,
          "next_tier_id": "uuid",
          "next_tier_name": "Platinum",
          "next_tier_threshold_amount": 10000
        }
      },
      "ticket_balances": [],
      "channel_email": true,
      "channel_sms": false,
      "channel_line": true,
      "channel_push": true,
      "addresses": [
        {
          "address_line_1": "123 Sukhumvit Road",
          "city": "Bangkok",
          "district": "Khlong Toei",
          "postcode": "10110"
        }
      ],
      "custom_fields": {
        "brand_interest": ["luxury", "fashion"]
      }
    }
  },
  "meta": {
    "request_id": "req_getuser001",
    "response_time_ms": 67
  }
}
```

When the user has no tier program assignment, `tier` is `null`. When assigned but no cache row exists yet, `tier` includes identity/threshold fields and `progress` is omitted.

Example curl

```
curl --location \
'https://open-api.rocket-loyalty.com/functions/v1/api-users/by-tel/%2B66812345678' \
--header 'x-api-key: YOUR_API_KEY_HERE'
```

Legacy slim payload (no tier block):

```
curl --location \
'https://open-api.rocket-loyalty.com/functions/v1/api-users/by-external-id/EXT_USER_002?
include_tier=false' \
--header 'x-api-key: YOUR_API_KEY_HERE'
```

5. Create Asset

Create new Assets in the Rocket Loyalty system.

Item	Value
Method	POST
URI	/api-assets
Content-Type	application/json

Request Data Model

Core Fields

Field	Required	Type	Remark
asset_type_code	Mandatory	String	Must be ASSET
name	Mandatory	String	Asset name
external_id	Optional	String	Partner external asset ID (unique)
serial_number	Optional	String	Equipment serial number
status	Optional	String	e.g. Purchased , Installed
purchase_date	Optional	Date	Format: YYYY-MM-DD
install_date	Optional	Date	Format: YYYY-MM-DD
external_user_id	Optional	String	External user ID or phone number
user_id	Optional	UUID	Internal user ID
sku_code	Optional	String	Product SKU code

Field	Required	Type	Remark
purchase_transaction_number	Optional	String	Related purchase transaction
upsert	Optional	Boolean	If <code>true</code> , updates existing asset; if <code>false</code> , errors if exists
custom_fields	Optional	Object	Merchant-defined custom fields (see examples below)

Example custom fields for ASSET type

Warranty & Usage:

Field	Type	Remark
warrantyPeriodTechnogym	Number	Warranty period in months
warrantyPeriodExtended	Number	Extended warranty period in months (example)
usageEndDate	Date	Format: YYYY-MM-DD

Product Information:

Field	Type	Remark
productName	String	Product display name
productCode	String	Partner product code (example)
product2Id	String	Partner product ID (example)
articleNumber	String	Article number

Optional CRM / ERP integration keys (examples):

Field	Type	Remark
salesOrder	String	Sales order number
recordTypeId	String	Partner record type (example)
quantity	Number	Quantity purchased
project	String	Partner project ID (example)
opportunity	String	Partner opportunity ID (example)
opportunityProduct	String	Partner opportunity product ID (example)
accountId	String	Partner account ID (example)
contactId	String	Partner contact ID (example)
parentId	String	Parent asset ID

Delivery Order:

Field	Type	Remark
doNumber	String	Delivery order number
doDate	Date	Format: YYYY-MM-DD
cnNumber	String	Credit note number

Financial & Classification:

Field	Type	Remark
price	Number	Asset price
category	String	Asset category
brand	String	Brand name
location	String	Physical location
tags	String	Classification tags
notes	String	Additional notes
description	String	Asset description

Example Request

```
{
  "asset_type_code": "ASSET",
  "name": "EXCITE LIVE CLIMB LIVE 700 METEOR BLACK",
  "external_id": "02iBW000000f6QYAQA",
  "serial_number": "1234",
  "status": "Purchased",
  "purchase_date": "2023-08-06",
  "external_user_id": "001BW00000B3Ait",
  "upsert": false,
  "custom_fields": {
    "warrantyPeriodTechnogym": null,
    "warrantyPeriodExtended": 24,
    "usageEndDate": null,
    "productName": "EXCITE LIVE CLIMB LIVE 700 METEOR BLACK",
    "productCode": "D-T01-CD03-DFEG3A10AN00EA2S",
    "product2Id": "01tBW0000001vMdYAI",
    "articleNumber": "D-T01-CD03-DFEG3A10AN00EA2S",
    "salesOrder": "233100523",
    "recordTypeId": "0126F000001WxVgQAK",
    "quantity": 1,
    "project": "a0iBW000000AOp3YAG",
    "opportunity": "006BW000006jxy9YAA",
    "opportunityProduct": "00kBW00000091ksYAA",
    "accountId": "001BW00000B3Ait",
    "contactId": null,
    "parentId": null,
    "doNumber": null,
    "doDate": null,
    "cnNumber": null,
    "price": 355300,
    "category": "Fitness Equipment",
    "brand": "Technogym",
    "location": "Warehouse A",
    "tags": null,
    "notes": null,
    "description": null
  }
}
```

Example Response — 200 Success

```
{
  "success": true,
  "data": {
    "asset_id": "7366abf1-59a3-4a57-b55e-8dc845213047",
    "external_id": "02iBW000000f6QYAQA",
    "name": "EXCITE LIVE CLIMB LIVE 700 METEOR BLACK",
    "serial_number": "1234",
    "status": "Purchased",
    "purchase_date": "2023-08-06",
    "custom_fields": { "... " }
  },
  "meta": {
    "request_id": "req_abc123",
    "response_time_ms": 145
  }
}
```

Example Response — 409 Asset Already Exists (when `upsert=false`)

```
{
  "success": false,
  "error": "Asset already exists",
  "code": "ASSET_EXISTS",
  "details": "Asset with external_id '02iBW0000000f6QYAQA' already exists. Use upsert=true to update.",
  "request_id": "req_abc124"
}
```

Example curl

```
curl --location 'https://open-api.rocket-loyalty.com/functions/v1/api-assets' \
--header 'Content-Type: application/json' \
--header 'x-api-key: YOUR_API_KEY_HERE' \
--data '{
  "asset_type_code": "ASSET",
  "name": "EXCITE LIVE CLIMB LIVE 700 METEOR BLACK",
  "external_id": "02iBW0000000f6QYAQA",
  "serial_number": "1234",
  "status": "Purchased",
  "purchase_date": "2023-08-06",
  "external_user_id": "001BW00000B3Ait",
  "custom_fields": {
    "warrantyPeriodExtended": 24,
    "productName": "EXCITE LIVE CLIMB LIVE 700 METEOR BLACK",
    "productCode": "D-T01-CD03-DFEG3A10AN00EA2S",
    "salesOrder": "233100523",
    "price": 355300,
    "category": "Fitness Equipment",
    "brand": "Technogym",
    "location": "Warehouse A"
  }
}'
```

6. Update Existing Asset

Update existing asset information. All fields are **OPTIONAL**.

Item	Value
Method	PATCH
URI	/api-assets/by-external-id/{external_id}
Content-Type	application/json

Alternative URIs:

- /api-assets/by-serial-number/{serial_number}
- /api-assets/by-asset-code/{asset_code}
- /api-assets/{asset_id} (UUID)

Request Data Model

Field	Type	Remark
name	String	Asset name
status	String	Asset status
purchase_date	Date	Format: YYYY-MM-DD
install_date	Date	Format: YYYY-MM-DD
serial_number	String	Equipment serial number
custom_fields	Object	Merges with existing custom fields (same 26 fields as create)

Important: Custom fields are **merged**, not replaced. To update specific fields, only include those fields in the `custom_fields` object.

Example Request

```
{
  "status": "Installed",
  "install_date": "2024-10-20",
  "custom_fields": {
    "location": "Gym Floor 3",
    "warrantyPeriodExtended": 36,
    "price": 400000
  }
}
```

Example Response — 200 Success

```
{
  "success": true,
  "data": {
    "asset_id": "7366abf1-59a3-4a57-b55e-8dc845213047",
    "external_id": "02iBW0000000f6QYAQA",
    "name": "EXCITE LIVE CLIMB LIVE 700 METEOR BLACK",
    "serial_number": "1234",
    "status": "Installed",
    "purchase_date": "2023-08-06",
    "install_date": "2024-10-20",
    "custom_fields": {
      "warrantyPeriodExtended": 36,
      "price": 400000,
      "location": "Gym Floor 3",
      "productCode": "D-T01-CD03-DFEG3A10AN00EA2S",
      "salesOrder": "233100523",
      "opportunity": "006BW000006jxy9YAA"
    },
    "updated_at": "2024-10-20T14:30:00.000Z"
  },
  "meta": {
    "request_id": "req_xyz789",
    "response_time_ms": 89
  }
}
```

Example Response — 404 Asset Not Found

```
{
  "success": false,
  "error": "Asset not found",
  "code": "ASSET_NOT_FOUND",
  "details": "No asset found with external_id '02iBW0000000f6QYAQA'",
  "request_id": "req_xyz790"
}
```

Example curl

```
curl --location --request PATCH \
  'https://open-api.rocket-loyalty.com/functions/v1/api-assets/by-external-id/02iBW0000000f6QYAQA' \
  --header 'Content-Type: application/json' \
  --header 'x-api-key: YOUR_API_KEY_HERE' \
  --data '{
    "status": "Installed",
    "install_date": "2024-10-20",
    "custom_fields": {
      "location": "Gym Floor 3",
      "warrantyPeriodExtended": 36,
      "price": 400000
    }
  }'
```

7. Create Maintenance Plan

Create new Maintenance Plans in the Rocket Loyalty system.

Item	Value
Method	POST
URI	/api-assets
Content-Type	application/json

Request Data Model

Core Fields

Field	Required	Type	Remark
asset_type_code	Mandatory	String	Must be MAINTENANCE_PLAN
name	Mandatory	String	Maintenance plan name
external_id	Optional	String	Partner external maintenance-plan ID (unique)
status	Optional	String	e.g. Active , Expired
external_user_id	Optional	String	External user / account reference
covered_assets	Optional	Array	Assets covered by this plan (see below)
upsert	Optional	Boolean	If true , updates existing; if false , errors if exists
custom_fields	Optional	Object	All maintenance plan fields (see below)

covered_assets Array Structure

Each covered asset can be identified by **ONE** of:

Field	Type	Remark
asset_id	UUID	Internal asset ID
external_id	String	Partner asset external ID
asset_code	String	Internal asset code
serial_number	String	Equipment serial number

```
"covered_assets": [  
  { "external_id": "02iBW0000000f6QYAQA" },  
  { "serial_number": "SN12345" }  
]
```

Custom Fields for MAINTENANCE_PLAN Type

Plan Identification:

Field	Type	Remark
<code>maintenancePlanNumber</code>	String	Unique plan number (e.g. MP-0411)
<code>maintenancePlanType</code>	String	e.g. Contract , Warranty
<code>maintenancePlanStatus</code>	String	e.g. Active , Expired
<code>maintenancePlanTitle</code>	String	Plan title/headline

Work Type:

Field	Type	Remark
<code>workTypeName</code>	String	e.g. Services Maintenance
<code>workTypeId</code>	String	Partner work type ID (example)

Work Order Configuration:

Field	Type	Remark
<code>workOrderGenerationStatus</code>	String	e.g. NotStarted , InProgress
<code>workOrderGenerationMethod</code>	String	e.g. WorkOrderPerAsset

Schedule & Timing:

Field	Type	Remark
<code>startDate</code>	Date	Format: YYYY-MM-DD
<code>endDate</code>	Date	Format: YYYY-MM-DD
<code>extendDate</code>	Date	Extension date if applicable
<code>frequency</code>	Number	Service frequency number
<code>frequencyType</code>	String	e.g. Months , Days
<code>generationTimeframe</code>	Number	Generation timeframe number
<code>generationTimeframeType</code>	String	e.g. Months
<code>nextSuggestedMaintenanceDate</code>	Date	Format: YYYY-MM-DD

Maintenance Window:

Field	Type	Remark
<code>maintenanceWindowStartDays</code>	Number	Window start in days
<code>maintenanceWindowEndDays</code>	Number	Window end in days

Optional CRM / ERP integration keys (examples):

Field	Type	Remark
serviceContractId	String	Partner service contract ID (example)
salesOrder	String	Sales order number
recordTypeId	String	Partner record type (example)
project	String	Partner project ID (example)
opportunity	String	Partner opportunity ID (example)
accountId	String	Partner account ID (example)
contactId	String	Partner contact ID (example)

Plan Relationships & Configuration:

Field	Type	Remark
parentMaintenancePlan	String	Parent plan ID for hierarchy
asset	String	Direct asset reference
serialNumber	String	Serial number reference
articleNumber	String	Article number
quantity	Number	Quantity value
mpRenewal	Boolean	Renewal flag
approvalStatus	String	e.g. NotRequired , Pending
allAssetInstalled	Boolean	All assets installed flag
activeExpire	String	Active/Expire status
description	String	Plan description

Example Request

```
{
  "asset_type_code": "MAINTENANCE_PLAN",
  "name": "6-Month Service Plan",
  "external_id": "1MPBW0000001Lt4AI",
  "status": "Active",
  "external_user_id": "001BW00000B3Ait",
  "upsert": false,
  "custom_fields": {
    "maintenancePlanNumber": "MP-0411",
    "maintenancePlanType": "Contract",
    "maintenancePlanStatus": "Active",
    "workTypeName": "Services Maintenance",
    "workTypeId": "08qBW000000CFhYAM",
    "workOrderGenerationStatus": "NotStarted",
    "workOrderGenerationMethod": "WorkOrderPerAsset",
    "startDate": "2024-02-22",
    "endDate": "2026-02-22",
    "frequency": 6,
    "frequencyType": "Months",
    "generationTimeframe": 24,
    "generationTimeframeType": "Months",
    "nextSuggestedMaintenanceDate": "2024-08-22",
    "salesOrder": "233100555",
    "recordTypeId": "0126F000001WxIOQA0",
    "project": "a0iBW000000AeaTYAS",
    "opportunity": "006BW000007ZIKbYAO",
    "accountId": "001BW00000B3Ait",
    "quantity": 0,
    "mpRenewal": false,
    "approvalStatus": "NotRequired",
    "allAssetInstalled": false,
    "activeExpire": "Active"
  },
  "covered_assets": [
    { "external_id": "02iBW0000000f6QYAQA" }
  ]
}
```

Example Response — 200 Success

```
{
  "success": true,
  "data": {
    "asset_id": "d83789b7-5ec2-4135-8822-f30afb11997a",
    "external_id": "1MPBW00000001Lt4AI",
    "name": "6-Month Service Plan",
    "status": "Active",
    "asset_type": "MAINTENANCE_PLAN",
    "custom_fields": { "... " },
    "covered_assets": [
      {
        "asset_id": "7366abf1-59a3-4a57-b55e-8dc845213047",
        "external_id": "02iBW0000000f6QYAQA",
        "name": "EXCITE LIVE CLIMB LIVE 700 METEOR BLACK",
        "serial_number": "1234",
        "article_number": "D-T01-CD03-DFEG3A10AN00EA2S"
      }
    ],
    "created_at": "2024-11-06T13:54:00.000Z"
  },
  "meta": {
    "request_id": "req_maint001",
    "response_time_ms": 212
  }
}
```

Example curl

```
curl --location 'https://open-api.rocket-loyalty.com/functions/v1/api-assets' \
--header 'Content-Type: application/json' \
--header 'x-api-key: YOUR_API_KEY_HERE' \
--data '{
  "asset_type_code": "MAINTENANCE_PLAN",
  "name": "6-Month Service Plan",
  "external_id": "1MPBW00000001Lt4AI",
  "status": "Active",
  "external_user_id": "001BW000000B3Ait",
  "custom_fields": { "... " },
  "covered_assets": [
    { "external_id": "02iBW0000000f6QYAQA" }
  ]
}'
```

8. Update Existing Maintenance Plan

Update existing Maintenance Plan details. All fields are **OPTIONAL**.

Item	Value
Method	PATCH
URI	/api-assets/by-external-id/{external_id}
Content-Type	application/json

Alternative URIs:

- /api-assets/by-asset-code/{asset_code}
- /api-assets/{asset_id} (UUID)

Request Data Model

Field	Type	Remark
name	String	Maintenance plan name
status	String	Plan status
custom_fields	Object	Merges with existing — all 35 fields available (see Create API)
covered_assets	Array	Replaces ALL linked assets (not merged)

Important Notes: - Custom fields are **merged** (partial updates supported) - covered_assets array **replaces** the entire relationship (not merged) - To add assets, include both existing and new assets in the array

Example Request

```
{
  "status": "Active",
  "custom_fields": {
    "workTypeName": "Services Maintenance - Updated",
    "maintenancePlanStatus": "Active",
    "nextSuggestedMaintenanceDate": "2024-12-22",
    "frequency": 3,
    "frequencyType": "Months"
  },
  "covered_assets": [
    { "external_id": "02iBW0000000f6QYAQA" },
    { "serial_number": "SN67890" }
  ]
}
```

Example Response — 200 Success

```
{
  "success": true,
  "data": {
    "asset_id": "d83789b7-5ec2-4135-8822-f30afb11997a",
    "external_id": "1MPBW0000001Lt4AI",
    "name": "6-Month Service Plan",
    "status": "Active",
    "asset_type": "MAINTENANCE_PLAN",
    "custom_fields": {
      "maintenancePlanNumber": "MP-0411",
      "workTypeName": "Services Maintenance - Updated",
      "nextSuggestedMaintenanceDate": "2024-12-22",
      "frequency": 3,
      "frequencyType": "Months"
    },
    "covered_assets": [
      {
        "asset_id": "7366abf1-59a3-4a57-b55e-8dc845213047",
        "external_id": "02iBW000000f6QYAQA",
        "name": "EXCITE LIVE CLIMB LIVE 700 METEOR BLACK",
        "serial_number": "1234"
      },
      {
        "asset_id": "8e6f3d06-c405-488f-961a-70bef350d5d5",
        "serial_number": "SN67890",
        "name": "BIKE PRO 500"
      }
    ],
    "updated_at": "2024-11-06T14:15:00.000Z"
  },
  "meta": {
    "request_id": "req_update001",
    "response_time_ms": 156
  }
}
```

Example curl

```
curl --location --request PATCH \
  'https://open-api.rocket-loyalty.com/functions/v1/api-assets/by-external-id/1MPBW0000001Lt4AI' \
  --header 'Content-Type: application/json' \
  --header 'x-api-key: YOUR_API_KEY_HERE' \
  --data '{
    "status": "Active",
    "custom_fields": {
      "workTypeName": "Services Maintenance - Updated",
      "frequency": 3,
      "frequencyType": "Months"
    },
    "covered_assets": [
      { "external_id": "02iBW000000f6QYAQA" },
      { "serial_number": "SN67890" }
    ]
  }'
```

9. Retrieve Asset / Maintenance Plan by ID

Retrieve existing asset or maintenance plan details.

Item	Value
Method	GET

URI Options:

URI	Lookup by
/api-assets/by-external-id/{external_id}	External ID
/api-assets/by-serial-number/{serial_number}	Serial number
/api-assets/by-asset-code/{asset_code}	Internal code
/api-assets/{asset_id}	UUID

Example — Get Asset

GET https://open-api.rocket-loyalty.com/functions/v1/api-assets/by-external-id/02iBW000000f6QYAQA

```
{
  "success": true,
  "data": {
    "asset": {
      "asset_id": "7366abf1-59a3-4a57-b55e-8dc845213047",
      "external_id": "02iBW000000f6QYAQA",
      "name": "EXCITE LIVE CLIMB LIVE 700 METEOR BLACK",
      "serial_number": "1234",
      "status": "Purchased",
      "purchase_date": "2023-08-06",
      "install_date": null,
      "asset_type": "ASSET",
      "user_id": null,
      "external_user_id": "001BW00000B3Ait",
      "custom_fields": { "...": },
      "covered_by_plans": []
    }
  },
  "meta": {
    "request_id": "req_get001",
    "response_time_ms": 78
  }
}
```

Example — Get Maintenance Plan

GET https://open-api.rocket-loyalty.com/functions/v1/api-assets/by-external-id/1MPBW0000001Lt4AI

```
{
  "success": true,
  "data": {
    "asset": {
      "asset_id": "d83789b7-5ec2-4135-8822-f30afb11997a",
      "external_id": "1MPBW0000001Lt4AI",
      "name": "6-Month Service Plan",
      "status": "Active",
      "asset_type": "MAINTENANCE_PLAN",
      "custom_fields": { "..."},
      "covered_assets": [
        {
          "asset_id": "7366abf1-59a3-4a57-b55e-8dc845213047",
          "external_id": "02iBW0000000f6QYAQA",
          "name": "EXCITE LIVE CLIMB LIVE 700 METEOR BLACK",
          "serial_number": "1234",
          "article_number": "D-T01-CD03-DFEG3A10AN00EA2S"
        }
      ]
    }
  },
  "meta": {
    "request_id": "req_get002",
    "response_time_ms": 95
  }
}
```

Example curl

```
curl --location \
'https://open-api.rocket-loyalty.com/functions/v1/api-assets/by-external-id/1MPBW0000001Lt4AI' \
--header 'x-api-key: YOUR_API_KEY_HERE'
```

10. Create Purchase Transaction

Create purchase transactions in the Rocket Loyalty system.

Item	Value
Method	POST
URI	/api-purchases
Content-Type	application/json

Request Data Model

User Identification

Field	Required	Type	Remark
external_user_id	Mandatory*	String	Buyer phone number or Partner contact ID (example)

Field	Required	Type	Remark
user_id	Mandatory*	UUID	Internal user ID (*at least one required)
seller_external_user_id	Optional	String	Seller phone number or ID
seller_user_id	Optional	UUID	Internal seller ID

Transaction Details

Field	Required	Type	Remark
final_amount	Mandatory	Number	Net amount customer pays
total_amount	Optional	Number	Defaults to final_amount
discount_amount	Optional	Number	Default: 0
tax_amount	Optional	Number	Default: 0

Transaction Metadata

Field	Required	Type	Remark
transaction_number	Optional	String	Auto-generated if not provided
transaction_date	Optional	Timestamp	Default: NOW() . Accepts ISO-8601 / timestampz text (date-only YYYY-MM-DD also works). Persisted on POST /api-purchases .
external_ref	Optional	String	External order number (old: external_order_no)
store_code	Optional	String	Store identifier (old: pos_store_code)
api_source	Optional	String	Source system name (partner identifier)

Transaction Control

Field	Required	Type	Remark
status	Optional	String	Default: completed . Options: pending , processing , completed , cancelled , refunded
payment_status	Optional	String	Default: pending
processing_method	Optional	String	Default: queue . Options: queue , direct , skip
earn_currency	Optional	Boolean	Default: true (awards points automatically)
notes	Optional	String	Additional notes

Line Items

Field	Required	Type	Remark
items	Optional	Array	Product line items (see below)

items Array Structure

Field	Required	Type	Remark
sku_code	Mandatory	String	Product variant code (old: variant_code)
quantity	Mandatory	Number	Quantity purchased (old: qty)
unit_price	Mandatory	Number	Price per unit
line_total	Optional	Number	Auto-calculated if not provided (old: net_sale_value)
discount_amount	Optional	Number	Default: 0
tax_amount	Optional	Number	Default: 0

Note: The old system’s variant_name is not required — the system resolves product name from sku_code lookup in product catalog.

Example Request

```
{
  "external_user_id": "+66863210111",
  "seller_external_user_id": "+66812345678",
  "store_code": "store_a1",
  "external_ref": "test_bill",
  "api_source": "partner_system",
  "transaction_date": "2024-08-02",
  "status": "completed",
  "payment_status": "paid",
  "final_amount": 3000,
  "total_amount": 3000,
  "discount_amount": 0,
  "tax_amount": 0,
  "processing_method": "queue",
  "earn_currency": true,
  "items": [
    {
      "sku_code": "12345",
      "quantity": 3,
      "unit_price": 1000,
      "line_total": 3000,
      "discount_amount": 0,
      "tax_amount": 0
    }
  ]
}
```

Example Response — 200 Success

```
{
  "success": true,
  "data": {
    "success": true,
    "transaction_id": "a1b2c3d4-5678-90ab-cdef-1234567890ab",
    "transaction_number": "TXN20241106000001",
    "user_id": "c573479a-fe36-48be-9f6f-a559fffe9016",
    "user_resolved": true,
    "seller_id": null,
    "store_id": null,
    "items_created": 1,
    "unknown_skus": ["12345"],
    "unknown_store": false
  },
  "meta": {
    "request_id": "req_purchase001",
    "response_time_ms": 234
  }
}
```

Note: `unknown_skus` lists any SKU codes not found in the product catalog. The purchase is still created successfully. Currency will be awarded via the configured `processing_method` (default: `queue`, within 60 seconds).

Example Response — 404 User Not Found

```
{
  "success": false,
  "error": "User not found",
  "code": "USER_NOT_FOUND",
  "details": "No user found with external_user_id '+66863210111'. Please create user first via /api-users endpoint.",
  "request_id": "req_purchase002"
}
```

Example curl

```
curl --location 'https://open-api.rocket-loyalty.com/functions/v1/api-purchases' \
--header 'Content-Type: application/json' \
--header 'x-api-key: YOUR_API_KEY_HERE' \
--data '{
  "external_user_id": "+66863210111",
  "seller_external_user_id": "+66812345678",
  "store_code": "store_a1",
  "external_ref": "test_bill",
  "api_source": "partner_system",
  "transaction_date": "2024-08-02",
  "status": "completed",
  "payment_status": "paid",
  "final_amount": 3000,
  "total_amount": 3000,
  "items": [
    {
      "sku_code": "12345",
      "quantity": 3,
      "unit_price": 1000,
      "line_total": 3000
    }
  ]
}'
```

Retrieve or update a purchase

These routes exist on the gateway. There is no public purchase-cancel in v1. Purchase → points earn may be asynchronous; use wallet POST when you need a synchronous credit.

Item	Value
Method	GET
URI	/api-purchases/{transaction_number}
Alt	/api-purchases?transaction_number= or ?transaction_id=

Item	Value
Method	PATCH
URI	/api-purchases/{transaction_number}
Content-Type	application/json

11. Redeem Reward

Redeem a reward for a member using points.

Item	Value
Method	POST

Item	Value
URI	/api-redemptions
Content-Type	application/json

Request Data Model

Field	Required	Type	Remark
user_id	Mandatory*	UUID	Rocket user id (*or resolve via users API first)
reward_id	Mandatory	UUID	Reward to redeem
quantity	Optional	Number	Default: 1

Member must have sufficient points_balance . Purchase earn can be asynchronous — use §13 Post Wallet Transaction when you need a synchronous balance credit before redeem.

Example Request

```
{
  "user_id": "a740f0db-28af-4427-8590-d10126d27452",
  "reward_id": "50efbf36-6b86-4e80-8739-2b5bd940367c",
  "quantity": 1
}
```

Example Response — 200 Success

```
{
  "success": true,
  "data": {
    "success": true,
    "message": "Reward redeemed successfully",
    "details": null,
    "data": {
      "new_balance": 250,
      "total_points_deducted": 150,
      "records_created": 1,
      "redemptions": [
        {
          "qty": 1,
          "reward_id": "50efbf36-6b86-4e80-8739-2b5bd940367c",
          "reward_name": "Example Reward",
          "redemption_id": "2d653ccc-7e4f-400e-9be9-ee6c43c4ede6",
          "redemption_code": "RW5417013002",
          "points_deducted": 150,
          "promo_code": null
        }
      ]
    }
  },
  "meta": {
    "request_id": "...",
    "response_time_ms": 120
  }
}
```

Use `data.data.redemptions[0].redemption_code` for subsequent get / cancel / mark-used calls.

Example curl

```
curl --location 'https://open-api.rocket-loyalty.com/functions/v1/api-redemptions' \
--header 'Content-Type: application/json' \
--header 'x-api-key: YOUR_API_KEY_HERE' \
--data '{
  "user_id": "a740f0db-28af-4427-8590-d10126d27452",
  "reward_id": "50efbf36-6b86-4e80-8739-2b5bd940367c",
  "quantity": 1
}'
```

12. Get / Cancel / Mark-Used Redemption

Get redemption

Item	Value
Method	GET
URI	/api-redemptions/{redemption_code}
Alt	/api-redemptions?redemption_id={uuid}

Mark used

Item	Value
Method	POST
URI	/api-redemptions/{redemption_code}/mark-used

```
{ "notes": "Used at store A" }
```

Cancel

Item	Value
Method	POST
URI	/api-redemptions/{redemption_code}/cancel

```
{ "reason": "Customer cancelled" }
```

Example curl — mark used

```
curl --location --request POST \  
  'https://open-api.rocket-loyalty.com/functions/v1/api-redemptions/RW5417013002/mark-used' \  
--header 'Content-Type: application/json' \  
--header 'x-api-key: YOUR_API_KEY_HERE' \  
--data '{ "notes": "smoke" }'
```

Example curl — cancel

```
curl --location --request POST \  
  'https://open-api.rocket-loyalty.com/functions/v1/api-redemptions/RW5417013002/cancel' \  
--header 'Content-Type: application/json' \  
--header 'x-api-key: YOUR_API_KEY_HERE' \  
--data '{ "reason": "customer request" }'
```

13. Post Wallet Transaction

Post a **points** or **ticket** earn or burn ledger delta. This is not an absolute balance setter.

Item	Value
Method	POST
URI	/api-wallet/transactions
Content-Type	application/json

`currency` defaults to `points`. Points balance remains on `GET /api-users/...` → `points_balance`. Ticket balances are on the same GET as `ticket_balances[]`. Store-credit / Shopify credit ticket types (`is_credit = true`) are rejected.

Request Data Model

User identification (exactly one)

Field	Required	Type	Remark
<code>user_id</code>	One of	UUID	Rocket user id
<code>external_user_id</code>	One of	String	Partner external user id
<code>tel</code>	One of	String	Phone
<code>email</code>	One of	String	Email
<code>line_id</code>	One of	String	LINE id

Transaction

Field	Required	Type	Remark
<code>transaction_type</code>	Mandatory	String	<code>earn</code> or <code>burn</code>
<code>amount</code>	Mandatory	Integer	Positive integer
<code>dedup_key</code>	Mandatory	String	1–200 chars; unique per merchant for a given payload
<code>currency</code>	Optional	String	<code>points</code> (default) or <code>ticket</code>
<code>ticket_type_id</code>	One of when <code>currency=ticket</code>	UUID	Ticket type id for this merchant
<code>ticket_code</code>	One of when <code>currency=ticket</code>	String	Merchant-unique ticket code (alternative to id)
<code>description</code>	Optional	String	Human-readable note
<code>metadata</code>	Optional	Object	Partner metadata; keys beginning with <code>_</code> are reserved

When `currency=ticket`, provide exactly one of `ticket_type_id` or `ticket_code`. Ticket types must be active and non-credit. Earn also requires the type's validity window (if set) to include now.

Ticket writes create **one ledger row per unit**. A post of `amount: 3` writes 3 rows. History lists those unit rows.

Idempotency

- Same `dedup_key` + same payload (including currency and ticket type) → `200` with `already_processed: true` (no second write).
- Same `dedup_key` + different amount/user/type/currency/ticket type → `409 IDEMPOTENCY_CONFLICT`.
- Burn that would make that currency's balance negative → `400 INSUFFICIENT_BALANCE` (hard fail, no partial write).
- Pooled ticket type with too few unassigned codes → `400 INSUFFICIENT_TICKET_POOL`.

Example Request — Earn

```
{
  "external_user_id": "EXT_USER_002",
  "transaction_type": "earn",
  "amount": 100,
  "dedup_key": "partner:order_456:earn",
  "description": "Order 456 loyalty credit",
  "metadata": {
    "order_id": "456"
  }
}
```

Example Response — 201 Created

```
{
  "success": true,
  "data": {
    "success": true,
    "already_processed": false,
    "wallet_ledger_id": "f0d2d7b2-ea73-43a0-b46b-91d1da9a153b",
    "user_id": "a740f0db-28af-4427-8590-d10126d27452",
    "transaction_type": "earn",
    "amount": 100,
    "currency": "points",
    "balance_after": 100,
    "points_balance": 100,
    "dedup_key": "partner:order_456:earn",
    "created_at": "2026-08-05T11:09:56.648809+00:00"
  },
  "meta": {
    "request_id": "...",
    "response_time_ms": 45
  }
}
```

Example Response — 200 Idempotent Replay

Same body as create, with `"already_processed": true` and the original `wallet_ledger_id`.

Example Response — 409 Conflict

```
{
  "success": false,
  "error": "Idempotency key already used with a different payload",
  "code": "IDEMPOTENCY_CONFLICT",
  "dedup_key": "partner:order_456:earn",
  "request_id": "..."
}
```

Example curl

```
curl --location 'https://open-api.rocket-loyalty.com/functions/v1/api-wallet/transactions' \
--header 'Content-Type: application/json' \
--header 'x-api-key: YOUR_API_KEY_HERE' \
--data '{
  "external_user_id": "EXT_USER_002",
  "transaction_type": "earn",
  "amount": 100,
  "dedup_key": "partner:order_456:earn",
  "description": "Order 456 loyalty credit"
}'
```

Example Request — Earn tickets

```
{
  "external_user_id": "EXT_USER_002",
  "transaction_type": "earn",
  "amount": 3,
  "currency": "ticket",
  "ticket_code": "RAFFLE_MAY",
  "dedup_key": "partner:order_456:raffle",
  "description": "Order 456 raffle tickets"
}
```

Example Response — 201 Created (ticket)

```
{
  "success": true,
  "data": {
    "success": true,
    "already_processed": false,
    "wallet_ledger_id": "f0d2d7b2-ea73-43a0-b46b-91d1da9a153b",
    "user_id": "a740f0db-28af-4427-8590-d10126d27452",
    "transaction_type": "earn",
    "amount": 3,
    "currency": "ticket",
    "ticket_type_id": "c00000000-0000-0000-0000-000000000001",
    "ticket_code": "RAFFLE_MAY",
    "balance_after": 3,
    "ticket_balance": 3,
    "dedup_key": "partner:order_456:raffle",
    "created_at": "2026-08-19T04:00:00.000000+00:00"
  },
  "meta": {
    "request_id": "...",
    "response_time_ms": 45
  }
}
```

14. List Wallet Transactions

Item	Value
Method	GET

Item	Value
URI	/api-wallet/transactions

Query parameters

Exactly one user identifier (`user_id` , `external_user_id` , `tel` , `email` , or `line_id`), plus:

Param	Required	Type	Remark
<code>from</code>	Optional	Timestamptz	<code>created_at >= from</code>
<code>to</code>	Optional	Timestamptz	<code>created_at < to</code> (require <code>from < to</code> when both set)
<code>transaction_type</code>	Optional	String	<code>earn</code> or <code>burn</code>
<code>currency</code>	Optional	String	<code>points</code> (default) or <code>ticket</code> . Default stays points-only.
<code>ticket_type_id</code>	Optional	UUID	Filter ticket history to one type (<code>currency=ticket</code> only)
<code>ticket_code</code>	Optional	String	Same filter by merchant ticket code
<code>limit</code>	Optional	Integer	1–100, default 50
<code>offset</code>	Optional	Integer	Default 0

Example Response — 200

```
{
  "success": true,
  "data": {
    "success": true,
    "user_id": "a740f0db-28af-4427-8590-d10126d27452",
    "total_count": 2,
    "limit": 50,
    "offset": 0,
    "transactions": [
      {
        "id": "f0d2d7b2-ea73-43a0-b46b-91d1da9a153b",
        "created_at": "2026-08-05T11:09:56.648809+00:00",
        "currency": "points",
        "transaction_type": "earn",
        "component": "adjustment",
        "amount": 100,
        "signed_amount": 100,
        "source_type": "manual",
        "description": "Order 456 loyalty credit",
        "balance_before": 0,
        "balance_after": 100,
        "expiry_date": null,
        "dedup_key": "partner:order_456:earn"
      }
    ]
  },
  "meta": {
    "request_id": "...",
    "response_time_ms": 30
  }
}
```

`dedup_key` in the response is the **client** key when present — never an internal prefixed key.

Example curl

```
curl --location \
  'https://open-api.rocket-loyalty.com/functions/v1/api-wallet/transactions?
    external_user_id=EXT_USER_002&limit=20&transaction_type=earn' \
  --header 'x-api-key: YOUR_API_KEY_HERE'
```

Error Codes

Common Errors

Code	Status	Description
MISSING_API_KEY	401	<code>x-api-key</code> header not provided
INVALID_API_KEY	401	API key invalid or expired
USER_NOT_FOUND	404	User identifier not found
ASSET_NOT_FOUND	404	Asset identifier not found

Code	Status	Description
ASSET_EXISTS	409	Asset already exists (upsert=false)
USER_EXISTS	409	User already exists (upsert=false)
VALIDATION_FAILED	400	Field validation failed
INSUFFICIENT_BALANCE	400	Wallet burn would exceed points or that ticket type's balance
INSUFFICIENT_TICKET_POOL	400	Pooled ticket type does not have enough unassigned codes
INVALID_CURRENCY	400	currency is not points or ticket
TICKET_TYPE_REQUIRED	400	Ticket post missing ticket_type_id / ticket_code
TICKET_TYPE_NOT_FOUND	400	Ticket type unknown for this merchant
TICKET_TYPE_NOT_AVAILABLE	400	Ticket type inactive or outside validity (earn)
TICKET_TYPE_CREDIT_FORBIDDEN	400	Store-credit / Shopify credit types cannot be posted
IDEMPOTENCY_CONFLICT	409	Wallet dedup_key reused with a different payload
TRANSACTION_LOCKED	400	Cannot modify completed transaction
GATEWAY_CONFIG_ERROR	500	API gateway misconfigured (ops)

Error Response Format

```

{
  "success": false,
  "error": "Error message",
  "code": "ERROR_CODE",
  "details": "Additional details",
  "request_id": "uuid"
}
```

Field Mapping Reference

Asset Fields (Old System → New)

Old Field Name	New Location	New Field Name	Notes
id	external_id	external_id	Partner asset external ID
name	name	name	Asset name

Old Field Name	New Location	New Field Name	Notes
serialNumber	serial_number	serial_number	Equipment serial
status	status	status	Asset status
purchaseDate	purchase_date	purchase_date	Purchase date
installDate	install_date	install_date	Installation date
warrantyPeriodTechnogym	custom_fields	warrantyPeriodTechnogym	Direct mapping
warrantyPeriodExtended	custom_fields	warrantyPeriodExtended	Direct mapping
usageEndDate	custom_fields	usageEndDate	Direct mapping
productName	custom_fields	productName	Separated from name
productCode	custom_fields	productCode	Direct mapping
product2Id	custom_fields	product2Id	Direct mapping
articleNumber	custom_fields	articleNumber	Direct mapping
salesOrder	custom_fields	salesOrder	Direct mapping
recordTypeId	custom_fields	recordTypeId	Direct mapping
quantity	custom_fields	quantity	Direct mapping
project	custom_fields	project	Direct mapping
opportunity	custom_fields	opportunity	Direct mapping
opportunityProduct	custom_fields	opportunityProduct	Direct mapping
accountId	custom_fields	accountId	Direct mapping
contactId	custom_fields	contactId	Direct mapping
parentId	custom_fields	parentId	Direct mapping
doNumber	custom_fields	doNumber	Direct mapping

Old Field Name	New Location	New Field Name	Notes
doDate	custom_fields	doDate	Direct mapping
cnNumber	custom_fields	cnNumber	Direct mapping
price	custom_fields	price	Direct mapping
description	custom_fields	description	Direct mapping

Maintenance Plan Fields (Old → New)

Old Field Name	New Location	New Field Name	Notes
id	external_id	external_id	Partner maintenance-plan ID
name	name	name	Plan name
status	status	status	Plan status
maintenancePlanNumber	custom_fields	maintenancePlanNumber	Direct mapping
maintenancePlanType	custom_fields	maintenancePlanType	Direct mapping
maintenancePlanStatus	custom_fields	maintenancePlanStatus	Direct mapping
maintenancePlanTitle	custom_fields	maintenancePlanTitle	New field
workTypeName	custom_fields	workTypeName	Direct mapping
workTypeId	custom_fields	workTypeId	New field
startDate	custom_fields	startDate	Direct mapping
endDate	custom_fields	endDate	Direct mapping
frequency	custom_fields	frequency	Direct mapping
frequencyType	custom_fields	frequencyType	Direct mapping
generationTimeframe	custom_fields	generationTimeframe	Direct mapping
generationTimeframeType	custom_fields	generationTimeframeType	Direct mapping
nextSuggestedMaintenanceDate	custom_fields	nextSuggestedMaintenanceDate	Direct mapping

Old Field Name	New Location	New Field Name	Notes
mpRenewal	custom_fields	mpRenewal	Direct mapping
approvalStatus	custom_fields	approvalStatus	Direct mapping
allAssetInstalled	custom_fields	allAssetInstalled	Direct mapping
activeExpire	custom_fields	activeExpire	Direct mapping
maintenanceAssets	covered_assets	covered_assets	Enhanced relationship structure

Bill Creation Fields (Old → New)

Old Field Name	New Field Name	Location	Notes
organization_id	(via API key)	Implicit	Merchant context from authentication
third_party_name	api_source	Body	Partner source system name
pos_store_code	store_code	Body	Direct mapping
external_order_no	external_ref	Body	External order reference
buyer_phone_number	external_user_id	Body	Phone number or user reference
seller_phone_number	seller_external_user_id	Body	Seller phone or reference
sale_date	transaction_date	Body	Transaction date
variant_code_list	items	Body	Array of line items
variant_code_list[].variant_code	items[].sku_code	Body	Product SKU code
variant_code_list[].variant_name	(auto-resolved)	—	Looked up from product catalog
variant_code_list[].qty	items[].quantity	Body	Quantity purchased
variant_code_list[].net_sale_value	items[].line_total	Body	Line total amount

User Fields Reference

Field Name	Type	Default	Available Values	Notes
user_stage	String	lead	lead , account , prospect , customer , churned	Customer lifecycle stage
brand_interest	Array	[]	luxury , sports , electronics , fashion , home	Stored in form_submissions

Data Formats

Success Response Format

All successful responses follow this structure:

```
{
  "success": true,
  "data": { },
  "meta": {
    "request_id": "uuid",
    "response_time_ms": 250
  }
}
```

Standard Headers

Request Headers:

- x-api-key — Your API key (required)
- Content-Type: application/json — for POST/PATCH

Response Headers:

- X-Request-Id — Unique request identifier for tracking
- X-Response-Time — Response time in milliseconds

Data Type Conventions

Type	Format
Dates	YYYY-MM-DD (e.g. 2024-10-20)
Timestamps	ISO 8601 with timezone
Numbers	Integers or decimals, JSON number type (no quotes)
Booleans	true or false (JSON boolean, not string)
Arrays	["value1", "value2"] — empty arrays [] allowed
UUIDs	xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxxx (case insensitive)

Type	Format
Phone numbers	+66XXXXXXXXX (E.164). Both 0XX and +66 accepted on input.