


dk::osal::Clock Class Reference

```
#include <DKOsaiClock.h>
```

Collaboration diagram for dk::osal::Clock:



Static Public Member Functions

static void	getSystemTime (struct timespec &ts)	Get current system time. (seconds + nanoseconds since epoch.) More...
static void	getMontonicTime (struct timespec &ts)	Get a monotonic time-stamp. (seconds + nanoseconds since some unspecified start.) More...
static void	addTimeOffsetMS (uint32_t msec, struct timespec &ts)	Add offset in milliseconds to timespec. More...
static void	addTimeOffsetUS (uint32_t usec, struct timespec &ts)	Add offset in microseconds to timespec. More...
static int64_t	getTimeDiffUS (const struct timespec &ts1, const struct timespec &ts2)	Calculate time delta in microseconds between two timespecs. More...

Member Function Documentation

◆ addTimeOffsetMS()

```
static void dk::osal::Clock::addTimeOffsetMS ( uint32_t      msec,
                                                struct timespec & ts
                                                )
```

static

Add offset in milliseconds to timespec.

Parameters

msec offset in milliseconds

ts pointer to timespec where time-stamp is stored. (ts must be normalized)

Requirement ID 751548

◆ addTimeOffsetUS()

```
static void dk::osal::Clock::addTimeOffsetUS ( uint32_t      usec,
                                                struct timespec & ts
                                                )
```

static

Add offset in microseconds to timespec.

Parameters

usec offset in microseconds

ts pointer to timespec where time-stamp is stored. (ts must be normalized)

Requirement ID 751549

◆ getMontonicTime()

```
static void dk::osal::Clock::getMontonicTime ( struct timespec & ts )
```

static

Get a monotonic time-stamp. (seconds + nanoseconds since some unspecified start.)

Parameters

ts pointer to timespec where time-stamp is stored.

requirement ID 751547

◆ getSystemTime()

```
static void dk::osal::Clock::getSystemTime ( struct timespec & ts )
```

static

Get current system time. (seconds + nanoseconds since epoch.)

Parameters

ts pointer to timespec where time-stamp is stored.

Requirement ID 751546

Function gets the current time of the clock specified by clock_id, and puts it into the buffer pointed to by tp.

Parameters

Returns 0 Success -1 An error occurred (errno is set). Errors: EFAULT- A fault occurred trying to access the buffers provided. EINVAL- Invalid clock_id. ESRCH- The process associated with this request doesn't exist.

Requirement ID 751546

◆ getTimeDiffUS()

```
static int64_t dk::osal::Clock::getTimeDiffUS ( const struct timespec & ts1,  
                                                const struct timespec & ts2  
                                                )
```

static

Calculate time delta in microseconds between two timespecs.

Parameters

ts1 start timespec

ts2 end timespec

Returns

time delta in microseconds

Requirement ID 751550

The documentation for this class was generated from the following files:

- /home/damudhar/29_8_audi/cluster-platform/dijkstra/abstraction/osal/src/posix/**DKOsaiClock.h**
- /home/damudhar/29_8_audi/cluster-platform/dijkstra/abstraction/osal/src/posix/**DKOsaiClock.cpp**