


CSigUnit_Registers.h File Reference

This graph shows which files directly or indirectly include this file:



[Go to the source code of this file.](#)

Macros

#define	MM_IO_SEERIS_BASE	0x56180000
#define	MM_IO_SEERIS_SIZE	0x3FFFF
#define	SIG_UNIT_0_REG_BASE	MM_IO_SEERIS_BASE + 0xD000
#define	SIG_UNIT_1_REG_BASE	MM_IO_SEERIS_BASE + 0xEC00
#define	SIG_UNIT_REG_SIZE	0x140
#define	DISENG_DISENGCFG_SRCSELECT0	0x0000B410u
#define	DISENG_DISENGCFG_SIG_SELECT0_FRAMEGEN	0x0 /* Source is FrameGen#0 output. */
#define	DISENG_DISENGCFG_SIG_SELECT0_GAMMACOR	0x1 /* Source is GammaCor#0 output. */
#define	DISENG_DISENGCFG_SIG_SELECT0_MATRIX	0x2 /* Source is Matrix#0 output. */
#define	DISENG_DISENGCFG_SIG_SELECT0_DITHER	0x3 /* Source is Dither#0 output. */
#define	DISENG_DISENGCFG_SRCSELECT1	0x0000B430u
#define	DISENG_DISENGCFG_SIG_SELECT1_FRAMEGEN	0x0 /* Source is FrameGen#1 output. */
#define	DISENG_DISENGCFG_SIG_SELECT1_GAMMACOR	0x1 /* Source is GammaCor#1 output. */
#define	DISENG_DISENGCFG_SIG_SELECT1_MATRIX	0x2 /* Source is Matrix#1 output. */
#define	DISENG_DISENGCFG_SIG_SELECT1_DITHER	0x3 /* Source is Dither#1 output. */
#define	DISENG_SIG_LOCKUNLOCK	0x00 /*Register to change the protection status of this address block. (sig*_LockUnlock)*/
#define	DISENG_SIG_LOCKUNLOCK_lock_key	0x5651F763u /* Decrements the unlock counter. When the counter value is null, lock protection is active. Reset counter value is 1. */
#define	DISENG_SIG_LOCKUNLOCK_unlock_key	0x691DB936u /* Increments the unlock counter. Max allowed value is 15. */

```

#define DISENG_SIG_LOCKUNLOCK_privilege_key 0xAEE95CDCu /* Enables privilege protection. Disabled
after reset. */

#define DISENG_SIG_LOCKUNLOCK_unprivilege_key 0xB5E2466Eu /* Disables privilege protection. */

#define DISENG_SIG_LOCKUNLOCK_freeze_key 0xFBE8B1E6u /* Freezes current protection status. Writing
keys to this register has no more effect until reset. */

#define DISENG_SIG_LOCKSTATUS 0x04 /*Protection status of this address block. (sig*_LockStatus)*/

#define INACTIVE_DISENG_SIG_LOCKSTATUS_RESET 0x0uL /*BIT Location : 0; Current status of lock
protection: 0 = inactive (unlock counter > 0), 1 = active (unlock counter == 0).*/

#define ACTIVE_DISENG_SIG_LOCKSTATUS_RESET 0x1uL

#define INACTIVE_DISENG_SIG_PRIVILEGESTATUS_RESET 0x0uL /*BIT Location : 4; Current status of
privilege protection: 0 = inactive , 1 = active. */

#define ACTIVE_DISENG_SIG_PRIVILEGESTATUS_RESET (0x1uL << 4)

#define CHANGED_DISENG_SIG_FREEZESTATUS_RESET 0x0uL /*BIT Location : 8; Current freeze status: 0
= protection status can be changed, 1 = cannot be changed. */

#define NOT_CHANGED_DISENG_SIG_FREEZESTATUS_RESET (0x1uL << 8)

#define DISENG_SIG_STATICCONTROL 0x08 /*Global configuration shared by all evaluation windows.
(sig*_StaticControl)*/

#define DISENG_SIG_SHDEN_RESET 0x0uL /*SHDEN: Enables shadow registers for RWS type fields (0 =
write through, 1 = shadowed). */

#define DISENG_SIG_SHDLDSSEL_LOCAL (0x0 << 4) /* Shadows are loaded at start of frame for each
evaluation window for which ShdLdReq has been set. */

#define DISENG_SIG_SHDLDSSEL_GLOBAL (0x1 << 4) /* Shadows of all evaluation windows are loaded
synchronous to the display stream (shadow load token received on frame input port). */

#define DISENG_SIG_SHDLDSSEL_RESET 0x0uL

#define DISENG_SIG_ERRTHRES_SHIFT (0x0 << 16) /*ERRTHRES: Number of frames with signature
violation before StsSigError is set for an evaluation window. */

#define DISENG_SIG_ERRTHRES_MASK 0xffuL

#define DISENG_SIG_ERRTHRESRESET_RESET (0x8uL << 24) /*ERRTHRESRESET: Number of
consecutive frames without signature violation before StsSigError is reset for an evaluation window. */

#define DISENG_SIG_PANICCOLOR 0x0C /*Overlay color for evaluation windows in panic mode.
(sig*_PanicColor)*/

#define DISENG_SIG_PANICALPHA_RESET (0x0uL << 7) /*Alpha mask bit. */

#define DISENG_SIG_PANICBLUE_RESET (0x0uL << 8) /*Blue color component. */

#define DISENG_SIG_PANICGREEN_RESET (0x0uL << 16) /*Green color component. */

#define DISENG_SIG_PANICRED_RESET (0x0uL << 24) /*Red color component. */

#define DISENG_SIG_EVALCONTROL0 0x10u /*Control settings for evaluation window 0.
(sig*_EvalControl0)*/

#define DISENG_SIG_EVALUPPERLEFT0 0x14u /*Upper left corner of evaluation window 0.
(sig*_EvalUpperLeft0)*/

#define DISENG_SIG_EVALLOWERRIGHT0 0x18u /*Lower right corner of evaluation window 0.
(sig*_EvalLowerRight0)*/

```

```
#define DISENG_SIG_SIGCRCREDREF0 0x1C /*Reference signature of red channel for evaluation window 0.
(sig*_SigCRCRedRef0)*/

#define DISENG_SIG_SIGCRCGREENREF0 0x20 /*Reference signature of green channel for evaluation
window 0. (sig*_SigCRCGreenRef0)*/

#define DISENG_SIG_SIGCRCBLUEREFO 0x24 /*Reference signature of blue channel for evaluation window
0. (sig*_SigCRCBlueRef0)*/

#define DISENG_SIG_SIGCRCREDO 0x28 /*Measured signature of red channel for evaluation window 0.
(sig*_SigCRCRed0)*/

#define DISENG_SIG_SIGCRCGREEN0 0x2C /*Measured signature of green channel for evaluation window 0.
(sig*_SigCRCGreen0)*/

#define DISENG_SIG_SIGCRCBLUE0 0x30 /*Measured signature of blue channel for evaluation window 0.
(sig*_SigCRCBlue0)*/

#define DISENG_SIG_EVALCONTROL1 0x34 /*Control settings for evaluation window 1. (sig*_EvalControl1)*/
#define DISENG_SIG_EVALUPPERLEFT1 0x38 /*Upper left corner of evaluation window 1.
(sig*_EvalUpperLeft1)*/

#define DISENG_SIG_EVALLOWERRIGHT1 0x3C /*Lower right corner of evaluation window 1.
(sig*_EvalLowerRight1)*/

#define DISENG_SIG_SIGCRCREDREF1 0x40 /*Reference signature of red channel for evaluation window 1.
(sig*_SigCRCRedRef1)*/

#define DISENG_SIG_SIGCRCGREENREF1 0x44 /*Reference signature of green channel for evaluation
window 1. (sig*_SigCRCGreenRef1)*/

#define DISENG_SIG_SIGCRCBLUEREFO1 0x48 /*Reference signature of blue channel for evaluation window
1. (sig*_SigCRCBlueRef1)*/

#define DISENG_SIG_SIGCRCRED1 0x4C /*Measured signature of red channel for evaluation window 1.
(sig*_SigCRCRed1)*/

#define DISENG_SIG_SIGCRCGREEN1 0x50 /*Measured signature of green channel for evaluation window 1.
(sig*_SigCRCGreen1)*/

#define DISENG_SIG_SIGCRCBLUE1 0x54 /*Measured signature of blue channel for evaluation window 1.
(sig*_SigCRCBlue1)*/

#define DISENG_SIG_EVALCONTROL2 0x58 /*Control settings for evaluation window 2. (sig*_EvalControl2)*/
#define DISENG_SIG_EVALUPPERLEFT2 0x5C /*Upper left corner of evaluation window 2.
(sig*_EvalUpperLeft2)*/

#define DISENG_SIG_EVALLOWERRIGHT2 0x60 /*Lower right corner of evaluation window 2.
(sig*_EvalLowerRight2)*/

#define DISENG_SIG_SIGCRCREDREF2 0x64 /*Reference signature of red channel for evaluation window 2.
(sig*_SigCRCRedRef2)*/

#define DISENG_SIG_SIGCRCGREENREF2 0x68 /*Reference signature of green channel for evaluation
window 2. (sig*_SigCRCGreenRef2)*/

#define DISENG_SIG_SIGCRCBLUEREFO2 0x6C /*Reference signature of blue channel for evaluation window
2. (sig*_SigCRCBlueRef2)*/
```

```
#define DISENG_SIG_SIGCRCRED2 0x70 /*Measured signature of red channel for evaluation window 2.
(sig*_SigCRCRed2)*/

#define DISENG_SIG_SIGCRCGREEN2 0x74 /*Measured signature of green channel for evaluation window 2.
(sig*_SigCRCGreen2)*/

#define DISENG_SIG_SIGCRCBLUE2 0x78 /*Measured signature of blue channel for evaluation window 2.
(sig*_SigCRCBlue2)*/

#define DISENG_SIG_EVALCONTROL3 0x7C /*Control settings for evaluation window 3. (sig*_EvalControl3)*/
#define DISENG_SIG_EVALUPPERLEFT3 0x80 /*Upper left corner of evaluation window 3.
(sig*_EvalUpperLeft3)*/

#define DISENG_SIG_EVALLOWERRIGHT3 0x84 /*Lower right corner of evaluation window 3.
(sig*_EvalLowerRight3)*/

#define DISENG_SIG_SIGCRCREDREF3 0x88 /*Reference signature of red channel for evaluation window 3.
(sig*_SigCRCRedRef3)*/

#define DISENG_SIG_SIGCRCGREENREF3 0x8C /*Reference signature of green channel for evaluation
window 3. (sig*_SigCRCGreenRef3)*/

#define DISENG_SIG_SIGCRCBLUEREFF3 0x90 /*Reference signature of blue channel for evaluation window
3. (sig*_SigCRCBlueRef3)*/

#define DISENG_SIG_SIGCRCRED3 0x94 /*Measured signature of red channel for evaluation window 3.
(sig*_SigCRCRed3)*/

#define DISENG_SIG_SIGCRCGREEN3 0x98 /*Measured signature of green channel for evaluation window 3.
(sig*_SigCRCGreen3)*/

#define DISENG_SIG_SIGCRCBLUE3 0x9C /*Measured signature of blue channel for evaluation window 3.
(sig*_SigCRCBlue3)*/

#define DISENG_SIG_EVALCONTROL4 0xA0 /*Control settings for evaluation window 4. (sig*_EvalControl4)*/
#define DISENG_SIG_EVALUPPERLEFT4 0xA4 /*Upper left corner of evaluation window 4.
(sig*_EvalUpperLeft4)*/

#define DISENG_SIG_EVALLOWERRIGHT4 0xA8 /*Lower right corner of evaluation window 4.
(sig*_EvalLowerRight4)*/

#define DISENG_SIG_SIGCRCREDREF4 0xAC /*Reference signature of red channel for evaluation window 4.
(sig*_SigCRCRedRef4)*/

#define DISENG_SIG_SIGCRCGREENREF4 0xB0 /*Reference signature of green channel for evaluation
window 4. (sig*_SigCRCGreenRef4)*/

#define DISENG_SIG_SIGCRCBLUEREFF4 0xB4 /*Reference signature of blue channel for evaluation window
4. (sig*_SigCRCBlueRef4)*/

#define DISENG_SIG_SIGCRCRED4 0xB8 /*Measured signature of red channel for evaluation window 4.
(sig*_SigCRCRed4)*/

#define DISENG_SIG_SIGCRCGREEN4 0xBC /*Measured signature of green channel for evaluation window 4.
(sig*_SigCRCGreen4)*/

#define DISENG_SIG_SIGCRCBLUE4 0xC0 /*Measured signature of blue channel for evaluation window 4.
(sig*_SigCRCBlue4)*/

#define DISENG_SIG_EVALCONTROL5 0xC4 /*Control settings for evaluation window 5. (sig*_EvalControl5)*/
```

```

#define DISENG_SIG_EVALUPPERLEFT5 0xC8 /*Upper left corner of evaluation window 5.
(sig*_EvalUpperLeft5)*/

#define DISENG_SIG_EVALLOWERRIGHT5 0xCC /*Lower right corner of evaluation window 5.
(sig*_EvalLowerRight5)*/

#define DISENG_SIG_SIGCRCREDREF5 0xD0 /*Reference signature of red channel for evaluation window 5.
(sig*_SigCRCRedRef5)*/

#define DISENG_SIG_SIGCRCGREENREF5 0xD4 /*Reference signature of green channel for evaluation
window 5. (sig*_SigCRCGreenRef5)*/

#define DISENG_SIG_SIGCRCBLUERE5 0xD8 /*Reference signature of blue channel for evaluation window
5. (sig*_SigCRCBlueRef5)*/

#define DISENG_SIG_SIGCRCRED5 0xDC /*Measured signature of red channel for evaluation window 5.
(sig*_SigCRCRed5)*/

#define DISENG_SIG_SIGCRCGREEN5 0xE0 /*Measured signature of green channel for evaluation window 5.
(sig*_SigCRCGreen5)*/

#define DISENG_SIG_SIGCRCBLUE5 0xE4 /*Measured signature of blue channel for evaluation window 5.
(sig*_SigCRCBlue5)*/

#define DISENG_SIG_EVALCONTROL6 0xE8 /*Control settings for evaluation window 6. (sig*_EvalControl6)*/

#define DISENG_SIG_EVALUPPERLEFT6 0xEC /*Upper left corner of evaluation window 6.
(sig*_EvalUpperLeft6)*/

#define DISENG_SIG_EVALLOWERRIGHT6 0xF0 /*Lower right corner of evaluation window 6.
(sig*_EvalLowerRight6)*/

#define DISENG_SIG_SIGCRCREDREF6 0xF4 /*Reference signature of red channel for evaluation window 6.
(sig*_SigCRCRedRef6)*/

#define DISENG_SIG_SIGCRCGREENREF6 0xF8 /*Reference signature of green channel for evaluation
window 6. (sig*_SigCRCGreenRef6)*/

#define DISENG_SIG_SIGCRCBLUERE6 0xFC /*Reference signature of blue channel for evaluation window
6. (sig*_SigCRCBlueRef6)*/

#define DISENG_SIG_SIGCRCRED6 0x100 /*Measured signature of red channel for evaluation window 6.
(sig*_SigCRCRed6)*/

#define DISENG_SIG_SIGCRCGREEN6 0x104 /*Measured signature of green channel for evaluation window
6. (sig*_SigCRCGreen6)*/

#define DISENG_SIG_SIGCRCBLUE6 0x108 /*Measured signature of blue channel for evaluation window 6.
(sig*_SigCRCBlue6)*/

#define DISENG_SIG_EVALCONTROL7 0x10C /*Control settings for evaluation window 7.
(sig*_EvalControl7)*/

#define DISENG_SIG_EVALUPPERLEFT7 0x110 /*Upper left corner of evaluation window 7.
(sig*_EvalUpperLeft7)*/

#define DISENG_SIG_EVALLOWERRIGHT7 0x114 /*Lower right corner of evaluation window 7.
(sig*_EvalLowerRight7)*/

#define DISENG_SIG_SIGCRCREDREF7 0x118 /*Reference signature of red channel for evaluation window 7.
(sig*_SigCRCRedRef7)*/

```

```
#define DISENG_SIG_SIGCRCGREENREF7 0x11C /*Reference signature of green channel for evaluation
window 7. (sig*_SigCRCGreenRef7)*/

#define DISENG_SIG_SIGCRCBLUEREF7 0x120 /*Reference signature of blue channel for evaluation window
7. (sig*_SigCRCBlueRef7)*/

#define DISENG_SIG_SIGCRCRED7 0x124 /*Measured signature of red channel for evaluation window 7.
(sig*_SigCRCRed7)*/

#define DISENG_SIG_SIGCRCGREEN7 0x128 /*Measured signature of green channel for evaluation window
7. (sig*_SigCRCGreen7)*/

#define DISENG_SIG_SIGCRCBLUE7 0x12C /*Measured signature of blue channel for evaluation window 7.
(sig*_SigCRCBlue7)*/

#define DISENG_SIG_SHADOWLOAD 0x130 /*Shadow load control register. (sig*_ShadowLoad)*/

#define DISENG_SIG_CONTINUOUSMODE 0x134 /*Signature operation mode control.
(sig*_ContinuousMode)*/

#define DISENG_SIG_SOFTWAREKICK 0x138 /*Signature measurement trigger. (sig*_SoftwareKick)*/

#define DISENG_SIG_STATUS 0x13C /*Module status. (sig*_Status)*/
```

Macro Definition Documentation

◆ ACTIVE_DISENG_SIG_LOCKSTATUS_RESET

```
#define ACTIVE_DISENG_SIG_LOCKSTATUS_RESET 0x1uL
```

◆ ACTIVE_DISENG_SIG_PRIVILEGESTATUS_RESET

```
#define ACTIVE_DISENG_SIG_PRIVILEGESTATUS_RESET (0x1uL << 4)
```

◆ CHANGED_DISENG_SIG_FREEZESTATUS_RESET

```
#define CHANGED_DISENG_SIG_FREEZESTATUS_RESET 0x0uL /*BIT Location : 8; Current freeze status: 0
= protection status can be changed, 1 = cannot be changed. */
```

◆ DISENG_DISENGCFG_SIG_SELECT0_DITHER

```
#define DISENG_DISENGCFG_SIG_SELECT0_DITHER 0x3 /* Source is Dither#0 output. */
```

◆ DISENG_DISENGCFG_SIG_SELECT0_FRAMEGEN

```
#define DISENG_DISENGCFG_SIG_SELECT0_FRAMEGEN 0x0 /* Source is FrameGen#0 output. */
```

◆ DISENG_DISENGCFG_SIG_SELECT0_GAMMACOR

```
#define DISENG_DISENGCFG_SIG_SELECT0_GAMMACOR 0x1 /* Source is GammaCor#0 output. */
```

◆ DISENG_DISENGCFG_SIG_SELECT0_MATRIX

```
#define DISENG_DISENGCFG_SIG_SELECT0_MATRIX 0x2 /* Source is Matrix#0 output. */
```

◆ DISENG_DISENGCFG_SIG_SELECT1_DITHER

```
#define DISENG_DISENGCFG_SIG_SELECT1_DITHER 0x3 /* Source is Dither#1 output. */
```

◆ DISENG_DISENGCFG_SIG_SELECT1_FRAMEGEN

```
#define DISENG_DISENGCFG_SIG_SELECT1_FRAMEGEN 0x0 /* Source is FrameGen#1 output. */
```

◆ DISENG_DISENGCFG_SIG_SELECT1_GAMMACOR

```
#define DISENG_DISENGCFG_SIG_SELECT1_GAMMACOR 0x1 /* Source is GammaCor#1 output. */
```

◆ DISENG_DISENGCFG_SIG_SELECT1_MATRIX

```
#define DISENG_DISENGCFG_SIG_SELECT1_MATRIX 0x2 /* Source is Matrix#1 output. */
```

◆ DISENG_DISENGCFG_SRCSELECT0

```
#define DISENG_DISENGCFG_SRCSELECT0 0x0000B410u
```

◆ DISENG_DISENGCFG_SRCSELECT1

```
#define DISENG_DISENGCFG_SRCSELECT1 0x0000B430u
```

◆ DISENG_SIG_CONTINUOUSMODE

```
#define DISENG_SIG_CONTINUOUSMODE 0x134 /*Signature operation mode control.  
(sig*_ContinuousMode)*/
```

◆ DISENG_SIG_ERRTHRES_MASK

```
#define DISENG_SIG_ERRTHRES_MASK 0xffuL
```

◆ DISENG_SIG_ERRTHRES_SHIFT

```
#define DISENG_SIG_ERRTHRES_SHIFT (0x0 << 16) /*ERRTHRES: Number of frames with signature  
violation before StsSigError is set for an evaluation window. */
```

◆ DISENG_SIG_ERRTHRESRESET_RESET

```
#define DISENG_SIG_ERRTHRESRESET_RESET (0x8uL << 24) /*ERRTHRESRESET: Number of consecutive  
frames without signature violation before StsSigError is reset for an evaluation window. */
```

◆ DISENG_SIG_EVALCONTROL0

```
#define DISENG_SIG_EVALCONTROL0 0x10u /*Control settings for evaluation window 0. (sig*_EvalControl0)*/
```

◆ DISENG_SIG_EVALCONTROL1

```
#define DISENG_SIG_EVALCONTROL1 0x34 /*Control settings for evaluation window 1. (sig*_EvalControl1)*/
```

◆ DISENG_SIG_EVALCONTROL2

```
#define DISENG_SIG_EVALCONTROL2 0x58 /*Control settings for evaluation window 2. (sig*_EvalControl2)*/
```

◆ DISENG_SIG_EVALCONTROL3

```
#define DISENG_SIG_EVALCONTROL3 0x7C /*Control settings for evaluation window 3. (sig*_EvalControl3)*/
```

◆ DISENG_SIG_EVALCONTROL4

```
#define DISENG_SIG_EVALCONTROL4 0xA0 /*Control settings for evaluation window 4. (sig*_EvalControl4)*/
```

◆ DISENG_SIG_EVALCONTROL5

```
#define DISENG_SIG_EVALCONTROL5 0xC4 /*Control settings for evaluation window 5. (sig*_EvalControl5)*/
```

◆ DISENG_SIG_EVALCONTROL6

```
#define DISENG_SIG_EVALCONTROL6 0xE8 /*Control settings for evaluation window 6. (sig*_EvalControl6)*/
```

◆ DISENG_SIG_EVALCONTROL7

```
#define DISENG_SIG_EVALCONTROL7 0x10C /*Control settings for evaluation window 7. (sig*_EvalControl7)*/
```

◆ DISENG_SIG_EVALLOWERRIGHT0

```
#define DISENG_SIG_EVALLOWERRIGHT0 0x18u /*Lower right corner of evaluation window 0.  
(sig*_EvalLowerRight0)*/
```

◆ DISENG_SIG_EVALLOWERRIGHT1

```
#define DISENG_SIG_EVALLOWERRIGHT1 0x3C /*Lower right corner of evaluation window 1.  
(sig*_EvalLowerRight1)*/
```

◆ DISENG_SIG_EVALLOWERRIGHT2

```
#define DISENG_SIG_EVALLOWERRIGHT2 0x60 /*Lower right corner of evaluation window 2.  
(sig*_EvalLowerRight2)*/
```

◆ DISENG_SIG_EVALLOWERRIGHT3

```
#define DISENG_SIG_EVALLOWERRIGHT3 0x84 /*Lower right corner of evaluation window 3.  
(sig*_EvalLowerRight3)*/
```

◆ DISENG_SIG_EVALLOWERRIGHT4

```
#define DISENG_SIG_EVALLOWERRIGHT4 0xA8 /*Lower right corner of evaluation window 4.  
(sig*_EvalLowerRight4)*/
```

◆ DISENG_SIG_EVALLOWERRIGHT5

```
#define DISENG_SIG_EVALLOWERRIGHT5 0xCC /*Lower right corner of evaluation window 5.  
(sig*_EvalLowerRight5)*/
```

◆ DISENG_SIG_EVALLOWERRIGHT6

```
#define DISENG_SIG_EVALLOWERRIGHT6 0xF0 /*Lower right corner of evaluation window 6.  
(sig*_EvalLowerRight6)*/
```

◆ DISENG_SIG_EVALLOWERRIGHT7

```
#define DISENG_SIG_EVALLOWERRIGHT7 0x114 /*Lower right corner of evaluation window 7.  
(sig*_EvalLowerRight7)*/
```

◆ DISENG_SIG_EVALUPPERLEFT0

```
#define DISENG_SIG_EVALUPPERLEFT0 0x14u /*Upper left corner of evaluation window 0.  
(sig*_EvalUpperLeft0)*/
```

◆ DISENG_SIG_EVALUPPERLEFT1

```
#define DISENG_SIG_EVALUPPERLEFT1 0x38 /*Upper left corner of evaluation window 1.  
(sig*_EvalUpperLeft1)*/
```

◆ DISENG_SIG_EVALUPPERLEFT2

```
#define DISENG_SIG_EVALUPPERLEFT2 0x5C /*Upper left corner of evaluation window 2.  
(sig*_EvalUpperLeft2)*/
```

◆ DISENG_SIG_EVALUPPERLEFT3

```
#define DISENG_SIG_EVALUPPERLEFT3 0x80 /*Upper left corner of evaluation window 3.  
(sig*_EvalUpperLeft3)*/
```

◆ DISENG_SIG_EVALUPPERLEFT4

```
#define DISENG_SIG_EVALUPPERLEFT4 0xA4 /*Upper left corner of evaluation window 4.  
(sig*_EvalUpperLeft4)*/
```

◆ DISENG_SIG_EVALUPPERLEFT5

```
#define DISENG_SIG_EVALUPPERLEFT5 0xC8 /*Upper left corner of evaluation window 5.  
(sig*_EvalUpperLeft5)*/
```

◆ DISENG_SIG_EVALUPPERLEFT6

```
#define DISENG_SIG_EVALUPPERLEFT6 0xEC /*Upper left corner of evaluation window 6.  
(sig*_EvalUpperLeft6)*/
```

◆ DISENG_SIG_EVALUPPERLEFT7

```
#define DISENG_SIG_EVALUPPERLEFT7 0x110 /*Upper left corner of evaluation window 7.  
(sig*_EvalUpperLeft7)*/
```

◆ DISENG_SIG_LOCKSTATUS

```
#define DISENG_SIG_LOCKSTATUS 0x04 /*Protection status of this address block. (sig*_LockStatus)*/
```

◆ DISENG_SIG_LOCKUNLOCK

```
#define DISENG_SIG_LOCKUNLOCK 0x00 /*Register to change the protection status of this address block.  
(sig*_LockUnlock)*/
```

◆ DISENG_SIG_LOCKUNLOCK_freeze_key

```
#define DISENG_SIG_LOCKUNLOCK_freeze_key 0xFBE8B1E6u /* Freezes current protection status. Writing  
keys to this register has no more effect until reset. */
```

◆ DISENG_SIG_LOCKUNLOCK_lock_key

```
#define DISENG_SIG_LOCKUNLOCK_lock_key 0x5651F763u /* Decrements the unlock counter. When the  
counter value is null, lock protection is active. Reset counter value is 1. */
```

◆ DISENG_SIG_LOCKUNLOCK_privilege_key

```
#define DISENG_SIG_LOCKUNLOCK_privilege_key 0xAEE95CDCu /* Enables privilege protection. Disabled  
after reset. */
```

◆ DISENG_SIG_LOCKUNLOCK_unlock_key

```
#define DISENG_SIG_LOCKUNLOCK_unlock_key 0x691DB936u /* Increments the unlock counter. Max  
allowed value is 15. */
```

◆ DISENG_SIG_LOCKUNLOCK_unprivilege_key

```
#define DISENG_SIG_LOCKUNLOCK_unprivilege_key 0xB5E2466Eu /* Disables privilege protection. */
```

◆ DISENG_SIG_PANICALPHA_RESET

```
#define DISENG_SIG_PANICALPHA_RESET (0x0uL << 7) /*Alpha mask bit. */
```

◆ DISENG_SIG_PANICBLUE_RESET

```
#define DISENG_SIG_PANICBLUE_RESET (0x0uL << 8) /*Blue color component. */
```

◆ DISENG_SIG_PANICCOLOR

```
#define DISENG_SIG_PANICCOLOR 0x0C /*Overlay color for evaluation windows in panic mode.  
(sig*_PanicColor)*/
```

◆ DISENG_SIG_PANICGREEN_RESET

```
#define DISENG_SIG_PANICGREEN_RESET (0x0uL << 16) /*Green color component. */
```

◆ DISENG_SIG_PANICRED_RESET

```
#define DISENG_SIG_PANICRED_RESET (0x0uL << 24) /*Red color component. */
```

◆ DISENG_SIG_SHADOWLOAD

```
#define DISENG_SIG_SHADOWLOAD 0x130 /*Shadow load control register. (sig*_ShadowLoad)*/
```

◆ DISENG_SIG_SHDEN_RESET

```
#define DISENG_SIG_SHDEN_RESET 0x0uL /*SHDEN: Enables shadow registers for RWS type fields (0 =  
write through, 1 = shadowed). */
```

◆ DISENG_SIG_SHDLDSEL_GLOBAL

```
#define DISENG_SIG_SHDLDSEL_GLOBAL (0x1 << 4) /* Shadows of all evaluation windows are loaded  
synchronous to the display stream (shadow load token received on frame input port). */
```

◆ DISENG_SIG_SHDLDSEL_LOCAL

```
#define DISENG_SIG_SHDLDSEL_LOCAL (0x0 << 4) /* Shadows are loaded at start of frame for each  
evaluation window for which ShdLdReq has been set. */
```

◆ DISENG_SIG_SHDLDSEL_RESET

```
#define DISENG_SIG_SHDLDSEL_RESET 0x0uL
```

◆ DISENG_SIG_SIGCRCBLUE0

```
#define DISENG_SIG_SIGCRCBLUE0 0x30 /*Measured signature of blue channel for evaluation window 0.  
(sig*_SigCRCBlue0)*/
```

◆ DISENG_SIG_SIGCRCBLUE1

```
#define DISENG_SIG_SIGCRCBLUE1 0x54 /*Measured signature of blue channel for evaluation window 1.  
(sig*_SigCRCBlue1)*/
```

◆ DISENG_SIG_SIGCRCBLUE2

```
#define DISENG_SIG_SIGCRCBLUE2 0x78 /*Measured signature of blue channel for evaluation window 2.  
(sig*_SigCRCBlue2)*/
```

◆ DISENG_SIG_SIGCRCBLUE3

```
#define DISENG_SIG_SIGCRCBLUE3 0x9C /*Measured signature of blue channel for evaluation window 3.  
(sig*_SigCRCBlue3)*/
```

◆ DISENG_SIG_SIGCRCBLUE4

```
#define DISENG_SIG_SIGCRCBLUE4 0xC0 /*Measured signature of blue channel for evaluation window 4.  
(sig*_SigCRCBlue4)*/
```

◆ DISENG_SIG_SIGCRCBLUE5

```
#define DISENG_SIG_SIGCRCBLUE5 0xE4 /*Measured signature of blue channel for evaluation window 5.  
(sig*_SigCRCBlue5)*/
```

◆ DISENG_SIG_SIGCRCBLUE6

```
#define DISENG_SIG_SIGCRCBLUE6 0x108 /*Measured signature of blue channel for evaluation window 6.  
(sig*_SigCRCBlue6)*/
```

◆ DISENG_SIG_SIGCRCBLUE7

```
#define DISENG_SIG_SIGCRCBLUE7 0x12C /*Measured signature of blue channel for evaluation window 7.  
(sig*_SigCRCBlue7)*/
```

◆ DISENG_SIG_SIGCRCBLUEREFO

```
#define DISENG_SIG_SIGCRCBLUEREFO 0x24 /*Reference signature of blue channel for evaluation window 0.  
(sig*_SigCRCBlueRef0)*/
```

◆ DISENG_SIG_SIGCRCBLUEREFO1

```
#define DISENG_SIG_SIGCRCBLUEREFO1 0x48 /*Reference signature of blue channel for evaluation window 1.  
(sig*_SigCRCBlueRef1)*/
```

◆ DISENG_SIG_SIGCRCBLUERE2

```
#define DISENG_SIG_SIGCRCBLUERE2 0x6C /*Reference signature of blue channel for evaluation window  
2. (sig*_SigCRCBlueRef2)*/
```

◆ DISENG_SIG_SIGCRCBLUERE3

```
#define DISENG_SIG_SIGCRCBLUERE3 0x90 /*Reference signature of blue channel for evaluation window 3.  
(sig*_SigCRCBlueRef3)*/
```

◆ DISENG_SIG_SIGCRCBLUERE4

```
#define DISENG_SIG_SIGCRCBLUERE4 0xB4 /*Reference signature of blue channel for evaluation window 4.  
(sig*_SigCRCBlueRef4)*/
```

◆ DISENG_SIG_SIGCRCBLUERE5

```
#define DISENG_SIG_SIGCRCBLUERE5 0xD8 /*Reference signature of blue channel for evaluation window  
5. (sig*_SigCRCBlueRef5)*/
```

◆ DISENG_SIG_SIGCRCBLUERE6

```
#define DISENG_SIG_SIGCRCBLUERE6 0xFC /*Reference signature of blue channel for evaluation window  
6. (sig*_SigCRCBlueRef6)*/
```

◆ DISENG_SIG_SIGCRCBLUERE7

```
#define DISENG_SIG_SIGCRCBLUERE7 0x120 /*Reference signature of blue channel for evaluation window  
7. (sig*_SigCRCBlueRef7)*/
```

◆ DISENG_SIG_SIGCRCGREEN0

```
#define DISENG_SIG_SIGCRCGREEN0 0x2C /*Measured signature of green channel for evaluation window 0.  
(sig*_SigCRCGreen0)*/
```

◆ DISENG_SIG_SIGCRCGREEN1

```
#define DISENG_SIG_SIGCRCGREEN1 0x50 /*Measured signature of green channel for evaluation window 1.  
(sig*_SigCRCGreen1)*/
```

◆ DISENG_SIG_SIGCRCGREEN2

```
#define DISENG_SIG_SIGCRCGREEN2 0x74 /*Measured signature of green channel for evaluation window 2.  
(sig*_SigCRCGreen2)*/
```

◆ DISENG_SIG_SIGCRCGREEN3

```
#define DISENG_SIG_SIGCRCGREEN3 0x98 /*Measured signature of green channel for evaluation window 3.  
(sig*_SigCRCGreen3)*/
```

◆ DISENG_SIG_SIGCRCGREEN4

```
#define DISENG_SIG_SIGCRCGREEN4 0xBC /*Measured signature of green channel for evaluation window 4.  
(sig*_SigCRCGreen4)*/
```

◆ DISENG_SIG_SIGCRCGREEN5

```
#define DISENG_SIG_SIGCRCGREEN5 0xE0 /*Measured signature of green channel for evaluation window 5.  
(sig*_SigCRCGreen5)*/
```

◆ DISENG_SIG_SIGCRCGREEN6

```
#define DISENG_SIG_SIGCRCGREEN6 0x104 /*Measured signature of green channel for evaluation window 6.  
(sig*_SigCRCGreen6)*/
```

◆ DISENG_SIG_SIGCRCGREEN7

```
#define DISENG_SIG_SIGCRCGREEN7 0x128 /*Measured signature of green channel for evaluation window 7.  
(sig*_SigCRCGreen7)*/
```

◆ DISENG_SIG_SIGCRCGREENREF0

```
#define DISENG_SIG_SIGCRCGREENREF0 0x20 /*Reference signature of green channel for evaluation  
window 0. (sig*_SigCRCGreenRef0)*/
```

◆ DISENG_SIG_SIGCRCGREENREF1

```
#define DISENG_SIG_SIGCRCGREENREF1 0x44 /*Reference signature of green channel for evaluation  
window 1. (sig*_SigCRCGreenRef1)*/
```

◆ DISENG_SIG_SIGCRCGREENREF2

```
#define DISENG_SIG_SIGCRCGREENREF2 0x68 /*Reference signature of green channel for evaluation  
window 2. (sig*_SigCRCGreenRef2)*/
```

◆ DISENG_SIG_SIGCRCGREENREF3

```
#define DISENG_SIG_SIGCRCGREENREF3 0x8C /*Reference signature of green channel for evaluation  
window 3. (sig*_SigCRCGreenRef3)*/
```

◆ DISENG_SIG_SIGCRCGREENREF4

```
#define DISENG_SIG_SIGCRCGREENREF4 0xB0 /*Reference signature of green channel for evaluation  
window 4. (sig*_SigCRCGreenRef4)*/
```

◆ DISENG_SIG_SIGCRCGREENREF5

```
#define DISENG_SIG_SIGCRCGREENREF5 0xD4 /*Reference signature of green channel for evaluation  
window 5. (sig*_SigCRCGreenRef5)*/
```

◆ DISENG_SIG_SIGCRCGREENREF6

```
#define DISENG_SIG_SIGCRCGREENREF6 0xF8 /*Reference signature of green channel for evaluation  
window 6. (sig*_SigCRCGreenRef6)*/
```

◆ DISENG_SIG_SIGCRCGREENREF7

```
#define DISENG_SIG_SIGCRCGREENREF7 0x11C /*Reference signature of green channel for evaluation  
window 7. (sig*_SigCRCGreenRef7)*/
```

◆ DISENG_SIG_SIGCRCRED0

```
#define DISENG_SIG_SIGCRCRED0 0x28 /*Measured signature of red channel for evaluation window 0.  
(sig*_SigCRCRed0)*/
```

◆ DISENG_SIG_SIGCRCRED1

```
#define DISENG_SIG_SIGCRCRED1 0x4C /*Measured signature of red channel for evaluation window 1.  
(sig*_SigCRCRed1)*/
```

◆ DISENG_SIG_SIGCRCRED2

```
#define DISENG_SIG_SIGCRCRED2 0x70 /*Measured signature of red channel for evaluation window 2.  
(sig*_SigCRCRed2)*/
```

◆ DISENG_SIG_SIGCRCRED3

```
#define DISENG_SIG_SIGCRCRED3 0x94 /*Measured signature of red channel for evaluation window 3.  
(sig*_SigCRCRed3)*/
```

◆ DISENG_SIG_SIGCRCRED4

```
#define DISENG_SIG_SIGCRCRED4 0xB8 /*Measured signature of red channel for evaluation window 4.  
(sig*_SigCRCRed4)*/
```

◆ DISENG_SIG_SIGCRCRED5

```
#define DISENG_SIG_SIGCRCRED5 0xDC /*Measured signature of red channel for evaluation window 5.  
(sig*_SigCRCRed5)*/
```

◆ DISENG_SIG_SIGCRCRED6

```
#define DISENG_SIG_SIGCRCRED6 0x100 /*Measured signature of red channel for evaluation window 6.  
(sig*_SigCRCRed6)*/
```

◆ DISENG_SIG_SIGCRCRED7

```
#define DISENG_SIG_SIGCRCRED7 0x124 /*Measured signature of red channel for evaluation window 7.  
(sig*_SigCRCRed7)*/
```

◆ DISENG_SIG_SIGCRCREDREF0

```
#define DISENG_SIG_SIGCRCREDREF0 0x1C /*Reference signature of red channel for evaluation window 0.  
(sig*_SigCRCRedRef0)*/
```

◆ DISENG_SIG_SIGCRCREDREF1

```
#define DISENG_SIG_SIGCRCREDREF1 0x40 /*Reference signature of red channel for evaluation window 1.  
(sig*_SigCRCRedRef1)*/
```

◆ DISENG_SIG_SIGCRCREDREF2

```
#define DISENG_SIG_SIGCRCREDREF2 0x64 /*Reference signature of red channel for evaluation window 2.  
(sig*_SigCRCRedRef2)*/
```

◆ DISENG_SIG_SIGCRCREDREF3

```
#define DISENG_SIG_SIGCRCREDREF3 0x88 /*Reference signature of red channel for evaluation window 3.  
(sig*_SigCRCRedRef3)*/
```

◆ DISENG_SIG_SIGCRCREDREF4

```
#define DISENG_SIG_SIGCRCREDREF4 0xAC /*Reference signature of red channel for evaluation window 4.  
(sig*_SigCRCRedRef4)*/
```

◆ DISENG_SIG_SIGCRCREDREF5

```
#define DISENG_SIG_SIGCRCREDREF5 0xD0 /*Reference signature of red channel for evaluation window 5.  
(sig*_SigCRCRedRef5)*/
```

◆ DISENG_SIG_SIGCRCREDREF6

```
#define DISENG_SIG_SIGCRCREDREF6 0xF4 /*Reference signature of red channel for evaluation window 6.  
(sig*_SigCRCRedRef6)*/
```

◆ DISENG_SIG_SIGCRCREDREF7

```
#define DISENG_SIG_SIGCRCREDREF7 0x118 /*Reference signature of red channel for evaluation window 7.  
(sig*_SigCRCRedRef7)*/
```

◆ DISENG_SIG_SOFTWAREKICK

```
#define DISENG_SIG_SOFTWAREKICK 0x138 /*Signature measurement trigger. (sig*_SoftwareKick)*/
```

◆ DISENG_SIG_STATICCONTROL

```
#define DISENG_SIG_STATICCONTROL 0x08 /*Global configuration shared by all evaluation windows.  
(sig*_StaticControl)*/
```

◆ DISENG_SIG_STATUS

```
#define DISENG_SIG_STATUS 0x13C /*Module status. (sig*_Status)*/
```

◆ INACTIVE_DISENG_SIG_LOCKSTATUS_RESET

```
#define INACTIVE_DISENG_SIG_LOCKSTATUS_RESET 0x0uL /*BIT Location : 0; Current status of lock  
protection: 0 = inactive (unlock counter > 0), 1 = active (unlock counter == 0).*/
```

◆ INACTIVE_DISENG_SIG_PRIVILEGESTATUS_RESET

```
#define INACTIVE_DISENG_SIG_PRIVILEGESTATUS_RESET 0x0uL /*BIT Location : 4; Current status of  
privilege protection: 0 = inactive , 1 = active. */
```

◆ MM_IO_SEERIS_BASE

```
#define MM_IO_SEERIS_BASE 0x56180000
```

◆ MM_IO_SEERIS_SIZE

```
#define MM_IO_SEERIS_SIZE 0x3FFFF
```

◆ NOT_CHANGED_DISENG_SIG_FREEZESTATUS_RESET

```
#define NOT_CHANGED_DISENG_SIG_FREEZESTATUS_RESET (0x1uL << 8)
```

◆ SIG_UNIT_0_REG_BASE

```
#define SIG_UNIT_0_REG_BASE MM_IO_SEERIS_BASE + 0xD000
```

◆ SIG_UNIT_1_REG_BASE

```
#define SIG_UNIT_1_REG_BASE  MM_IO_SEERIS_BASE + 0xEC00
```

◆ SIG_UNIT_REG_SIZE

```
#define SIG_UNIT_REG_SIZE  0x140
```