

KDFlow: A User-Friendly and Efficient Knowledge Distillation Framework for Large Language Models

Songming Zhang^{1,2,3*}, Xue Zhang^{1,2}, Tong Zhang³, Bojie Hu³,
Yufeng Chen^{1,2}, and Jinan Xu^{1,2}

¹ School of Computer Science and Technology, Beijing Jiaotong University, Beijing, China

² Key Laboratory of Big Data & Artificial Intelligence in Transportation,
(Beijing Jiaotong University), Ministry of Education

³ Weixin AI

{smzhang22, zhang_xue, chenylf, jaxu}@bjtu.edu.cn

Abstract

Knowledge distillation (KD) is widely used to compress and post-train large language models (LLMs), yet many existing frameworks execute teacher inference with the same training-oriented backend as student optimization, leading to suboptimal efficiency. In this paper, we propose **KDFlow**, a novel framework for LLM distillation that features a **decoupled architecture** and employs SGLang for teacher inference. KDFlow combines SGLang for teacher inference with PyTorch FSDP2 for student optimization, allowing each model to run on a backend tailored to its workload. To enable **efficient full-vocabulary distillation** in this decoupled architecture, KDFlow transfers the teacher’s final hidden states via Ray’s object store and re-computes teacher logits on each student worker using a frozen copy of the teacher’s output head. Furthermore, our framework supports both off-policy and on-policy distillation and incorporates cross-tokenizer algorithms through highly extensible and user-friendly APIs. Experiments show that KDFlow achieves a **1.44× to 6.36×** speedup over MS-SWIFT in off-policy distillation and a **1.43× to 1.75×** speedup over verl in on-policy distillation. KDFlow further scales to 64 GPUs, achieving 3.68× and 2.52× strong-scaling speedups in two representative model configurations. The code and documentation are publicly available.

[Code](#) [Documentation](#)

1 Introduction

Large Language Models (LLMs) have demonstrated remarkable capabilities across diverse tasks, yet their substantial parameter scales pose significant challenges for deployment in resource-constrained environments. Knowledge Distillation (KD) offers an effective approach to addressing this challenge by transferring knowledge from a large




Figure 1: Training time per step and the proportion of teacher forward time under different distillation configurations. The teacher’s MoE architecture poses challenges for FSDP, while being well-supported by SGLang.

teacher model to a compact student model (Hinton et al., 2015).

Despite extensive research and application of KD, the infrastructure for LLM distillation remains suboptimal. In a typical KD process, the teacher and student models play distinct roles: the teacher performs only forward passes (inference), while the student requires both forward and backward passes (training). However, most existing frameworks, such as TRL (von Werra et al., 2020) or MS-SWIFT (Zhao et al., 2025), run both models with a unified training backend. This creates a structural mismatch, as a training engine designed for gradient computation and optimizer state management is ill-suited to the teacher’s inference-heavy workload. As a result, the throughput of LLM distillation is often bounded by inefficient teacher execution, especially for Mixture-of-Experts (MoE) teachers (see Figure 1).

To address this issue, we present **KDFlow**, a high-performance framework designed specifically for LLM distillation. KDFlow decouples the teacher and student backends by assigning the

*Corresponding author.

Features	TRL	MS-SWIFT	EasyDistill	ROLL	Slime	verl	KDFlow (Ours)
KD-Native Design			✓				✓
Decoupled Backends		✓			✓	✓	✓
Off-Policy Distillation	✓	✓	✓	✓			✓
On-Policy Distillation	✓	✓		✓	✓	✓	✓
Self Distillation		✓				✓	✓
Cross-Tokenizer Distillation	✓						✓
Multi-Teacher Distillation		✓		✓	✓	✓	✓
Logits/Logprobs	full vocab	full vocab	full vocab	top- <i>k</i> vocab sampled tokens	sampled tokens	top- <i>k</i> vocab sampled tokens	full vocab
Divergence Metrics	FKL, RKL, JSD	FKL, RKL, JSD	FKL, RKL	off-policy: FKL, RKL, JSD, Skewed F(R)KL, AKL, on-policy: RKL	RKL	RKL	FKL, RKL, JSD, Skewed F(R)KL, AKL, TVD

Table 1: Comparisons between KDFlow and existing frameworks.

student to PyTorch FSDP2 and the teacher to the high-throughput inference engine SGLang (Zheng et al., 2024). A key challenge in this architecture is transferring full teacher logits from SGLang processes to FSDP processes: directly transferring full-vocabulary logits is prohibitively expensive for current LLM training¹, while transferring only top-*k* logits breaks the mathematical equivalence of the distillation objective. KDFlow solves this by collecting compact teacher hidden states from SGLang and recomputing the full logit distribution on the student side, reducing communication overhead while preserving standard KD. Compared with MS-SWIFT, KDFlow delivers a $1.44\times$ to $6.36\times$ training speedup in off-policy distillation, with larger gains for Mixture-of-Experts (MoE) teachers. In end-to-end on-policy distillation, KDFlow achieves a $1.43\times$ to $1.75\times$ speedup over verl and demonstrates effective scaling from 8 to 64 GPUs.

Despite the decoupled design, KDFlow abstracts away distributed communication and integrates with standard Hugging Face model formats, allowing users to initiate KD with only a few lines of configuration.

Overall, the contributions of KDFlow include:

- **Efficient Architecture:** KDFlow decouples teacher inference from student training by serving the teacher with SGLang and transferring compact hidden states across processes, achieving a $1.44\times$ to $6.36\times$ speedup over MS-SWIFT in off-policy distillation, a $1.43\times$ to $1.75\times$ speedup over verl in on-policy distillation, and effective scaling to 64 GPUs.
- **Comprehensiveness:** KDFlow supports comprehensive KD features (e.g., off/on-policy,

cross-tokenizer, and multi-teacher distillation) and provides multiple built-in divergence metrics and algorithms, making it an out-of-the-box toolkit for LLM distillation.

- **User-Friendly Design:** KDFlow is a lightweight framework based on FSDP2, and decouples the algorithms from the whole distillation pipeline.

2 Related Work

2.1 Knowledge Distillation for LLMs

Knowledge Distillation (KD) was first proposed by Hinton et al. (2015) to compress large models into smaller ones. For LLMs, KD is commonly divided into black-box (Kim and Rush, 2016) and white-box distillation (Zhang et al., 2023; Gu et al., 2023; Agarwal et al., 2024; Ko et al., 2024; Wu et al., 2025). White-box KD aligns the student and teacher output distributions with divergence metrics, providing richer supervision and often better performance. The paradigm has also expanded from off-policy distillation on static datasets to on-policy distillation, where the student learns from its own generated data (Gu et al., 2023; Agarwal et al., 2024; Xiao et al., 2026). Recent work further studies cross-tokenizer KD to handle vocabulary mismatches between teacher and student models (Wan et al., 2024; Boizard et al., 2024; Zhang et al., 2024, 2025; Cui et al., 2025; Chen et al., 2025; Minixhofer et al., 2025). Despite these algorithmic advances, a flexible and efficient framework for KD research remains lacking, which motivates this work.

2.2 Existing Frameworks

Existing LLM training and distillation frameworks provide useful support but still have important lim-

¹For 128 sequences with length 4096, full BF16 logits from Qwen3 models occupy $128 \times 4096 \times 151936 \times 2\text{bytes} \approx 160\text{GB}$ of memory.




Figure 2: Overview of KDFlow. The framework is built on Ray (Moritz et al., 2018) and decouples the distillation pipeline by allocating the teacher model to SGLang and the student model to FSDP2. Solid and dashed arrows illustrate the data flow for off-policy and on-policy distillation, respectively. Notably, KDFlow transfers compact hidden states from the teacher rather than full logits to reduce communication overhead.

itations. TRL (von Werra et al., 2020) and Easy-Distill (Wang et al., 2025a) support KD with homogeneous training engines, which underutilize hardware during teacher forward passes. Slime (Zhu et al., 2025) and verl (Sheng et al., 2025) decouple inference and training with engines like vLLM/SGLang, but they are not KD-specialized and only support on-policy distillation with incomplete logit information. MS-SWIFT (Zhao et al., 2025) supports both off-policy and on-policy distillation, but its implementation is relatively heavy. By contrast, **KDFlow** is a lightweight and efficient KD framework covering full KD scenarios, as detailed in Table 1.

3 The Design of KDFlow

The overall framework of KDFlow is presented in Figure 2. To address the inefficiency of using a single homogeneous engine for both inference and training, we adopt a top-down decoupled design. In this section, we introduce the system architecture, the core communication mechanism, the distillation workflows, and the algorithm abstractions.

3.1 System Architecture

The KD process typically involves multiple stages: teacher inference, student training, and student rollout, which require different backends during training. Therefore, KDFlow is built upon Ray to manage distributed processes efficiently. As shown in the middle part of Figure 2, the architecture consists of a single controller (Trainer) and three functionally independent actor groups:

- **Trainer (Single Controller):** Trainer is the central coordinator that manages the dataset, controls the training loop, and organizes the data flow among different actor groups. KDFlow supports both OffPolicyKDTrainer and OnPolicyKDTrainer.
- **RolloutActorGroup:** RolloutActorGroup is used for the rollout process of the student model during on-policy distillation. Following frontier RL frameworks like Slime (Zhu et al., 2025), it uses SGLang Router to connect multiple SGLang HTTP servers for load-balanced inference. Moreover, KDFlow uses a colocated mode and updates model weights




Figure 3: Comparison of different decoupled distillation approaches.

in SGLang via CUDA Interprocess Communication (IPC).

- **TeacherActorGroup:** TeacherActorGroup manages multiple TeacherRayActor instances that execute the forward pass of the teacher. Specifically, we initialize an SGLang engine² in each TeacherRayActor to obtain the teacher’s hidden states. This allows KDFlow to leverage SGLang’s high-throughput and flexible parallel strategies for teacher-model inference.
- **StudentActorGroup:** StudentActorGroup is deployed with PyTorch FSDP2. It handles the standard training processes for the student model, including forward pass, backward pass, and optimizer state management. Then it returns training status (e.g., the loss values) for logging.

This decoupled architecture ensures that the inference-heavy teacher model and the training-heavy student model run on their respective optimized backends, significantly improving hardware utilization.

3.2 Efficient Communication via Hidden States

In the decoupled architecture, the teacher and student typically run in separate processes, making the

²The SGLang engine is more compatible with NumPy ndarray objects than the SGLang HTTP server.

transfer of teacher knowledge a key bottleneck. Directly transmitting full logit distributions becomes prohibitive due to their large data volume, while transferring only top-k logits reduces bandwidth at the cost of breaking the mathematical equivalence of distillation and degrading performance. To address this issue, KDFlow adopts hidden-state transfer and logit recomputation, as shown in Figure 3. Instead of sending full logits, the TeacherActorGroup outputs only the teacher’s final hidden states, whose dimension (e.g., 4096) is much smaller than the vocabulary size (e.g., 151936). KDFlow further uses shared memory and the Ray shared object mechanism for zero-copy transfer across processes. After receiving the teacher’s hidden states, each StudentRayActor locally recomputes the full logit distributions using the teacher’s language model head. This design substantially reduces communication volume while preserving the mathematical equivalence to standard logit-based KD.

3.3 Distillation Workflows

Governed by the Single Controller, KDFlow seamlessly supports two main distillation workflows, illustrating the flexible data routing among the decoupled actors:

Off-Policy Distillation (Solid lines in Figure 2): The student learns from a static dataset. The Trainer sends the prompts and the corresponding responses directly to the TeacherActorGroup to obtain the teacher’s hidden states. These hidden states, along with the inputs, are then passed to the StudentActorGroup to compute the distillation loss and update the student’s weights.

On-Policy Distillation (Dashed lines in Figure 2): The student learns from data generated by the student itself. First, the Trainer sends prompts to the RolloutActorGroup to generate responses. Next, these prompt-response pairs are sent to the TeacherActorGroup to obtain the teacher’s hidden states. Then, the data and hidden states flow into the StudentActorGroup for gradient updates. Finally, the updated weights of the student model are synchronized back to the RolloutActorGroup to ensure the next generation step uses the latest policy.

3.4 Comprehensive Abstractions and Algorithms

To provide a user-friendly and out-of-the-box toolkit, KDFlow strictly separates the underlying system pipeline from the distillation algorithms. As




Figure 4: Loss curves of KDFlow and the pure FSDP implementation when distilling Qwen3-30B-A3B to Qwen3-4B.

Model	Framework	AlpacaEval 2.0	
		LC-Win Rate (%)	Win Rate (%)
Original Student	Qwen3-1.7B	26.09	21.99
Distilled Student	MS-SWIFT	28.40	27.86
	KDFlow (Pure FSDP)	28.18	28.20
	KDFlow	28.23	28.32
	KDFlow (On-Policy)	28.29	29.95
Teacher	Qwen3-30B-A3B	68.65	66.52

Table 2: Student model performance on AlpacaEval 2.0 after distillation with different frameworks.

shown at the bottom of Figure 2, KDFlow provides built-in support for various KD algorithms and divergence metrics, including Forward KL (FKL), Reverse KL (RKL), Jensen-Shannon Divergence (JSD), and Total Variation Distance (TVD). Users can also easily implement their custom distillation losses or algorithms with minimal code, eliminating the need to understand the complex distributed communication logic. Furthermore, KDFlow natively supports cross-tokenizer distillation. When the teacher and student models have different vocabularies, directly aligning their full logit distributions is impossible. Therefore, KDFlow implements the DSKDv2 (Zhang et al., 2025) algorithm for cross-tokenizer knowledge distillation.

With this decoupled design and efficient communication mechanism, KDFlow significantly improves the overall training throughput, which we will demonstrate in the following experiments.

4 Experiments

In this section, we comprehensively evaluate the KDFlow framework from the following five perspectives: (1) **Loss Correctness**: We validate the loss correctness of KDFlow by recording and analyzing its loss curves against those of the standard FSDP baseline. (2) **KD Performance**: We

compare the knowledge distillation performance of KDFlow with that of baseline frameworks on a representative downstream task. (3) **Training Efficiency**: We compare KDFlow with existing frameworks in both off-policy and on-policy distillation settings. (4) **Multi-Node Scalability**: We evaluate how KDFlow scales from one to eight nodes. (5) **Cross-Tokenizer Distillation**: We evaluate KDFlow when the teacher and student use different tokenizers.

4.1 Experimental Setup

We evaluate KDFlow on both instruction-following and mathematical-reasoning distillation tasks. The loss validation, downstream performance, and off-policy efficiency experiments use multiple Qwen3 student sizes with both dense and MoE teachers; the on-policy experiments additionally cover a DeepSeek-based configuration on DAPO-Math-17K, while the cross-tokenizer experiment distills Qwen3-14B into Llama3.2-3B. Off-policy framework comparisons use a single 8-GPU server, the on-policy efficiency comparison uses two 8-GPU nodes, and the scalability experiment uses up to eight such nodes. We report loss curves, AlpacaEval 2.0 performance in standard and cross-tokenizer settings, end-to-end training time, and multi-node scaling behavior. Detailed model, dataset, baseline, hardware, and training configurations are provided in Appendix A.

4.2 Loss Curve Validation

The core technical innovation of KDFlow is to leverage SGLang as the teacher backend and collect the teacher’s hidden states to recompute full logits on the student side. However, recent studies on RL training have shown that high-throughput inference engines may introduce numerical discrepancies during model execution, particularly for MoE models (Yao et al., 2025; Qi et al., 2025; Ma et al., 2025; Zheng et al., 2025). This motivates us to investigate whether such discrepancies affect the distillation behavior of KDFlow. Specifically, we compare the loss curves produced by KDFlow with those of a standard KD implementation, where the teacher and student are executed within the same FSDP process. As shown in Figure 4, the loss curves of KDFlow align well with the baseline throughout the entire training process. Moreover, the loss curves almost overlap for FP8 and BF16 teacher inference, which suggests that FP8 teacher inference is an efficient alternative for LLM distillation.

Framework	Training Backend	Student: Qwen3-4B			Student: Qwen3-1.7B		
		Qwen3-14B	Qwen3-32B	Qwen3-30B-A3B	Qwen3-14B	Qwen3-32B	Qwen3-30B-A3B
TRL	ZeRO-3	21.3s/it	31.5s/it	-	13.3s/it	23.4s/it	-
MS-SWIFT	ZeRO-3	16.6s/it	24.8s/it	43.2s/it	11.5s/it	20.1s/it	36.9s/it
ROLL	FSDP2	38.4s/it	56.9s/it	67.9s/it	26.8s/it	45.6s/it	53.8s/it
KDFlow (BF16 Teacher)	FSDP2	12.3s/it	15.7s/it	11.3s/it	7.6s/it	10.9s/it	5.9s/it
KDFlow (FP8 Teacher)	FSDP2	11.5s/it	13.5s/it	11.1s/it	6.7s/it	8.7s/it	5.8s/it
Speedup	-	1.44×	1.84×	3.89×	1.72×	2.31×	6.36×

Table 3: Off-policy training efficiency comparison (seconds per iteration) across different distillation frameworks. **Speedup** is calculated using KDFlow (FP8) against the best-performing baseline (i.e., MS-SWIFT). All frameworks use identical training settings: global batch size=128, gradient accumulation=8, and max length=4096.

4.3 Downstream Task Performance

Beyond training loss, we evaluate the effectiveness of the student models trained via KDFlow on downstream tasks to ensure our decoupled architecture does not compromise distillation performance. We perform off-policy distillation from Qwen3-30B-A3B to Qwen3-1.7B using the Forward KL (FKL) divergence across all frameworks. Table 2 presents the performance evaluation on the AlpacaEval 2.0 benchmark. The student model distilled via KDFlow achieves an LC-Win Rate of 28.23% and a Win Rate of 28.32%, demonstrating significant improvement over the un-distilled Qwen3-1.7B baseline. The on-policy variant further improves the Win Rate to 29.95%, showing the flexibility of KDFlow across different distillation workflows. Moreover, when compared to the students distilled using the MS-SWIFT and pure FSDP baselines, the performance differences remain within a negligible range. We also report the teacher model performance as a reference, where Qwen3-30B-A3B achieves an LC-Win Rate of 68.65% and a Win Rate of 66.52%. These results indicate that KDFlow safely optimizes the system execution pipeline and reduces communication overhead while strictly preserving the distillation quality. KDFlow acts as a transparent, high-performance infrastructure that faithfully executes KD algorithms without sacrificing downstream performance.

4.4 Training Efficiency

4.4.1 Off-Policy Distillation Efficiency

We compare the training speed of KDFlow with existing LLM distillation frameworks in the off-policy setting, where the rollout cost in on-policy distillation is excluded to better isolate the efficiency of teacher-student training. Specifically, we measure the average training time per step across

different teacher-student setups. As shown in Table 3, KDFlow is consistently the fastest framework among all FSDP2- and DeepSpeed ZeRO-3-based candidates, achieving a $1.44\times$ to $6.36\times$ speedup over MS-SWIFT. The advantage is especially pronounced for the MoE teacher Qwen3-30B-A3B, where standard training engines suffer from inefficient routing and expert management. By serving the teacher with SGLang and transferring compact hidden states instead of full logits, KDFlow reduces the distillation time to 5.8s/it.

4.4.2 On-Policy Distillation Efficiency

We further compare the end-to-end efficiency of KDFlow against verl and MS-SWIFT in the on-policy distillation setting on two nodes. The experiments are conducted on DAPO-Math-17K (Yu et al., 2025) with two student-teacher configurations: (1) Qwen3-1.7B-Base as the student and Qwen3-14B as the teacher, and (2) DeepSeek-R1-Distill-1.5B as the student and JustRL-DeepSeek-1.5B as the teacher. Detailed hyperparameters and deployment configurations are provided in Appendix A.

Table 4 reports end-to-end epoch time, covering rollout generation, teacher inference, student optimization, and weight synchronization. Under the same 16-GPU budget, verl partitions the GPUs between the student and teacher, whereas KDFlow colocates both models across the shared GPU pool. This design allows GPUs to be reused across alternating inference and training stages, reducing idle capacity and improving overall resource utilization. Overall, KDFlow achieves the lowest epoch time in both configurations: 8.1 and 3.7 hours, corresponding to $1.75\times$ and $1.43\times$ speedups over verl, respectively, demonstrating consistent efficiency gains across different student-teacher pairs.

Framework	OPD Style	GPU Allocation	Qwen3-14B → Qwen3-1.7B-Base		JustRL-1.5B → DS-R1-Distill-1.5B	
			Time (h)	Speedup	Time (h)	Speedup
verl	PG	8S + 8T	14.2	1.00×	5.3	1.00×
MS-SWIFT	PG	8S + 8T	18.6	0.76×	13.7	0.39×
	GKD	Colocate	10.6	1.34×	5.8	0.91×
KDFlow	GKD	Colocate	8.1	1.75×	3.7	1.43×

Table 4: End-to-end time per epoch for on-policy distillation on DAPO-Math-17K. Speedup is calculated relative to verl in each setting. All frameworks use FSDP2 for student training. “8S + 8T” indicates 8 GPUs for the student and 8 GPUs for the teacher.




Figure 5: Multi-node scalability of KDFlow for on-policy distillation. Scaling from 8 to 64 GPUs yields a 3.68× speedup for the Qwen3 setting and a 2.52× speedup for the DeepSeek setting. Each node contains eight NVIDIA H20 GPUs.

4.5 Multi-Node Scalability

We evaluate the scalability of KDFlow using the same two on-policy configurations as in §4.4.2 on 1, 2, 4, and 8 nodes, each with eight NVIDIA H20 GPUs, while fixing the dataset, training configuration, and one-epoch workload.

As shown in 5, KDFlow consistently benefits from additional computational resources across both configurations. For the Qwen3 configuration, increasing the number of GPUs from 8 to 64 reduces the epoch time from 14.0 hours to 3.8 hours, yielding a 3.68× speedup. For the DeepSeek configuration, the epoch time decreases from 5.8 hours to 2.3 hours, corresponding to a 2.52× speedup. The Qwen3 configuration exhibits stronger scaling, as its larger teacher model benefits more from the parallel computation of additional GPU resources. Overall, these results demonstrate that KDFlow effectively scales beyond a single node and can support large-scale on-policy distillation across distributed GPU clusters.

Model	Setting	AlpacaEval 2.0	
		LC-Win Rate (%)	Win Rate (%)
Original Student	Llama3.2-3B	15.26	18.45
Distilled Student	SeqKD	29.72	39.32
	DSKD + KL	32.88	42.54
Teacher	Qwen3-14B	73.31	72.51

Table 5: Cross-tokenizer distillation performance on AlpacaEval 2.0.

4.6 Cross-Tokenizer Distillation

We further verify KDFlow in a cross-tokenizer setting, where the teacher and student use different tokenizers and cannot be directly aligned through vanilla full-vocabulary KL divergence. Specifically, we distill knowledge from Qwen3-14B into Llama3.2-3B and find that KDFlow’s DSKD-based objective further improves over sequence-level KD. As shown in Table 5, DSKD + KL improves the LC-Win Rate from 29.72% to 32.88% and the Win Rate from 39.32% to 42.54% compared with sequence-level KD.

5 Conclusion

In this paper, we present **KDFlow**, an efficient and user-friendly framework for LLM knowledge distillation, which decouples SGLang-based teacher inference from FSDP2-based student training. By transferring teacher hidden states and recomputing logits on the student side, KDFlow reduces communication overhead while preserving theoretical equivalence to full-vocabulary KD. KDFlow achieves 1.44× to 6.36× speedups over MS-SWIFT in off-policy distillation and 1.43× to 1.75× speedups over verl in on-policy distillation, while demonstrating strong multi-node scalability. With native support for off-policy, on-policy, and cross-tokenizer distillation, KDFlow provides a flexible infrastructure for efficient LLM compression and post-training.

Limitations

While KDFlow significantly improves the efficiency and flexibility of LLM distillation, it has certain limitations. First, although KDFlow demonstrates effective scaling up to 64 GPUs, its current student training backend is built entirely upon PyTorch FSDP2 and lacks the complex 3D parallelism of Megatron-LM (Shoeybi et al., 2019); scalability to substantially larger models and clusters therefore remains unverified. Second, as a

research-oriented framework, KDFlow currently lacks some industrial-grade optimizations, such as asynchronous training, which are crucial for training on clusters with thousands of GPUs. However, KDFlow explicitly prioritizes the needs of the research community: user-friendliness, high flexibility, and rapid prototyping. By abstracting away complex distributed communication logic, KDFlow allows researchers to easily implement and test novel off-policy, on-policy, or cross-tokenizer distillation algorithms with minimal engineering overhead. Integrating Megatron-LM and further optimizations remain important directions for our future work.

References

- Rishabh Agarwal, Nino Vieillard, Yongchao Zhou, Piotr Stanczyk, Sabela Ramos Garea, Matthieu Geist, and Olivier Bachem. 2024. On-policy distillation of language models: Learning from self-generated mistakes. In *The twelfth international conference on learning representations*.
- Nicolas Boizard, Kevin El Haddad, Céline Hudelot, and Pierre Colombo. 2024. Towards cross-tokenizer distillation: the universal logit distillation loss for llms. *arXiv preprint arXiv:2402.12030*.
- Yijie Chen, Yijin Liu, Fandong Meng, Yufeng Chen, Jinan Xu, and Jie Zhou. 2025. Enhancing cross-tokenizer knowledge distillation with contextual dynamical mapping. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 8005–8018.
- Xiao Cui, Mo Zhu, Yulei Qin, Liang Xie, Wengang Zhou, and Houqiang Li. 2025. Multi-level optimal transport for universal cross-tokenizer knowledge distillation on language models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 23724–23732.
- Yuxian Gu, Li Dong, Furu Wei, and Minlie Huang. 2023. Minillm: Knowledge distillation of large language models. *arXiv preprint arXiv:2306.08543*.
- Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. 2015. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*.
- Yoon Kim and Alexander M Rush. 2016. Sequence-level knowledge distillation. In *Proceedings of the 2016 conference on empirical methods in natural language processing*, pages 1317–1327.
- Jongwoo Ko, Sungnyun Kim, Tianyi Chen, and Se Young Yun. 2024. Distillm: Towards streamlined distillation for large language models. *Proceedings of Machine Learning Research*, 235:24872–24895.
- Wenhan Ma, Hailin Zhang, Liang Zhao, Yifan Song, Yudong Wang, Zhifang Sui, and Fuli Luo. 2025. Stabilizing moe reinforcement learning by aligning training and inference routers. *arXiv preprint arXiv:2510.11370*.
- Benjamin Minixhofer, Ivan Vulić, and Edoardo M Ponti. 2025. Cross-tokenizer distillation via approximate likelihood matching.
- Philipp Moritz, Robert Nishihara, Stephanie Wang, Alexey Tumanov, Richard Liaw, Eric Liang, Melih Elibol, Zongheng Yang, William Paul, Michael I Jordan, and 1 others. 2018. Ray: A distributed framework for emerging {AI} applications. In *13th USENIX symposium on operating systems design and implementation (OSDI 18)*, pages 561–577.
- Penghui Qi, Zichen Liu, Xiangxin Zhou, Tianyu Pang, Chao Du, Wee Sun Lee, and Min Lin. 2025. Defeating the training-inference mismatch via fp16. *arXiv preprint arXiv:2510.26788*.
- Guangming Sheng, Chi Zhang, Zilingfeng Ye, Xibin Wu, Wang Zhang, Ru Zhang, Yanghua Peng, Haibin Lin, and Chuan Wu. 2025. Hybridflow: A flexible and efficient rlhf framework. In *Proceedings of the Twentieth European Conference on Computer Systems*, pages 1279–1297.
- Mohammad Shoeybi, Mostofa Patwary, Raul Puri, Patrick LeGresley, Jared Casper, and Bryan Catanzaro. 2019. Megatron-lm: Training multi-billion parameter language models using model parallelism. *arXiv preprint arXiv:1909.08053*.
- Leandro von Werra, Younes Belkada, Lewis Tunstall, Edward Beeching, Tristan Thrush, Nathan Lambert, Shengyi Huang, Kashif Rasul, and Quentin Galouédec. 2020. [TRL: Transformers Reinforcement Learning](#).
- Fanqi Wan, Xinting Huang, Deng Cai, Xiaojun Quan, Wei Bi, and Shuming Shi. 2024. Knowledge fusion of large language models. *arXiv preprint arXiv:2401.10491*.
- Chengyu Wang, Junbing Yan, Wenrui Cai, Yuanhao Yue, and Jun Huang. 2025a. Easydistill: A comprehensive toolkit for effective knowledge distillation of large language models. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 787–795.
- Weixun Wang, Shaopan Xiong, Gengru Chen, Wei Gao, Sheng Guo, Yancheng He, Ju Huang, Jiaheng Liu, Zhendong Li, Xiaoyang Li, and 1 others. 2025b. Reinforcement learning optimization for large-scale learning: An efficient and user-friendly scaling library. *arXiv preprint arXiv:2506.06122*.
- Taiqiang Wu, Chaofan Tao, Jiahao Wang, Runming Yang, Zhe Zhao, and Ngai Wong. 2025. Rethinking kullback-leibler divergence in knowledge distillation for large language models. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 5737–5755.

- Bangjun Xiao, Bingquan Xia, Bo Yang, Bofei Gao, Bowen Shen, Chen Zhang, Chenhong He, Chiheng Lou, Fuli Luo, Gang Wang, and 1 others. 2026. Mimo-v2-flash technical report. *arXiv preprint arXiv:2601.02780*.
- An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.
- Feng Yao, Liyuan Liu, Dinghuai Zhang, Chengyu Dong, Jingbo Shang, and Jianfeng Gao. 2025. [Your efficient rl framework secretly brings you off-policy rl training](#).
- Qiyang Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Tiantian Fan, Gaohong Liu, Lingjun Liu, Xin Liu, and 1 others. 2025. Dapo: An open-source llm reinforcement learning system at scale. *arXiv preprint arXiv:2503.14476*.
- Songming Zhang, Yunlong Liang, Shuaibo Wang, Yufeng Chen, Wenjuan Han, Jian Liu, and Jinan Xu. 2023. [Towards understanding and improving knowledge distillation for neural machine translation](#). In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8062–8079, Toronto, Canada. Association for Computational Linguistics.
- Songming Zhang, Xue Zhang, Zengkui Sun, Yufeng Chen, and Jinan Xu. 2024. Dual-space knowledge distillation for large language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 18164–18181.
- Xue Zhang, Songming Zhang, Yunlong Liang, Fandong Meng, Yufeng Chen, Jinan Xu, and Jie Zhou. 2025. A dual-space framework for general knowledge distillation of large language models. *arXiv preprint arXiv:2504.11426*.
- Yuze Zhao, Jintao Huang, Jinghan Hu, Xingjun Wang, Yunlin Mao, Daoze Zhang, Zeyinzi Jiang, Zhikai Wu, Baole Ai, Ang Wang, and 1 others. 2025. Swift: a scalable lightweight infrastructure for fine-tuning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 29733–29735.
- Chujie Zheng, Kai Dang, Bowen Yu, Mingze Li, Huiqiang Jiang, Junrong Lin, Yuqiong Liu, Hao Lin, Chencan Wu, Feng Hu, and 1 others. 2025. Stabilizing reinforcement learning with llms: Formulation and practices. *arXiv preprint arXiv:2512.01374*.
- Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Tianle Li, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zhuohan Li, Zi Lin, Eric P Xing, Joseph E. Gonzalez, Ion Stoica, and Hao Zhang. 2023. [Lmsys-chat-1m: A large-scale real-world llm conversation dataset](#). *Preprint*, arXiv:2309.11998.
- Lianmin Zheng, Liangsheng Yin, Zhiqiang Xie, Chuyue Livia Sun, Jeff Huang, Cody Hao Yu, Shiyi Cao, Christos Kozyrakis, Ion Stoica, Joseph E Gonzalez, and 1 others. 2024. Sglang: Efficient execution of structured language model programs. *Advances in neural information processing systems*, 37:62557–62583.
- Zilin Zhu, Chengxing Xie, Xin Lv, and slime Contributors. 2025. slime: An llm post-training framework for rl scaling. <https://github.com/THUDM/slime>. GitHub repository. Corresponding author: Xin Lv.

A Experimental Setup Details

A.1 Off-Policy Distillation

Models and Data. We randomly sample 100,000 instruction-following prompts from LMSys-Chat-1M (Zheng et al., 2023) and generate responses with Qwen3-14B. The loss validation, downstream performance, and efficiency experiments use Qwen3-14B, Qwen3-32B, and Qwen3-30B-A3B as teachers and Qwen3-4B and Qwen3-1.7B as students (Yang et al., 2025). The cross-tokenizer experiment uses Qwen3-14B as the teacher and Llama3.2-3B as the student. For AlpacaEval 2.0, we use Qwen3-235B-2507-Instruct as the evaluator model.

Baselines and Configuration. We compare KD-Flow with TRL (von Werra et al., 2020), ROLL (Wang et al., 2025b), and MS-SWIFT (Zhao et al., 2025). The efficiency experiments use a global batch size of 128, gradient accumulation of 8, and a maximum sequence length of 4,096. All off-policy experiments run on one server with 8 NVIDIA H20 GPUs and CUDA 12.9.

A.2 On-Policy Distillation

Models and Data. We use DAPO-Math-17K (Yu et al., 2025) and evaluate two teacher–student configurations: Qwen3-14B $\rightarrow$ Qwen3-1.7B-Base and JustRL-DeepSeek-1.5B $\rightarrow$ DeepSeek-R1-Distill-1.5B.

Training Configuration. The maximum input and generation lengths are 1,024 and 7,168, respectively; each rollout batch contains 64 prompts and four sampled responses per prompt. All frameworks use the same dataset and generation settings, with optimization hyperparameters matched where supported.

Baselines and Hardware. We compare KDFlow with verl (Sheng et al., 2025) and MS-SWIFT. The efficiency comparison uses two identical 8-GPU H20 nodes with CUDA 12.9: verl and MS-SWIFT with PG-OPD allocate 8 GPUs each to the student and teacher, whereas MS-SWIFT with GKD and KDFlow colocate them over the shared 16 GPUs. The scalability experiments use the same one-epoch workloads and generation settings on one, two, four, and eight identical nodes.