Recognising without recalling:

a small recurrent memory recognises long after it stops recalling

Ivan Rodkin

benchmark: `irodkin/recognition-memory`

Takeaway

A memory can tell whether an input is familiar long after it can no longer reproduce it.

- Shrinking a GDN-2 state, **exact recall fails first**: small states still recognise sequences **2–8**× longer than they can copy.
- At $16{\times}4$, $N{=}256$ the memory **trained for recognition** is ahead: acc9 **0.88** [0.74–1.00] vs. **0.45** [0.27–0.63] for surprise (chance 0.11).
- Training it needs a **length curriculum**, and at small states it is **not reproducible**: the same seed can learn or collapse.

Hypothesis

Memory need not *reproduce* the past. It can instead *recognise* whether an input is consistent with it, using low **surprise** as the familiarity signal. Checking is easier than generating, so recognition should need **less capacity** than recall.

Benchmark: one sequence, eight near-copies

Uniform i.i.d. tokens, vocabulary 16 (4 bits each), $N = 4 \dots 256$. Each comes with **8 corrupted copies**: one forced change plus $p = \frac{1}{N-1}$ elsewhere, so **2 changes on average**.

true	3	a	0	f	7	7	c	1	9	e	4	2	b	5	d	8
copy	3	a	0	f	7	2	c	1	9	e	4	2	b	5	d	8

Task. Score the true sequence and its 8 copies.
acc9: true one ranked first (chance $1/9$). **pairwise**: true beats one copy (chance $1/2$).

Capacity, in theory. Recall needs all $4N$ bits (1,024 at $N{=}256$). Recognition needs a few: keeping only the token sum mod 16 (4 bits) gives acc9 0.85; adding a position-weighted sum (8 bits) gives 0.965, at *every* N.

Model: one network, two readouts

2-layer Gated DeltaNet-2 (`fla`), width 128, one head. The only memory is the recurrent state, $d_k{\times}d_v$ per layer: $128{\times}128$ (16,384 numbers) down to $16{\times}4$ (64).

state $S_t \in \mathbb{R}^{d_k \times d_v}$ carries x forward


BOS | sequence $x_{1..N}$ | SEP | candidate $c_{1..N}$

Recall model
trained to copy x (next-token CE)
score $=$ −surprise
$= \sum_j \log p(c_j \mid x, c_{<j})$

Recognition model
trained on "is $c = x$?"
(BCE, or ranking loss)
score $=$ logit at the last token

1 Full-size state: recall is easy, recognition needs a curriculum

At $128{\times}128$ the **recall model** copies every length almost perfectly (exact copy 0.988 at $N{=}256$), and its surprise ranks the true sequence first in *every* test sample. The **recognition model**, trained directly, fails from $N{=}64$ on: its loss sits at $\ln 2$ (a constant output) for all 35k steps. The same network learns recall in $<1{,}000$ steps, so this is an **optimisation** failure, not a capacity limit.
Length curriculum: for the first half of training, use prefixes $16, 32, \dots, N$ (equal time each), plus an **easy-negative warm-up** (heavily corrupted negatives that fade out); then full length.




Validation acc9 (full length), $128{\times}128$. Curriculum runs: 3 epochs; others: 10 (first 11k steps).

- **Length curriculum**: acc9 $= 1.000$ at $N{=}128$ and 256. The warm-up alone fixes only $N{=}64$.
- With it, **all 72** sweep and seed runs train; none ends at $\ln 2$.

2 Small states: training is a coin flip

The same code and seed gave acc9 **0.871** in the sweep and **0.058** in a rerun on another GPU model (kernels aren't bit-identical). Each small-state run is one draw from a two-humped distribution. Tried: a **ranking loss**, loss $= \mathrm{softplus}(s_{\text{neg}} - s_{\text{true}})$ on the same last-token score, curriculum from length 4.



Recognition model, baseline and ranking loss, 3 runs per configuration ($16{\times}4$–$16{\times}16$). (a) hollow: $N{=}256$. (b) filled: 10 epochs; hollow: 20, more curriculum time on long prefixes.


- Up to $N{=}128$ the **ranking loss** fails less (2 vs. 7 of 33 below 0.95; $p{=}0.07$): suggestive, not significant. It also collapses (0.06).
- At $N{=}256$ it is worse (0.92 vs. 0.96), and 20 epochs hurt both (b).

What a failed run is (28 instrumented reruns):

- **The right comparison, less precise.** It uses order (shuffles caught 0.995) and is no sum checksum (sum-kept edits 0.936 = random 0.937), but catches a single change 0.89 vs. 0.997.
- **Decided during the curriculum:** 78–81% vs. 98–99% single-change detection at its end; only 86–90% after.

3 Shrinking the state: recall goes first

6 state sizes ($16{\times}4$ to $128{\times}128$) × 7 lengths × 2 objectives, 10 epochs each, tested on 100k sequences; 3 seeds at the three smallest states. Recognition model: BCE + length curriculum.



Three smallest states, seeds 0–2, test acc9 and recall: mean (line), min–max (band), each seed (dots).

- **Recognition outlasts recall.** Longest length that passes (powers of 2 tested):

state	$16{\times}4$	$16{\times}8$	$16{\times}16$	$32{\times}32$	$64{\times}64$	$128{\times}128$
exact copy ≥ 0.9	32	32	64	128	128	≥ 256
surprise acc9 ≥ 0.99	64	128	≥ 256	≥ 256	≥ 256	≥ 256
recognition* acc9 ≥ 0.99	**128**	≥ 256	≥ 256	≥ 256	≥ 256	≥ 256

At the three smallest states recognition reaches **2–8**× the copy length; from $32{\times}32$ up, $N{=}256$ hides the gap. At $16{\times}16$, $N{=}256$ the recall model keeps ≥ 536 of 1,024 bits, copies nothing exactly, yet both readouts score ≥ 0.996. *Best of the 3 sweep runs (1 from $32{\times}32$ up); the median run fails at shorter lengths. Fresh seeds 3–5 take $16{\times}4$ to ≥ 256. Bar 0.99: an 8-bit checksum already scores 0.965.

- **Smallest state: the recognition model is ahead.**

$16{\times}4$	recall tokens	surprise, 3 runs	recognition, 6 runs
$N{=}128$	0.30	0.59 [0.09–0.97]	**0.98** [0.95–1.00]
$N{=}256$	0.20	0.45 [0.27–0.63]	**0.88** [0.74–1.00]

At $N{=}256$ its worst run (0.74) beats surprise's best (0.63). Few runs per cell, but large margins.

- Near capacity, **surprise** depends on what the memory chose to keep: 0.97, 0.73, 0.09 across seeds at $N{=}128$.
- At $16{\times}8$ the two are about even ($N{=}256$: 0.94 vs. 0.98).

Next

- **More runs per cell** (6–10, both readouts) to measure failure rates.
- **Train precision early**: keep 1–2-token negatives from the start, or restart weak runs.
- **Harder benchmarks** where checksums fail; K stored sequences per context.

3 seeds at $16{\times}4$–$16{\times}16$ for $N \geq 16$ (6 recognition runs in the $16{\times}4$ table), seed 0 elsewhere. The three smallest states shrink d_v only (fla kernels need $d_k \geq 16$); across them the parameter count changes by 4%.