# Recognising without recalling:

## a small recurrent memory recognises long after it stops recalling

Ivan Rodkin

benchmark: `irodkin/recognition-memory`

### Takeaway

A memory can tell whether an input is familiar long after it can no longer reproduce it.

- Shrinking a GDN-2 state, **exact recall fails first**: copying stops at $N{=}32$–$512$, yet every state's best run recognises at $N{=}1{,}024$.
- At $16{\times}4$, $N{=}256$ the memory **trained for recognition** is ahead: acc9 **0.88** [0.74–1.00] vs. **0.45** [0.27–0.63] for surprise (chance 0.11).
- Training it needs a **length curriculum**, and at small states it is **not reproducible**: the same seed can learn or collapse.

### Hypothesis

Memory need not *reproduce* the past. It can instead *recognise* whether an input is consistent with it, using low **surprise** as the familiarity signal. Checking is easier than generating, so recognition should need **less capacity** than recall.

### Benchmark: one sequence, eight near-copies

Uniform i.i.d. tokens, vocabulary 16 (4 bits each), $N = 4 \ldots 1{,}024$. Each comes with **8 corrupted copies**: one forced change plus $p = \frac{1}{N-1}$ elsewhere, so **2 changes on average**.


| | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| true | 3 | a | 0 | f | 7 | 7 | c | 1 | 9 | e | 4 | 2 | b | 5 | d | 8 |
| copy | 3 | a | 0 | f | 7 | 2 | c | 1 | 9 | e | 4 | 2 | b | 5 | d | 8 |

**Task.** Score the true sequence and its 8 copies.
**acc9**: true one ranked first (chance $1/9$). **pairwise**: true beats one copy (chance $1/2$).

**Capacity, in theory.** Recall needs all $4N$ bits (1,024 at $N{=}256$). Recognition needs a few: keeping only the token sum mod 16 (4 bits) gives acc9 0.85; adding a position-weighted sum (8 bits) gives 0.965, at *every* $N$.


### Model: one network, two readouts

2-layer Gated DeltaNet-2 (`fla`), width 128, one head. The only memory is the recurrent state, $d_k{\times}d_v$ per layer: $128{\times}128$ (16,384 numbers) down to $16{\times}4$ (64).




### 1 Full-size state: recall is easy, recognition needs a curriculum

At $128{\times}128$, $N{\le}256$ the **recall model** copies almost perfectly (exact copy $0.988$ at $N{=}256$), and its surprise ranks the true sequence first in *every* test sample. The **recognition model**, trained directly, fails from $N{=}64$ on: its loss sits at $\ln 2$ (a constant output) for all 35k steps. The same network learns recall in $<1{,}000$ steps, so this is an **optimisation** failure, not a capacity limit.
**Length curriculum:** for the first half of training, use prefixes $16, 32, \ldots, N$ (equal time each), plus an **easy-negative warm-up** (heavily corrupted negatives that fade out); then full length.





Validation acc9 (full length), $128{\times}128$. Curriculum runs: 3 epochs; others: 10 (first 11k steps).

- **Length curriculum**: acc9 $= 1.000$ at $N{=}128$ and $256$. The warm-up alone fixes only $N{=}64$.
- With it, **all 72** sweep and seed runs train; none ends at $\ln 2$.

### 2 Small states: training is a coin flip

The same code and seed gave acc9 **0.871** in the sweep and **0.058** in a rerun on another GPU model (consistent with non-deterministic kernels). Outcomes are two-humped. Tried: a **ranking loss**, loss $= \mathrm{softplus}(s_{\text{neg}} - s_{\text{true}})$ on the same score, curriculum from length 4.




Recognition model, baseline and **ranking loss**, 3 runs per configuration ($16{\times}4$–$16{\times}16$). (a) hollow: $N{=}256$. (b) filled: 10 epochs; hollow: 20, more curriculum time on long prefixes.


- Up to $N{=}128$ the **ranking loss** fails less (2 vs. 7 of 33 below 0.95; $p{=}0.07$, not significant) but also collapses (0.06); at $N{=}256$ it is worse (0.92 vs. 0.96). No evidence 20 epochs help; possibly worse (b).

**What a failed run is** (28 instrumented reruns):

- **The right comparison, less precise.** It uses order (shuffles caught 0.995) and is no sum checksum (sum-kept edits 0.936 = random 0.937), but catches a single change 0.89 vs. 0.997.
- **Decided during the curriculum:** 78–81% vs. 98–99% single-change detection at its end; only 86–90% after.
- **Small-edit negatives from step 1 don't help** ($16{\times}4$, $N{=}16, 32$): 7 of 24 runs fail with a 25% share, as without; 11 of 24 with 50%.

### 3 Shrinking the state: recall goes first

6 states ($16{\times}4$ to $128{\times}128$), lengths up to 1,024, 2 objectives, 10 epochs each; 3 seeds at the smallest three. Recognition model: BCE + length curriculum.




Three smallest states, seeds 0–2: mean (line), min–max (band), each seed (dots). Recall model not run past 256 at $16{\times}4$, $16{\times}8$. $N{\ge}512$: fresh corruptions in training.

- **Recognition outlasts recall.** Longest length that passes:

| state | $16{\times}4$ | $16{\times}8$ | $16{\times}16$ | $32{\times}32$ | $64{\times}64$ | $128{\times}128$ |
|---|---|---|---|---|---|---|
| exact copy $\ge 0.9$ | 32 | 32 | 64 | 128 | 128 | 512 |
| **surprise** acc9 $\ge 0.99$ | 64† | 128† | 1k+ | 1k+ | 1k+ | 1k+ |
| **recognition** acc9 $\ge 0.99$ | **1k+** | **1k+** | 512 | 256 | 1k+ | 1k+ |

Every state has a run that recognises at $N{=}1{,}024$: at least **32**× its copy length at the two smallest, $2{\times}$ at the largest. Best of 3 runs (1 from $32{\times}32$ up); 1k+: passes at 1,024, the longest tested. †Not run past 256. Bar 0.99: an 8-bit checksum scores 0.965. Corruptions: ∼2 tokens at every length.

- **Strongest result, least reliable.** $16{\times}4$ passes at $N{=}1{,}024$ in 1 of 3 runs (0.99; others 0.82, 0.69) and in none at $N{=}512$; its median run passes up to $N{=}128$, $4{\times}$ its copy length. These misses look like training, not capacity: $16{\times}8$ passes at $N{=}1{,}024$, $32{\times}32$ just misses (0.989).
- **Smallest state: the recognition model is ahead.**

| $16{\times}4$ | recall tokens | **surprise**, 3 runs | **recognition**, 6 runs |
|---|---|---|---|
| $N{=}128$ | 0.30 | 0.59 [0.09–0.97] | **0.98** [0.95–1.00] |
| $N{=}256$ | 0.20 | 0.45 [0.27–0.63] | **0.88** [0.74–1.00] |

At $N{=}256$ its worst run (0.74) beats surprise's best (0.63). Few runs per cell, but large margins.

- **Surprise** depends more on what the memory keeps than on how much: at $16{\times}16$, $N{=}1{,}024$ a run keeping 9% of the bits scores 0.997, one keeping 13% scores 0.84.
- At $16{\times}8$ the two are about even ($N{=}256$: 0.94 vs. 0.98).

### Next

- **More runs per cell** (6–10, both readouts) to measure failure rates.
- **Restarts**: train several starts for ∼5k steps, continue the lowest-loss one; needs testing, as the step-4k loss predicts the outcome only weakly ($\rho{=}-0.47$). Training changes tried so far don't remove the failures.
- **Harder benchmarks** where checksums fail; $K$ sequences per context.

3 seeds at $16{\times}4$–$16{\times}16$ for $N \ge 16$ (6 recognition runs in the $16{\times}4$ table), seed 0 elsewhere. The three smallest states shrink $d_v$ only (fla kernels need $d_k \ge 16$); across them the parameter count changes by 4%.