Agent estate scan results

Complete. Every listed source was read in full.

Estate	example-code
Scan	`example-code-20261114T140215Z-7af93865`
As of (UTC)	2026-11-14T14:02:15.928Z
Scanner	agt_example, version 0.15.0
Scanner manifest	`sha256:885886a3315b34fb8bc870a37fcd34993ee77af4abdaf9fca5052311b8f1f053`
Report contract	inflect-agent-harness/4
Ladder version	`sha256:b3aa459c8e48dc7dc7528f117de754cf1be24e53f7ec47c8ac81c471ec28d7ae`
Signed report SHA-256	`6b6ef1fece711f3bccc0770c03657a293f26e0d22e8a4a3e05566677cdc5b0fc`
Signer	Pinned: verified against a key supplied apart from the report

The estate in numbers

Agents found	1
Judged	1 (have a level)
Not judged	0 (no level stated)
Below their bar	1 of the judged agents held to a bar
Shadow agents	0
Unregistered identities	0 (no sign of a model; held to no bar)
Orphan credentials	0
Can pay	0 (code calls a payment client)
Sources incomplete	0 of 1
Findings	2
Registration from	The operator’s inventory (declared by the operator, not observed)

Judged agents per level

Not judged, and not counted above: 0.

1. Completeness per source

Every source this scan lists was read in full, so each result below rests on a whole read.

Source	Status	Reason	Rows read	Agents found
code	Complete		1	1

What this scan could not evidence

The highest level this run could have stated for any agent is H1 Registered. A criterion nobody answered counts as not met, so no agent is shown above that level, whatever its real state. The bar is H2 for an agent that only reads and H3 for one that can write or reach outside the estate.

Criterion with no configured reader	Why	Readers that would
H2.credential_bound	A reader exists; this run did not configure it (READER_NOT_CONFIGURED)	entra-sp, gcp-sa, cicd, inflect-register
H2.grant_kind_declared	A reader exists; this run did not configure it (READER_NOT_CONFIGURED)	okta-app, gcp-sa, cicd, inflect-register
H2.tools_allowlisted	A reader exists; this run did not configure it (READER_NOT_CONFIGURED)	cicd, inflect-register
H2.audience_tokens	A reader exists; this run did not configure it (READER_NOT_CONFIGURED)	inflect-register
H2.policy_card	A reader exists; this run did not configure it (READER_NOT_CONFIGURED)	inflect-register
H3.manifests_pinned	A reader exists; this run did not configure it (READER_NOT_CONFIGURED)	inflect-register
H3.payloads_guarded	A reader exists; this run did not configure it (READER_NOT_CONFIGURED)	inflect-register
H3.propose_not_commit	A reader exists; this run did not configure it (READER_NOT_CONFIGURED)	inflect-register
H3.prior_state_reads	A reader exists; this run did not configure it (READER_NOT_CONFIGURED)	inflect-register
H3.skills_declared	A reader exists; this run did not configure it (READER_NOT_CONFIGURED)	inflect-register
H3.delegation_narrows	A reader exists; this run did not configure it (READER_NOT_CONFIGURED)	inflect-register
H3.egress_enforced	A reader exists; this run did not configure it (READER_NOT_CONFIGURED)	inflect-register
H4.ledger_baseline	No reader in scanent reports this criterion (NO_READER)	None
H4.receipts	No reader in scanent reports this criterion (NO_READER)	None
H4.kill_switch_drilled	No reader in scanent reports this criterion (NO_READER)	None
H4.token_budget	No reader in scanent reports this criterion (NO_READER)	None
H5.asi_coverage	No reader in scanent reports this criterion (NO_READER)	None
H5.evidence_emitted	No reader in scanent reports this criterion (NO_READER)	None
H5.skills_evaluated	No reader in scanent reports this criterion (NO_READER)	None
H5.sample_audit	No reader in scanent reports this criterion (NO_READER)	None
H5.independent_audit	No reader in scanent reports this criterion (NO_READER)	None

2. Findings by severity

Critical	0
High	2

Medium	0
Low	0

HIGH UNPINNED_WRITE_TOOL code:example/support/agent.py#support_executor

Unpinned write-capable tool on agent code:example/support/agent.py#support_executor

A harness scan (scan example-code-20261114T140215Z-7af93865, scanner agt_example) found 1 write-capable tool(s) with no pinned definition on agent code:example/support/agent.py#support_executor: lookup_order on code://example/support/agent.py#L7. A tool the agent may call with a definition nobody reviewed can change under it without anyone noticing.

`Reference UNPINNED_WRITE_TOOL:code:example/support/agent.py#support_executor`

HIGH HARNESS_SHORTFALL code:example/support/agent.py#support_executor

Agent code:example/support/agent.py#support_executor is below the harness bar (H1, bar H3)

A harness scan (scan example-code-20261114T140215Z-7af93865, scanner agt_example) found agent code:example/support/agent.py#support_executor at H1, whose reach is WRITE_OR_EXTERNAL; the bar for that reach is H3. Criteria blocking the next rung: H2.credential_bound, H2.grant_kind_declared, H2.tools_allowlisted, H2.audience_tokens, H2.policy_card. This finding never blocks the agent: it closes when a later scan shows the agent at the bar, or with a time-limited acceptance by the agent's owner. The level H1 rests in part on what the operator declared in the inventory; on what the sources observed alone it is H0.

`Reference HARNESS_SHORTFALL:code:example/support/agent.py#support_executor`

3. Agents and their levels

One row per agent, those that most need a reader first: not judged, then below their bar, then the lowest levels. An unregistered automated identity is held to no bar.

Agent	Registration	Reach	Level	Bar
`code:example/support/agent.py#support_executor (Support order lookup, name declared by the operator)`	Declared by the operator	Write or external	H1 Registered; H0 on observation alone	H3: Below bar

4. Agents and criteria

Each cell is the shared table model's state for one criterion, by its code. The criteria are numbered; the key is below the table.

E Evidenced: a source observed it. D Evidenced on what the operator declared in the inventory, not observed. M Reported met without evidence; counts as not met. N Not met: a source saw it fail. n Not met on what the operator declared in the inventory; no source saw it fail. · Unanswered: a configured reader could have reported it and none did; counts as not met. – Not readable: nothing this run was configured to read could have reported it; counts as not met.

			H1				H2								H3							H4					H5			
Agent	**Level**	**Standing**	**1**	**2**	**3**	**4**	**5**	**6**	**7**	**8**	**9**	**10**	**11**	**12**	**13**	**14**	**15**	**16**	**17**	**18**	**19**	**20**	**21**	**22**	**23**	**24**	**25**
`code:example/support/agent.py#support_executor`	H1	Below	**D**	**D**	**D**	**D**	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–

Key to the criteria

No.	Criterion	In words	No.	Criterion	In words
1	`H1.registered`	registered	14	`H3.skills_declared`	skills declared
2	`H1.owner`	owner	15	`H3.delegation_narrows`	delegation narrows
3	`H1.axes_declared`	axes declared	16	`H3.egress_enforced`	egress enforced
4	`H1.tier_scored_fresh`	tier scored fresh	17	`H4.ledger_baseline`	ledger baseline
5	`H2.credential_bound`	credential bound	18	`H4.receipts`	receipts
6	`H2.grant_kind_declared`	grant kind declared	19	`H4.kill_switch_drilled`	kill switch drilled
7	`H2.tools_allowlisted`	tools allowlisted	20	`H4.token_budget`	token budget
8	`H2.audience_tokens`	audience tokens	21	`H5.asi_coverage`	asi coverage
9	`H2.policy_card`	policy card	22	`H5.evidence_emitted`	evidence emitted
10	`H3.manifests_pinned`	manifests pinned	23	`H5.skills_evaluated`	skills evaluated
11	`H3.payloads_guarded`	payloads guarded	24	`H5.sample_audit`	sample audit
12	`H3.propose_not_commit`	propose not commit	25	`H5.independent_audit`	independent audit
13	`H3.prior_state_reads`	prior state reads			

5. Each agent

One section per agent, in the order of the table above. Every criterion is listed under its state.

Support order lookup

Id	`code:example/support/agent.py#support_executor`
Name	Support order lookup (declared by the operator)
Classification	Registered
Registration	`Declared by the operator (inventory:row-1)`
Reach	Write or external
Found through	`code (read in full)`
Owner	support-operations (declared by the operator)
Purpose	Answers customers' questions about an order's status (declared by the operator)
Owner observed	`None read from the estate`
Level	H1 Registered; H0 on observation alone
Bar	H3, and it is below it.
Next rung needs	H2.credential_bound, H2.grant_kind_declared, H2.tools_allowlisted, H2.audience_tokens, H2.policy_card
Credentials, tools	1 credentials; 1 tools, 1 that can write, 1 of those not pinned
Payment	Code read; no payment client seen in the agent's own file. Not evidence that it cannot pay.

D Declared: H1.registered (evidence inventory:sha256:28892c7767866a58#row-1); H1.owner (evidence inventory:sha256:28892c7767866a58#row-1); H1.axes_declared (evidence inventory:sha256:28892c7767866a58#row-1); H1.tier_scored_fresh (evidence inventory:sha256:28892c7767866a58#row-1)

– Not readable: H2.credential_bound; H2.grant_kind_declared; H2.tools_allowlisted; H2.audience_tokens; H2.policy_card; H3.manifests_pinned; H3.payloads_guarded; H3.propose_not_commit; H3.prior_state_reads; H3.skills_declared; H3.delegation_narrows; H3.egress_enforced; H4.ledger_baseline; H4.receipts; H4.kill_switch_drilled; H4.token_budget; H5.asi_coverage; H5.evidence_emitted; H5.skills_evaluated; H5.sample_audit; H5.independent_audit

Findings: HIGH UNPINNED_WRITE_TOOL; HIGH HARNESS_SHORTFALL

6. Shadow agents, unregistered identities and orphan credentials

Shadow agents (0)

Not registered, and showing a sign of a model.

None.

Unregistered identities (0)

Not registered, and showing no sign of a model. The scan cannot show that one of these runs no model. None is held to the agent bar.

None.

Orphan credentials (0)

Credentials a source, read in full, saw bound to no agent.

None.

Agents whose code calls a payment client (0)

Read from code. Where none is seen, that is what the reader saw in the agent's own file, not evidence that it cannot pay.

None.

7. Since the previous run

This output directory held no earlier run, so there is nothing to compare with.

What this document does not say

- A source that was not read in full closes nothing: an agent found through it, or one a verdict source could have reported on, is not judged and has no level.
- A criterion nobody answered counts as not met. Unanswered means a configured reader could have reported it and none did; not readable means nothing this run was configured to read could have.
- A criterion the operator declared in the inventory is never shown as observed. The level on observation alone is stated beside any level that rests on a declaration.
- An unregistered automated identity shows no sign of a model and is held to no bar. The scan cannot show that it runs no model.
- A scan that found no agents evidences nothing. It is a finding, never a clean result.
- Where code was read and no payment client was seen, that is what the reader saw in the agent’s own file. It is not evidence that the agent cannot pay.
- This is derived from the signed report and the operator’s inventory. The signed report is the record.

The files of this run: report.signed.json, results.json, agents.csv, findings.csv, summary.html, report.pdf, manifest.json.