

Import Libraries to Read

```
library(readr)
library(ggplot2)
library(dplyr)
library(broom)
library(Tmisc)
library(caret)
library(caret)
library(splines)
library(party)
library(leaps)
library(glmnet)
```

Apply Functions

(m=matrix, a=array, l=list, v=vector, d=dataframe)

apply(x,index,fun) [input: m; output: a or l; applies function fun to rows/cols/cells (index) of x]

lapply(x,fun) [input l; output l; apply fun to each element of list x]

sapply(x,fun) [input l; output v; user friendly wrapper for lapply(); see also replicate()]

tapply(x,index,fun) [input l output l; applies fun to subsets of x, as grouped based on index]

Clustering

```
plot(1:nc, wss, type="b", xlab="Number of Clusters", ylab="Within groups sum of squares")
```

```
wssplot <- function(data, nc=15, seed=1-234){ wss <- (nrow(data)-1)*sum(apply(data,2,var)) for (i in 2:nc){ set.seed(seed) wss[i] <- sum(kmeans(data, centers=i)$withinss)}
```

GGplot

```
ggplot(mydata, aes(xvar, yvar)) +
geom_point(aes(color=groupvar)) +
geom_smooth(method="lm")
```

qplot(x = cty, y = hwy, data = mpg, geom = "point") [Creates a complete plot with given data, geom, and mappings. Supplies many useful defaults]

last_plot() [Returns the last plot]

ggsave("plot.png", width = 5, height = 5) [Saves last plot as 5' x 5' file named "plot.png" in working directory. Matches file type to file extension]

Setup

createDummyFeatures(obj=,target=,method=,cols=) [creates (0,1) flags for each non-numeric variable excluding target]

****normalizeFeatures(obj=,target=,method=,cols=,range=,on.constant=)**

center subtract mean

scale divide by std. deviation

standardize center and scale

range linear scale to given range

mergeSmallFactorLevels(task=,cols=,min.perc=) [combine infrequent factor levels into single merged level]

Basic Codes

```
read_csv("path/nhanes.csv")
```

View(df)

filter(df, ...) [Filters data frame according to condition]

mean, median, range [na.rm=TRUE]

t.test(y~grp, data=df)

wilcox.test(y~grp, data=df)

anova(lmfit)

TukeyHSD(aov(lmfit)) [ANOVA Post-hoc pairwise contrasts]

xt <- xtabs(~x1+x2, data=df)

addmargins(xt)

prop.table(xt)

chisq.test(xt)

fisher.test(xt)

mosaicplot(xt)

factor(x, levels=c("wt", "mutant"))

relevel(x, ref="wildtype")

power.t.test(n, power, sd, delta)

power.prop.test(n, power, p1, p2)

tidy() augment() glance() [Model tidying functions in the broom package]



By [deleted]
cheatography.com/deleted-77271/

Published 26th February, 2019.
Last updated 26th February, 2019.
Page 1 of 2.

Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
<https://apollopad.com>

Model Functions

aov(formula, data) [analysis of variance model]

lm(formula, data) [fit linear models]

glm(formula, family, data) [fit generalized linear models]

nls(formula, data) [nonlinear least-squares estimates of the nonlinear model parameters]

lmer(formula, data) [fit mixed effects model]

(lme4); lme() or **(nlme)**

anova(fit, data...) [provides sequential sums of squares and corresponding F-test for objects]

contrasts(fit, contrasts = TRUE) [view contrasts associated with a factor]

contrasts(fit, how.many) <- value

glht(fit, linfct) [makes multiple comparisons using a linear function linfct (mutcomp)]

summary(fit) [summary of model, often w/ t-values]

confint(parameter) [confidence intervals for one or more parameters in a fitted model]

predict(fit,...) [predictions from fit]

Decision Tree

ctree(formula,data) [formula is a formula describing the predictor and response variables]

Data Information

is.na(x)	is.nan(x)
is.null(x)	is.array(x)
is.complex(x)	is.character(x)
is.data.frame(x)	is.numeric(x)
head(x)	tail(x)
summary(x)	str(x)
length(x)	dim(x)
dimnames(x)	attr(x,which)
nrow(x)	ncol(x)
NROW(x)	NCOL(x)
class(x)	unclass(x)

Data Splitting and Manipulating

createDataPartition(y,p=0.8) [createDataPartition splits a vector 'y' with 80 percent data in one part and 20 percent in other part]

trainControl(summaryFunction = <R function>, classProbs = <logical>) [It is used for controlling training parameters like resampling, number of folds, iteration etc.]

densityplot.rfe(x,data,...) [Lattice functions for plotting resampling results of recursive feature selection]

featureplot(x,y,plot...) [A shortcut to produce lattice plots]

Polynomial regression

$medv = b_0 + b_1 * lstat + b_2 * lstat^2$

lm(medv ~ lstat + I(lstat^2), data = train.data)

lm(medv ~ poly(lstat, 2, raw = TRUE), data = train.data)

Spline Model

spline(x,y) [cubic spline interpolation]

splineKnots(object)

knots <- quantile(train.data\$lstat, p = c(0.25, 0.5, 0.75))

Step-wise Selection

null <- lm(Formula~1, data=dtrain)

full <- lm(Formula~., data=dtrain)

step(null, scope=list(lower=null, upper=full), direction="forward")

step(full, scope=list(lower=full, upper=null), direction="backward")

Preprocessing

Transformations, filters, and other operations can be applied to the predictors with the **preProc** option.

train(, preProc = c("method1", "method-2"), ...)

train determines the order of operations; the order that the methods are declared does not matter.

recipes package has a more extensive list of preprocessing operations.

