

# Backend Documentation draft

POST    backend/hasheS

This request takes a payload containing a hash

```
PAYLOAD = {  
  "Hash": "hashXyZ"  
}
```

# Backend Documentation draft

**returns**

```
{
  "hash report": [
    {
      "Hash": "hashxYZ",
      "Hash_name": "Name",
      "harmless": 82,
      "malicious": 0,
      "suspicious": 1,
      "undetected": 10,
      "timeout": 0
    },
    {
      "Hash": "XashYZh",
      "Hash_name": "Name2",
      "harmless": 82,
      "malicious": 0,
      "suspicious": 1,
      "undetected": 10,
      "timeout": 0
    }
  ],
  "count": 2,
  "status_msg": "OK"
}
```

# Backend Documentation draft

GET backend/hashes ??? (defunct)

This request returns all the hashes from the table (idk if this is necessary but just to be on the safe side ... )

## returns

```
{
  "reports": [
    {
      "Hash": "hashxYZ",
      "Hash_name": "Name",
      "harmless": 82,
      "malicious": 0,
      "suspicious": 1,
      "undetected": 10,
      "timeout": 0
    },
    {
      "Hash": "XashYZh",
      "Hash_name": "Name2",
      "harmless": 82,
      "malicious": 0,
      "suspicious": 1,
      "undetected": 10,
      "timeout": 0
    }
  ],
  "count": 2,
  "status_msg": "OK"
}
```

# Backend Documentation draft