

R Notebook

Parametros:

```
Measure = Accuracy
Columns = sampling, weight_space, underbagging
Performance = holdout_measure_residual
Filter keys = NULL
Filter values = NULL
```

```
library("scmamp")
library(dplyr)
```

Tratamento dos dados

Carregando data set compilado

```
ds = read.csv("/home/rodrigo/Dropbox/UNICAMP/IC/estudo_cost_learning/SummaryResults/summary_compilation.csv")
ds = filter(ds, learner != "classif.rusboost")
summary(ds)
```

```
##           learner      weight_space
## classif.ksvm      :17100  Mode :logical
## classif.randomForest:17100 FALSE:41040
## classif.rusboost   :    0  TRUE :10260
## classif.xgboost    :17100  NA's :0
##
##
##
##           measure      sampling      underbagging
## Accuracy              :10260  ADASYN:10260  Mode :logical
## Area under the curve   :10260  FALSE :30780  FALSE:41040
## F1 measure             :10260  SMOTE :10260  TRUE :10260
## G-mean                 :10260              NA's :0
## Matthews correlation coefficient:10260
##
##
## tuning_measure  holdout_measure  holdout_measure_residual
## Min.      :-0.1277  Min.      :-0.2120  Min.      :-0.4658
## 1st Qu.: 0.6911  1st Qu.: 0.4001  1st Qu.: 0.1994
## Median : 0.9700  Median : 0.8571  Median : 0.5581
## Mean   : 0.7903  Mean   : 0.6718  Mean   : 0.5298
## 3rd Qu.: 0.9975  3rd Qu.: 0.9900  3rd Qu.: 0.8755
## Max.    : 1.0000  Max.    : 1.0000  Max.    : 1.0000
## NA's    :1077    NA's    :1077    NA's    :1077
## iteration_count      dataset      imba.rate
## Min.      :1         abalone      : 900  Min.      :0.0010
## 1st Qu.:1          adult        : 900  1st Qu.:0.0100
## Median :2          bank         : 900  Median :0.0300
## Mean   :2          car          : 900  Mean   :0.0286
```

```
## 3rd Qu.:3      cardiocography-10clases: 900 3rd Qu.:0.0500
## Max. :3      cardiocography-3clases : 900 Max. :0.0500
## NA's :1077 (Other) :45900
```

Filtrando pela metrica

```
ds = filter(ds, measure == params$measure)
```

Filtrando o data set

```
if(params$filter_keys != 'NULL' && !is.null(params$filter_keys)){
  dots = paste0(params$filter_keys, " == '",params$filter_values, "'")
  ds = filter_(ds, .dots = dots)
}
```

```
summary(ds)
```

```
##          learner      weight_space
## classif.ksvm      :3420  Mode :logical
## classif.randomForest:3420 FALSE:8208
## classif.rusboost   :    0  TRUE :2052
## classif.xgboost    :3420  NA's :0
##
##
##
##          measure      sampling  underbagging
## Accuracy          :10260  ADASYN:2052  Mode :logical
## Area under the curve :    0  FALSE :6156  FALSE:8208
## F1 measure          :    0  SMOTE :2052  TRUE :2052
## G-mean              :    0              NA's :0
## Matthews correlation coefficient:    0
##
##
## tuning_measure  holdout_measure  holdout_measure_residual
## Min. :0.09041  Min. :0.01517  Min. :0.0346
## 1st Qu.:0.96185 1st Qu.:0.95349 1st Qu.:0.3809
## Median :0.98796 Median :0.98113 Median :0.7239
## Mean :0.95509  Mean :0.94933  Mean :0.6600
## 3rd Qu.:0.99669 3rd Qu.:0.99347 3rd Qu.:0.9428
## Max. :1.00000  Max. :1.00000  Max. :1.0000
## NA's :204      NA's :204      NA's :204
## iteration_count      dataset      imba.rate
## Min. :1      abalone      : 180  Min. :0.0010
## 1st Qu.:1      adult      : 180  1st Qu.:0.0100
## Median :2      bank      : 180  Median :0.0300
## Mean :2      car      : 180  Mean :0.0286
## 3rd Qu.:3      cardiocography-10clases: 180 3rd Qu.:0.0500
## Max. :3      cardiocography-3clases : 180 Max. :0.0500
## NA's :204      (Other)      :9180
```

Computando as médias das iteracoes

```
ds = group_by(ds, learner , weight_space , measure , sampling , underbagging , dataset , imba.rate)
ds = summarise(ds, tuning_measure = mean(tuning_measure), holdout_measure = mean(holdout_measure),
               holdout_measure_residual = mean(holdout_measure_residual))

ds = as.data.frame(ds)
```

Criando dataframe

```
# Dividindo o ds em n, um para cada técnica
splited_df = ds %>% group_by_at(.vars = params$columns) %>% do(vals = as.data.frame(.)) %>% select(vals)

# Juntando cada uma das partes horizontalmente em um data set
df_tec_wide = do.call("cbind", splited_df)

# Renomeando duplicacao de nomes
colnames(df_tec_wide) = make.unique(colnames(df_tec_wide))

# Selecionando apenas as medidas da performance escolhida
df_tec_wide_residual = select(df_tec_wide, matches(paste("^", params$performance, "$|", params$performance)))

# Renomeando colunas
new_names = NULL
for(i in (1:length(splited_df))){
  id = toString(sapply(splited_df[[i]][1, params$columns], as.character))
  new_names = c(new_names, id)
}
colnames(df_tec_wide_residual) = new_names

# Verificando a dimensao do df
dim(df_tec_wide_residual)
```

```
## [1] 684 5
```

```
# Renomeando a variavel
df = df_tec_wide_residual

head(df)
```

```
## ADASYN, FALSE, FALSE FALSE, FALSE, FALSE FALSE, FALSE, TRUE
## 1 0.3572658 0.3329890 0.6153581
## 2 0.3572658 0.3329890 0.6153581
## 3 0.3810826 0.3311463 0.6504465
## 4 0.3933596 0.3513412 0.6178953
## 5 0.4186973 0.4313027 0.5874736
## 6 0.4186973 0.4313027 0.5874736
## FALSE, TRUE, FALSE SMOTE, FALSE, FALSE
## 1 0.3297176 0.3553719
## 2 0.3297176 0.3553719
## 3 0.3214872 0.3728814
## 4 0.3425249 0.4019884
## 5 0.3964926 0.4211234
## 6 0.3964926 0.4211234
```

```
summary(df)
```

```
## ADASYN, FALSE, FALSE FALSE, FALSE, FALSE FALSE, FALSE, TRUE
## Min. :0.03682 Min. :0.0367 Min. :0.04134
## 1st Qu.:0.38896 1st Qu.:0.3327 1st Qu.:0.58083
## Median :0.72316 Median :0.6794 Median :0.78629
## Mean :0.65921 Mean :0.6325 Mean :0.72168
## 3rd Qu.:0.94404 3rd Qu.:0.9499 3rd Qu.:0.91828
## Max. :0.99992 Max. :1.0000 Max. :0.99985
```

```
## NA's :33          NA's :6          NA's :5
## FALSE, TRUE, FALSE SMOTE, FALSE, FALSE
## Min. :0.0367      Min. :0.03682
## 1st Qu.:0.3325     1st Qu.:0.38002
## Median :0.6721     Median :0.71339
## Mean :0.6308       Mean :0.65560
## 3rd Qu.:0.9487     3rd Qu.:0.94968
## Max. :1.0000       Max. :1.00000
## NA's :6           NA's :18
```


Verificando a média de cada coluna selecionada

```
for(i in (1:dim(df)[2])){
  print(paste("Media da coluna ", colnames(df)[i], " = ", mean(df[,i], na.rm = TRUE), sep=""))
}

## [1] "Media da coluna ADASYN, FALSE, FALSE = 0.659211626562193"
## [1] "Media da coluna FALSE, FALSE, FALSE = 0.632486883725381"
## [1] "Media da coluna FALSE, FALSE, TRUE = 0.721681494090847"
## [1] "Media da coluna FALSE, TRUE, FALSE = 0.630764193944798"
## [1] "Media da coluna SMOTE, FALSE, FALSE = 0.655600329487413"
```

Fazendo teste de normalidade

```
plotDensities(data = na.omit(df))
```



Testando as diferencas

```
friedmanTest(df)
```

```
##
## Friedman's rank sum test
##
## data: df
## Friedman's chi-squared = 155.43, df = 4, p-value < 2.2e-16
```

Testando as diferencas par a par

```
test <- nemenyiTest (df, alpha=0.05)
abs(test$diff.matrix) > test$statistic
```

```
##      ADASYN, FALSE, FALSE FALSE, FALSE, FALSE FALSE, FALSE, TRUE
## [1,]          FALSE          TRUE          TRUE
## [2,]          TRUE          FALSE          TRUE
## [3,]          TRUE          TRUE          FALSE
## [4,]          TRUE          FALSE          TRUE
## [5,]          FALSE          TRUE          TRUE
##      FALSE, TRUE, FALSE SMOTE, FALSE, FALSE
## [1,]          TRUE          FALSE
```

```
## [2,]          FALSE          TRUE
## [3,]          TRUE          TRUE
## [4,]          FALSE          TRUE
## [5,]          TRUE          FALSE
```

Plotando os ranks

```
print(colMeans(rankMatrix(df)))
```

```
## ADASYN, FALSE, FALSE  FALSE, FALSE, FALSE  FALSE, FALSE, TRUE
##          2.952485          3.369152          2.486842
##  FALSE, TRUE, FALSE  SMOTE, FALSE, FALSE
##          3.367690          2.823830
```

Plotando grafico de Critical Difference

```
result = tryCatch({
  plotCD(df, alpha=0.05, cex = 0.35)
}, error = function(e) {})
```

