

R Notebook

Parametros:

Measure = Matthews correlation coefficient
Columns = sampling, weight_space, underbagging
Performance = holdout_measure
Filter keys = NULL
Filter values = NULL

```
library("scmamp")  
library(dplyr)
```

Tratamento dos dados

Carregando data set compilado

```
ds = read.csv("/home/rodrigo/Dropbox/UNICAMP/IC/estudo_cost_learning/SummaryResults/summary_compilation.  
ds = filter(ds, learner != "classif.rusboost")  
summary(ds)
```

```
##           learner      weight_space  
## classif.ksvm      :17100  Mode :logical  
## classif.randomForest:17100 FALSE:41040  
## classif.rusboost   :    0  TRUE :10260  
## classif.xgboost    :17100  NA's :0  
##  
##  
##  
##           measure      sampling      underbagging  
## Accuracy           :10260  ADASYN:10260  Mode :logical  
## Area under the curve :10260  FALSE :30780  FALSE:41040  
## F1 measure           :10260  SMOTE :10260  TRUE :10260  
## G-mean              :10260           NA's :0  
## Matthews correlation coefficient:10260  
##  
##  
## tuning_measure  holdout_measure  holdout_measure_residual  
## Min.   :-0.1277  Min.   :-0.2120  Min.   :-0.4658  
## 1st Qu.: 0.6911  1st Qu.: 0.4001  1st Qu.: 0.1994  
## Median : 0.9700  Median : 0.8571  Median : 0.5581  
## Mean   : 0.7903  Mean   : 0.6718  Mean   : 0.5298  
## 3rd Qu.: 0.9975  3rd Qu.: 0.9900  3rd Qu.: 0.8755  
## Max.   : 1.0000  Max.   : 1.0000  Max.   : 1.0000  
## NA's   :1077    NA's   :1077    NA's   :1077  
## iteration_count      dataset      imba.rate  
## Min.   :1          abalone      : 900  Min.   :0.0010  
## 1st Qu.:1          adult      : 900  1st Qu.:0.0100  
## Median :2          bank      : 900  Median :0.0300  
## Mean   :2          car      : 900  Mean   :0.0286
```

```
## 3rd Qu.:3      cardiocography-10clases: 900 3rd Qu.:0.0500
## Max. :3      cardiocography-3clases : 900 Max. :0.0500
## NA's :1077 (Other) :45900
```

Filtrando pela metrica

```
ds = filter(ds, measure == params$measure)
```

Filtrando o data set

```
if(params$filter_keys != 'NULL' && !is.null(params$filter_keys)){
  ds = filter_at(ds, .vars = params$filter_keys, .vars_predicate = any_vars(. == params$filter_values))
}
```

```
summary(ds)
```

```
##          learner      weight_space
## classif.ksvm      :3420  Mode :logical
## classif.randomForest:3420 FALSE:8208
## classif.rusboost   :    0  TRUE :2052
## classif.xgboost    :3420  NA's :0
##
##
##
##          measure      sampling  underbagging
## Accuracy          :    0  ADASYN:2052  Mode :logical
## Area under the curve :    0  FALSE :6156  FALSE:8208
## F1 measure          :    0  SMOTE :2052  TRUE :2052
## G-mean              :    0              NA's :0
## Matthews correlation coefficient:10260
##
##
## tuning_measure  holdout_measure  holdout_measure_residual
## Min.   :-0.1277  Min.   :-0.2120  Min.   :-0.46576
## 1st Qu.: 0.3307  1st Qu.: 0.0000  1st Qu.: 0.03886
## Median : 0.8174  Median : 0.4907  Median : 0.21377
## Mean   : 0.6548  Mean   : 0.4657  Mean   : 0.30966
## 3rd Qu.: 0.9890  3rd Qu.: 0.8152  3rd Qu.: 0.53139
## Max.   : 1.0000  Max.   : 1.0000  Max.   : 1.00000
## NA's   :225     NA's   :225     NA's   :225
## iteration_count      dataset      imba.rate
## Min.    :1          abalone          : 180  Min.    :0.0010
## 1st Qu.:1          adult             : 180  1st Qu.:0.0100
## Median :2          bank              : 180  Median :0.0300
## Mean    :2          car                : 180  Mean    :0.0286
## 3rd Qu.:3          cardiocography-10clases: 180  3rd Qu.:0.0500
## Max.    :3          cardiocography-3clases : 180  Max.    :0.0500
## NA's    :225      (Other)              :9180
```

Computando as médias das iteracoes

```
ds = group_by(ds, learner , weight_space , measure , sampling , underbagging , dataset , imba.rate)
ds = summarise(ds, tuning_measure = mean(tuning_measure), holdout_measure = mean(holdout_measure),
               holdout_measure_residual = mean(holdout_measure_residual))

ds = as.data.frame(ds)
```

Criando dataframe

```
# Dividindo o ds em n, um para cada técnica
splited_df = ds %>% group_by_at(.vars = params$columns) %>% do(vals = as.data.frame(.)) %>% select(vals)

# Juntando cada uma das partes horizontalmente em um data set
df_tec_wide = do.call("cbind", splited_df)

# Renomeando duplicacao de nomes
colnames(df_tec_wide) = make.unique(colnames(df_tec_wide))

# Selecionando apenas as medidas da performance escolhida
df_tec_wide_residual = select(df_tec_wide, matches(paste("^", params$performance, "$|", params$performance)))

# Renomeando colunas
new_names = NULL
for(i in (1:length(splited_df))){
  id = toString(sapply(splited_df[[i]][1, params$columns], as.character))
  new_names = c(new_names, id)
}
colnames(df_tec_wide_residual) = new_names

# Verificando a dimensao do df
dim(df_tec_wide_residual)
```

```
## [1] 684 5
```

```
# Renomeando a variavel
df = df_tec_wide_residual

summary(df)
```

```
## ADASYN, FALSE, FALSE FALSE, FALSE, FALSE FALSE, FALSE, TRUE
## Min. : -0.06657 Min. : -0.04044 Min. : -0.06927
## 1st Qu.: 0.10500 1st Qu.: 0.00000 1st Qu.: 0.17622
## Median : 0.47437 Median : 0.53612 Median : 0.37560
## Mean : 0.47796 Mean : 0.47690 Mean : 0.41910
## 3rd Qu.: 0.82994 3rd Qu.: 0.84465 3rd Qu.: 0.62900
## Max. : 1.00000 Max. : 1.00000 Max. : 1.00000
## NA's :32 NA's :6 NA's :6
## FALSE, TRUE, FALSE SMOTE, FALSE, FALSE
## Min. : -0.03836 Min. : -0.0748
## 1st Qu.: 0.00000 1st Qu.: 0.1152
## Median : 0.50398 Median : 0.4830
## Mean : 0.47172 Mean : 0.4839
## 3rd Qu.: 0.83988 3rd Qu.: 0.8393
## Max. : 1.00000 Max. : 1.0000
## NA's :11 NA's :20
```

Verificando a média de cada coluna selecionada


```
for(i in (1:dim(df)[2])){
  #print(df[,i])
}
```

```
print(paste("Media da coluna ", colnames(df)[i], " = ", mean(df[,i], na.rm = TRUE), sep=""))
}
```

```
## [1] "Media da coluna ADASYN, FALSE, FALSE = 0.477962273506577"
## [1] "Media da coluna FALSE, FALSE, FALSE = 0.47690369276557"
## [1] "Media da coluna FALSE, FALSE, TRUE = 0.419103377167762"
## [1] "Media da coluna FALSE, TRUE, FALSE = 0.471719912101946"
## [1] "Media da coluna SMOTE, FALSE, FALSE = 0.483939594059321"
```

Fazendo teste de normalidade

```
plotDensities(data = na.omit(df))
```



Testando as diferencas

```
friedmanTest(df)
```

```
##
## Friedman's rank sum test
##
## data: df
## Friedman's chi-squared = 23.296, df = 4, p-value = 0.0001105
```

Testando as diferenças par a par

```
test <- nemenyiTest (df, alpha=0.05)
abs(test$diff.matrix) > test$statistic
```

```
##      ADASYN, FALSE, FALSE FALSE, FALSE, FALSE FALSE, FALSE, TRUE
## [1,]          FALSE          FALSE          TRUE
## [2,]          FALSE          FALSE          TRUE
## [3,]           TRUE          TRUE         FALSE
## [4,]          FALSE          FALSE          TRUE
## [5,]          FALSE          FALSE          TRUE
##      FALSE, TRUE, FALSE SMOTE, FALSE, FALSE
## [1,]          FALSE          FALSE
## [2,]          FALSE          FALSE
## [3,]           TRUE          TRUE
## [4,]          FALSE          FALSE
## [5,]          FALSE          FALSE
```

Plotando grafico de Critical Difference

```
result = tryCatch({
  plotCD(df, alpha=0.05, cex = 0.35)
}, error = function(e) {})
```

